

JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)	
BF20292-24B	LCD HIGH OUTPUT WHITE 8400°k RGB	1820 @ 0°C	810	5	38,000 ± 10%	20,000	

^{*} RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		METRIC DIMENSIONS ARE IN MILLIMETERS		COMPONENTS COPPODATION							
			THIRD ANGLE	TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0	TITLE	MIN	IATURE COL	D CAT			
Α	DIMENSION CHANGES		PROJECTION DRAWN BY L. WENGSTROM	ANGLE +/- 0 APPV'D BY DATE F.D. 12/19/02	SIZE	FSCM NO. 55335	DRAWING		2-24B		
REV. NO.	RELEASED DESCRIPTION/ECO NUMBER	2/28/02 APPV'D DATE		PRAWING -	SCALE	-	RELEASED DATE 2/28/02	REVISIO DATE	n 12/19/02	NO. A	SHEET 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for CCFL Fluorescent Lamps category:

Click to view products by JKL manufacturer:

Other Similar products are found below:

BF20170-38B BF4142-20B BF20137-26B BF2698-20B CF20228-31B CF26349-28B BF22140-24B BF22180-28B BF26180-24B BF5118-20B BF20125-28B BF20325-24B BF26214-20B BF26230-24B BF26240-24B BF26250-24B BF2661-24B BF386-20B BF20218-24B BF20226-24B BF20292-24B BF22258-25B BF22312-45B BF26318-20B BF3100-20B BF3228-21B BF5165-20B CF20305-24B BF3300-20B BF350-20B