

| JKL PART NUMBER | LENGTH A +/- 2mm | COLOR | STARTING CIRCUIT VOLTAGE VS (Vrms) | OPERATING LAMP VOLTAGE VL (Vrms) | OPERATING LAMP CURRENT IL (mArms) | BRIGHTNESS (CANDELA/m2) | *RATED LIFE (HRS) | |
|-----------------------|------------------|---|--|--|---|--|----------------------|--|
| BF350-20B | 50mm | | 500 | 195 | 5 ± 1 | 28000 ± 2800 | 20,000 | |
| BF375-20B | 75mm | | 525 | 210 | 5 ± 1 | 28000 ±2800 | 20,000 | |
| BF386-20B | 86mm | RGB HIGH OUTPUT WHITE 5400° KELVIN (REF.) | 540 | 220 | 5 ± 1 | 28000 ± 2800 | 20,000 | |
| BF3100-20B | 100mm | | 665 | 270 | 5 ± 1 | 28000 ± 2800 | | |
| BF3115-20B | 115mm | | 685 | 287 | 5 ± 1 | 28000 ± 2800 | 20,000 | |
| BF3130-20B | 130mm | | 705 | 305 | 5 ± 1 | 28000 ± 2800 | 20,000 | |
| BF3160-20B | 160mm | | 850 | 345 | 5 ± 1 | 28000 ± 2800 | 20,000 | |
| BF3180-20B | 180mm | | 940 | 380 | 5 ± 1 | 28000 ± 2800 | 20,000 | |
| BF3216-20B | 216mm | | 1100 | 440 | 5 ± 1 | 28000 ± 2800 28000 ± 2800 28000 ± 2800 | 20,000 | |
| BF3240-20B | 240mm | | 1150 | 480 | 5 ± 1 | | 20,000 | |
| BF3250-20B | 250mm | | 1200 | 520 | 5 ± 1 5 ± 1 | | | |
| BF3275-20B | 275mm | | 1275 | 593 | | 28000 ± 2800 | 20,000 | |
| BF3300-20B | 300mm | | 1350 | 665 | 5 ± 1 | 28000 ± 2800 | 20,000 | |
| BF3360-20B | 360mm | | 1500 | 785 | 5 ± 1 | 28000 ± 2800 | 20,000 | |
| BF3380-20B | 380mm | | 1590 | 825 | 5 ± 1 | 28000 ± 2800 | 20,000 | |

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

| | | | METRIC | DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS | • | KI | L COMPON | NENTS COR | PORAT | TION |
|------|--|----------|--|--|------------------|---------|----------------|-----------|--------|--------|
| F | ADD PART NUMBER BF3115-20B | 12/19/02 | (++++++++++++++++++++++++++++++++++++ | OTHERWISE SPECIFIED | TITLE | N 41N 1 | ATUDE OOL | | | |
| E | ADD PART NUMBER BF3180-20B & BF3380-20B 11/30/0 ADD PART NUMBER BF3240-20B 4/26/01 | |] \ \ | 1 PL +/- 0.2 | | MIN | IATURE COLI | CATHODE | ATHODE | |
| D | | | THIRD ANGLE | 2 PL +/- 0.20 | FLUORESCENT LAMP | | | | | |
| С | ADD PART NUMBER BF3130-20B | 9/11/00 | PROJECTION | ANGLE +/- 0 | | | | -/ \IVII | | |
| В | ADD PART NUMBER BF375-20B | 4/21/00 | DRAWN BY | APPV'D BY DATE | SIZE | | DRAWING | | | |
| Α | LENGTH ±5 TO ±2 | 2/25/00 | L. WENGSTROM | F.D. 12/19/02 | Α | 55335 | NO. BF | 3-20B | | |
| | RELEASED - CANCEL BF-3mm DIA DRAWING 2/21/00 | | - CAD DRAWING - | | SCALE | | RELEASED | REVISION | REV. | SHEET |
| REV. | DESCRIPTION/ECO AI | | | | | | DATE 2/21/00 | | No. F | 4 4 |
| NO. | D. NUMBER DATE | | MANUAL REVISIONS NOT PERMITTED | | | NONE | -···- 2/2 1/00 | 12/19/02 | 110. | I OF I |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for CCFL Fluorescent Lamps category:

Click to view products by JKL manufacturer:

Other Similar products are found below:

BF20170-38B BF4142-20B BF20137-26B BF2698-20B CF20228-31B CF26349-28B BF22140-24B BF22180-28B BF26180-24B BF5118-20B BF20125-28B BF20325-24B BF26214-20B BF26230-24B BF26240-24B BF26250-24B BF2661-24B BF386-20B BF20218-24B BF20226-24B BF20292-24B BF22258-25B BF22312-45B BF26318-20B BF3100-20B BF3228-21B BF5165-20B CF20305-24B BF3300-20B BF350-20B