








SPECIFICATIONS

Current Rating: 9A AC,DC
Voltage Rating: 600V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 10mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1500V AC/minute
Material: Nylon 66,UL94V-2
Color: Natural(Translucent)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
C4255HM-02P	4.20	9.60
C4255HM-03P	8.40	13.80
C4255HM-04P	12.60	18.00
C4255HM-05P	16.80	22.20

				JOINT TECH ELECTRONIC IND. CO., LTD.		
				JOY DAY INDUSTRIAL CO., LTD.		
				UNIT	SCALE	SHEET
			mm		1 of 1	TITLE: 4.20mm PITCH HOUSING-PLUG, SINGLE ROW, MINI-FIT
			DRAWN BY		APPROVED BY	
			李勤		董正一	
			2006.06.07		2006.06.07	
			GENERAL TOLERANCE			
			X. X±0.25		ANGLE±	
A0	NEW RELEASE	2006.06.07	X. XX±0.15			DRAW NO. : C4255HM-XP
REV.	DESCRIPTION	DATE	X. XXX±0.05			
						REV. A0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) *category:*

Click to view products by [Joint Tech](#) *manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)