

NOTE:

- 1. MAT'L WIRE: 26 AWG, 1007 UL/CSA APPROVED
- 2. CONTACTS: PHOSPHOR BRONZE, NICKEL PLATE
- 3. BODY: MOLDED POLYETHYLENE
- 4.RED WIRE CONNECTED TO FEMALE CONTACT; BLACK WIRE CONNECTED TO MALE CONTACT.
- 5. ★ REF. DIMENSION MUST FIT INDUSTRY STANDARD 9 VOLT BATTERY.

	ALL OUTSIDE HAD ±.020 TOLERANCE	
8.23.21	ALL OUTSIDE HAD ±.020 TOLERANCE C1 WAS .512+.015/005, ADD NOT 5 CHANGE AS PER ECN 21-096	C
6.1.05	CHANGE AS PER ECN 05-029	В
3.10.05	CHANGE AS PER ECN 05-017	Α
DATE	DESCRIPTION RE	

PART NO.	'L' DIM.
2241	4.000 [101.60]
2242	6.000 [152.40]
2243	8.000 [203.20]

	KEYSTONE ELECTRONICS CORP.					
	www.keyelco.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500					
	PART NAME					
	PREMIUM '9' VOLT 'T' STYLE BATTERY STRAP					
	MATERIAL					
AS NOTED						
	FINISH AS NOTED	BOONE DATE 8.08.85				
	ASNOTED	APP'D SCALE 2X				
	TOLERANCES INCH [MM] CODE	DWG NO.				
	DECIMAL ± .020 [± 0.50] ANGULAR ± 1° UNLESS OTHERWISE SPECIFIED	2241-2243				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for 9V Battery Snaps & Contacts category:

Click to view products by Keystone manufacturer:

Other Similar products are found below:

139B 173P 274 532-SWH 266 1295 12BC2202-GR 271 12BH615D-GR 121-0624/O-GR 636 67 68 72 724 79 856 265 967 968 80

BX0023 BX0026 BX0033 1290 1290-79 1291 1291-79 1294 203-P 2239 2240 229 232 232-M 233 233-M 234 234-M 235 235-M

237-M 245 261 263 264 269 272 303-P 593