

Aluminum Electrolytic Capacitor

KN series

KFSON

- ◆ Load life 2000 Hrs at 105°C
- ◆ RoHS Compliant




Specifications 規格表

Ltem 項目	Performance Characteristics 特性參數									
Operating Temperature Range 工作溫度範圍	-40 to +105℃					-25 to +105℃				
Rated Voltage Range 額定電壓範圍	16 to 100 VDC					160 to 500 VDC				
Capacitance Range 容量範圍	68 to 56000 μF									
Capacitance Tolerance 靜電容量偏差	±20% (120Hz, +20℃)									
Leakage Current 漏電流	After 5 minutes at 20° C application of rated voltage, leakage current is not more than 0.01CV or 1.5mA, whichever is smaller C: Nominal Capacitance(μF) V: Rated Voltage(V)									
Dissipation Factor 損耗角正切值 tan δ (%)	rated voltage (V)	16	25	35	50	63	100	160-400	450-500	
	tan δ (Max)	50	40	40	30	20	20	15	20	
Low Temperature Characteristics 低溫特性	impedance ratio max 電容器最大阻抗比值									
	rated voltage (V)	16	25	35	50	63	100	160-400	450-500	
	Z(-25℃)/Z(+20℃)	4	4	4	4	4	4	4	8	
	Z(-40℃)/Z(+20℃)	15	15	15	15	15	15	15	-	-
Load Life 使用壽命	105℃施加額定工作電壓2000小時，經恢復後，產品性能應滿足以下要求 The following specifications shall be satisfied when the capacitors are restored to 20℃ after subjected to DC voltage with the rated ripple current is applied for 2000H at 105℃									
	Capacitance change		≡±20% of the initial value							
	D.F. (tan δ)		≡200% of the specified value							
	Leakage current		≡The specified value							
Shelf Life 存儲特性	105℃放置1000小時，經恢復後20℃后，產品性能應滿足以下要求 The following specifications shall be satisfied when the capacitors are restored to 20℃ after exposing them for 1000 hours at 105℃ without voltage applied.									
	Capacitance change		≡±20% of the initial value							
	D.F. (tan δ)		≡150% of the specified value							
	Leakage current		≡The specified value							

Diagram of Dimensions 外形尺寸圖 (mm)

●Standard Terminal Type : S (Φ22 ~ Φ35)



Aluminum Electrolytic Capacitor

KN series



Frequency Coefficient

Frequency Voltage (v)	50/60 Hz	120 Hz	300 Hz	1K Hz	10K Hz	≥50K Hz
≤100V	0.95	1.00	1.07	1.13	1.19	1.20
160-250V	0.87	1.00	1.17	1.32	1.45	1.50
≥350	0.80	1.00	1.16	1.30	1.41	1.43

Standard Ratings

Rated Voltage	Rated Capacity	Size φ D*L	Rated ripple current
V	μ F	mm	A
16V	3300	22*26	1.17
		22*26	1.53
	4700	25*26	1.55
		22*31	2.02
	6800	25*26	2.02
		30*26	2.02
		22*31	2.20
	8200	22*31	2.79
		25*26	2.79
		30*26	2.81
	10000	22*36	3.06
		30*26	3.06
		22*41	3.24
	15000	25*36	3.24
		30*26	3.24
		35*32	3.24
		22*51	3.54
	18000	25*46	3.51
		30*36	3.51
		35*32	3.54
		25*51	4.25
	22000	30*36	4.08
		35*32	4.08
		25*51	4.30
	27000	30*41	4.30
		35*32	4.30
		30*46	4.83
	33000	35*37	4.83
		30*51	5.78
		35*42	5.78
	47000	35*45	6.32
		35*47	6.48

Rated Voltage	Rated Capacity	Size φ D*L	Rated ripple current
V	μ F	mm	A
25V	3300	22*26	1.48
		25*26	1.48
	4700	22*26	1.88
		25*26	1.90
	6800	22*31	2.60
		25*26	2.60
		30*26	2.60
	8200	22*36	3.14
		25*31	3.14
		30*26	3.14
	10000	22*41	3.50
		25*36	3.50
		30*31	3.50
		35*27	3.50
	12000	22*46	4.02
		25*41	4.02
		30*31	4.02
		35*27	4.02
	15000	25*46	4.58
		30*36	4.58
		35*32	4.58
	18000	25*51	4.82
		30*41	4.82
		35*32	4.79
	22000	30*46	5.12
		35*37	5.12
		27000	5.30
	33000	35*52	6.09
	39000	35*52	6.20
	47000	35*52	6.30

Rated ripple current (A,rms) at 105℃, 120Hz

Aluminum Electrolytic Capacitor

KN series

KFSON

Standard Ratings

Rated Voltage	Rated Capacity	Size Φ D*L	Rated ripple current
V	μ F	mm	A
35V	1500	22*26	1.26
	2200	22*26	1.35
		25*26	1.45
	2700	22*26	1.55
		25*26	1.65
	3300	22*26	1.80
		25*26	1.90
	4700	22*36	2.42
		25*26	2.30
		30*26	2.54
	6800	22*41	3.24
		25*36	3.24
		30*26	3.21
		35*27	3.24
	10000	25*46	3.96
		30*36	3.96
		35*27	3.75
	12000	25*51	4.21
		30*41	4.21
		35*32	4.21
	15000	30*46	4.69
		35*37	4.69
	22000	35*52	5.50
	27000	35*52	5.80
		35*45	5.60
	33000	35*52	5.90

Rated ripple current (A,rms) at 105℃, 120Hz

Rated Voltage	Rated Capacity	Size Φ D*L	Rated ripple current
V	μ F	mm	A
50V	1500	22*26	1.10
		25*26	1.02
	2200	22*31	1.65
		25*26	1.65
	2700	22*31	1.85
		25*26	1.85
		30*26	1.95
	3300	22*36	2.24
		25*31	2.24
		30*26	2.24
	4700	22*46	2.95
		25*36	2.80
		30*31	2.95
		35*27	2.95
	6800	25*46	3.23
		30*41	3.20
		35*32	3.26
	8200	30*46	3.58
		35*37	3.58
	10000	30*51	4.11
		30*45	4.01
		35*42	4.11
		30*40	4.00
		25*50	3.90
		35*30	3.86
	15000	35*52	5.05
	18000	35*52	5.30
	22000	35*60	5.50

Aluminum Electrolytic Capacitor

KN series



Standard Ratings

Rated Voltage	Rated Capacity	Size ΦD*L	Rated ripple current
V	μF	mm	A
63V	820	22*26	0.75
	1000	22*26	0.85
		25*26	0.85
	1500	22*26	1.10
		25*26	1.12
		30*26	1.14
	1800	22*31	1.40
		25*26	1.40
	2200	22*36	1.65
		25*31	1.65
		30*26	1.65
	2700	22*41	2.07
		25*36	2.07
		30*26	2.07
	3300	22*46	2.46
		25*36	2.40
		30*31	2.48
		35*27	2.48
	3900	25*41	2.92
		30*36	3.05
		35*27	3.05
	4700	25*51	3.43
		30*41	3.43
		35*32	3.43
	5600	30*46	3.86
		35*37	3.86
	6800	30*51	4.64
		35*42	4.64
	8200	35*47	5.05
	10000	35*52	5.75
		30*60	5.65
		30*50	5.35
	15000	35*52	5.40
		35*60	5.56

Rated ripple current (A,rms) at 105℃, 120Hz

Rated Voltage	Rated Capacity	Size ΦD*L	Rated ripple current
V	μF	mm	A
100V	330	22*26	0.54
	470	22*26	0.79
		25*26	0.81
	560	22*26	0.90
		25*26	0.95
	680	22*31	1.02
		25*26	1.02
		30*26	1.14
	820	22*31	1.26
		25*26	1.26
		30*26	1.32
	1000	22*36	1.38
		25*31	1.38
		30*26	1.38
	1200	22*41	1.65
		25*36	1.65
		30*31	1.65
	1500	22*46	1.83
		25*41	1.83
		30*31	1.83
		35*27	1.83
	1800	25*41	2.52
		30*36	2.52
		35*32	2.52
	2200	25*51	3.03
		30*41	3.03
		35*32	3.03
	2700	30*46	4.10
		35*37	4.10
	3300	30*56	4.59
		35*47	4.59
	3900	35*47	4.98
	4700	35*52	5.03
		35*40	4.80
		30*50	4.65
	5600	35*60	5.10
	5600	35*52	5.09
	6800	35*60	5.20

Aluminum Electrolytic Capacitor

KN series



Standard Ratings

Rated Voltage	Rated Capacity	Size φD*L	Rated ripple current	Rated Voltage	Rated Capacity	Size φD*L	Rated ripple current
V	μ F	mm	A	V	μ F	mm	A
160V	220	22*26	0.42	200V	470	22*41	1.57
	330	22*31	0.98			25*36	1.59
		25*26	0.98			30*31	1.65
		30*26	1.00			35*27	1.65
	470	22*36	1.21			22*30	1.55
		25*31	1.21			22*36	1.65
		30*26	1.21			25*30	1.65
		22*31	1.15		560	22*46	1.81
	560	22*41	1.40			25*41	1.85
		25*36	1.40			30*31	1.85
		30*31	1.40			35*27	1.85
		35*27	1.40		680	22*51	2.04
	680	22*46	1.64			25*46	2.07
		25*36	1.58			30*30	2.04
		30*31	1.65			35*32	2.17
		35*27	1.71			25*35	2.00
		22*36	1.49			25*30	1.98
	820	25*41	1.76			22*40	2.00
		30*36	1.85		820	25*51	2.30
		35*32	1.85			30*35	2.30
	1000	25*51	2.15			25*35	2.20
		30*41	2.15			25*40	2.20
		35*32	2.15			25*45	2.25
	1200	25*56	2.46			22*50	2.20
		30*46	2.46		1000	30*40	2.62
		35*37	2.46			35*37	2.62
	1500	30*51	2.80			25*45	2.55
		35*42	2.80			25*40	2.51
	1800	30*51	3.13			35*30	2.50
		35*42	3.13			25*50	2.55
	2200	35*52	3.26			30*30	2.45
		35*42	3.18			30*35	2.51
	3300	35*52	3.50		1200	30*50	3.00
		35*45	3.35		1500	35*42	3.00
200V	330	22*36	1.21		1800	35*47	3.28
		25*31	1.21		2200	35*50	4.10
		30*26	1.21			30*50	3.85
	390	22*36	1.33		2700	35*50	4.10
		25*31	1.34			35*45	3.80
		30*31	1.45				

Rated ripple current (A,rms) at 105℃, 120Hz

Aluminum Electrolytic Capacitor

KN series



Standard Ratings

Rated Voltage	Rated Capacity	Size Φ D*L	Rated ripple current
V	μ F	mm	A
250V	220	22*36	1.00
		25*31	1.00
		22*30	0.95
	330	22*46	1.28
		25*36	1.28
		30*31	1.28
	390	35*27	1.28
		22*46	1.48
		30*31	1.48
	470	35*27	1.48
		25*41	1.76
		30*36	1.76
	470	35*32	1.76
		25*30	1.56
		25*35	1.60
	470	22*36	1.56
		30*30	1.68
		22*40	1.68
	560	25*51	1.93
		30*41	1.93
		35*32	1.93
	680	25*40	2.15
		30*46	2.22
		35*37	2.22
	680	30*51	2.48
		22*45	2.15
		30*35	2.20
	820	25*45	2.46
		30*35	2.43
		30*51	2.48
	820	35*42	2.48
		25*40	2.20
		35*30	2.25
	1000	30*50	2.74
		30*40	2.65
		35*47	2.80
	1000	30*45	2.70
		35*50	3.00
		35*55	3.00
	1200	35*50	3.50
		35*55	3.50
		35*55	5.00
	2200	35*60	5.10
		35*70	5.10

Rated Voltage	Rated Capacity	Size Φ D*L	Rated ripple current
V	μ F	mm	A
400V	100	22*36	0.82
		25*31	0.82
		22*25	0.70
	100	25*25	0.80
		22*36	0.90
		25*31	0.90
	120	22*25	0.80
		25*25	0.85
		22*41	0.98
	150	25*36	0.98
		30*31	0.95
		35*27	0.95
	150	22*30	0.90
		25*25	0.90
		25*36	1.05
	180	30*30	1.21
		30*41	1.21
		25*40	1.21
	220	25*35	1.21
		35*32	1.21
		22*40	1.10
	220	25*30	1.10
		30*25	1.10
		30*40	1.40
	270	25*40	1.30
		30*35	1.30
		30*40	1.57
	330	35*30	1.57
		22*45	1.50
		25*40	1.50
	330	30*35	1.50
		35*35	1.60
		30*30	1.50
	390	30*40	1.68
		35*42	1.71
		35*45	1.94
	470	25*50	1.80
		30*40	1.80
		35*35	1.80
	470	30*50	1.85
		30*45	1.85
		35*40	1.85
	470	35*50	1.98

Rated ripple current (A,rms) at 105℃, 120Hz

Aluminum Electrolytic Capacitor

KN series



Standard Ratings

Rated Voltage	Rated Capacity	Size Φ D*L	Rated ripple current
V	μ F	mm	A
400V	560	35*50	2. 23
		30*45	2. 23
		35*45	2. 40
		35*40	2. 40
	680	35*62	2. 85
		35*50	2. 83
		35*45	2. 80
		30*50	2. 70
		35*40	2. 65
	820	35*62	2. 90
		35*45	2. 83
		35*50	2. 85
	1000	35*70	3. 20
		35*65	3. 15
		35*60	3. 15
		35*50	3. 10
	1200	35*70	3. 30
		35*65	3. 30
		35*60	3. 30
450V	82	22*36	0. 64
		25*31	0. 64
		30*26	0. 64
	100	22*41	0. 74
		25*31	0. 74
		30*31	0. 74
		22*25	0. 70
		22*35	0. 72
		25*25	0. 72
	120	22*46	0. 82
		25*36	0. 82
		30*31	0. 82
		22*30	0. 80
		25*25	0. 80
		25*30	0. 80
		30*25	0. 80
	150	22*51	0. 96
		25*41	0. 96
		30*36	0. 96
		35*27	0. 96
		22*30	0. 90
		22*35	0. 90
		25*30	0. 90
		25*35	0. 95
		30*25	0. 95
		30*30	0. 95

Rated Voltage	Rated Capacity	Size Φ D*L	Rated ripple current
V	μ F	mm	A
450V	180	25*46	1. 14
		30*36	1. 10
		35*32	1. 14
	220	25*35	1. 20
		30*41	1. 24
		35*37	1. 24
		22*40	1. 20
		25*40	1. 20
		25*50	1. 20
		30*30	1. 20
	270	30*51	1. 48
		35*42	1. 48
	330	30*40	1. 60
		30*50	1. 64
		25*50	1. 60
		30*35	1. 60
		35*30	1. 60
		35*45	1. 70
		30*30	1. 60
	390	35*40	1. 80
		35*52	1. 86
		35*35	1. 65
	470	35*50	1. 90
		35*45	1. 90
		30*50	1. 90
		30*60	1. 90
	560	35*50	2. 40
		35*45	2. 40
		35*40	2. 40
	680	30*50	2. 40
		35*60	2. 90
		35*55	2. 85
		35*50	2. 85
		35*45	2. 80
		30*55	2. 80
	820	35*70	3. 20
		35*65	3. 20
		35*60	3. 20
		35*55	3. 10
		35*56	3. 10
	1000	35*70	3. 30
		35*65	3. 30
	1200	35*80	3. 60

Rated ripple current (A,rms) at 105℃, 120Hz

Aluminum Electrolytic Capacitor

KN series



Standard Ratings

Rated Voltage	Rated Capacity	Size ΦD*L	Rated ripple current
V	μ F	mm	A
500V	100	22*40	0.90
		22*45	0.94
		25*40	0.94
		30*30	0.94
	120	25*40	0.94
		30*30	0.94
		35*25	0.94
	150	25*40	1.10
		30*35	1.13
		35*30	1.13
	180	25*50	1.39
		30*40	1.40
	220	30*40	1.50
		30*45	1.60
		35*35	1.60
		35*40	1.60
	270	30*50	1.70
		35*40	1.70
	330	30*55	2.10
		30*60	2.10
		35*50	2.10
	390	35*55	2.50
		35*50	2.47
	470	35*55	2.60
		35*60	2.65
	680	35*70	3.10
		35*60	2.90
	820	35*80	3.80
		40*70	3.80
	1000	40*80	4.70

Rated ripple current (A,rms) at 105℃, 120Hz

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Aluminium Electrolytic Capacitors - Snap In](#) ***category:***

Click to view products by [KFSON](#) ***manufacturer:***

Other Similar products are found below :

[EET-XB2W221LA](#) [108LMB200M2ED](#) [LGM2W181MELA25](#) [MVK-25VC33-M-6.3*5](#) [ALC40F1012DH](#) [ALC40E1004EL](#)
[LGZ2W151MELB40](#) [LGZ2W271MELC45](#) [LGZ2W221MELC40](#) [LGZ2W151MELC30](#) [LGZ2W121MELC25](#) [ALA8DA561EF500](#)
[DCMC142T250AB2A](#) [ESMH630VSN123MA45U](#) [ESMH630VRT183MB50U](#) [CL271MPI40B](#) [E81D251VNN331MQ35U](#)
[ELXS451VNN820MP25S](#) [ESMM181VSN402QA70U](#) [ELXG160VNN562MP25S](#) [ESMH160VNN104MA80U](#) [EKMW421VSN391MQ45S](#)
[KN821M25035*30C](#) [152EC0351](#) [KS200M821SI225*35TA-1B1ET](#) [EKHE451VSN102MR60Z](#) [TDA63V4700M22*50 V](#) [152EC0325](#)
[HP221M450N350AP4](#) [152EC0329](#) [LAO-50V103MS45PX#B](#) [152EC0566](#) [KN331M45035*30A](#) [KN821M45035*56P4](#) [152EC0327](#)
[HP471M250N300AP4](#) [TLS500V100M25.4*30 V](#) [KN331M40030*30A](#) [TLS315VS470M30*30 VS](#) [152EC0337](#) [TDA35VS4700M22*30 VS](#)
[KM450M681SI235*50TA-1A3Et](#) [152EC0340](#) [KN221M40025*30A](#) [152EC0328](#) [450USC470MEFCSN35X45](#) [152EC0332](#) [152EC0339](#)
[KS331M45030*50A](#) [152EC0344](#)