




Technical data:
Insulator body: Glass filled thermoplastic Polyester.
self-extinguishing, rated
Current Rating: 3 AMP.
Contact Phosphor bronze
plating Gold or tin over nickel
Operating Temperature: -40°C to +105°C.



			产品名称 TITLE	MJ-6B2.54*6.0			材料 MATERIAL			版本 VER	单位 UNITS	MM	日期 DATE	2013/4/10	
			零件名称 ACCESSORY			数量 QNTY		比例 SCALE			制图 DRAWN		杨世剑		角法 DROJ
			深圳市金航标电子有限公司				www.kinghelm.com.cn			一般公差		审核			
变更次数	变 更 内 容 Content of Change	担当 ACT	KH-2.54TXM-H6.0-W				0755-28190160			x.	±0.5	核准			
										.x	±0.3				
										.xx	±0.05				
										x	±5°				
											核 准 APPROVED				第三角法

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) *category:*

Click to view products by [Kingham](#) *manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)