


Deep Impact Socket

3435S

3/8"

- ANSI / ASME B107.2




KT NO.	inch	D1 mm	D2 mm	l mm	L mm		
343508S	1/4	10.8	19	10	63.5	62	6 / 120
343510S	5/16	13.0	19	12	63.5	71	6 / 120
343512S	3/8	15.3	19	12	63.5	82	6 / 120
343514S	7/16	17.0	19	13	63.5	84	6 / 120
343516S	1/2	18.2	19	14	63.5	113	6 / 120
343518S	9/16	20.7	22	14	65	114	6 / 120
343520S	5/8	23.8	22	16	65	126	6 / 96
343522S	11/16	24.5	22	17	65	138	6 / 96
343524S	3/4	27.0	22	20	65	154	6 / 96
343526S	13/16	29.5	22	22	65	156	6 / 96
343528S	7/8	30.8	22	22	65	172	5 / 60

Impact Star Socket

3575M

3/8"

- For torx external screw
- DIN 3121



KT NO.	Size	D1 mm	D2 mm	l mm	L mm		
357505M	E5	9.6	19	4.0	32	31	12 / 360
357506M	E6	10.2	19	5.0	32	31	12 / 360
357507M	E7	10.8	19	6.0	32	33	12 / 360
357508M	E8	11.5	19	6.5	32	35	12 / 360
357510M	E10	12.0	19	7.0	32	33	12 / 360
357512M	E12	14.0	19	9.0	32	34	12 / 360
357514M	E14	17.0	19	9.5	32	40	12 / 360

Impact Bit Socket

KT No. & D1



- Air pressure must not exceed 90PSI (6.3bar)
- Adjust your air tool to its lowest torque output, should this torque level not be enough, increase it gradually

3051

3/8"

- For phillips head screw
- DIN 3121



KT NO.	⊕ No.	L mm		
305101	PH1	55	33	12 / 360
305102	PH2	55	35	12 / 360
305103	PH3	55	40	12 / 360
305104	PH4	55	45	12 / 360

3052

3/8"

- For slotted head screw
- DIN 3121



KT NO.	Tip width mm	L mm		
305255	5.5	55	32	12 / 360
305208	8	55	39	12 / 360
305210	10	55	45	12 / 360

3055M

3/8"

- For hexagon head screw
- DIN 3121



KT NO.	mm	L mm	Max. torq N-m		
305504M	H4	55	20.8	34	12 / 360
305505M	H5	55	36.0	38	12 / 360
305506M	H6	55	62.4	40	12 / 360
305507M	H7	55	97.0	43	12 / 360
305508M	H8	55	144.0	46	12 / 360
305510M	H10	55	264.0	55	12 / 360
305512M	H12	55	480.0	65	12 / 360
305514M	H14	55	650.0	77	12 / 288
305516M	H16	55	680.0	91	12 / 288
305517M	H17	55	715.0	99	12 / 288

3055S

3/8"

- For hexagon head
- DIN 3121



KT NO.	inch	L mm	Max. torq N-m		
305504S	1/8	55	18.8	34	12 / 360
305545S	9/64	55	20.8	34	12 / 360
305505S	5/32	55	22.5	36	12 / 360
305506S	3/16	55	36.0	36	12 / 360
305507S	7/32	55	62.4	38	12 / 360
305508S	1/4	55	93.6	41	12 / 360
305510S	5/16	55	144.0	46	12 / 360
305512S	3/8	55	264.0	54	12 / 360
305516S	1/2	55	518.0	71	12 / 360

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Screwdrivers, Nut Drivers & Socket Drivers](#) ***category:***

Click to view products by [KING TONY](#) ***manufacturer:***

Other Similar products are found below :

[1406504-2](#) [30246](#) [5739](#) [6962](#) [9977](#) [EMF](#) [75340](#) [SF-TX 15X80 VDE](#) [SF-TX 20X80 VDE](#) [998](#) [LN25MMN](#) [P8N](#) [THS9N](#) [HS10N](#) [FSD1N](#)
[SDR11N](#) [320-9508-023 MS](#) [27627](#) [40462](#) [73508](#) [720LC/21](#) [861RI/6](#) [861TQS/1](#) [861TQS/10](#) [SF-TXH 25X100](#) [SF-TX 25X100 VDE](#) [SF-TX](#)
[30X100 VDE](#) [SZS 1,2X8,0 VDE](#) [SF-M BH](#) [SZS 0,8X4,0 VDE](#) [SZK PH3 VDE](#) [TSD-M SAC-BIT ADAPTER](#) [13010003](#) [18120001](#)
[05078635001](#) [05042750001](#) [05028161001](#) [233513M](#) [012560008](#) [012560013](#) [012560047](#) [012560009](#) [PGT040](#) [19101012](#) [012560001](#)
[012560054](#) [012560051](#) [233013M](#) [012560063](#) [223055M](#)