

# LED strip K-0480-24V

Ref. K-0480-24V



Dimensions: Width [W]: 8 mm | Max run length [L]: 10 m | Cut every [C]: 100 mm | LED spacing [D]: 12.5 mm | Height [H]: 1.6 mm



- CRI 90+
- Superior color consistency and dimming performance
- Smooth regulation of brightness
- Clean line of light when paired with most KLUS extrusions and LIGER cover

## TECHNICAL SPECIFICATIONS

IP protection rating	20	Color temperature	Lumen output	Efficiency	Ref
CRI	90	■ 2700 K	554 lm/m	115 lm/W	K-27-0480-24V
Only valid for white	yes	■ 3000 K	572 lm/m	119 lm/W	K-30-0480-24V
Working temperature from	-20°C	■ 3500 K	583 lm/m	121 lm/W	K-35-0480-24V
Working temperature up to	60°C	■ 4000 K	607 lm/m	126 lm/W	K-40-0480-24V
Input voltage	24 V DC	■ 5000 K	601 lm/m	125 lm/W	K-50-0480-24V
Power consumption	4.8 W/m				
Beam angle	120°				
MacAdam's ellipse	3 SDMC				
Number of LEDs per 1 m	70				
Number of LEDs per cut section	7 pcs				
Energy consumption	5 kWh/1000h				
Does not contain mercury and lead	yes				
Dimmable	yes				
No UV IR radiation	yes				

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Lighting Bars and Strips](#) category:*

*Click to view products by [KLUS](#) manufacturer:*

Other Similar products are found below :

[LFBLL-SW823-24V-8S125-20](#) [S010060CC3PZ](#) [HH-SX144F008W24 -2835 WW WHITE PCB IP20](#) [HH-SRGB840F010W24-COB](#)  
[N004120BB1LZ \(6000K\)](#) [N004120BC1LZ \(3000K\)](#) [N008120BB1LZ \(BLUE\)](#) [N008120BC1LZ \(4000K\)](#) [S008144CA4SA1/C1 \(RGB+4000K](#)  
[IP20\)](#) [S0121134ZC3PZ](#) [N013060CA3SA1](#) [HQS-12W-60LED-NW-WP-12V-5M](#) [HQS-6W-60LED-WW-WP-24V-5M](#) [S020240BC1DC0/C3](#)  
[HQS-12W-60LED-WW-WP-24V-5M](#) [HQS-12W-60LED-NW-24V-5M](#) [S012060CC4DC0/C3](#) [HQS-9.6W-120LED-NW-WP-12V-5M](#) [HQS-](#)  
[6W-60LED-W-12V-5M](#) [HQS-12W-60LED-WW-12V-5M](#) [HH-SRGB60F310W12-5050 WHITE PCB IP65A](#) [HQS-6W-60LED-NW-12V-5M](#)  
[HQS-6W-60LED-NW-24V-5M](#) [TAMA LED K-30-2400-24V 24W/M](#) [TAMA LED K-CR30-1440-24 14,4W/M](#) [TAMA LED KWP-GHD30-](#)  
[0960-24 9,6W/M](#) [TAMA LED K-1920-120-RGB-24V 19.2W/M](#) [TAMA LED K-40-1091-24V 9.1W/M](#) [TAMA LED K-30-1091-24V 9.1W/M](#)  
[TAMA LED K-RGB-0700-24V](#) [TAMA LED K-VHE40-1440-24V 14,4W/M](#) [TAMA LED K-HD30-0480-24 4,8W/M](#) [TAMA LED K-HD40-](#)  
[0480-24 4,8W/M](#) [TAMA LED K-HD30-1440-24 14,4W/M](#) [TAMA LED K-VHE30-1440-24V 14,4W/M](#) [TAMA LED K-30-0480-24 4.8 W/M](#)  
[TAMA K-30/18-0960-24V](#) [TAMA LED K-VHE40-0960-24V 9.6W/M](#) [TAMA LED K-30-1440-24V 14.4W/M](#) [TAMA LED K-30-0960-24V](#)  
[9.6W/M](#) [TAMA LED K-HD30-0960-24 9,6W/M](#) [TAMA LED K-CR40-0960-24 9,6W/M](#) [HQS-9.6W-120LED-W-24V-5M](#) [TAMA LED](#)  
[KWP-GHD30-1440-24 14,4W/M](#) [HQS-12W-60LED-W-12V-5M](#) [TAMA LED KWP-GHD30-0480-24 4,8W/M](#) [HQS-6W-60LED-W-24V-5M](#)  
[K-HE-30-0960-HD-24V](#) [HQS-12W-60LED-WW-24V-5M](#) [TAMA LED KWP-GHD40-1440-24 14,4W/M](#)