

FBHA Series

Chip Ferrite Bead High Current Type
Size 0402




FEATURES

- Noise reduction solution for power line.
- Compared to the FBA series, has low direct current resistance for compatibility with large currents, optimal for low power consumption. Various frequency characteristics with 2 materials of different features for countermeasures against everything from general signals to high-speed signals.
- Performs well even in signal lines where low direct current resistance is required.
- AEC-Q200 qualified.
- Operating temperature: -55 to +150 °C (including self-temperature rise)
- Quantity: 10000PCS


APPLICATION

- Power line filter for body controls, and car multimedia etc.

Dimensions: [mm]



Land Pattern: [mm]









Electrical Properties:


Part No	Z @ 100 MHz (Ω)	Tolerance	R _{DC} (Ω)	I _R (mA)
FBHA0402-100-252R	10	±25%	0.050	2500
FBHA0402-330-302R	33	±25%	0.022	3000
FBHA0402-600-252R	60	±25%	0.032	2500
FBHA0402-800-232R	80	±25%	0.038	2300
FBHA0402-121-202R	120	±25%	0.095	2000
FBHA0402-221-152R	220	±25%	0.150	1500

I_R referring to 40K self-heating above ambient temperature

Typical Electrical Characteristics:



Soldering Reflow:



Preheat condition: 150 ~200 °C / 60~120 sec.


Allowed time above 217 °C: 60~150 sec.

Max temperature: 260 °C.

Allowed Reflow time: 3x max.


Packaging Information:

Tape Dimension:




Series	A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
FBHA0402	0.62±0.03	1.12±0.03	1.5±0.1	4.0±0.1	2.0±0.1	8.0±0.3	0.60±0.03	1.75±0.1	0.60±0.03

Peel force of top cover tape:




The peel force of top cover tape shall be between 0.14 to 0.58 N

Reel Dimension: [mm]



Packaging Quantity:



Cautions and Warnings:

Storage Conditions:

- The storage period is within 12 months after the completion of production. Be sure to follow the storage conditions (temperature: -5 to 35°C, humidity: 75% RH Max). If the storage period elapses, the soldering of the terminal electrodes may deteriorate. The warranty period is one year.
- Product should not be exposed to environment with high temperature, high humidity, dust, corrosive gas and etc.
- Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- Please always handle products carefully to prevent any damage caused by dropping down or inappropriate removing.

Operation Instructions:

- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- Before soldering, be sure to preheat components. The preheating temperature should be set so that the temperature difference between the solder temperature and chip temperature does not exceed 150°C.
- Soldering corrections after mounting should be within the range of the conditions determined in the specifications. If overheated, a short circuit, performance deterioration, or lifespan shortening may occur.
- Generally, Koher might not be familiar with either customer's specific application or actual requests as customer does. As a result customer shall be responsible for checking and confirming whether Koher product with the performance described in the product specification is suitable for using in customer's particular application or not.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ferrite Beads](#) category:

Click to view products by [KOHER](#) manufacturer:

Other Similar products are found below :

[CZB1JGTTD152P](#) [CZB2AFTTD800P](#) [CZB2AGTTD121P](#) [PE-0402FB121ST](#) [AB 3X2X3SM](#) [NCB0603R301TR050F](#) [CZB2BFTTE301P](#)
[CZB2BFTTE601P](#) [4221R-1](#) [EMI0805R-600](#) [NCB0805A102TR040F](#) [EMI0805R-220](#) [WLBD1005HCU330TL](#) [WQBD1608HCU121TH](#)
[WLBD1608K2U252TB](#) [WLBD1608K2U800TP](#) [BBPY00160808301Y00](#) [BBPY00100505102Y00](#) [BBNQ00100505121Y00](#)
[BBPY00160808121Y00](#) [BBFY00100505221YHP](#) [ABPY00100505601Y00](#) [BBPY00201209101Y00](#) [ABPY00201209301Y00](#)
[ABPY00160808100Y00](#) [BBPY00160808601Y00](#) [BBPY00201209500Y00](#) [BBGK00160808121Y00](#) [BBPY00160808102Y00](#)
[ABM160808U301T](#) [BBPY00201209100Y00](#) [BBPY00100505100Y00](#) [BBPY00160808101Y00](#) [ABUP00100505600Y00](#)
[ABPY00321611121Y00](#) [ABPY00160808102Y00](#) [ABPY00160808221Y00](#) [BMC2AY0300AG](#) [BMC2AY0060AG](#) [BMC2AY0600AN](#)
[BMC2AY0220AN](#) [LLMCC201208T420RG](#) [LAMGL160808T102RD](#) [BMC2AY0120AN](#) [2176487-2](#) [2176486-4](#) [BMC2AY1000AN](#)
[LLMGA160808T601RG](#) [2176487-1](#) [LLMCC201208T250NG](#)