









Recommended PCB Layout
Tolerance: ± 0.05 (Top View)



Gasket
(Included)

Materials and Finish

Insulator & Cap: High Temp.,
UL94V-0 Rated,
Color: Black

Contact Material:
Copper Alloy

Contact Plating:
Standard: Gold Flash Plated in
Contact Area, Matte Tin in Solder
Area.

Shell: Stainless Steel,
30u" Min. Nickel Plated

Gasket: Silicone Rubber, Black

Electrical Specifications

Current Rating: 3.0A

Rated Voltage: 28V

Contact Resistance:
40 Milliohms Max.

Insulation Resistance:
100 Megohms Min.

Dielectric Withstanding Voltage:
100V AC RMS For 1 Minute.

Mechanical Specifications

Insertion Force: 5N - 20N

Extraction Force: 8N - 20N
(6N - 20N After 10,000 Cycles)

Durability: 10,000 Cycles

Operating Temperature:
-20°C to 85°C

Ingress Protection: IP67

USB Type-C Pin Assignments


Pin	Signal	Pin	Signal
A5	CC1	A1	GND
A9	Vbus	B9	Vbus
A12	GND	B5	CC2

Tolerances

X.X ± 0.35
X.XX ± 0.25
Unless Stated
Otherwise

RoHS COMPLIANT

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	12/18/24	New Drawing	C. Kelleher	C. Kelleher	C. Kelleher	12/11/24
A0.1	01/10/25	Add Gasket, Voltage	C. Kelleher	C. Kelleher	C. Kelleher	
A1	04/23/25	Release Drawing	K.Wang	C. Kelleher	C. Kelleher	
A1.1	05/07/25	Update Drawing	K.Wang	C. Kelleher	C. Kelleher	



mm

KUSBV67X-TH-CS-6-BTR

IP67 USB Type C Receptacle, Vertical, Thru-Hole,

6 Pin, Black, Tape & Reel W/Pick-up Cap, RoHS



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [Kycon](#) manufacturer:

Other Similar products are found below :

[A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [217450-1](#) [KUSBX-AS2N-W](#) [30-498-6](#) [SK-60A-2](#) [30-489](#) [A-USB A-2P-C](#) [USBFTVSCCG](#) [E8110-001-01](#) [MUSBA81130](#) [USB3FTV7APEG](#) [4198](#) [17-200011](#) [1040870124](#) [914-614A2025S10200](#) [1002-001-BL-KIT](#) [MUSBR-AHD2-M41-SK](#) [GSB3116344HR](#) [GSB343K331HR](#) [USBF21GSCC](#) [U221-041N-1WVS62-F5D](#) [HYCW153-USBD05-500B](#) [HYCW219-USBD05-075B](#) [HYCW148-USBD05-117B](#) [HYCW149-USBD05-740B](#) [HYCW204-USBD05-108B](#) [HYCW214-USBA04-113B](#) [HYCW213-USBA04-113B](#) [KMMX-BSMT35S-1-B30TR](#) [GT-2A001F-CGNG1](#) [GT-USB-7010i](#) [HC-ST-003-07-J](#) [918-418K2022Y40028](#) [920-462A2021Y10104](#) [AF 90°](#) [WJDG ZB](#) [TYPE-C 6P LCH10.5](#) [MICRO 7.2ZB5.0](#) [AM 180°](#) [MINI 5PTP-GZ](#) [TYPE-C 16PLC-H10.0](#) [TYPE-C 6PLCH10.5 073](#) [MINI 5P](#) [90°4J](#) [10.0 180°ZCZB-HJ](#) [AF 180°WJB15.0](#) [TYPE-C 6P CC](#) [MICRO 5.9ZB5.0\(040\)](#) [10.0 HCHTZB6.3](#) [10.0 180° ZCJB-HJ](#) [TYPE-C](#) [14PLC-H10.0](#)