



# xPico® Wi-Fi SMT

Embedded Wireless  
Device Server



## AN INNOVATIVE, MOBILE-READY, WI-FI® SOLUTION FOR M2M AND IOT APPLICATIONS

As an innovative, mobile ready solution, the Lantronix® xPico® Wi-Fi SMT device server sets new standards for its customers by enabling IoT applications that deliver highly desired smartphone and tablet functionality. Once complex, Wi-Fi implementation is now greatly simplified with xPico Wi-Fi SMT's unique and robust feature set including: simultaneous Soft AP and client mode, zero host load and configuration by customization. These, along with Lantronix's commitment to reliability, quality and ease of use, support developers to quickly leverage mobile solutions for their applications, while reducing their total cost of ownership across their products' life cycle.

### Tablet & Smartphone Enable Your Devices

Access your data and devices from anywhere – wired or wireless. Lantronix's device server application and protocol stacks enable seamless remote access to device data, simplifying design integration, all while providing robust connectivity – including the ability to access data from any mobile device, including smartphones and tablets.

### Robust Networking Solution

The Lantronix xPico Wi-Fi SMT device is an extremely compact, low power networking solution that enables wireless LAN connectivity on virtually any solution with a SPI, USB (device) or serial interface.

### Simultaneous Access Point & Client Mode

The xPico Wi-Fi SMT is a state-of-the-art solution that offers all the functions one can expect including a unique simultaneous Soft AP and client mode. This allows for easy points of access for those devices that do not include or have a limited user interface while maintaining a secure network connection.

### Cost Savings & Faster Time-To-Market

As one of the smallest embedded device servers in the world, xPico Wi-Fi SMT can be utilized in designs typically intended for chip solutions. Its "zero host load" eliminates the need for drivers on the connected microcontroller, thus making implementation easy and fast with virtually no need to write a single line of code. This makes the xPico Wi-Fi SMT an ideal choice to offload Wi-Fi connectivity to your products, which translates to considerably lower development costs and faster time-to-market.

As xPico Wi-Fi SMT meets FCC Class B, UL and EN EMC and safety compliance, your development time is shortened. xPico Wi-Fi SMT can reduce the overall cost of ownership compared to the competition.

### xPico Wi-Fi SMT Highlights

- Low profile footprint: 18.3 x 26.1 x 3.0mm
- Version available with an on-module antenna
- Low power (6µA Standby)
- Can be operated off batteries
- IEEE 802.11 b/g/n (2.4 GHz)
- Simultaneous Soft AP and client mode
- Complete device server application with full IP stack and web server
- Dual serial port with data rate of up to 921 kbps
- SPI with clock rate of 30MHz
- USB 2.0 full rate device mode\*
- Industrial temperature range: -40° to +85° C
- 5-Year limited warranty



## Features and Specifications

### Wireless LAN Interface

- IEEE 802.11 b/g and IEEE 802.11n (single stream) WLAN interface (2.4 GHz only)
- IEEE 802.11 d/h/i/j/k/w/r
- u.FL connector and RF pads for optional external antenna (XPCW1002100B)

### Serial Interface

- Two Serial CMOS Ports (3.3V, 5V tolerant)
- 300 to 921.6 Kbps
- Flow control XON/XOFF, RTS/CTS
- Lantronix tunneling application

### Host Interface

- Dual Serial Port, SPI, USB 2.0\* (device)
- 8 GPIO

### Network Protocols

- TCP/IP, UDP/IP\*, DHCP, ARP, ICMP, DHCP, Auto-IP, DNS

### Networking Capabilities

- Soft Access Point with DHCP Server
- QuickConnect: Dynamic Profiles facilitate easy and rapid connections to access points

### Management and Control

- Web Server - Landing Page
- CLI (Serial Monitor Port)
- XML import and Export (XCR)
- Field upgradable firmware (OTA)

### Security

- IEEE 802.11i Support – WPA-Personal, WPA2-Personal
- 256-bit AES Encryption\*

### Architecture

- ARM Cortex M3 class processor with on-chip Flash and SRAM
- 1MB Flash and 128 KB SRAM
- 1MB SPI Flash storage

### Power

- Input Voltage: 3.3VDC
- Low power consumption of approximately 6µA standby

### Physical Interface

- 56-Pad SMT Castellation

### Environmental

- Operating Temperature: -40° to +85° C
- Storage Temperature : -40° to +85° C
- Relative Humidity: 0% to 90% non-condensing

### Certifications

- FCC Class B, UL and EN EMC

### Packaging

- Dimensions:
  - XPCW1002100: 26.1mm (L) x 18.3mm (W) x 3.0mm (H)

\*Software support for these features available in a future software release.

Please contact sales representatives for more information.

©2017 Lantronix, Inc. All rights reserved. Lantronix and xPico are registered trademarks of Lantronix, Inc. in the U.S. and certain other countries. Wi-Fi is a registered trademark of Wi-Fi Alliance. All other trademarks and trade names are the property of their respective owners. MPB-00018 Rev C

- XPCW1003100: 30.1mm (L) x 18.3mm (W) x 3.0mm (H)
- Weight: 2.5g

### Warranty

- 5-Year Limited

### Tablet & Smartphone enable devices

xPico WiFi SMT provides simultaneous Soft AP and Client mode, allowing for easy points of access while maintaining a secure network without the need for special clients.

### Other members of the xPico product family:

#### xPico

A chip-sized networking solution that enables Ethernet connectivity on virtually any device.

#### xPico IAP

A chip-sized networking solution that enables Ethernet connectivity on devices for industrial and automation applications that require MODBUS support.

Part Number	Description
XPCW1002100B	xPico Wi-Fi W1002 – IEEE 802.11 b/g/n Device Server Module, Extended Temp, SMT, Bulk, RoHS
XPCW1003100B	xPico Wi-Fi W1003 – IEEE 802.11 b/g/n Device Server Module, Extended Temp, w/ On-Module Antenna SMT, Bulk, RoHS
XPCW1003100S	xPico Wi-Fi W1003 – IEEE 802.11 b/g/n Device Server Module, Extended Temp, SMT, Sample, RoHS
XPCW1002100K	EVALUATION KIT with xPico Wi-Fi W1002 Wi-Fi Module, SMT on Carrier Board, IEEE 802.11 b/g/n, with U.FL and Antenna Sample
XPCW1003100K	EVALUATION KIT with xPico Wi-Fi W1003 Wi-Fi Module, SMT 802.11 b/g/n, On-Module Antenna

### Ordering Information

#### Americas

800.422.7055  
sales@lantronix.com  
http://www.lantronix.com  
NASDAQ: LTRX

#### Asia/Pacific/Japan

+852 3428.2338  
asiapacific\_sales@lantronix.com  
China: +86.21.6237.8868  
Shanghai@lantronix.com

#### Europe

+31 (0) 76.52.3.6.74 4  
EMEA@lantronix.com

India: +91 994-551-2488  
Sales\_India@lantronix.com

Indonesia: +91 994-551-2488  
sales\_indonesia@lantronix.com

Japan: +81.3.3273.8850  
Sales\_Japan@lantronix.com

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Servers](#) category:*

*Click to view products by [Lantronix](#) manufacturer:*

Other Similar products are found below :

[70002259](#) [70002261](#) [VESR321-ML](#) [NBLM-LM1CR](#) [EKI-1528TI-VDC-CE](#) [ADAM-4570L-DE](#) [ADAM-4571-CE](#) [XPC100200S-01](#) [ESP904](#)  
[96NIC-10G2P-IN](#) [ADAM-4570-CE](#) [ADAM-4571L-DE](#) [AGS-913I-R11A1E](#) [EKI-1361-MB-BE](#) [EKI-1362-BE](#) [EKI-1362-MB-BE](#) [EKI-1522-CE](#) [EKI-1524I-CE](#) [EKI-1526-CE](#) [EKI-1526I-CE](#) [EKI-1528-CE](#) [ABDN-ER-IN5018](#) [ESP901](#) [ESP902](#) [ESR901](#) [ESR904](#) [BB-VESR902T](#)  
[VESR902D](#) [70002412](#) [70002263](#) [70002265](#) [70002269](#) [70002271](#) [70002277](#) [70002279](#) [70002281](#) [70002285](#) [70002404](#) [70002406](#) [70002410](#)  
[70002414](#) [70002418](#) [ED1100002-01](#) [ED2100002-01](#) [ED41000P0-01](#) [ED41000P2-01](#) [PEN100100A-01-IT](#) [PXC2102G2-01](#) [SD2101002-11](#)  
[UD1100002-01](#)