



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REV A DRAWING RELEASED	11/15/2018	DGUTTADAUR
B	ECN 10958; ADD CABLE CHARACTERISTICS INFORMATION	01/28/2021	DGUTTADAUR



PART NUMBER	LENGTH FEET [METERS]
TRD628ALS-BLU-1	1.0 [.30]
TRD628ALS-BLU-3	3.0 [.91]
TRD628ALS-BLU-5	5.0 [1.52]
TRD628ALS-BLU-7	7.0 [2.13]
TRD628ALS-BLU-10	10.0 [3.05]
TRD628ALS-BLU-14	14.0 [4.26]
TRD628ALS-BLU-20	20.0[6.10]

NOTES:

MATERIAL:

PLUG HOUSING: POLYCARBONATE, CLEAR, UL94V-0
CONTACTS: PHOSPHOR BRONZE
CABLE JACKET: LOW SMOKE ZERO HALOGEN, BLUE
PLUG SHIELDING: BRASS

FINISH:

CONTACTS: 50 μ INCHES GOLD IN CONTACT AREA
OVER 100 μ INCHES NICKEL PLATE OVERALL
PLUG SHIELDING: NICKEL PLATED

CABLE CHARACTERISTICS:

UL TYPE: CM-LS, 1685
CORROSION RESISTANCE: IEC 60754
SMOKE EMISSION: UL 1685
SHIELDED, FOUR TWISTED PAIR, CAT 6A MODULAR CABLE
CONDUCTORS: 28 AWG STRANDED TINNED COPPER
SHIELDING: ALUMINUM POLYESTER ALUMINUM FOIL SHIELD AND DRAIN WIRE
CABLE JACKET NOM. DIAM. .190[4.83]

MISCELLANEOUS:

PLUG CONFORMS TO TIA-1096.
OPERATING TEMPERATURE RANGE: -20°C TO 75 °C
CABLE ASSEMBLY TO BE TESTED FOR CONTINUITY.
CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN
ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]		APPROVALS	DATE	 an INFINITI® brand 50 High Street, West Mill, North Andover, MA 01845 USA. Phone: 1.800.341.5266 1.978.682.6936			
OVERALL CABLE LENGTH TOLERANCE:		DRAWN BY DCUI	09/20/2018			CATEGORY	TELECOM/MODULAR
<12 [305] = +1 [25] / -0		CHECKED BY SPAN	09/20/2018				
>12 [305] <60 [1524] = +2 [51] / -0		APPROVED BY DGUTTADAUR	09/20/2018				
>60 [1524] <120 [3048] = +4 [102] / -0							
>120 [3048] <300 [7620] = +6 [152] / -0							
>300 [7620] = +5% / -0							
ALL OTHER DIMENSIONAL TOLERANCES:		CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		PRODUCT DESCRIPTION			
.X = ± .2 [5] FRACTIONS				CA CAT6A 28AWG RJ45 BLU, LSZH&CM			
.XX = ± .02 [.5] ± 1/32				SIZE A			
.XXX = ± .005 [.13] ANGLES ± 1°				CAGE CODE 43321			
THIRD-ANGLE PROJECTION		COLOR VARIATIONS MAY OCCUR		DWG. NO. TRD628ALS-BLU			
				REV. B			
				SCALE: NONE			
				CAD FILE: TRD628ALS-BLU.SLDRW			
				SHEET 1 OF 1			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ethernet Cables / Networking Cables](#) ***category:***

Click to view products by [L-Com](#) ***manufacturer:***

Other Similar products are found below :

[73-7795-1](#) [MCJB2-10P6Q7-120](#) [84909-0204](#) [1-1997459-2](#) [1-1997459-3](#) [ASP-144414-04](#) [E16A06002M030](#) [18169-0524](#) [1969343-6](#)
[C5UMB3FBG](#) [21949-1](#) [360031](#) [AX100351](#) [09459711142](#) [73-7793-1](#) [WHU18-1836-060](#) [1-3636-620-5214](#) [STS](#) [09470303023](#) [09459711118](#)
[1404682](#) [C5SMB14FBG](#) [CA21116001](#) [WK-100](#) [UTPCH22VLY](#) [UTPSP50BLY](#) [C6F1106003](#) [UTPSP16MRDY](#) [UTPSP16MGRY](#)
[UTP28CH30MBL](#) [AX105520](#) [CAPFCU-B25](#) [CB8MMBK-B100](#) [DK-1511-002/B](#) [STP6X1BU](#) [904873-000](#) [17-103134](#) [1110401155](#)
[09459711186](#) [EL6614](#) [MRC191ZN79H1](#) [SSFPP-P03M0-2](#) [1426514](#) [1413684](#) [1426515](#) [1414043](#) [1413685](#) [7000-44511-6590150](#) [7000-](#)
[44511-7940300](#) [7000-44561-7940150](#)