



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REV A DRAWING RELEASED	04/01/2019	DFRISIELLO



MODEL NUMBER	LENGTH FEET [METERS]
TRD695AHFP-BLK-1	1.0 [.30]
TRD695AHFP-BLK-2	2.0 [.61]
TRD695AHFP-BLK-3	3.0 [.91]
TRD695AHFP-BLK-5	5.0 [1.52]
TRD695AHFP-BLK-10	10.0 [3.05]
TRD695AHFP-BLK-15	15.0 [4.57]
TRD695AHFP-BLK-25	25.0 [7.62]
TRD695AHFP-BLK-50	50.0 [15.24]
TRD695AHFP-BLK-75	75.0 [22.86]
TRD695AHFP-BLK-100	100.0 [30.48]
TRD695AHFP-BLK-125	125.0 [38.10]
TRD695AHFP-BLK-150	150.0 [45.72]



CABLE CHARACTERISTICS:

VOLTAGE RATING: 300V


TEMPERATURE RANGE: -40° C TO +75° C

NOTES:

1. PLUG CONFORMS TO TIA-1096
2. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
3. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM PACKAGING SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:

EU ROHS DIRECTIVE (MOST RECENT RELEASED VERSION)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0% ALL OTHER DIMENSIONAL TOLERANCES: X = ±.2 [5.08] XX = ±.02 [1.51] XXX = ±.005 [1.3]	APPROVALS		DATE		 50 HIGH STREET NORTH ANDOVER, MA 01845
	DRAWN BY DFRISIELLO		03/28/2019		
	CHECKED BY DGUTTADAURO		03/28/2019		
	APPROVED BY DGUTTADAURO		03/28/2019		
	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY				TELECOM/MODULAR PRODUCT DESCRIPTION RJ45 C6A SF/UTP 26STR PUR BLK HI FLEX OUTDOOR 300V
	COLOR VARIATIONS MAY OCCUR				
	SIZE A	FSCM NO. 43321	DWG. NO. TRD695AHFP-BLK	REV. A	
	SCALE: NONE		CAD FILE: TRD695AHFP-BLK.SLDDRW	SHEET 1 OF 1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ethernet Cables / Networking Cables](#) ***category:***

Click to view products by [L-Com](#) ***manufacturer:***

Other Similar products are found below :

[73-7795-1](#) [MCJB2-10P6Q7-120](#) [84909-0204](#) [1-1997459-2](#) [1-1997459-3](#) [ASP-144414-04](#) [E16A06002M030](#) [18169-0524](#) [1969343-6](#)
[C5UMB3FBG](#) [21949-1](#) [360031](#) [AX100351](#) [09459711142](#) [73-7793-1](#) [WHU18-1836-060](#) [1-3636-620-5214](#) [STS](#) [09470303023](#) [09459711118](#)
[1404682](#) [C5SMB14FBG](#) [CA21116001](#) [WK-100](#) [UTPCH22VLY](#) [UTPSP50BLY](#) [C6F1106003](#) [UTPSP16MRDY](#) [UTPSP16MGRY](#)
[UTP28CH30MBL](#) [AX105520](#) [CAPFCU-B25](#) [CB8MMBK-B100](#) [DK-1511-002/B](#) [STP6X1BU](#) [904873-000](#) [17-103134](#) [1110401155](#)
[09459711186](#) [EL6614](#) [MRC191ZN79H1](#) [SSFPP-P03M0-2](#) [1426514](#) [1413684](#) [1426515](#) [1414043](#) [1413685](#) [7000-44511-6590150](#) [7000-](#)
[44511-7940300](#) [7000-44561-7940150](#)