

6

5


4

3

2

1

| REVISION |     |                       |            |                        |
|----------|-----|-----------------------|------------|------------------------|
| ZONE     | REV | DESCRIPTION           | DATE       | CHANGED BY             |
|          | C   | UPDATED PER ECO-14731 | 07/11/2025 | BZHANG                 |
|          |     |                       |            | APPROVED<br>GUTTADAURO |



## NOTES

## MATERIAL:

SLIP ON HOOD: THERMOPLASTIC POLYURETHANE, BLACK  
INSULATOR: NYLON, BLACK  
SHELL/SCREW NUT: BRASS, NICKEL PLATE  
M12 CONTACTS: PHOSPHOR BRONZE, 15μ" MIN. GOLD PLATE  
SNAGLESS BOOT: LOW SMOKE ZERO HALOGEN, BLACK  
RJ45 HOUSING: POLYCARBONATE, CLEAR UL96V-0  
RJ45 SHIELD/STRAIN RELIEF: BRASS, NICKEL PLATE  
RJ45 CONTACTS: PHOSPHOR BRONZE, 50μ" MIN. GOLD PLATE IN CONTACT AREA OVER NICKEL PLATE OVERALL

## ELECTRICAL:

NOMINAL VOLTAGE RATING: 125 VAC/VDC  
MAX CURRENT: 1.5A

## APPLICATION:

INGRESS PROTECTION RATING IS IP68 (MATED,P1 ONLY).

## ENVIRONMENTAL:

OPERATING TEMPERATURE RANGE: -40°C TO +80°C  
CABLE JACKET: OIL, SUNLIGHT AND WELD SPLATTER RESISTANT  
CABLE FLEX LIFE: 1 MILLION CYCLE TEST (10X CABLE OD)  
10 MILLION CYCLE TEST (20X CABLE OD)


## MISCELLANEOUS

CABLE ASSEMBLIES TO BE TESTED FOR CONTINUITY  
CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED.

## REGULATORY COMPLIANCE:

EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



| PART NUMBER    | LENGTH |        |
|----------------|--------|--------|
|                | FEET   | METERS |
| TRG504-T4T-05M | 1.64   | 0.5    |
| TRG504-T4T-1M  | 3.28   | 1.0    |
| TRG504-T4T-2M  | 6.56   | 2.0    |
| TRG504-T4T-3M  | 9.84   | 3.0    |
| TRG504-T4T-5M  | 16.41  | 5.0    |
| TRG504-T4T-10M | 32.82  | 10.0   |
| TRG504-T4T-15M | 49.22  | 15.0   |

UNLESS OTHERWISE SPECIFIED  
LEADING DIMENSIONS ARE INCHES  
DIMENSIONS IN [ ] ARE MILLIMETERS

TOLERANCES:  
X = ±.2 [5]  
.XX = ±.02 [0.5]  
.XXX = ±.005 [0.13]  
FRACTIONS  
± 1/32  
ANGLES ± 1°

CABLE LENGTH TOLERANCES:  
≤12 [305] = +1 [25] / -0  
>12 [305] ≤ 60 [1524] = +2 [51] / -0  
>60 [1524] ≤ 120 [3048] = +4 [102] / -0  
>120 [3048] ≤ 300 [7620] = +6 [152] / -0  
>300 [7620] = +5% / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY  
AND SUBJECT TO CHANGE WITHOUT NOTICE  
UN-DIMENSIONED/NON-CRITICAL FEATURES  
MAY VARY IN SIZE AND LOCATION  
COLORS MAY VARY

**L-com**  
an INFINIT® brand

Website: [www.L-com.com](http://www.L-com.com)  
Phone: 1.800.341.5266 | 1.978.682.6936



INTERPRET ALL DIMENSIONS AND  
TOLERANCES PER ASME Y14.5

SCALE: NONE SHEET: 1 OF 1

DESCRIPTION  
CATEGORY 5e M12 IP68 4 POSITION D CODE DOUBLE  
SHIELDED SF/UTP INDUSTRIAL OUTDOOR HIGH FLEX CABLE,  
M12 M TO RJ45 M, CMX TPE, TEAL

| SIZE | CAGE CODE | DRAWN BY | ITEM NO.   | REV |
|------|-----------|----------|------------|-----|
| A    | 43321     | DCUI     | TRG504-T4T | C   |

6

5

4

3

2

1

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for*** [Ethernet Cables / Networking Cables](#) ***category:***

***Click to view products by*** [L-Com](#) ***manufacturer:***

Other Similar products are found below :

[73-7795-1](#) [MCJB2-10P6Q7-120](#) [84909-0204](#) [1-1997459-2](#) [1-1997459-3](#) [ASP-144414-04](#) [E16A06002M030](#) [18169-0524](#) [1969343-6](#)  
[C5UMB3FBG](#) [21949-1](#) [360031](#) [AX100351](#) [09459711142](#) [73-7793-1](#) [WHU18-1836-060](#) [1-3636-620-5214](#) [STS](#) [09470303023](#) [09459711118](#)  
[1404682](#) [C5SMB14FBG](#) [CA21116001](#) [WK-100](#) [UTPCH22VLY](#) [UTPSP50BLY](#) [C6F1106003](#) [UTPSP16MRDY](#) [UTPSP16MGRY](#)  
[UTP28CH30MBL](#) [AX105520](#) [CAPFCU-B25](#) [CB8MMBK-B100](#) [DK-1511-002/B](#) [STP6X1BU](#) [904873-000](#) [17-103134](#) [1110401155](#)  
[09459711186](#) [EL6614](#) [MRC191ZN79H1](#) [SSFPP-P03M0-2](#) [1426514](#) [1413684](#) [1426515](#) [1414043](#) [1413685](#) [7000-44511-6590150](#) [7000-](#)  
[44511-7940300](#) [7000-44561-7940150](#)