

Standard



Image for illustrative purpose only

Summary

[Request a quote](#)

[BKT series](#)

[See video assembly instructions](#)

[Customer Drawing](#)

Number of contacts Low Voltage	12
Wire Size/AWG	30 - 22
Gender	Standard
Plug	Plug - Straight
Locking system	Push-pull
Jacket cable outside diameter [mm]	7.80 - 9.20 mm
Size	3B

https://www.lemo.com/int_en/solutions/originals/b-indoor-keyed/fgg-3b-312-clad92z.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Suggested matching part

EGG.3B.312.CLL
PHG.3B.312.CLLD92Z

Series

B - Indoor keyed

https://www.lemo.com/int_en/solutions/originals/b-indoor-keyed/fgg-3b-312-clad92z.html

LEMO products and services are provided “as is”. LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Technical details

Electrical Configuration

Number of contacts Low Voltage	12
Contact Termination Low voltage	Solder
R (max) - electrical contact resistance	4.8 mOhm
Insert configuration value	3B.312 - 12 Low Voltage
Insulator	L: PEEK (UL 94 / V-0/1.5)
Rated current	9 A
Test voltage contact-contact	2 kV DC
Test voltage contact-shell	1.4 kV DC
Max. Solid Conductor	0.34 mm ² (AWG 22)
Max. Stranded Conductor	0.34 mm ² (AWG 22)
Bucket Dia.	0.8 mm (0.031 in)
Contact Dia.	0.9 mm (0.035 in)
Wire Size/AWG	30 - 22
Gender	Standard

Form & Material

Shell style / Model id	FG - Straight plug, cable adapter and nut for fitting a bend relief
Plug	Straight
Housing material	Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces
Locking system	Push-pull
Keying	G: 1 key (alpha=0, plug: male contacts, receptacle: female contacts)
Colour	Grey
Variant	Nut for fitting a bend relief
Weight	46.96 g

https://www.lemo.com/int_en/solutions/originals/b-indoor-keyed/fgg-3b-312-clad92z.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Environment

Technical domain	Audio Video, Energy and Industrial, Medical, Semiconductor, Specialties and Other, Test and Measurement, Transportation, Aerospace and UAV
Environmental sealing (IP rating)	IP50
Endurance	5000 mating cycles
Temperature range	-55°C / +250°C (max. temperature valid for short periods of use.)
Climatic Category	55/175/21
Humidity (max)	<=95% [at 60 deg C /140 F]
Shielding (min)	75 dB (10 MHz)
Shielding (min)	40 dB (1 GHz)
Shock Resistance	100 g [6 ms]
Vibration	15 g [10 Hz - 2000 Hz]
Salt Spray Corrosion	>1000 hr

Cable fixation

Cable termination protection	For cable bend relief
Fixation type	Cable collet
Jacket cable outside diameter [mm]	7.80 - 9.20 mm

Recommended By Lemo

Caps

Compatible cap	BFG.3B.112.NAS
Plastic Cap	BFG.3B.100.PCSG
Soft Cap	BFZ.3B.100.SCN

Bend Reliefs

GMA.3B.090.DG	GMA.3B.090.DA	GMA.3B.090.DB
GMA.3B.090.DJ	GMA.3B.090.DM	GMA.3B.090.DN
GMA.3B.090.DR	GMA.3B.090.DS	GMA.3B.090.DV

Tools

Spanner	DCP.91.023.TN
Spanner wrench	DCD.3B.ZZZ.PA150

https://www.lemo.com/int_en/solutions/originals/b-indoor-keyed/fgg-3b-312-clad92z.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Circular Push Pull Connectors](#) category:

Click to view products by [LEMO](#) manufacturer:

Other Similar products are found below :

[6407-249V-11273P](#) [6408-201V-13273](#) [6408-202V-13343](#) [6408-202V-17343](#) [FFA.1S.130.LC](#) [6408-201V-11273](#) [6408-201V-11343](#) [6408-202V-25273](#) [GMA.4B.013.DN](#) [1331E103MZ](#) [342491](#) [PCA.1S.303.ZLLT](#) [FHG.00.305.CLAD35](#) [1332E319FZ](#) [341140](#) [300374](#) [SOB.187.GN](#)
[JBXEA2G003MSNDS](#) [GA1M07-P08LFG0-0000](#) [JBXFN0G07MSSDSR](#) [1331M295MS1](#) [FNG.1B.304.U2034](#) [JBXER1G04MCSDSR](#)
[JBXEA2G04MSNDS](#) [JBXER1G03MCSDSR](#) [S41M08-P02MPN0-528S](#) [702.098.001.000.000](#) [FGG.2B.560.ZZF](#) [FGG.2B.560.ZZK](#)
[FGG.4B.555.ZZF](#) [FGG.4B.555.ZZK](#) [S10K0C-P05PFG0-5000](#) [FGG.2B.314.CYBM21Z](#) [FLA.2S.303.CLAC62Z](#) [1332E103MZ](#)
[PHG.2T.326.CLLC55](#) [FCG.4B.133.CZZ](#) [FGA.2B.306.CLAD62Z](#) [FGG.2B.514.CLAD92Z](#) [NX-C10WAM-P09XMM0-0000](#) [NX-G80YAR-P03WJG0-000L](#) [NX-G81YAR-P05WJG0-000L](#) [EGN.2M.304.XLM](#) [pcp.2s.304.cllc87](#) [EGG.2B.660.ZZF](#) [EGG.2B.660.ZZK](#)
[715.645.097.003.945](#) [702.645.900.320.000](#) [09 0412 80 04](#) [300196](#)