



LEOPARD IMAGING INC

LI-JETSON-IMX274-DUAL

Data Sheet

Key Features


- Compatible with Nvidia Jetson TX1 / TX2 Developer Kit
- Sony Diagonal 7.20 mm (Type 1/2.5) CMOS Image Sensor IMX274
- Active Pixels: 3864 (H) x 2196 (V)
- Pixel Size: 1.62 x 1.62 μm
- Dual Camera
- Baseline: 50 cm
- Color Sensor
- Interface: MIPI output
- Supports M12 lens
- Includes IR cut filter (on lens)
- Connector: QTH-060-04-H-D-A-TR
- Module Size: 75 x 40 mm
- Weight: ~ 34 g
- Part#:

LI-JETSON-IMX274-DUAL-HK
LI-JETSON-IMX274-DUAL-SUN



Overview



The LI-JETSON-IMX274-DUAL is a high-performance 8 Megapixel stereo camera based on two Sony IMX274 image sensors and a MIPI connector. It's compatible with Nvidia Jetson TX1 / TX2 Developer kit and supports 3840 x 2160 (4K) @ 60 fps video output.



Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035, USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email: sales@leopardimaging.com
Website: www.leopardimaging.com

Lens Information






LI-JETSON-IMX274-HK	LI-JETSON-IMX274-SUN
	
■ Lens Part#: HK-8145-457-1 ■ Focal Length: 8 mm ■ F/#: 2.0 ■ Distortion: < -5% ■ FOV(D/H/V): 51° / 42° / 24° ■ BFL: 7.62 mm ■ FB: 6.51 mm ■ Element: 6G + IRF ■ Thread size: M12 x P0.5 ■ IR cut filter spec: - Tavg ≥ 88% @ 440 – 620 nm - T = 50% @ 648 +/- 10 nm - Tavg ≤ 3% @ 700 – 1000 nm - T < 5% @ 1050 nm	■ Lens Part#: SYD1201A ■ Focal Length: 3.7 mm ■ F/#: 2.8 +/- 5% ■ Distortion: -1.0% ■ FOV(D/H/V): 92° / 83° / 53° ■ BFL: 3.99 +/- 0.2 mm ■ FFL: 3.69 +/- 0.3 mm ■ TTL: 24.83 +/- 0.3 mm ■ Element: 4G2GM + IRF ■ Thread size: M12 x P0.5 ■ IR cut filter spec: - Tavg > 85% @ 420 – 650 nm



Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035, USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email: sales@leopardimaging.com
Website: www.leopardimaging.com

Dimensions




Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035, USA
 Phone: +1-408-263-0988
 Fax: +1-408-217-1960
 Email: sales@leopardimaging.com
 Website: www.leopardimaging.com


Pin Assignment

Connector J10

- Part#: QTH-060-04-H-D-A-TR
- Number of Positions: 120
- Number of Rows: 2
- Pitch: 0.5 mm



EEPROM



Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035, USA
 Phone: +1-408-263-0988
 Fax: +1-408-217-1960
 Email: sales@leopardimaging.com
 Website: www.leopardimaging.com

Compatible with Nvidia Jetson TX1/TX2 Developer Kit



Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035, USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email: sales@leopardimaging.com
Website: www.leopardimaging.com

Reliability Testing

Temperature test	Conditions	Time
High temperature	60°C	24H
Low temperature	-10°C	24H
Vibration Test	Conditions	Time
Random vibration	200 rmp (1 box)	30 min
Drop Test	Weight	Height
Drop	0.45-9.54 Kg (1 box)	76 cm
Drop	9.55-18.63 Kg (1 box)	61 cm
Drop	18.64-27.72 Kg (1 box)	46 cm
Drop	27.73-45.45 Kg (1 box)	31 cm
Other Test		
Exterior Visual Inspection	After each phase of the Temperature, Vibration and Drop test, do exterior visual inspection. 1. No obvious dents or scratches 2. No parts loosening or falling apart 3. No missing parts	
Image Test	After each phase of the Temperature, Vibration and Drop test, do image test. 1. No dust issue 2. No dead pixels 3. No unexpected Noises 4. No other unexpected image issues	
Focus Test	After each phase of the Temperature, Vibration and Drop test, check the focus of the camera at required focusing distance.	
EEPROM	Check the EEPROM ID of each unit	



Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035, USA
 Phone: +1-408-263-0988
 Fax: +1-408-217-1960
 Email: sales@leopardimaging.com
 Website: www.leopardimaging.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cameras & Camera Modules](#) ***category:***

Click to view products by [Leopard Imaging](#) ***manufacturer:***

Other Similar products are found below :

[1202](#) [73-540-420I](#) [Web Camera module 5.0M pixel](#) [LI-USB30-OX05B1S-VCSEL-OMS-96717-200H](#) [LI-USB30-IMX490-GMSL2-120H](#) [LI-USB30-OV2312-GMSL2-110H](#) [LI-IMX675-MIPI-076H](#) [82635DSD456](#) [LI-AR0234CS-GMSL2-OWL](#) [5390](#) [5389](#) [107821](#) [LI-IMX728-9295-070H](#) [OAK-1-W-PoE](#) [LI-AR0341-GM2B-124H](#) [LI-IMX563-MIPI-AF](#) [LI-VENUS-OX03F10-OAX40-GM2A-060H](#) [STC-MCS163U3V](#) [LI-OG01A1B-MIPI-146D](#) [LI-VB1940-VCL-OMS-FP3-137H](#) [106681](#) [107402](#) [108010](#) [1202](#) [AC164150](#) [SEN0158](#) [2392](#) [106695](#) [106988](#) [107146](#) [106732](#) [LI-USB30-AR023ZWDR](#) [LI-OV2640-USB-M6](#) [LI-OV5640-MIPI-AF-NIR](#) [82635DSASMDLPRQ](#) [106692](#) [106687](#) [106493](#) [106688](#) [106682](#) [106694](#) [106989](#) [106693](#) [106696](#) [106683](#) [107140](#) [106982](#) [106685](#) [107141](#) [107147](#)