







G	RoHS									G																																																																																	
F	SPECIFICATIONS Rated Current:1.5AMP Contact Resistance:20mΩ Max Withstand Voltage:500V AC/DC Insulation Resistance:1000MΩ Min Operation Temperature:-40°c to +105°c						Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)			F																																																																																	
E	Contact Material:Brass Contact Plating:Au Over Ni Insulator Material:Polyester(UL94V-0) Standard: PA6T Max.Processing Temp: 230°C for 30-60 seconds (260°C for 10 seconds)									E																																																																																	
D										D																																																																																	
C										C																																																																																	
B										B																																																																																	
A	<table border="1"><thead><tr><th colspan="4"></th><th colspan="2">OPERATION</th><th colspan="2">DRAW</th><th>SCALE</th><th>FIT</th><th colspan="2" rowspan="4">深圳市连盛精密连接器有限公司</th></tr><tr><th colspan="4"></th><th>X.X</th><th>±0.30</th><th colspan="2"></th><th>UNIT</th><th>mm</th></tr><tr><th colspan="4"></th><th>X.XX</th><th>±0.20</th><th colspan="2">CHECK</th><th>SIZE</th><th>A4</th></tr><tr><th colspan="4"></th><th>X.XXX</th><th>±0.10</th><th colspan="2"></th><th>SHEET</th><th>1/1</th></tr><tr><th>REV</th><th>DATE</th><th>MODIFICATION DESCRIPTION</th><th>CHANGE</th><th></th><th>Angle</th><th>±3°</th><th>APPROVE</th><th></th><th></th><th>TITLE:</th><th>PART NO.</th><th>1020200135</th></tr><tr><td></td><td></td><td></td><td></td><td></td><th>DIM</th><th>TOL</th><td></td><td></td><td></td><td></td><td></td><td>2.0FH H4.3mm 2x4pin SMT W4.50</td></tr></thead><tbody><tr><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td></td><td></td><td></td><td></td></tr></tbody></table>													OPERATION		DRAW		SCALE	FIT	深圳市连盛精密连接器有限公司						X.X	±0.30			UNIT	mm					X.XX	±0.20	CHECK		SIZE	A4					X.XXX	±0.10			SHEET	1/1	REV	DATE	MODIFICATION DESCRIPTION	CHANGE		Angle	±3°	APPROVE			TITLE:	PART NO.	1020200135						DIM	TOL						2.0FH H4.3mm 2x4pin SMT W4.50	1	2	3	4	5	6	7	8	9					A
				OPERATION		DRAW		SCALE	FIT	深圳市连盛精密连接器有限公司																																																																																	
				X.X	±0.30			UNIT	mm																																																																																		
				X.XX	±0.20	CHECK		SIZE	A4																																																																																		
				X.XXX	±0.10			SHEET	1/1																																																																																		
REV	DATE	MODIFICATION DESCRIPTION	CHANGE		Angle	±3°	APPROVE			TITLE:	PART NO.	1020200135																																																																															
					DIM	TOL						2.0FH H4.3mm 2x4pin SMT W4.50																																																																															
1	2	3	4	5	6	7	8	9																																																																																			

Max.Processing Temp: 230°C for 30–60 seconds
(260°C for 10 seconds)



				OPERATION		DRAW			SCALE	FIT	深圳市连盛精密连接器有限公司	
				X.X	±0.30					UNIT		
				X.XX	±0.20	CHECK			SIZE	A4	PART NO.	1020200135
A0	2018.07.23	NEW DRAWING		X.XXX	±0.10					SHEET		
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	Angle	±3°	APPROVE					TITLE:	2.0FH H4.3mm 2x4pin SMT W4.50
				DIM	TOL					PROJ.		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) ***category:***

Click to view products by [Liansheng](#) ***manufacturer:***

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)