

1			2			3			4			5			6			7			8			9		
RoHS																										
SPECIFICATIONS																										
Rated Current:3.0AMP																										
Contact Resistance:20mΩ Max																										
Withstand Voltage:1000V AC/DC																										
Insulation Resistance:1000MΩ Min																										
Operation Temperature:-40°c to +105°c																										
Contact Material:Brass																										
Contact Plating:Au Over Ni																										
Insulator Material:Polyester(UL94V-0)																										
Standard: PA6T																										
Max.Processing Temp: 230°C for 30-60 seconds																										
(260°C for 10 seconds)																										
Recommended P.C.B Layout(Top Side)																										
(PCB BOARD TOLERANCE±0.05)																										
REV																										
DATE																										
MODIFICATION DESCRIPTION																										
CHANGE																										
DIM																										
TOL																										
APPROVE																										
CHECK																										
SIZE																										
SHEET																										
1/1																										
PRD.																										
TITLE:																										
PART NO.																										
1020300250																										
2.54FH H8.5mm 1x10pin 180° W2.5mm																										
深圳市连盛精密连接器有限公司																										
A0																										
2012.03.28																										
NEW DRAWING																										
REV																										
DATE																										
MODIFICATION DESCRIPTION																										
CHANGE																										
DIM																										
TOL																										
APPROVE																										
CHECK																										
SIZE																										
SHEET																										
1/1																										
PRD.																										
TITLE:																										
PART NO.																										
1020300250																										
2.54FH H8.5mm 1x10pin 180° W2.5mm																										
深圳市连盛精密连接器有限公司																										

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) ***category:***

Click to view products by [Liansheng](#) ***manufacturer:***

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)