

	1	2	3	4	5	6	7	8	9																																															
G	RoHS																																																							
F	SPECIFICATIONS						Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)																																																	
E	Rated Current:3.0AMP Contact Resistance:20mΩ Max Withstand Voltage:1000V AC/DC Insulation Resistance:1000MΩ Min Operation Temperature:-40℃ to +105℃																																																							
D	Contact Material:Brass Contact Plating:Au Over Ni Insulator Material:Polyester(UL94V-0) Standard: PA6T																																																							
C	Max.Processing Temp: 230℃ for 30-60 seconds (260℃ for 10 seconds)																																																							
B							<table border="1"><caption>Dimension antitheses list</caption><thead><tr><th>ITEM</th><th>PB</th><th>PC</th><th>PW</th><th>H</th><th>W</th></tr></thead><tbody><tr><td>001</td><td>9.0</td><td></td><td>7.1</td><td>8.5</td><td>5.0</td></tr><tr><td>002</td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>		ITEM	PB	PC	PW	H	W	001	9.0		7.1	8.5	5.0	002																																			
ITEM	PB	PC	PW	H	W																																																			
001	9.0		7.1	8.5	5.0																																																			
002																																																								
A				<table border="1"><thead><tr><th colspan="2">OPERATION</th><th rowspan="2">DRAW</th><th rowspan="2">SCALE</th><th rowspan="2">FIT</th><th colspan="2" rowspan="2">深圳市连盛精密连接器有限公司</th></tr><tr><th></th><th></th></tr></thead><tbody><tr><td></td><td>X.X</td><td>±0.30</td><td></td><td></td><td></td><td></td></tr><tr><td></td><td>X.XX</td><td>±0.20</td><td>CHECK</td><td></td><td></td><td></td></tr><tr><td></td><td>X.XXX</td><td>±0.10</td><td></td><td></td><td></td><td></td></tr><tr><td></td><td>Angle</td><td>±3°</td><td>APPROVE</td><td></td><td></td><td></td></tr><tr><td></td><td>DIM</td><td>TOL</td><td></td><td></td><td></td><td></td></tr></tbody></table>			OPERATION		DRAW	SCALE	FIT	深圳市连盛精密连接器有限公司					X.X	±0.30						X.XX	±0.20	CHECK					X.XXX	±0.10						Angle	±3°	APPROVE					DIM	TOL					<table border="1"><thead><tr><th>PART NO.</th><th>1020300868</th></tr><tr><th>TITLE:</th><td>2.54FH H=8.5 W=5.0 2*18P SMT=7.1 总高9.0 U-A型 AU1U 青铜 PA6T</td></tr></thead></table>		PART NO.	1020300868	TITLE:	2.54FH H=8.5 W=5.0 2*18P SMT=7.1 总高9.0 U-A型 AU1U 青铜 PA6T
OPERATION		DRAW	SCALE	FIT	深圳市连盛精密连接器有限公司																																																			
	X.X	±0.30																																																						
	X.XX	±0.20	CHECK																																																					
	X.XXX	±0.10																																																						
	Angle	±3°	APPROVE																																																					
	DIM	TOL																																																						
PART NO.	1020300868																																																							
TITLE:	2.54FH H=8.5 W=5.0 2*18P SMT=7.1 总高9.0 U-A型 AU1U 青铜 PA6T																																																							
	1	2	3	4	5	6	7	8	9																																															

2.54FH H=8.5 W=5.0 2*18P SMT=7.1 总高9.0
U-A型 AU1U 青铜 PA6T

PRO.1

PRO.1

PRO.1

PRO.1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) ***category:***

Click to view products by [Liansheng](#) ***manufacturer:***

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)