

G	RoHS								G																								
F	SPECIFICATIONS Rated Current:3.0AMP Contact Resistance:20mΩ Max Withstand Voltage:1000V AC/DC Insulation Resistance:1000MΩ Min Operation Temperature:-40℃ to +105℃ Contact Material:Brass Contact Plating:Au Over Ni Insulator Material:Polyester(UL94V-0) Standard: PA6T Max.Processing Temp: 230℃ for 30-60 seconds (260℃ for 10 seconds)								F																								
E							Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)			E																							
D										D																							
C								C																									
B	<table border="1"> <thead> <tr> <th colspan="6">Dimension antitheses list</th></tr> <tr> <th>ITEM</th><th>PB</th><th>PC</th><th>PW</th><th>H</th><th>W</th></tr> </thead> <tbody> <tr> <td>001</td><td>9.0</td><td></td><td>7.1</td><td>8.5</td><td>5.0</td></tr> <tr> <td>002</td><td></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>								Dimension antitheses list						ITEM	PB	PC	PW	H	W	001	9.0		7.1	8.5	5.0	002						B
Dimension antitheses list																																	
ITEM	PB	PC	PW	H	W																												
001	9.0		7.1	8.5	5.0																												
002																																	
A					OPERATION				SCALE	FIT	深圳市连盛精密连接器有限公司																						
					X.X ±0.30	DRAW			UNIT	mm																							
					X.XX ±0.20				SIZE	A4																							
					X.XXX ±0.10	CHECK			SHEET	1/1																							
	A0	2012.03.28	NEW DRAWING		Angle ±3°	APPROVE			PROJECT	◆	PART NO.	1020300875																					
	REV	DATE	MODIFICATION DESCRIPTION	CHANGE	DIM TOL						TITLE:	2.54FH H=8.5 W=5.0 2*30P SMT=7.1 总高9.0 U-A型 AU1U 青铜 PA6T																					
	1	2	3	4	5	6	7	8	9																								

				OPERATION		DRAW			SCALE	FIT	深圳市连盛精密连接器有限公司	
				X.X	±0.30					UNIT		
				X.XX	±0.20	CHECK			SIZE	A4	PART NO.	1020300875
A0	2012.03.28	NEW DRAWING		X.XXX	±0.10				SHEET	1/1		
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	Angle	±3°	APPROVE					TITLE:	2.54FH H=8.5 W=5.0 2*30P SMT=7.1 总高9.0 U-A型 AU1U 青铜 PA6T
				DIM	TOL				PROJ.			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) *category:*

Click to view products by [Liansheng](#) *manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)