


SC1003-01ETG

5 V, 7 A, SOD882, Unidirectional Discrete TVS Diode, General Purpose ESD Protection

HF RoHS Pb

**Pinout****Functional Block Diagram**

Description

The SC1003-01ETG diodes are fabricated in a proprietary silicon avalanche technology. These diodes provide a high ESD (electrostatic discharge) protection level for electronic equipment. The SC1003-01ETG TVS can safely absorb repetitive ESD strikes at ± 30 kV (contact discharge, IEC 61000-4-2) without performance degradation. Additionally, each diode can safely dissipate 7 A of 8/20 μ s surge current (IEC 61000-4-5) with very low clamping voltages.

Features

- ESD, IEC 61000-4-2, ± 30 kV contact/air
- EFT, IEC 61000-4-4, 40 A (5/50 ns)
- Maximum surge tolerance, IEC 61000-4-5 2nd edition, 7 A (8/20 μ s)
- Low leakage current of 0.1 μ A (Max) at 5 V
- Low clamping voltage
- Tiny SOD882 (JEDEC MO-236) package saves board space
- Halogen free, lead free and RoHS compliant

Applications

- Digital cameras
- Mobile phones
- PDAs
- Portable navigation components
- Portable medical components

SC1003-01ETG

5 V, 7 A, SOD882, Unidirectional Discrete TVS Diode, General Purpose ESD Protection

Absolute Maximum Ratings

Symbol	Parameter	Value	Units
I_{PP}	Peak Current ($t_p = 8/20 \mu s$)	7	A
T_{OP}	Operating Temperature	-40 to 125	°C
T_{STOR}	Storage Temperature	-55 to 150	°C



CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the component. This is a stress only rating and operation of the component at these or any other conditions above those indicated in the operational sections of this specification is not implied.

Electrical Characteristics ($T_{OP}=25^{\circ}C$)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Units
Reverse Standoff Voltage	V_{RWM}				5	V
Breakdown Voltage	V_{BR}	$I_R = 1 \text{ mA}$	6.0	7.8	8.5	V
Forward Voltage Drop	V_F	$I_F = 10 \text{ mA}$		0.8	1.2	V
Reverse Leakage Current	I_{LEAK}	$V_R = 5 \text{ V}$			100	nA
Clamp Voltage ¹	V_C	$I_{PP} = 16 \text{ A}$, $t_p = 0.2/100 \text{ ns}$ (TLP), I/O to GND		11		V
		$I_{PP} = 1 \text{ A}$, $t_p = 8/20 \mu s$, I/O to GND		8.5		V
		$I_{PP} = 7 \text{ A}$, $t_p = 8/20 \mu s$, I/O to GND		12		V
Dynamic Resistance ²	R_{DYN}	TLP, $t_p = 100 \text{ ns}$, I/O to GND		0.25		Ω
ESD Withstand Voltage ^{1,3}	V_{ESD}	IEC 61000-4-2 (Contact Discharge)	± 30			kV
		IEC 61000-4-2 (Air Discharge)	± 30			kV
Diode Capacitance ¹	C_{IO-GND}	Reverse Bias = 0 V, $f = 1 \text{ MHz}$, I/O to GND		30		pF

Note:


- Parameter is guaranteed by design and/or component characterization
- Transmission Line Pulse (TLP) with 100ns width, 0.2 ns rise time, and average window $t_1 = 70 \text{ ns}$ to $t_2 = 90 \text{ ns}$
- Device stressed with ten non-repetitive ESD pulses according to IEC61000-4-2 ($R = 330 \Omega$, $C = 150 \text{ pF}$).

Capacitance vs. Reverse Bias**Clamping Voltage vs I_{PP}** 


SC1003-01ETG

5 V, 7 A, SOD882, Unidirectional Discrete TVS Diode, General Purpose ESD Protection

Positive Transmission Line Pulsing (TLP) Plot




Negative Transmission Line Pulsing (TLP) Plot



IEC 61000-4-2 +8 kV Contact ESD Clamping Voltage



IEC 61000-4-2 -8 kV Contact ESD Clamping Voltage




SC1003-01ETG

5 V, 7 A, SOD882, Unidirectional Discrete TVS Diode, General Purpose ESD Protection

Soldering Parameters

Reflow Condition		Pb-free assembly
Pre Heat	- Temperature Min ($T_{s(min)}$)	150 °C
	- Temperature Max ($T_{s(max)}$)	200 °C
	- Time (min to max) (t_s)	60 – 120 seconds
Average Ramp Up Rate (Liquidus) Temp (T_L) to Peak		3 °C/second max
$T_{s(max)}$ to T_L - Ramp-up Rate		3 °C/second max
Reflow	- Temperature (T_L) (Liquidus)	217 °C
	- Temperature (t_L)	60 – 150 seconds
Peak Temperature (T_p)		260 ^{+0/-5} °C
Time Within 5 °C of Actual Peak Temperature (t_p)		30 seconds
Ramp-down Rate		6 °C/second max
Time 25 °C to Peak Temperature (T_p)		8 minutes max
Do Not Exceed		260 °C




Product Characteristics

Lead Plating	Matte Tin
Lead Material	Copper alloy
Body Material	Molded compound
Flammability	UL recognized compound meeting flammability rating V-0


Ordering Information

Part Number	Package	Min. Order Qty.
SC1003-01ETG	SOD882	10000

Part Marking System




Part Numbering System




SC1003-01ETG


5 V, 7 A, SOD882, Unidirectional Discrete TVS Diode, General Purpose ESD Protection

Package Dimensions — SOD882

Symbol	Millimeters		
	Min	Nom	Max
A	0.45	0.50	0.55
A1	0.00	0.02	0.05
L1	0.20	0.25	0.30
L2	0.45	0.50	0.55
D	0.95	1.00	1.05
E	0.55	0.60	0.65
e	0.65 BSC		
h	0.07	0.12	0.17

Embossed Carrier Tape & Reel Specification — SOD882

Symbol	Millimeters		
	Min	Nom	Max
A0	0.63	0.70	0.77
B0	1.06	1.12	1.20
D0	1.50	1.55	1.60
D1	0.30	0.45	0.60
E	1.65	1.75	1.85
F	3.40	3.50	3.60
K0	0.54	0.60	0.66
P0	3.90	4.00	4.10
P1	1.90	2.00	2.10
P2	1.95	2.00	2.05
T	0.15	0.20	0.25
W	7.80	8.00	8.30

Component Orientation in Tape

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [ESD Protection Diodes / TVS Diodes](#) ***category:***

Click to view products by [Littelfuse](#) ***manufacturer:***

Other Similar products are found below :

[60KS200C](#) [D5V0F4U5P5-7](#) [P4KE27CA](#) [P6KE11CA](#) [JAN1N6461](#) [P6KE8.2A](#) [JANTX1N6475](#) [SA60CA](#) [SA64CA](#) [SMBJ12CATR](#)
[SMBJ33CATR](#) [SMBJ8.0A](#) [ESD101-B1-02ELS E6327](#) [ESD112-B1-02EL E6327](#) [CPDT-5V0USP-HF](#) [HSPC16701B02TP](#) [JANTX1N6052A](#)
[D3V3Q1B2DLP3-7](#) [SCM1293A-04SO](#) [ESD200-B1-CSP0201 E6327](#) [CEN955 W/DATA](#) [ESD101-B1-02EL E6327](#) [5KP48A](#) [5KP90A](#)
[15KPA36A-LF](#) [P4KE56CA](#) [P4KE68A](#) [P6KE13CA](#) [P6KE43CA](#) [P6SMBJ20CA](#) [JANTX1N6072A](#) [SR2835ESKG](#) [SA90CA](#) [SA8.5A](#) [SA18A](#)
[SA11CA](#) [SMCJ78CA](#) [SMBJ51CA](#) [JANTX1N5650A](#) [SMDA05LC-LF](#) [30KPA48A-LF](#) [GPZ1275](#) [P4KE6.8A](#) [CPDQC12VE-HF](#)
[GRPADATAJANTX1N6041A](#) [DSILC6-4SC6](#) [5KP45A-TP](#) [SMLJ26A-TP](#) [D5V0Q1B2CSP-7](#) [NSPM3042MXT5G](#)