

LoRaSCAN



LoRaSCAN-FM

2D Wireless Barcode Scanner

Wireless barcode scanner for
Automated Industrial applications



Key Features

- Scans many popular barcode types
- Extremely long range wireless transmission of 3km+ indoors
- 50-750mm scanning range
- 24V Powered | 24V Dry contact trigger | 24V Pulse Output
- Surface mounting brackets included, pole mount optional
- Industrial rugged design for factory environments



24V



Datasheet



Video



Order

www.lorascan.co.uk

LoRaSCAN

LoRaSCAN-HHR Specification



Scanning

- Resolution: 640*480 3mil/0.1mm (PCS90%, CODE 39)
- Scanner type: CMOS
- Illumination: Red Light LED 525±10nm, 5600K LED (lighting)
- Print contrast ratio: 15%
- Scan angle: Roll ±360°, Pitch ±60°, Skew ±55°
- Scanning distance: 50mm ~ 750mm
- Manual, Autosense & Continuous scan modes

Wireless

- Very long range wireless transmission
- 8km outdoor, 3km indoor (line of sight)
- Internal antenna
- 868MHz – 925MHz for worldwide usage
- Robust & secure industrial protocol
- All data encrypted as standard

Electrical

- 24VDC powered (power supply not included)
- 24V dry contact to trigger scanning
- 24V pulse output following successful scan
- Energy saving 2 minute auto shutdown
- Includes Phoenix contact connector MC 1,5/ 5-STF-3,81
- Blue LED power indicator

Physical

- IP67 rated
- 120mm x 120mm x 70mm
- -20 to + 50 degrees C operating temperature range

Regulatory

- CE
- FCC
- RoHS

Ordering

- LORASCAN-FM
Wireless scanner, surface mount accessories
- LORASCAN-FM-STARTER
Wireless scanner, connector & USB wireless receiver dongle
- LORASCAN-USB
USB wireless receiver dongle



Datasheet



Video



Order

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) category:

Click to view products by [LPRS](#) manufacturer:

Other Similar products are found below :

[FAB118](#) [ATX6022/14GP7](#) [ATX6022/8](#) [9441560000](#) [73-546-001](#) [60016-023](#) [PCE-DP10-00A1E](#) [60016-002](#) [60006-004](#) [SNAP-PAC-SB2](#)
[60011-093](#) [ADAM-4541-C](#) [ADAM-4510S-F](#) [USB-CARD-READER](#) [USB-RS485](#) [USB-SATA](#) [TD501D232H](#) [RSM232D](#) [TD502D232H](#)
[RS232 TO RS485](#) [TD302D232H](#) [TD501D232H](#) [RSM232](#) [RSM232D](#) [TD301D232H](#) [TD302D232H](#) [TD502D232H](#) [20270](#) [20294](#) [50260](#)
[40961](#) [20277](#) [ZHB5105J](#) [EUR0001H](#) [ZHB2301G](#) [50985](#) [USO9ML4](#) [TTL/CAN-USB](#) [4000-68000-4170000](#) [4000-68000-0220000](#) [4000-](#)
[68512-0940003](#) [4000-68000-0090000](#) [6ES73317KF020AB0](#) [6ES71556AA010BN0](#) [6ES71936AR000AA0](#) [GPS50M](#) [FAB8020785](#) [1020882](#)
[1021056](#) [1021058](#)