





Features

- ✧ Plastic package has underwriters laboratory flammability classification 94V-0
- ✧ For surface mounted applications
- ✧ Low profile package
- ✧ Built-in strain relief, ideal for automated placement
- ✧ High temperature soldering:
- ✧ 250°C/10 seconds at terminals

Mechanical Data

- ✧ Case: JEDEC DO-214AB, molded plastic over passivated chip
- ✧ Polarity: Color band denotes cathode end
- ✧ Weight: 0.007 ounces, 0.21 gram

SMC/DO-214AB



Dimensions in inches and (millimeters)

Marking Information



LGE: Lu Guang Electronic
XXXX: marking code (S5A-S5Y)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS






Ratings at 25°C ambient temperature unless otherwise specified

		S5A	S5B	S5D	S5G	S5J	S5K	S5M	S5T	S5W	S5X	S5Y	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	1300	1600	1800	2000	V
Maximum RMS voltage	V_{RWS}	35	70	140	280	420	560	700	760	820	880	940	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	1300	1600	1800	2000	V
Maximum average forward rectified current @ $T_L=90^\circ\text{C}$	$I_{F(AV)}$	5.0											A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	150											A
Maximum Instantaneous forward voltage at 5.0 A	V_F	1.15											V
Maximum DC reverse current @ $T_A=25^\circ\text{C}$ at rated DC blocking voltage @ $T_A=125^\circ\text{C}$	I_R	10											μA
Typical junction capacitance	C_J	35											pF
Typical thermal resistance (NOTE 2)	$R_{\theta JA}$	40											$^\circ\text{C/W}$
Operating junction and storage temperature range	T_J, T_{STG}	-55-----+150											$^\circ\text{C}$

NOTE: 1. Measured at 1.0MHz and applied reverse voltage of 4.0 Volts

2. Thermal resistance from junction to ambient and junction to lead P.C.B. mounted on 0.27"X0.27"(7.0X7.0mm²) copper pad areas

Ratings AND Characteristic Curves

FIG.1 – FORWARD DERATING CURVE

FIG.2 PEAK FORWARD SURGE CURRENT

FIG.3 – TYPICAL FORWARD CHARACTERISTICS

FIG.4 – TYPICAL REVERSE CHARACTERISTICS

FIG.5-TYPICAL JUNCTION CAPACITANCE


PACKAGE	SPQ/PCS	CARTON SPQ/PCS	CARTON SIZE/CM	CARTON GW/KG	CARTON NW/KG
SMC	3000/REEL	42000	36X36X36.5	18.50	15.50

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Diodes - General Purpose, Power, Switching category](#):

Click to view products by [Luguang manufacturer](#):

Other Similar products are found below :

[RD0306T-TL-H](#) [RD0506T-TL-H](#) [DCD010-TB-E](#) [SDAA13](#) [1N914BTR](#) [D291S45T](#) [MM230L-CAA](#) [JAN1N3600](#) [BYW95B/A52A](#)
[BAV70HDW-7](#) [BAS28 TR](#) [1SS388-TP](#) [SI-A1125](#) [SHV-06JNS-Q](#) [2CL75A](#) [MCL4148PF](#) [1SS226,LF\(T](#) [1SS352\(TPH3,F\)](#) [1SS306\(TE85L.F\)](#)
[KDS122-RTK/P](#) [KDS135-RTK/PU](#) [DB107](#) [LS4148PF](#) [P1200M](#) [KDS160E-RTL/P](#) [DB106S](#) [DB207](#) [DB157](#) [DB155](#) [DB206](#) [2CL74](#) [1A7](#)
[DB105](#) [DB156S](#) [DB206S](#) [DB156](#) [BAV199](#) [DL4007](#) [2CL3512H](#) [1SS181,LF\(T](#) [CRG09A,LXGQ](#) [CRG09A,LQ\(M](#) [DB106](#) [SDUR1530](#)
[S2KTR](#) [S2MTR](#) [GL1M](#) [CD4148WSP](#) [CD4148WTP](#) [1N5404](#)