




UNCONTROLLED DOCUMENT

PART NUMBER		REV.
OED-SR-105F		B
REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #10534.	7.8.99
B	E.C.N. #10BRDR. & REDRAWN.	5.1.03



ELECTRO-OPTICAL CHARACTERISTICS $T_A=25^{\circ}\text{C}$

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH			940		nm	
INPUT:						
FORWARD VOLTAGE	V_f			1.3	V	$I_f = 10\text{mA}$
REVERSE CURRENT	I_r			10	μA	$V_r = 5\text{V}$
OUTPUT:						
COLLECTOR DARK CURRENT	I_{ceo}			0.2	μA	$V_{ce} = 10\text{V}$
COLLECTOR LIGHT CURRENT	I_L	90			μA	$V_{ce} = 5\text{V}$ $I_f = 10\text{mA}$
LEAKAGE CURRENT	I_{ceod}			0.2	μA	$V_{ce} = 5\text{V}$ $I_f = 10\text{mA}$
SWITCHING SPEEDS:						
RISING TIME	T_r		30		μS	$V_{cc} = 2\text{V}$ $I_c = 0.1\text{mA}$
FALLING TIME	T_f		25		μS	$R_l = 1\text{K}\ \Omega$

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	SYMBOL	MAX	UNITS
INPUT:			
REVERSE VOLTAGE	V_r	5	V
POWER DISSIPATION	P_d	75	mW
FORWARD CURRENT	I_f	50	mA
OUTPUT:			
COLLECTOR POWER DISSIPATION	P_c	50	mW
COLLECTOR CURRENT	I_c	20	mA
C-E VOLTAGE	V_{ceo}	30	V
E-C VOLTAGE	V_{eco}	3	V
OPERATING TEMP.	T_{opr}	-20 TO +85	°C
STORAGE TEMP.	T_{stg}	-30 TO +100	°C
SOLDERING TEMP.	T_{sol}	+240	°C
2.0mm FROM BODY	dist.		5 SEC. MAX

REPLACES PART #: OED-SG-105F

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.=+DECIMAL PRECISION MAX.=+0.00 -DECIMAL PRECISION

UNCONTROLLED DOCUMENT

REV.	PART NUMBER
B	OED-SR-105F
REFLECTIVE PHOTO SENSOR, RIGHT ANGLE LEADS.	

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:	CHECKED BY:	APPROVED BY:	DATE:
CT			5.1.03
		PAGE:	1 OF 1
		SCALE:	N/A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Optical Switches, Reflective, Phototransistor Output](#) *category:*

Click to view products by [Lumex](#) *manufacturer:*

Other Similar products are found below :

[LTH-1650-01](#) [HOA1180-106](#) [NJL5303R-TE1](#) [ITR8307/L24/TR8](#) [RPR-359F](#) [OPR5005](#) [EE-SF5-B](#) [QRD1114](#) [ITR8307](#) [ITR-20001T](#) [ITR-20002](#) [ITR-8307/TR8](#) [ITR9606-F](#) [HOA0708-001](#) [HOA0709-001](#) [HOA0709-011](#) [HOA1180-001](#) [HOA1180-002](#) [HOA1397-001](#) [HOA1406-003](#) [HOA2498-002](#) [LTH-209-01](#) [NJL5501R-TE1](#) [NJL5902R-2-TE1](#) [EE-SB5](#) [EE-SB5-B](#) [EE-SF5](#) [EE-SPY302](#) [EE-SPY311](#) [EE-SPY401](#) [EE-SPY402](#) [EE-SPY411](#) [EE-SPY412](#) [EE-SPZ301A](#) [EE-SPZ401A](#) [EESB5MW12](#) [EE-SY110](#) [EE-SY113](#) [EE-SY169](#) [EE-SY169A](#) [EE-SY171](#) [EE-SY190](#) [EE-SY199](#) [EE-SY671](#) [EE-SY672](#) [QRD1113](#) [QRE1113](#) [QRE1113GR](#) [SFH 9206](#) [RPI-1035](#)