

XST-3535-UV

Surface Mount

UVC LED




Table of Contents

| | |
|-----------------------------|----|
| Binning and Ordering | |
| Information..... | 2 |
| Optical and Electrical | |
| Characteristics | 4 |
| Mechanical Dimensions | 7 |
| Soldering Profile | 8 |
| Product Shipping & Labeling | |
| Information..... | 9 |
| Precautions for Use..... | 10 |
| History of Changes | 11 |

Features:

- UVC LED with emission wavelength between 270 nm and 285 nm
- High Optical Power: 100 mW+ of UVC power at maximum rated current
- Compact form factor: 3.5 mm x 3.5 mm package
- Narrow viewing angle of 60 degrees
- Standard SMT Process
- RoHS and REACH compliant

Applications

- Air Purification
- Water Purification
- Surface Disinfection
- Medical Device Sterilization
- Appliance Sterilization
- Food & Beverage Preparation

XST-3535-UV Binning Structure

XST-3535-UV LEDs are tested at a drive current of 350 mA, 20 ms single pulse at 25° C and placed into one of the following radiometric flux (FF), wavelength (WWW) and forward voltage bins bins.

Radiometric Flux Bins

The LEDs can also be driven at higher drive currents, to achieve the correlated flux values listed in the table.

| Flux Bin (FF) | Minimum Flux (mW) 350 mA, 25° C | Maximum Flux (mW) 350 mA, 25° C | Correlated Minimum Flux (mW) at 25° C | | |
|---------------|------------------------------------|------------------------------------|---------------------------------------|--------|--------|
| | | | 500 mA | 650 mA | 800 mA |
| CD | 35 | 40 | 49 | 64 | 79 |
| CE | 40 | 45 | 56 | 74 | 90 |
| CF | 45 | 50 | 63 | 83 | 101 |
| CG | 50 | 55 | 70 | 92 | 113 |
| CH | 55 | 60 | 77 | 101 | 124 |

Note 1: Product lifetime is a function of drive current. Sustained operation at absolute maximum current of 800 mA will result in a reduction of device lifetime compared to typical forward drive currents (350 mA-500 mA). Actual device lifetimes will also depend on junction temperature. Contact Luminus for information on product lifetime.

Wavelength Bins

| Wavelength Bin (WWW) | Minimum Wavelength (nm) | Maximum Wavelength (nm) |
|----------------------|-------------------------|-------------------------|
| 270 | 270 | 275 |
| 275 | 275 | 280 |
| 280 | 280 | 285 |

Note 2: Luminus maintains a +/- 6% tolerance on flux measurements and +/- 1 nm on wavelength measurements.

Note 3: Individual flux bins are not orderable. Please refer to product ordering information on page 3 for a list of ordering part numbers.

Forward Voltage Bins

| Voltage Bin | Minimum Forward Voltage (V) | Maximum Forward Voltage (V) |
|-------------|-----------------------------|-----------------------------|
| V3 | 5.0 | 5.5 |
| V4 | 5.5 | 6.0 |
| V5 | 6.0 | 6.5 |
| V6 | 6.5 | 7.0 |
| V7 | 7.0 | 7.5 |

Part Number Nomenclature

XST — 3535 — <UV> — <A##> — <FF###>

| Product Family | Package Type | Color | Package Configuration | Bin kit |
|--------------------------------|-----------------------|-------------|-----------------------|--|
| XST: UVC Surface Mount Package | 3535: 3.5 mm x 3.5 mm | Ultraviolet | A60: 60 degree lens | Flux and Wavelength bin kit code - See ordering informaton |

Ordering Part Numbers

The table below lists ordering part numbers available for XST-3535-UV LEDs. The part number includes a bin kit, a group of flux and wavelength bins described in page 2, that are shippable for a given ordering part number. Individual flux bins are not orderable. Flux bin listed is minimum bin shipped - higher bins may be included at Luminus' discretion.

| Wavelength Range | Wavelength Bins | Radiometric Flux | | Ordering Part Number |
|------------------|-----------------|-------------------|----------------|--------------------------|
| | | Bin Kit Flux Code | Min. Flux (mW) | |
| 270-280 | 270, 275 | CD | 35 | XST-3535-UV-A60-CD270-00 |
| 275-280 | 275 | CD | 35 | XST-3535-UV-A60-CD275-01 |
| 280-285 | 280 | CD | 35 | XST-3535-UV-A60-CD280-01 |
| 275-285 | 275, 280 | CD | 35 | XST-3535-UV-A60-CD275-00 |
| 270-280 | 270, 275 | CE | 40 | XST-3535-UV-A60-CE270-00 |
| 275-280 | 275 | CE | 40 | XST-3535-UV-A60-CE275-01 |
| 280-285 | 280 | CE | 40 | XST-3535-UV-A60-CE280-01 |
| 275-285 | 275, 280 | CE | 40 | XST-3535-UV-A60-CE275-00 |

Optical and Electrical Characteristics^{1,3}

| Parameter | Symbol | Value | Unit |
|--|-----------------|-------|------|
| Minimum Forward Voltage | V_{f-min} | 5.0 | V |
| Typical Forward Voltage | V_{f-typ} | 6.45 | V |
| Maximum Forward Voltage | V_{f-max} | 7.5 | V |
| FWHM | $\Delta\lambda$ | 10 | nm |
| Viewing Angle | $2\theta_{1/2}$ | 60 | ° |
| Thermal Resistance (junction-solder point) | R_{th} | 5.0 | °C/W |

Absolute Maximum Ratings^{2,3}

| Parameter | Symbol | Value | Unit |
|----------------------|-------------|-------|------|
| Forward Current | I_{f-max} | 800 | mA |
| Junction Temperature | T_j | 100 | °C |

Note 1: Ratings are based on operation at a constant junction temperature of $T_j = 25^\circ\text{C}$. Test conditions: 350 mA, 20 ms pulse at 25°C .


Note 2: Product lifetime is a function of drive current. Sustained operation at absolute maximum current of 800 mA will result in a reduction of device lifetime compared to typical forward drive currents (350-500 mA). Actual device lifetimes will also depend on junction temperature. Contact Luminus for details.

Note 3: XST-3535-UV LEDs are short wavelength, deep UV LEDs. During operation, the LED emits high intensity UVC radiation, which is harmful to skin and eyes. UV light is also hazardous to skin and may cause cancer. Avoid exposure to deep UV light when LED is operational.

Optical & Electrical Characteristics


Relative Power vs. Forward Current

$\phi/\phi_{(350\text{ mA})}$, 20 ms pulse, $T_j = 25^\circ\text{C}$




Relative Power vs. Junction Temperature

$\phi/\phi_{(25^\circ\text{C})}$, 20 ms pulse, 350 mA




Peak Wavelength Shift vs. Forward Current

$\lambda_p = \lambda_p(I_f) - \lambda_p(350\text{ mA})$, 20 ms pulse, $T_j = 25^\circ\text{C}$




Peak Wavelength Shift vs. Junction Temperature

$\lambda_p = \lambda_p(T_j) - \lambda_p(25^\circ\text{C})$, 20 ms pulse, $I_f = 350\text{ mA}$




Forward Voltage vs Forward Current




Forward Voltage Shift vs. Junction Temperature


$\Delta V_f = V_f(T_j) - V_f(25^\circ\text{C})$, 20 ms pulse, $I_f = 350\text{ mA}$




Typical Spectrum




Radiation Pattern



Mechanical Dimensions



Recommended Solder Pad and Stencil Pattern




Recommended Stencil Pattern

| | |
|-----------------|-----------------|
| Solder Pad | 3.6 mm x 1.6 mm |
| Stencil Pattern | 2.8 mm x 1.2 mm |

Soldering Profile


| Profile Setting | Pb-Free Profile |
|---|-----------------|
| Average Ramp-up Rate ($T_{s_{max}}, T_p$) | 1 °C/sec |
| Preheat Temperature Min ($T_{s_{min}}$) | 100-150 °C |
| Preheat Temperature Max ($T_{s_{max}}$) | 180-200 °C |
| Preheat Time ($t_{s_{min}}$ to $t_{s_{max}}$) | 60-120 sec |
| Liquidus Temperature (T_L) | 217 °C |
| Time Maintained Above T_L (t_L) | 50-80 sec |
| Peak / Classification Temperature (T_p) | 260 °C |
| Time within 5°C of Actual Peak Temp (t_p) | Max 10 sec |
| Ramp-Down Rate | 2-3 °C /sec |
| 25°C to Peak Temperature time | 4 mins |

Luminus recommends that users follow the recommended soldering profile provided by the manufacturer of the solder paste used. Note that this general guideline may not apply to all PCB designs and configurations.




Product Shipping & Labeling Information

All XST-3535 products are packaged and labeled with their respective bin as outlined in the tables on pages 2 & 3. Each reel will only contain one flux and one wavelength bin



XST-3535-UV Label Information



Precautions for storage, handling and use of UV LEDs

1. UV Light

XST-3535-UV LEDs are short wavelength, deep UV LEDs. During operation, the LED emits high intensity UVC radiation, which is harmful to skin and eyes. UV light is also hazardous to skin and may cause cancer. Avoid exposure to deep UV light when LED is operational.

Precautions must be taken to avoid looking directly at the UV light without the use of UV light protective glasses. Do not look directly at the front or at the LED's lens when LED is operational.

2. Static Electricity (ESD)


While XST 3535 LEDs have built-in Zener protection diodes, they are particularly sensitive to ESD (Electrostatic Discharge). Static electricity and surge voltages seriously damage UV LEDs and can result in complete failure of the device. Precautions must be taken against ESD when handling or operating these devices.

3. Operating Conditions

In order to ensure the correct functioning of these LEDs, compliance to maximum allowed specifications is important. UV LEDs are particularly sensitive to drive currents that exceed the max operating specifications and may be damaged by such drive currents. The use of current regulated drive circuits is strongly recommended when operating these devices. Customers should also provide adequate thermal management to ensure LEDs do not exceed maximum recommended temperatures. Operating LEDs at temperatures in excess of specification will result in damage and possibly complete failure of the device.

History of Changes

| Rev | | Description of Change |
|-----|------------|---|
| 01 | 06/11/2019 | Initial release |
| 02 | 11/04/2019 | Tape and Reel drawing |
| 03 | 04/04/2020 | Additional ordering part numbers introduced, increased max current rating |
| 03 | 05/19/2020 | Editorial change- spectrum reflects 275 nm Bins |
| 04 | 06/17/2020 | Defined higher bin (CH: 55-60 mW) |
| 05 | 11/2020 | New wavelength bins and Vf bins introduced. Updated drawing |



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [High Power LEDs - Single Colour](#) category:

Click to view products by [Luminus Devices](#) manufacturer:

Other Similar products are found below :

[GA CSSPM1.23-KTLP-W3-0-350-R18](#) [L135-L567003500000](#) [L1CU-VLT1000000000](#) [L1C1-VLT1000000000](#) [KY DDLM31.FY-8H7J-5F5G-W4A4-140-R18](#) [KY DDLM31.23-8F5H-36-C4U4-140-R18](#) [LS G6SP.01-7C8D-68-G3R3](#) [KT DDLM31.13-6H7J-36-W4A4-140-R18](#) [KS DDLM31.23-8E6G-68-C4U4-140-R18](#) [KB DDLM31.13-6D7E-25-24A4-140-R18](#) [GT CS8PM1.13-LSLU-26-1-350-B-R18](#) [XPEBRY-L1-0000-00S02](#) [SPHWH2L3D30ED4V0H3](#) [LUWCQ7P-LPLR-5E8G-1-K](#) [LTPL-C034UVH410](#) [XPEROY-L1-0000-00B02](#) [GD CSSPM1.14-UOVJ-W4-1](#) [LST1-01F06-GRN1-00](#) [KY DMLS31.23-8J7L-46-M3W3](#) [KY DMLQ31.23-HYKX-46-J3T3](#) [GD CS8PM1.14-UOVJ-W4-1](#) [XQEEPR-00-0000-000000A01-SB01](#) [LST1-01G01-UV02-00](#) [LST1-01F06-RYL1-00](#) [LST1-01F06-FRD1-00](#) [LST1-01G01-UV01-00](#) [LST1-01G01-PRD1-00](#) [XQEROY-00-0000-000000Q01-SB01](#) [LST1-01G01-UV03-00](#) [LST1-01G01-RYL1-00](#) [L135-A589003500000](#) [L135-L567L00000000](#) [L1C1-GRN1000000000](#) [LA G6SP-DAFA-24-1](#) [LS G6SP-CADB-1-1-Z](#) [LY H9PP-HZJZ-46-1](#) [SMTL6-RC](#) [MLEBLU-A1-0000-000U01](#) [MLEBLU-A1-0000-000U05](#) [MLEGRN-A1-0000-000101](#) [MLESRD-A1-0000-000W01](#) [XBDAMB-00-0000-000000701](#) [XBDAMB-00-0000-000000801](#) [XBDBLU-00-0000-000000201](#) [XBDBLU-00-0000-000000202](#) [XBDGRN-00-0000-000000B01](#) [XBDGRN-00-0000-000000C01](#) [XBDGRN-00-0000-000000C02](#) [XBDGRN-00-0000-000000D02](#) [XBDRDO-00-0000-000000801](#)