


MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918
Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

Force 2 Click





PID: MIKROE-4046

Force 2 Click is a mikroBUS™ add-on board with circuitry for implementing Honeywell's FSS1500NGT Series force sensors into your projects (with a single zone force sensing resistor included with the click). This Click board™ utilizes FSS1500NGT force sensor which is designed to be one of the most reliable force sensor available as illustrated by 20 million Mean Cycles to Failure (MCTF) at 25 °C [77 °F] rating. This low profile Surface Mount Technology (SMT) sensor allows for automated assembly on a printed circuit board, often helping the customer to reduce assembly costs, while maintainging precise and reliable force sensing performance in a compact commercial-grade package.

Force 2 Click is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board $^{\text{m}}$ comes as a fully tested product, ready to be used on a system equipped with the mikroBUS $^{\text{m}}$ socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Specifications

Туре	Force
Applications	FSS1500NGT sensor is used in medical and industrial purposes, like infusionand ambulatory non-invasive pumps, kidney dialysis machines, load and compression sensing, variable tension control, robotic endeffector, etc.
On-board modules	FSS015NGT Honeywell's FSS-SMT Series force sensor
Key Features	FSS015NGT force sensor on it and the force sensing range is 0-15N with overforce up to 45N
Interface	Analog
Compatibility	mikroBUS
Click board size	S (28.6 x 25.4 mm)
Input Voltage	5V

Resources

mikroBUS™

mikroSDK

Click board™ Catalog

Click boards™


Downloads

Force 2 click example on Libstock

Force 2 click 2D and 3D files

Force 2 click schematic

FSS1500NGT datasheet







health and safety management system.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multiple Function Sensor Development Tools category:

Click to view products by MikroElektronika manufacturer:

Other Similar products are found below:

MAXWSNENV# STEVAL-MKIT01V1 KT-O2-25%-TB200A-E KT-TVOC-200-TB200A KT-NmHc-200-TB200A SEN0344 PIM520

PIM518 PIM519 PIM502 EVAL-AD7746HDZ AS7022-EVALKIT ALTEHTG2SMIP OB1203SD-U-EVK MIKROE-4265 ARG-LDKT

EV_ICG-20660L GX-F12A-P GX-F15A GX-F6A-P GX-F8B GX-H12A-P GX-H15AI-P GX-H6A-P 1093 MIKROE-2455 MIKROE-2458

MIKROE-2507 MIKROE-2508 MIKROE-2516 MIKROE-2529 1458 MIKROE-1628 176 189 1893 2106 ATQT4-XPRO GX-F12AI-P

GX-F15A-P GX-F8A-P GX-FL15B-P GX-H15A-P GX-H6AI-P GX-H8AI-P GX-H8A-P GX-F15AI-P GX-FL15A-P GX-H15A