

Mikromedia 5 for STM32F7 Resistive FPI with frame



PID: MIKROE-6159

Rich with peripherals

Mikromedia 5 for STM32F7 Resistive FPI with frame is not limited to multimedia-based applications only. USB, WiFi and RF connectivity options, digital motion sensor, battery charging functionality, piezo-buzzer, SD card reader, RTC, and much more expands its use beyond the multimedia.

Mikromedia 5 for STM32F7 Resistive FPI with frame has three mikroBUS™ Shuttle connectors, a brand-new addition to the mikroBUS™ standard in the form of a 2x8-pin IDC header with 1.27mm (50mil) pitch. [mikroBUS™ Shuttle](#) extension board is an add-on board equipped with the conventional mikroBUS™ socket, which ensures compatibility with 894 [Click boards™](#).

Awesome graphics on MCU driven TFT

Mikromedia 5 for STM32F7 Resistive FPI with frame is a compact development board designed as a complete solution for the rapid development of multimedia and GUI-centric applications. By featuring a 5" TFT display with resistive touch screen driven by the powerful graphics controller that can display the 24-bit color palette (16.7 million colors), along with a DSP-powered embedded sound CODEC IC, represents a perfect solution for any type of multimedia application.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
ISO 14001: 2015 certification of environmental management system.
OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).

Develop-on & build-in the same board

Mikromedia 5 for STM32F7 RESISTIVE FPI (FPI stands for Front Panel Integration) with frame is designed as the complete solution. It can be implemented directly into any project, with no additional hardware modifications. At its core, there is a powerful 32-bit [STM32F407ZGT6](#) microcontroller from [STMicroelectronics](#), which provides sufficient processing power for the most demanding tasks. Board has a TFT display with a metal frame, and four mounting holes that enable simple installation in various kinds of industrial appliances. For most uses, a nice casing is all that is needed to turn this product into a high-performance, feature-rich device. This board requires the use of an external programmer and debugger, preferably [CODEGRIP](#) or mikroProg. The microcontroller can be programmed and debugged over the JTAG/SWD compatible 2x5 pin header, labeled as [PROG/DEBUG](#).

Specifications

Type	mikromedia
Architecture	ARM (32-bit)
Display size	5"
Resolution	800x480px
Graphic controller	SSD1963
Touch Screen	Resistive
Input Voltage	3.3V
Silicon Vendor	STM
mikroBUS No.	3
Frame Type	Metal Frame
Features	Batt. Chg. when OFF,WiFi,USB Type C,USB Host,SD Card,RF,ON/OFF switch,MP3,External DC source,Battery Powered
Display type	mikromedia

Downloads

[Mikromedia 5 for STM32F7 Resistive FPI with frame manual](#)

[Mikromedia 5 for STM32F7 Resistive FPI with frame schematic](#)

[Mikromedia 5 for STM32F7 Resistive FPI with frame 2D and 3D files](#)

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
ISO 14001: 2015 certification of environmental management system.
OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Display Modules](#) category:

Click to view products by [MikroElektronika](#) manufacturer:

Other Similar products are found below :

[17978](#) [20135](#) [MIKROMEDIA 3 FOR PIC32MZ CAPACITIVE FPI](#) [19885](#) [1.5inch OLED Module](#) [ULCD-104D](#) [6SL32550AA004JA2](#)
[6SL32550AA004CA1](#) [11769](#) [MIKROMEDIA FOR DSPIC33](#) [MIKROMEDIA FOR PIC24](#) [MIKROMEDIA FOR STELLARIS M3](#)
[MIKROMEDIA HMI 3.5 RES](#) [MIKROMEDIA HMI 5](#) [MIKROMEDIA PLUS FOR FT90X](#) [MIKROMEDIA PLUS FOR PIC32MX7 SHIELD](#)
[MIKROMEDIA PROTO SHIELD](#) [14628](#) [MIKROMEDIA 5 FOR TIVA SHIELD](#) [MIKROMEDIA CONNECT SHIELD](#) [MIKROMEDIA FOR](#)
[ARM](#) [MIKROMEDIA FOR PSOC5LP](#) [MIKROMEDIA HMI 4.3 UXB](#) [MIKROMEDIA HMI 7](#) [MIKROMEDIA HMI BREAKOUT BOARD](#)
[16381](#) [17916](#) [18205](#) [18207](#) [18625](#) [PIS-0260](#) [GEN4-ULCD-70D](#) [2402630](#) [2402980](#) [2402981](#) [2403461](#) [HMIDT351](#) [MIKROE-3158](#)
[MIKROE-3159](#) [HMIS5T](#) [GEN4-ULCD-50DT-SB-AR](#) [GEN4-ULCD-50DCT-CLB-SB-AR](#) [GEN4-ULCD-70DCT-CLB-SB-AR](#) [gen4-](#)
[4DCAPE-50CT-CLB](#) [2402629](#) [gen4-4DCAPE-50T](#) [gen4-4DCAPE-43CT-CLB](#) [gen4-4DCAPE-70T](#) [CleO50A](#) [gen4-4DCAPE-43T](#)