



NC10MX-TOP

8+2 pole male cable connector, TRUE OUTDOOR PROTECTION (TOP), gold contacts

The X-TOP series is a "heavy-duty" XLR cable connector series for outdoor use. IP65 rated and TOP approved in consideration to UL50E by mating with related cable or chassis connector of the XLR TOP range

Features & Benefits

- Heavy-duty sealed XLR connector range for harsh and demanding environment
- Suitable for data offering CAT 5e performance and power up to 16 A and 50 V - exceeds PoE+ capabilities
- IP65 rated and TOP approved in consideration to UL50E by mating with related cable or chassis connector of the XLR TOP range
- Superior ruggedness compared to RJ45 type connectors
- High impact UV resistant materials
- IEC 61984 certified

Technical Information

Product	
Title	NC10MX-TOP
Connection Type	XLR
Gender	Male

Electrical	
Contact resistance	≤ 3 mΩ
Dielectric strength	1 kVdc
Insulation resistance	> 10 GΩ (initial)
Number of electronical contacts	8 + 2
Rated current per contact	16 A (power pins), 3 A (data pins)
Rated voltage	50 V
Cable shield - shell connection:	choosable
Transmission performance	CAT 5e

Mechanical	
Cable O.D.	7.0 - 10.0 mm
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	2.5 mm²/<1 mm²
	8 x 24 AWG + 2 x 16AWG
Type of terminations	Solder contacts
Locking device	Latch lock

Material

Bushing	UV-resistant rubber
Contact plating	Gold (Au) over Nickel (Ni)
Contacts	Brass
Insert	Polyamide
Locking element	St3K32 (latch) / Ck 67 (spring)
Shell	Zinc diecast
Shell plating	Nickel
Strain relief	Polyacetal
Sealing jacket	UV-resistant rubber

Environmental

Flammability acc. to UL94	V-0 (insert)
Standard compliance	IEC 61076-2-103
Protection class acc. IEC 60529	IP65 (mated)
Solderability acc. to	IEC 60068-2-20
Temperature range	-30 °C to +80 °C
Pollution degree	II

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [XLR Connectors](#) category:

Click to view products by [Neutrik](#) manufacturer:

Other Similar products are found below :

[026-4026-100](#) [103F](#) [103M](#) [1502 03](#) [203F](#) [203FM](#) [203M](#) [203P](#) [2410 07](#) [303B](#) [318](#) [321](#) [366](#) [366R](#) [367](#) [367R](#) [383A](#) [387A](#) [387AX](#) [389X](#)
[3FD-H-I](#) [3FD-H-I\(0\)](#) [3FD-H-I-B](#) [3FD-L-I\(O\)](#) [3FD-V-I](#) [3FD-V-I-0](#) [3FD-V-I\(0\)](#) [3FD-V-I-B](#) [3MC-I](#) [3MD-H-I](#) [3MD-H-I-B](#) [3MD-V-I](#)
[3MD-V-I-B](#) [52500016-400](#) [52590060-300](#) [5XNACF/PC90L \(CP300405\)](#) [5XNACM/PC90\(CP300255\)](#) [700-0400](#) [700-0500](#) [701-0300](#) [701-0400](#) [702-0300](#) [702-0400](#) [702-0500](#) [703-0300](#) [703-0400](#) [703-0500](#) [705-0500](#) [707-0300](#) [708-0300](#)