



NC4MDX-TOP

4 pole male chassis connector, TRUE OUTDOOR PROTECTION (TOP)

The X-TOP series is a "heavy-duty" XLR chassis connector for outdoor use. IP65 rated and TOP approved in consideration to UL50E by mating with related cable or chassis connector of the XLR TOP range

Features & Benefits

- Heavy-duty sealed XLR connector range for harsh and demanding environment
- High impact UV-resistant materials
- IP65 rated and TOP approved in consideration to UL50E by mating with related cable or chassis connector of the XLR TOP range
- IEC 61984 certified

Technical Information

Product	
Title	NC4MDX-TOP
Connection Type	XLR
Gender	Male

Electrical	
Contact resistance	$\leq 5\text{ m}\Omega$
Dielectric strength	1,5 kVdc
Insulation resistance	$> 10\text{ G}\Omega$ (initial)
Rated current per contact	10 A
Rated voltage	50 V

Mechanical	
Insertion force	$\leq 20\text{ N}$
Withdrawal force	$\leq 20\text{ N}$
Lifetime	> 1000 mating cycles
Wiring	Solder contacts
Locking device	Latch lock
Mounting direction	Front mounting
Chassis shape	D

Material	
Contact plating	Gold (Au) over Nickel (NI)
Contacts	Brass
Insert	Polyamide
Locking element	Stainless steel
Gasket	TPE
Shell	Polyamide

Environmental	
Flammability acc. to UL94	V-0
Standard compliance	IEC 61076-2-103
Protection class acc. IEC 60529	IP65
Solderability acc. to	IEC 60068-2-20
Temperature range	-30 °C to +80 °C
Pollution degree acc. to IEC 60664-1	II

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [XLR Connectors](#) category:

Click to view products by [Neutrik](#) manufacturer:

Other Similar products are found below :

[026-4026-100](#) [103F](#) [103M](#) [1502 03](#) [203F](#) [203FM](#) [203M](#) [203P](#) [2410 07](#) [303B](#) [318](#) [321](#) [366](#) [366R](#) [367](#) [367R](#) [383A](#) [387A](#) [387AX](#) [389X](#)
[3FD-H-I](#) [3FD-H-I\(0\)](#) [3FD-H-I-B](#) [3FD-L-I\(O\)](#) [3FD-V-I](#) [3FD-V-I-0](#) [3FD-V-I\(0\)](#) [3FD-V-I-B](#) [3MC-I](#) [3MD-H-I](#) [3MD-H-I-B](#) [3MD-V-I](#)
[3MD-V-I-B](#) [52500016-400](#) [52590060-300](#) [5XNACF/PC90L \(CP300405\)](#) [5XNACM/PC90\(CP300255\)](#) [700-0400](#) [700-0500](#) [701-0300](#) [701-0400](#) [702-0300](#) [702-0400](#) [702-0500](#) [703-0300](#) [703-0400](#) [703-0500](#) [705-0500](#) [707-0300](#) [708-0300](#)