



## NC4MX-TOP

4 pole male cable connector, TRUE OUTDOOR PROTECTION (TOP), gold contacts

The X-TOP series is a "heavy-duty" XLR cable connector for outdoor use. Outdoor protected by mating with related cable connector of the XLR TOP range (IP65).

Gold contacts are standard.

### Features & Benefits

- Heavy-duty sealed XLR connector range for harsh and demanding environment
- Outdoor protection according to IP65
- Uses high impact UV resistant materials
- IEC 61984 certified

Technical Information

| Product         |           |
|-----------------|-----------|
| Title           | NC4MX-TOP |
| Connection type | XLR       |
| Gender          | Male      |

| Electrical                |                                 |
|---------------------------|---------------------------------|
| Contact resistance        | $\leq 3\text{ m}\Omega$         |
| Dielectric strength       | 1,5 kVdc                        |
| Insulation resistance     | $> 10\text{ G}\Omega$ (initial) |
| Rated current per contact | 10 A                            |
| Rated voltage             | 50 V                            |

| Mechanical       |                        |
|------------------|------------------------|
| Cable O.D.       | 5.0 – 8.0 mm           |
| Insertion force  | $\leq 20\text{ N}$     |
| Withdrawal force | $\leq 20\text{ N}$     |
| Lifetime         | $> 1000$ mating cycles |
| Wiresize         | $< 2.5\text{ mm}^2$    |
|                  | 16 AWG                 |
| Wiring           | Solder contacts        |
| Locking device   | Latch lock             |

| Material        |                                 |
|-----------------|---------------------------------|
| Bushing         | UV-resistant rubber             |
| Contact plating | Gold (Au) over Nickel (Ni)      |
| Contacts        | Brass                           |
| Insert          | Polyamide                       |
| Locking element | St3K32 (latch) / Ck 67 (spring) |
| Shell           | Zinc diecast                    |
| Shell plating   | Nickel                          |
| Strain relief   | Polyacetal                      |
| Sealing jacket  | UV-resistant rubber             |

| Environmental                        |                  |
|--------------------------------------|------------------|
| Flammability acc. to UL94            | V-0 (insert)     |
| Standard compliance                  | IEC 61076-2-103  |
| Protection class acc. IEC 60529      | IP65 (mated)     |
| Solderability acc. to                | IEC 60068-2-20   |
| Temperature range                    | -30 °C to +80 °C |
| Pollution degree acc. to IEC 60664-1 | II               |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [XLR Connectors](#) category:*

*Click to view products by [Neutrik](#) manufacturer:*

Other Similar products are found below :

[026-4026-100](#) [103F](#) [103M](#) [1502 03](#) [203F](#) [203FM](#) [203M](#) [203P](#) [2410 07](#) [303B](#) [318](#) [321](#) [366](#) [366R](#) [367](#) [367R](#) [383A](#) [387A](#) [387AX](#) [389X](#)  
[3FD-H-I](#) [3FD-H-I\(0\)](#) [3FD-H-I-B](#) [3FD-L-I\(O\)](#) [3FD-V-I](#) [3FD-V-I-0](#) [3FD-V-I\(0\)](#) [3FD-V-I-B](#) [3MC-I](#) [3MD-H-I](#) [3MD-H-I-B](#) [3MD-V-I](#)  
[3MD-V-I-B](#) [52500016-400](#) [52590060-300](#) [5XNACF/PC90L \(CP300405\)](#) [5XNACM/PC90\(CP300255\)](#) [700-0400](#) [700-0500](#) [701-0300](#) [701-0400](#) [702-0300](#) [702-0400](#) [702-0500](#) [703-0300](#) [703-0400](#) [703-0500](#) [705-0500](#) [707-0300](#) [708-0300](#)