



FEMALE

3004	3 0 0 4 2 0 1	4 0 6 3 0 0 7 2 1	3 4	3 5 4
A04	A05	A08	D04	B05

NOTE:

MATERIAL

M12 INSULATOR PA66, UL94V-0, BLACK
CONTACT GOLD FLASH PLATED BRASS
NUT & SHELL NICKEL PLATED BRASS

ELECTRICAL

RATED CURRENT 2A(8P) / 4A(4/5P)

VOLTAGE 30V(8P) / 60V(5P) / 250V(4P)

INSULATOR RESISTANCE 100 MOhms MIN.
CONTACT RESISTANCE 10 mOhms MAX.
MATING CYCLES 100 CYCLES MIN

ENVIRONMENT

OPERATION TEMPERATURE -40°C TO $+85^{\circ}\text{C}$

IP RATING IP67

RECOMMENDED TORQUE 0.4Nm TO 0.8Nm

858FYYY-203RCS1

SERIES

858F = M12 FIELD INSTALLABLE

CONTACT ARRANGEMENT

A04 = 4P A-CODE

A05 = 5P A-CODE

A08 = 8P A-CODE

D04 = 4P D-CODE

B05 = 5P B-CODE

GENDER

2 = FEMALE

CABLE OD

C = 4mm-8mm OD

CONTACT PLATING

ROHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:

J. KADEL

DATE: 02/04/2022

UNITS = mm

DO NOT SCALE FROM DRAWING

NorComp

1 = GOLD FLASH

SCALE: SHEET NTS

DWG NO.

858FYYY-203RCS1

REV

0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by NorComp manufacturer:

Other Similar products are found below:

600X518037X MA1EAF1200 6STD15PCR99B70A 8R4000A16M020 8R4A00A18M020 8R5000A16M005 1200910008 1200910011 1300140094 130203-0054 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-01016 41-40011 41-40017 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00002 43-01166 41-40005 41-40016 43-00161 43-01191 XS3P-M421-2 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R4006A16A120 8R4000A16M010 RKC 50/16 1R3004A20A1201 6-22279-3 N03FA03144 1300140077 XS8A-0441 859RD04-103R004 860RD04-213R004 860RD04-213R004 860-X08-213R004 1-213245-2 2273142-2