Technical data sheet Cable gland, EX area, PG thread

Art.-Nr. 2050102





Cable gland with EG design type approval certificate for products and protection systems for use in accordance with the regulations in explosion-hazard area. Directive 94/9/EC. EC design type approval certificate number: PTB 99 ATEX 3112X and ... 3113X.

With PG connection thread according to IEC 423.

Robust cap-nut cable gland with large sealing area, as well as strain relief and torsion protection for high sealing demands.

 $Sealing\ ring\ of\ chloroprene/nitrile\ rubber,\ moulded\ sealing,\ so\ no\ connection\ thread\ sealing\ ring$ needed, VDE-tested.

Protection rating IP 68 at 5 bar.














Polyamide

Master data

| Item No. | 2050102 |
|---------------------|----------------------|
| Туре | VTEC EX PG48 SW |
| Description 1 | Cable gland, EX area |
| Dimension | PG48 |
| Colour | Black |
| Material | Polyamide |
| Material symbol | PA |
| Smallest sales unit | 5,00 pcs |
| Weight | 9,46 kg/100 pcs. |

Technical specifications




| Dimension L min. | 42,00 mm |
|--------------------------------|------------------|
| Dimension L max. | 58,00 mm |
| Dimension L1 | 14,00 mm |
| Dimension L2 | 9,00 mm |
| Dimension L3 | 33,00 mm |
| SW | 65,00 mm |
| Version | Straight |
| Type of seal | Sealing ring |
| Bend protection | \boxtimes |
| Sealing range D | 30,00 - 44,00 mm |
| explosion-proof | \checkmark |
| Flat cable threaded connection | \boxtimes |
| For Ex zone | Ex area 22 |
| For Ex zone dust | 22 |
| Thread | Pg 48 |
| Thread type | PG |
| Thread length | 14,00 mm |
| Thread increase | 1,50 mm |
| Nominal thread size | 48,00 |
| Glass-fibre reinforced | \boxtimes |
| Halogen-free | \checkmark |
| Multiple sealing insert | \boxtimes |
| With locknut | \boxtimes |
| Impact resistant | \boxtimes |
| | |

Technical data sheetCable gland, EX area, PG thread



Art.-Nr. 2050102

Technical specifications



| Hexagonal corner dimension | 74,00 mm |
|------------------------------------|-------------------|
| Protection rating | IP68 |
| Splittable gland | |
| max. permitted ambient temperature | -20,00 - 70,00 °C |
| Strain relief option | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Glands, Strain Reliefs & Cord Grips category:

Click to view products by OBO BETTERMANN manufacturer:

Other Similar products are found below:

120-116-1-1-20BP 120-116-1-1-32BE 120-117-40 120-123-14 120-123-16 120-125-16 120-125-16R 120-125-16Y 120-125-24Y 120-125-28R 120-125-32 120-125-32R 120-125-40 120-125-56 120-126-14 120-126-16 120-126-20 120-126-20BL 120-126-20R 120-126-24 120-126-28 120-126-32 120-126-40BL 120-116-1-1-06BP-509 120-116-1-1-06CP 120-116-1-1-16BE 120-116-1-1-28BP 120-123-20 120-123-24 120-123-32 120-125-20 120-125-20Y 120-125-24 120-125-24R 120-125-28Y 120-126-14BL 120-126-16R 120-126-16Y 120-126-24BL 120-126-28BL 120-126-32BL 120-126-40 120-126-48 120-126-48BL 1300980012 1300980105 DBZM-6828 1498 15190-103 R2