


## ODU MEDI-SNAP<sup>®</sup>, Receptacle for front or rear panel mounting

### General information

Part number	G51M08-P08QF00-0040
Termination	PCB
Size	1
Locking principle	Break-Away, Push-Pull
Coding	0°



The pin layout corresponds to the view on the termination area

### Contact insert description

Number of contacts	8
Contact type	Sockets
Contact diameter	0.7 mm
Insulator material	PEEK
Termination	PCB
Termination diameter	0.5 mm

Reverse gender on request

### Technical information

Max. creepage and air clearance distance	0.6 mm (Contact to contact)	IEC 60601-1: 1MOPP, 2MOPP*
Nominal current single contact	6 A	IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003)
Nominal current insert	3,9 A	VDE 0298-4:2003
Test voltage	0.95 kV AC	EIA-364-20F:2019-02

All shown connectors are rated to a safety extra low voltage (SELV) of less than 50 V AC / 75 V DC, according to IEC 61140:2016 (VDE 0140-1:2016) Protection against electric shock - Common aspects for installation and equipment. In case other standards rule a specific use of the connector, the application specific safety criteria shall be considered first. In this context, lower voltage ratings may be valid. Warning: Danger to life for operating voltages above 50 V AC / 120 V DC!

\* As per IEC 60601-1:2012 (VDE 0750-1:2013-12). Max working voltage of the medical electrical device 250 V AC (degree of pollution 2).

## Mechanical and environmental data

Degree of protection*	IP50
Operating temperature	-50 °C – 120 °C
Mating cycles	5000

\*mated & unmated condition

## Insulator materials MEDI-SNAP®

	Standard	PEEK
Flammability rating	UL 94	V-0/1.5
Operation temperature		-50 to +250 °C
Dielectric strength	IEC 60243-1:2013 (VDE 0303-21:2014)	19 kV/mm
Comparative figure of the creep resistance CTI	IEC 60112: 2009 (VDE 0303-11:2010)	175
Water absorption	ASTM D 570:1998 / ISO 62:2008	0.1 %
Insulation resistance	IEC 60512-3-1:2002 (DIN EN 60512-3-1:2003-01)	$> 1 \times 10^{12} \Omega$

## Material and surface treatments

Housing	PSU black
Color option	Yellow
Contact	Cu-alloy with gold finish

All shown connectors are defined without breaking capacity (COC) according to IEC 61984:2008 (VDE 0627:2009).

ODU MEDI-SNAP® and MINI-SNAP® are UL-approved (E110586).

ODU reserves the right to make changes based on the current state of knowledge without prior notice without being obliged to provide replacement deliveries or refinements of older designs.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Circular Push Pull Connectors](#) category:*

*Click to view products by [ODU](#) manufacturer:*

Other Similar products are found below :

[6407-249V-11273P](#) [6408-201V-13273](#) [6408-202V-13343](#) [6408-202V-17343](#) [FGC.2B.303.CYBD42Z](#) [FGJ.0B.304.CYZZ](#) [PLC.M1.0SL.LA](#)  
[1589430-2](#) [169-0105-02](#) [FFA.1S.130.LC](#) [6408-201V-11273](#) [6408-201V-11343](#) [6408-202V-25273](#) [980-0009-471](#) [NCG044SC2DC006](#)  
[GMA.4B.013.DN](#) [1331E103MZ](#) [342491](#) [PCA.1S.303.ZLLT](#) [FHG.00.305.CLAD35](#) [39050630713002](#) [1332E319FZ](#) [342379](#)  
[PAG.M0.6SL.AC52G](#) [300374](#) [SOB.187.GN](#) [FFA.2S.130.LC](#) [JBXEA2G003MSNDS](#) [JBXFN0G07MSSDSR](#) [FNG.1B.304.U2034](#)  
[JBXER1G04MCSDSR](#) [JBXEA2G04MSNDS](#) [1331M303FS](#) [JBXER1G03MCSDSR](#) [FEG.1B.302.CYBD52](#) [S41M08-P02MPN0-528S](#) [FLBB-](#)  
[05EGFS-GCP-001](#) [FLBB-05FGMS-GCP-207](#) [PCA.1S.306.CLCC66](#) [702.098.001.000.000](#) [10-711587-040](#) [FGG.2B.560.ZZF](#)  
[FGG.2B.560.ZZK](#) [FGG.4B.555.ZZF](#) [FGG.4B.555.ZZK](#) [PHG.4K.310.CLCC11](#) [ECG.2B.514.CLL](#) [GA1M08-P04LJG0-0000](#) [S10K0C-](#)  
[P05PFG0-5000](#) [FGB.1K.316.CLAC55Z](#)