



SOT-23



MARKING: K6N

1. Emitter1
2. Base1
3. Collector2
4. Emitter2
5. Base2
6. Collector1

Features

Complementary pair(3906+3906)
High stability and high reliability
Epitaxial planar die construction
Halogen free and RoHS compliant

Mechanical Data

SOT-363 Small Outline Plastic Package
Epoxy UL: 94V-0

Maximum Ratings & Thermal Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified.)



Parameters	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	60	V
Collector-Emitter Voltage	V_{CEO}	40	V
Emitter -Base Voltage	V_{EBO}	6	V
Collector Current-Continuous	I_C	200	mA
Collector Power Dissipation	P_C	200	mW
Junction Temperature	T_j	150	°C
Storage Temperature	T_{stg}	-55-+150	°C
Thermal resistance From junction to ambient	$R_{\theta JA}$	625	°C/W

Electrical Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified.)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=10\mu A, I_E=0$	60			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=1mA, I_B=0$	40			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=10\mu A, I_C=0$	5			V
Collector cut-off current	I_{CBO}	$V_{CB}=30V, I_E=0$			50	nA
Emitter cut-off current	I_{EBO}	$V_{EB}=5V, I_C=0$			50	nA
DC current gain	$h_{FE(1)}$	$V_{CE}=1V, I_C=0.1mA$	40			
	$h_{FE(2)}$	$V_{CE}=1V, I_C=1mA$	70			
	$h_{FE(3)}$	$V_{CE}=1V, I_C=10mA$	100		300	
	$h_{FE(4)}$	$V_{CE}=1V, I_C=50mA$	60			
	$h_{FE(5)}$	$V_{CE}=1V, I_C=100mA$	30			
Collector-emitter saturation voltage	$V_{CE(sat)1}$	$I_C=10mA, I_B=1mA$			0.2	V
	$V_{CE(sat)2}$	$I_C=50mA, I_B=5mA$			0.3	V
Base-emitter saturation voltage	$V_{BE(sat)1}$	$I_C=10mA, I_B=1mA$	0.65		0.85	V
	$V_{BE(sat)2}$	$I_C=50mA, I_B=5mA$			0.95	V
Transition frequency	f_T	$V_{CE}=20V, I_C=10mA, f=100MHz$	300			MHz
Delay time	t_d	$V_{CC}=3V, V_{BE(off)}=-$			35	nS
Rise time	t_r	$0.5V, I_C=10mA, I_{B1}=-I_{B2}=1mA$			35	nS
Storage time	t_s	$V_{CC}=3V, I_C=10mA, I_{B1}=-I_{B2}=1mA$			200	nS
Fall time	t_f				50	nS

Ratings and Characteristic Curves




Summary of Packing Options

Package	Packing Description	Packing Quantity	Industry Standard
SOT-363	Tape/Reel, 7" reel	3000	EIA-481-1

Package Outline Dimensions:

SOT-363



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bipolar Transistors - BJT](#) ***category:***

Click to view products by [PAKER Microelectronics](#) ***manufacturer:***

Other Similar products are found below :

[MCH4017-TL-H](#) [MMBT-2369-TR](#) [NJVMJD148T4G](#) [NTE16](#) [NTE195A](#) [2N4401-A](#) [2N6728](#) [2SB1204S-TL-E](#) [2SC4731T-AY](#) [2SC5488A-TL-H](#) [FMC5AT148](#) [2N2369ADCSM](#) [2N2907A](#) [2N3904-NS](#) [2SB1324-TD-E](#) [2SC5231C8-TL-E](#) [CPH6501-TL-E](#) [BULD128DT4](#) [CPH6021-TL-H](#) [MCH6102-TL-E](#) [2N3879](#) [30A02MH-TL-E](#) [NTE13](#) [NTE282](#) [NTE350](#) [NTE81](#) [JANSR2N2907AUB](#) [JANSR2N2222AUB](#) [CMLT3946EG TR](#) [SNSS40600CF8T1G](#) [CMLT3906EG TR](#) [GRP-DATA-JANS2N2907AUB](#) [GRP-DATA-JANS2N2222AUA](#) [MMDT3946FL3-7](#) [2N4240](#) [JANS2N3019](#) [MSB30KH-13](#) [2N2221AUB](#) [2SD1815T-TL-E](#) [Jantxv2N3810](#) [2N6678](#) [2N2907Ae4](#) [2N3963](#) [50C02MH-TL-E](#) [Jantx2N5415](#) [CPH3123-TL-E](#) [SMBT35200MT1G](#) [SMMJT350T1G](#) [NSVDTA113EM3T5G](#) [MBT3904DW1T1H](#)