

A. System Overview

BT2HT Hand Operated Installation Tool for Strapping

B1. Cable Ties

- Strap side entry
- Multi-position rear handle provides flexibility for a one or two hand installation
- Adjustable tension control
- Easy removal of excess strap
- Installs (3) sizes: 0.38 inch (9.5mm), 0.50 inch (12.7mm), and 0.63 inch (15.9mm)
- Replacement cutter blade and handle available

B2. Cable Accessories



B3. Stainless Steel Ties

| Part Number | Part Description | Std. Pkg. Qty. |
|-----------------|--|----------------|
| BT2HT | Installation tool for use with 0.38" (9.5mm), 0.50" (12.7mm), and 0.63" (15.9mm) widths of Panduit® Pan-Steel® Strapping. Tensions, cuts strapping, and secures the buckle tab. Lever cut off. | 1 |
| KRT2BLD | Replacement cutter blade for RT2HT and BT2HT. | 1 |
| KRT2HNDL | Replacement Cutter Handle for RT2HT and BT2HT | 1 |

C1. Wiring Duct

C2. Surface Raceway

NEW! BT75SDT Hand Operated Installation Tool for MS75 Strapping

C3. Abrasion Protection

- Screw drive tension mechanism provides high tension with minimal effort, reducing operator fatigue
- Heavy duty construction offers a longer service life
- Strapping side entry allows quick side entry of the strap into tool to speed installation

C4. Cable Management



D1. Terminals

| Part Number | Part Description | Std. Pkg. Qty. |
|----------------|--|----------------|
| BT75SDT | Installation tool for use with 0.75" (19.1mm) width strapping only. Tensions and cuts strapping. Screwdriver required for buckle closure (not included). | 1 |

D2. Power Connectors

D3. Grounding Connectors

PCS Cushion Sleeve

E1. Labeling Systems

- Black neoprene sleeving used with Pan-Steel® Stainless Steel Ties, custom length banding, and MS strap
- Used on applications requiring improved gripping on non-resilient objects
- Can be used indoors or outdoors (excellent ultraviolet resistance, good resistance to petroleum, and many chemicals)
- Isolation between dissimilar metals allows the ties and straps to be used with aluminum cable tray
- Provides full separation between the ties and the bundle
- Operating temperature range -40°F (-40°C) to 200°F (93°C)

E2. Labels



E3. Pre-Printed & Write-On Markers

| Part Number | Used with Pan-Steel® Ties/Strapping | Width | | Length | | Std. Pkg. Qty.‡ |
|--------------------|-------------------------------------|-------|------|--------|------|-----------------|
| | | In. | mm | Ft. | m | |
| PCSS-B-CR | MLT/S | .33 | 8.4 | 100 | 30.5 | 1 |
| PCSH-B-CR | MLT/LH/H | .47 | 11.9 | 100 | 30.5 | 1 |
| PCSSH-B-CR* | MLT/EH/SH and MS Straps | .91 | 23.1 | 100 | 30.5 | 1 |

E4. Permanent Identification



E5. Lockout/Tagout & Safety Solutions

*Meets MIL-R-6855
‡Order in number of reels required.
Pkg. -CR = 100 ft. (30.5m) reel.

F. Index

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Spiral Wraps, Sleeves, Tubing & Conduit](#) category:

Click to view products by [Panduit](#) manufacturer:

Other Similar products are found below :

[601203-000](#) [CTA-0053](#) [8426-11](#) [8429-9](#) [8445-7.5](#) [8450](#) [120-104-24](#) [120-113-16B](#) [120-116-1-1-09BE](#) [120-116-1-1-09BF](#) [120-116-1-1-09BP](#)
[120-116-1-1-12BE](#) [120-116-1-1-12BP](#) [120-116-1-1-20BP](#) [120-116-1-1-32BE](#) [120-117-40](#) [120-123-06](#) [120-123-10](#) [120-123-14](#) [120-123-16](#)
[120-125-12BL](#) [120-125-12R](#) [120-125-16](#) [120-125-16R](#) [120-125-16Y](#) [120-125-20R](#) [120-125-24Y](#) [120-125-28](#) [120-125-28R](#) [120-125-32](#)
[120-125-32R](#) [120-125-40](#) [120-125-56](#) [120-126-09](#) [120-126-09BL](#) [120-126-12](#) [120-126-12BL](#) [120-126-14](#) [120-126-16](#) [120-126-16BL](#) [120-](#)
[126-20](#) [120-126-20BL](#) [120-126-20R](#) [120-126-24](#) [120-126-28](#) [120-126-32](#) [120-126-40BL](#) [120-126-52](#) [120-126-52BL](#) [120-104-12](#)