

Shielded Category 6A Patch Cords

SPECIFICATIONS

Category 6A/Class E_A S/FTP patch cords shall be constructed of 26 AWG stranded copper cable and a modular plug on each end. All Patch cords shall be wired to be compatible with both T568A and T568B wiring schemes.



TECHNICAL INFORMATION

Category 6A/Class E_A performance:	Exceeds ANSI/TIA-568.2-D Category 6A and ISO 11801 Class E _A channel requirements at swept frequencies up to 500 MHz
Cable diameter:	0.232 in. (5.9mm) nominal
FCC compliance:	Complies with ANSI/TIA-1096-A (formerly FCC Part 68); contacts plated with 50 microinches of gold for superior performance
IEC compliance:	Meets IEC 60603-7
PoE compliance:	Supports IEEE 802.3af/802.3at and 802.3bt type 3 and type 4 PoE applications
RoHS compliance:	Compliant
Flammability rating:	LSZH rated

KEY FEATURES AND BENEFITS

Performance tested:	Confidence that each patch cord delivers specified performance
Integral pair manager:	Optimizes performance and consistency by reducing untwist at plug
Slender strain relief boot:	Provides easy access in high-density applications
Robust construction:	Rated to 2500 mating cycles

APPLICATIONS

Key applications include:

- 10GBASE-T Ethernet
- Wireless deployment
- Power over Ethernet
- Voice Over Internet Protocol (VoIP)

Shielded Category 6A Patch Cords

Meter lengths: S6XPC^{^M}**

Strain Relief Bar

Straight: SRBS19BL-XY

Extended 2": SRB19BLY

With hook and loop ties: SRBM19BLY

With adjustable clips: SRBWCY

Multi-depth: SRB19MDBL

[^]Meter lengths: 1, 1.5, 2, 2.5, 3, 3.5, 5, 10, or 15 meters

^{**}Colors: BU (Blue) or IG (International Gray)

ØLengths 1 meter to 15 meters or 6 inches to 49 feet are guaranteed to meet TIA and ISO component and channel requirements

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ethernet Cables / Networking Cables](#) ***category:***

Click to view products by [Panduit](#) ***manufacturer:***

Other Similar products are found below :

[73-7795-1](#) [MCJB2-10P6Q7-120](#) [84909-0204](#) [1-1997459-2](#) [1-1997459-3](#) [ASP-144414-04](#) [E16A06002M030](#) [18169-0524](#) [1969343-6](#)
[C5UMB3FBG](#) [21949-1](#) [360031](#) [AX100351](#) [09459711142](#) [73-7793-1](#) [WHU18-1836-060](#) [1-3636-620-5214](#) [STS](#) [09470303023](#) [09459711118](#)
[1404682](#) [C5SMB14FBG](#) [CA21116001](#) [WK-100](#) [UTPCH22VLY](#) [UTPSP50BLY](#) [C6F1106003](#) [UTPSP16MRDY](#) [UTPSP16MGRY](#)
[UTP28CH30MBL](#) [AX105520](#) [CAPFCU-B25](#) [CB8MMBK-B100](#) [DK-1511-002/B](#) [STP6X1BU](#) [904873-000](#) [17-103134](#) [1110401155](#)
[09459711186](#) [EL6614](#) [MRC191ZN79H1](#) [SSFPP-P03M0-2](#) [1426514](#) [1413684](#) [1426515](#) [1414043](#) [1413685](#) [7000-44511-6590150](#) [7000-](#)
[44511-7940300](#) [7000-44561-7940150](#)