## **Standards**

The main standard driving pipe markers is ASME A13.1-2007. The standard is only regarded as a guideline, and provides recommendations for legends, shapes, sizes, colors and the locations of pipe markers.

OD of pipe covering (in)	Length of pipe marker (in)	Height of Letter (in)
0.75 - 1.25	8	0.5
1.5 - 2	8	0.75
2.5 - 6	12	1.25
8 - 10	24	2.5
>10	32	3.5

Table 1 - Marker and Legend sizes based on pipe outside diameter according to ASME A13.1-2007





Table 2 - Marker color recommendations according to ASME A13.1-2007

A typical pipe would have the following legend identifier and arrows to specify flow - see example below:



Pipe markers should be positioned according to the following criteria:

- Markers are easily seen from the normal angle of approach, for example, below the centerline of the pipe is overhead, and above the centerline if the pipe is below eye level
- · Labels are required at the following locations
  - Adjacent to all valves and flanges
  - Adjacent to all changes of direction
  - On both sides of wall or floor penetrations
  - At regular intervals on straight runs (50' is the acceptable maximum spacing, but closer spacing might be necessary for visibility)



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Identification category:

Click to view products by Panduit manufacturer:

Other Similar products are found below:

CU6337-000 CU6342-000 FCA-410-12 11631010 1-1768037-1 1-1768037-2 1-1768050-0 PXLK-VI Q62184-1 A64304-000

HK032WE1NF038B 1330-0519-10 1395200-1 1395202-1 DMVF050WE-30086 D-SCE-1K-2.4-50-4-CS7834 1538738-1 E90935-000

EC1238-000 EC1465-000 EC1855-000 EC1859-000 EC1863-000 EC5415-000 EC7277-000 EC7352-000 EC7603-000 EC7707-000

EC7735-000 EC7768-000 EC7828-000 EC7854-000 EC7952-000 EC8128-000 1768037-8 1768041-7 NC-127191-10-9

HS048WE2NF038B C03232-000 HTCM-SCE-14-4H-9 HTMS-3/16-9 HT-SCE-1/4-2.0-4 HT-SCE-3/16-2.0-4 HTTMS-1/2-1.50-9 HTTMS-1/2-4H-9 HX-SCE-19.0-50-9 HX-SCE-6.4-50-4 C25254-000 CA5939-000 CA7155-000