

STRONGHOLD™ 4 Way Adhesive Backed Cable Tie Mounts:

StrongHold 4-way adhesive backed cable tie mounts are mounted with rubber-based adhesive foam tape. The adhesive backing provides a dependable method for securing wires and cables quickly and are an alternative to mechanical fasteners, providing lower installed cost.

- Allows cable tie entry from all four sides
- Available in 3 sized to meet application needs
- Rubber-Based Adhesive provides a strong and reliable bond



Part Number	Used with StrongHold Cable Ties	Material	Size L. X W	Max. Static Load (lb, N)	Adhesive Type	Std. Pkg Qty.	Std. Ctn. Qty.
SMP12A-3X	S*-18, S*-40	Natural Nylon 6.6	.785 x .785 (20 x 20)	18lb, 80N	Rubber	30	300
SMP12A-C	S*-18, S*-40	Natural Nylon 6.6	.785 x .785 (20 x 20)	18lb, 80N	Rubber	100	1000
SMP12A-M	S*-18, S*-40	Natural Nylon 6.6	.785 x .785 (20 x 20)	18lb, 80N	Rubber	1000	5000
SMP16A-3X	S*-18, S*-40, S*-50	Natural Nylon 6.6	.976 x .976 (25 x 25)	40lb, 180N	Rubber	30	300
SMP16A-C	S*-18, S*-40, S*-50	Natural Nylon 6.6	.976 x .976 (25 x 25)	40lb, 180N	Rubber	100	1000
SMP16A-M	S*-18, S*-40, S*-50	Natural Nylon 6.6	.976 x .976 (25 x 25)	40lb, 180N	Rubber	1000	5000
SMP18A-3X	S*-18, S*-40, S*-50	Natural Nylon 6.6	1.169 x 1.169 (30 x 30)	49lb, 220N	Rubber	30	300
SMP18A-C	S*-18, S*-40, S*-50	Natural Nylon 6.6	1.169 x 1.169 (30 x 30)	49lb, 220N	Rubber	100	1000
SMP18A-M	S*-18, S*-40, S*-50	Natural Nylon 6.6	1.169 x 1.169 (30 x 30)	49lb, 220N	Rubber	1000	5000
SMP12A-3X0	S*-18, S*-40	Black Nylon 6.6	.785 x .785 (20 x 20)	18lb, 80N	Rubber	30	300
SMP12A-C0	S*-18, S*-40	Black Nylon 6.6	.785 x .785 (20 x 20)	18lb, 80N	Rubber	100	1000
SMP12A-M0	S*-18, S*-40	Black Nylon 6.6	.785 x .785 (20 x 20)	18lb, 80N	Rubber	1000	5000
SMP16A-3X0	S*-18, S*-40, S*-50	Black Nylon 6.6	.976 x .976 (25 x 25)	40lb, 180N	Rubber	30	300
SMP16A-C0	S*-18, S*-40, S*-50	Black Nylon 6.6	.976 x .976 (25 x 25)	40lb, 180N	Rubber	100	1000
SMP16A-M0	S*-18, S*-40, S*-50	Black Nylon 6.6	.976 x .976 (25 x 25)	40lb, 180N	Rubber	1000	5000
SMP18A-3X0	S*-18, S*-40, S*-50	Black Nylon 6.6	1.169 x 1.169 (30 x 30)	49lb, 220N	Rubber	30	300
SMP18A-C0	S*-18, S*-40, S*-50	Black Nylon 6.6	1.169 x 1.169 (30 x 30)	49lb, 220N	Rubber	100	1000
SMP18A-M0	S*-18, S*-40, S*-50	Black Nylon 6.6	1.169 x 1.169 (30 x 30)	49lb, 220N	Rubber	1000	5000

Rubber-based Adhesive is the best choice for most adhesive mount applications, including applications where powder coated surfaces are being used. This pressure sensitive tape can be used in indoor environments with temperatures ranging from -20°F to 120°F (-29°C to 49°C). Rubber-based Adhesive Foam Tape is the most widely used and generally recommended foam tape for wire routing applications.

Installation Guidelines Preparation

For best results, mounts should be applied to a clean, dry, and grease-free surface. It is recommended that for each individual application, a solvent or cleanser be used to thoroughly prepare the surface for mount installation.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cable Tie Mounts](#) category:

Click to view products by [Panduit](#) manufacturer:

Other Similar products are found below :

[CTB75X75BKA-C](#) [08443-0](#) [10035-0](#) [1689174-1](#) [08445-0](#) [10351-0](#) [10029-0](#) [08484-0](#) [08446-0](#) [08318-0](#) [FTH-5-DHB](#) [BMB0901](#) [BMB0902](#)
[BMB0903](#) [151-02258](#) [151-25619](#) [151-00356](#) [PKB-1/4-0](#) [61724510](#) [70362](#) [17104](#) [70431](#) [17084](#) [7TAG009820R0050](#) [61724910](#) [S4NY-140-](#)
[0-C](#) [TC1103](#) [TC223-TB](#) [TTCC-R14](#) [TTCC-S8](#) [TTCC-R5](#) [TTCC-R6](#) [TTCC-R9](#) [TTCC-R12](#) [TTCC-R4](#) [TTCC-S6](#) [TTCC-R10](#) [TTCC-S5](#)
[TTCC-S14](#) [TTCC-S7](#) [TTCC-R7](#) [TTCC-S10](#) [FTH-13R-19-M](#) [SMP18A-C](#) [150-77950](#) [156-02462](#) [156-02527](#) [SMP16A-C0](#) [06290](#) [10044](#)