


HC-M-05-MWF-F - Contact insert module



1118096

<https://www.phoenixcontact.com/us/products/1118096>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert module, number of positions: 5, power contacts: 5, Socket, Push-in connection, 400 V, 16 A, 0.5 mm² ... 2.5 mm², application: Power, with disconnect zone for fuse plugs, component connectors, and isolating plugs

Your advantages

- Easy installation without tools, even when mounted, with push-in connection technology
- Function moves into the connector
- Function directly at the application
- Multifunction slot in the module
- Reliable wiring
- Shock-resistant and vibration-resistant

Commercial data

Item number	1118096
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF62
Product key	AF7ACE
GTIN	4063151046484
Weight per piece (including packing)	52.4 g
Weight per piece (excluding packing)	52.4 g
Customs tariff number	85366990
Country of origin	CN

HC-M-05-MWF-F - Contact insert module



1118096

<https://www.phoenixcontact.com/us/products/1118096>

Technical data

Notes

General	only use flexible conductors with ferrules
General	Connectors may be operated only when there is no load/voltage.
General	For HEAVYCON housing type B6 to B48, HC-M-B...MF-... module carrier frame required

Product properties

Product type	Modular contact insert
Series	HC-M-05
Application	Power
Number of positions	5
Connection profile	5
No. of power contacts	5
Contact material type	turned
Special properties	Use in HEAVYCON panel-mount base type B6 ... B48

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Connection data

Connection technology

Connection technology	Push-in connection
-----------------------	--------------------

Conductor connection

Conductor cross section	0.5 mm ² ... 2.5 mm ²
Connection cross section AWG	21 ... 14
Stripping length of the individual wire	10 mm ±1 mm

Dimensions

Dimensional drawing	
Width	33.9 mm
Height	54.7 mm
Length	29.3 mm

Mechanical characteristics

Minimum housing height	72 mm
Contact diameter	2.5 mm

Electrical properties

HC-M-05-MWF-F - Contact insert module



1118096

<https://www.phoenixcontact.com/us/products/1118096>

Rated voltage (III/3)	400 V
Rated surge voltage	4 kV
Rated current	16 A

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PC

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

HC-M-05-MWF-F - Contact insert module


1118096

<https://www.phoenixcontact.com/us/products/1118096>




Drawings

Dimensional drawing




Dimensional drawing


Schematic diagram



Connector pin assignment, connection side



Derating diagram for flexible conductors



Derating diagram for flexible conductors with ferrule

HC-M-05-MWF-F - Contact insert module



1118096

<https://www.phoenixcontact.com/us/products/1118096>

Classifications

ECLASS

ECLASS-15.0	27440217
ECLASS-13.0	27440217

ETIM

ETIM 9.0	EC000438
----------	----------

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heavy Duty Power Connectors](#) ***category:***

Click to view products by [Phoenix Contact](#) ***manufacturer:***

Other Similar products are found below :

[6646137-1](#) [6646138-1](#) [6646940-1](#) [6651091-1](#) [6651525-1](#) [6651529-1](#) [73080254296](#) [73080255059](#) [7310205040001](#) [7487](#) [PS25/A0420/63](#)
[AN0024023](#) [1643543-1](#) [1791340000](#) [NLDFT-3-BL-L-S120-M40A](#) [NLDFT-N-W-L-C240-M40B](#) [NLS-2-R-C240-M40B](#) [NLS-3-BL-C240-](#)
[M40B](#) [NLS-N-W-C240-M40B](#) [NPS-3-BL-T6](#) [C148 10A005 000 9](#) [2-1589900-8](#) [9300480317](#) [19000005132](#) [AN0024202](#) [AN0264023](#) [279-](#)
[0841-10100A](#) [281-0334-00100A](#) [419-2083-301](#) [078238-1613](#) [078238-2910](#) [078239-2912](#) [078239-2910](#) [078239-2911](#) [078239-2913](#)
[09370009946](#) [09305160521](#) [09370240318](#) [1-1104457-5](#) [5352I](#) [73000005327](#) [73000005329](#) [73080956756](#) [73080965056](#) [1926075-1](#)
[6646136-1](#) [6646979-1](#) [1103021-2](#) [NPDFT-3-BL-L-T6](#) [46562-1559](#)