

# BS-MAGAZINE PROFILE L - Magazine mounting profile



1640723

<https://www.phoenixcontact.com/us/products/1640723>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Mounting profile for magazines with marking area.

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1640723       |
| Packing unit                         | 10 pc         |
| Minimum order quantity               | 10 pc         |
| Sales key                            | BH21          |
| Product key                          | BH2XX1        |
| GTIN                                 | 4067923167155 |
| Weight per piece (excluding packing) | 185 g         |
| Customs tariff number                | 39162000      |
| Country of origin                    | DE            |

# BS-MAGAZINE PROFILE L - Magazine mounting profile



1640723

<https://www.phoenixcontact.com/us/products/1640723>

## Technical data

### Dimensions

|        |        |
|--------|--------|
| Width  | 51 mm  |
| Height | 21 mm  |
| Length | 988 mm |

### Material specifications

|          |                  |
|----------|------------------|
| Color    | black (RAL 9005) |
| Material | ABS              |

### Environmental and real-life conditions

#### Ambient conditions

|                                                 |                                                                             |
|-------------------------------------------------|-----------------------------------------------------------------------------|
| Optimum ambient temperature (storage/transport) | 20.00 °C 60.00 % 2 years at 15°C ... 25°C and 50% ... 70% relative humidity |
| Ambient temperature (operation)                 | 5 °C ... 35 °C                                                              |
| Ambient temperature (storage/transport)         | 0 °C ... 60 °C                                                              |
| Permissible humidity (operation)                | 10 % ... 80 %                                                               |
| Permissible humidity (storage/transport)        | 20 % ... 80 %                                                               |
| Resistance to UV radiation                      | Adhesive tape, UV-resistant, protect from direct sunlight during storage.   |

## Mounting

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Assembly note | <p>Installation note:</p> <p>Taking the adhesive instructions into account, the L profile must only be installed in a horizontal mounting position. The surface must be sufficiently firm, smooth, and able to carry the required weight, e.g., stainless steel sheeting. Maximum weight load: 7 kg/10 cm width at 10° tilt, maximum.</p> <p>Adhesive instructions:</p> <p>The surfaces and joining pieces must be dry and clean. Avoid any condensation of moisture on the surfaces to be bonded. The joining pieces must be free of dust, grease, oil, and release agents. Loose paint or top layers must be removed or solidified. Apply pressure (10 N/cm² ... 15 N/cm², approximately) using a pressure roller or surface press. The curing time of the adhesive bonding is 24 hours.</p> |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

# BS-MAGAZINE PROFILE L - Magazine mounting profile



1640723

<https://www.phoenixcontact.com/us/products/1640723>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 21101030 |
| ECLASS-15.0 | 21101030 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC011819 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 22101500 |
|-------------|----------|

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for*** [Racks & Rack Cabinet Accessories](#) ***category:***

***Click to view products by*** [Phoenix Contact](#) ***manufacturer:***

Other Similar products are found below :

[HTS10](#) [A48P36G](#) [CM05](#) [TS170](#) [DP-3U](#) [5261304-07](#) [CG3-160G](#) [AEG-4000G](#) [AEG-3000G](#) [SR3-41](#) [29478](#) [SC11-1](#) [M6124-4007-A-24](#)  
[HD138](#) [1CP108A](#) [AC68BRAC3](#) [AEG-3000B](#) [AEG-4000B](#) [AEG-5000B](#) [AEG-5000G](#) [02100.0-00](#) [RM632SCPG-8](#) [8074-632-A](#) [FLEX-](#)  
[PLATE1UR](#) [244422](#) [264091](#) [AEG-2000G](#) [1CM104A](#) [CFS-1.50/3.00](#) [7198](#) [CC-2](#) [CCK60-84-00](#) [92100117-01](#) [HD7-2](#) [CG3-K02/25](#) [TS204](#)  
[1404-0016-12](#) [HD105](#) [8361-1032-ss](#) [8385-1032-A-22](#) [SC02MFA-SS](#) [m6261-6010-ss](#) [8115-632-ss](#) [8221-2520-a-24](#) [8019-256-a](#) [TBV17-12-](#)  
[Semi-gloss BlackPAIR](#) [SS350-14-Black TexturedPAIR](#) [UPS 7-5-5-Blue/White](#) [UPR 350-17-7 Plain](#) [UPS 7-14-9-Blue/White](#)