


XT 1,5-TWIN - Feed-through terminal block



1641116

<https://www.phoenixcontact.com/in/products/1641116>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 500 V, nominal current: 17.5 A, number of connections: 3, number of positions: 1, connection method: Push-X-connection, Rated cross section: 1.5 mm², cross section: 0.25 mm² - 1.5 mm², mounting type: NS 35/7,5, NS 35/15, color: gray

Your advantages

- Maximum ease of use thanks to the effortless and tool-free Push-X technology
- Quick installation of all types of conductors with and without ferrule
- Open clamping chambers guarantee quick wiring on site
- Clear identification of the conductor connection
- Full flexibility thanks to the standardized CLIPLINE complete bridging, marking, and testing accessories
- Compact wiring of three conductors in a single terminal block
- Optimized for manual and automated wiring

Commercial data

Item number	1641116
Packing unit	50 pc
Minimum order quantity	50 pc
Product key	BE2512
GTIN	4067923166783
Weight per piece (including packing)	7.44 g
Weight per piece (excluding packing)	7.44 g
Country of origin	CN

XT 1,5-TWIN - Feed-through terminal block



1641116

<https://www.phoenixcontact.com/in/products/1641116>

Technical data

Notes

General

Note	The max. load current must not be exceeded by the total current of all connected conductors.
------	--

Product properties

Product type	Multi-conductor terminal block
Product family	XT
Area of application	Railway industry
	Machine building
	Plant engineering
	Process industry
Number of positions	1
Number of connections	3
Number of rows	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	6 kV
Maximum power dissipation for nominal condition	0.56 W

Connection data

Number of connections per level	3
Nominal cross section	1.5 mm ²
Rated cross section AWG	16
Connection method	Push-X-connection
Stripping length	10 mm ... 12 mm
Internal cylindrical gage	A1
Connection in acc. with standard	IEC 60947-7-1
Conductor cross-section rigid	0.25 mm ² ... 1.5 mm ²
Cross section AWG	24 ... 14 (converted acc. to IEC)
Conductor cross-section flexible	0.34 mm ² ... 2.5 mm ²
Conductor cross-section, flexible [AWG]	22 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.34 mm ² ... 1.5 mm ² (1.5 mm ² only with rectangular compression in one position)
Flexible conductor cross-section (ferrule with plastic sleeve)	0.34 mm ² ... 1.5 mm ² (1.5 mm ² only with rectangular compression in one position)
Nominal current	17.5 A
Maximum load current	17.5 A

XT 1,5-TWIN - Feed-through terminal block



1641116

<https://www.phoenixcontact.com/in/products/1641116>

Nominal voltage	500 V
Nominal cross section	1.5 mm ²

Dimensions

Width	4.2 mm
Height	57.5 mm
Depth	35.25 mm
Depth on NS 35/7,5	36.75 mm
Depth on NS 35/15	44.25 mm

Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Electrical tests

Surge voltage test

Result	Test passed
--------	-------------

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 1.5 mm ²	0.18 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	1.89 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Mechanical tests

XT 1,5-TWIN - Feed-through terminal block



1641116

<https://www.phoenixcontact.com/in/products/1641116>

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 35
Result	Test passed

Test for conductor damage and slackening

Rotation speed	9 rpm
Revolutions	135
Conductor cross-section/weight	0.2 mm ² / 0.2 kg
	0.34 mm ² / 0.2 kg
	1.5 mm ² / 0.4 kg
	2.5 mm ² / 0.7 kg
Result	Test passed

Environmental and real-life conditions

Aging

Temperature cycles	192
Result	Test passed

Needle-flame test

Time of exposure	30 s
Result	Test passed

Oscillation/broadband noise

Specification	EN 50155:2021-07
Spectrum	Long life test category 1, class B, body mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 150 \text{ Hz}$
ASD level	0.964 (m/s ²)/Hz
Acceleration	5.72 m/s ²
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Specification	EN 50155:2021-07
Pulse shape	Half-sine
Acceleration	50 m/s ²
Shock duration	30 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating;
---------------------------------	--

XT 1,5-TWIN - Feed-through terminal block



1641116

<https://www.phoenixcontact.com/in/products/1641116>

	for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15

XT 1,5-TWIN - Feed-through terminal block



1641116

<https://www.phoenixcontact.com/in/products/1641116>

Drawings

Circuit diagram



XT 1,5-TWIN - Feed-through terminal block



1641116

<https://www.phoenixcontact.com/in/products/1641116>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/in/products/1641116>

 CSA Approval ID: 2030668				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
B				
	300 V	15 A	22 - 14	-
C				
	300 V	15 A	22 - 14	-
D				
	300 V	10 A	22 - 14	-

 cULus Recognized Approval ID: E60425				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
B				
	300 V	15 A	22 - 14	-
C				
	300 V	15 A	22 - 14	-
F				
	300 V	15 A	22 - 14	-
D				
	300 V	10 A	22 - 14	-

XT 1,5-TWIN - Feed-through terminal block



1641116

<https://www.phoenixcontact.com/in/products/1641116>

Classifications

ECLASS

ECLASS-13.0	27250101
ECLASS-15.0	27250101

ETIM

ETIM 9.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DIN Rail Terminal Blocks](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[00110420202](#) [00175550302](#) [NFT2-WH](#) [35956](#) [5520682](#) [1-591651-1](#) [592814-1](#) [592814-3](#) [NRA37-12](#) [PLU3-WH](#) [90.001](#) [CTS95/120N](#)
[0363660000](#) [DK 4QV/35](#) [PT 2,5-TG](#) [3210185](#) [CMC2-2/R](#) [5746.2/P](#) [RAU035610015](#) [91.255](#) [CMDDB25/2](#) [1SNK906310R0000](#) [JB6-10](#)
[1SNA179534R2200](#) [1SNA115141R1000](#) [2821630000](#) [CF4U\(L\)/110-240V/BL](#) [81201003](#) [1SNK505214R0000](#) [\(ZS4-D-CH-UD\)](#)
[1SNK505311R0000](#) [\(ZS4-S-T2\)](#) [VG03-0031](#) [1SNK506316R0000](#) [\(ZS6-S-4S-T2\)](#) [1SNK705210R0000](#) [\(ZK2.5-D2\)](#) [1SNL316010R0000](#)
[\(DBL160\)](#) [1SNK506011R0000](#) [\(ZS6-3S\)](#) [81102015](#) [1SNK508418R0000](#) [\(ZS10-SF\)](#) [81002007](#) [1SNK506213R0000](#) [\(ZS4-T3-R1\)](#) [81602015](#)
[81302002](#) [1SNL312530R0000](#) [\(DBL125-3\)](#) [81003005](#) [1SNK708010R0000](#) [\(ZK6\)](#) [1SNK531010R0000](#) [\(ZS150\)](#) [1SNK806713R0000](#) [\(CDK4-](#)
[E\)](#) [1SNK705010R0000](#) [\(ZK2.5\)](#) [81202015](#) [VG03-0054](#) [1SNK705512R0000](#) [\(ZK2.5-L-L-PE\)](#) [1SNK805015R0000](#) [\(ZDK2.5-11\)](#)
[1SNK806010R0000](#) [\(ZDK4-22\)](#) [1SNK505313R0000](#) [\(ZS4-SP\)](#)