


HC-M-01-CT-F-120 - Contact insert module



1683513

<https://www.phoenixcontact.com/us/products/1683513>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert module, number of positions: 1, power contacts: 1, control contacts: 0, Socket, Crimp connection, 1000 V, 300 A, 95 mm² ... 120 mm², application: Power, without crimp contacts

Commercial data

Item number	1683513
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF65
Product key	AF7ACE
GTIN	4067923238817
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85389099
Country of origin	PL

HC-M-01-CT-F-120 - Contact insert module



1683513

<https://www.phoenixcontact.com/us/products/1683513>

Technical data

Notes

General	Order crimp contacts separately
General	Order crimp contacts separately

Mounting

Assembly note	To ensure correct use, installation in housing with IP54 protection or better is required
---------------	---

Product properties

Product type	Modular contact insert
Series	HC-M-01
Application	Power
Number of positions	1
Connection profile	1
Number of module slots	2
No. of power contacts	1
No. of control contacts	0
Contact material type	turned

Connection data

Connection technology

Connection technology	Crimp connection
-----------------------	------------------

Conductor connection

Conductor cross section	95 mm ² ... 120 mm ² (The cross section specification refers to the geometric cross section of the cable used)
Connection cross section AWG	3/0 ... 4/0 (The cross section specification refers to the geometric cross section of the cable used)

Dimensions

Width	34 mm
Height	61.9 mm
Length	29.5 mm

Mechanical characteristics

Contact diameter	9.5 mm
------------------	--------

Electrical properties

Rated voltage (III/3)	1000 V
Rated surge voltage	8 kV
Rated current	300 A

Mechanical properties

HC-M-01-CT-F-120 - Contact insert module



1683513

<https://www.phoenixcontact.com/us/products/1683513>

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Material specifications

Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PC
Standards/regulations	PC


Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Drawings

Diagram



Derating diagram calculated with derating factor 0.9

HC-M-01-CT-F-120 - Contact insert module



1683513

<https://www.phoenixcontact.com/us/products/1683513>

Classifications

ECLASS

ECLASS-13.0	27440217
ECLASS-15.0	27440217

ETIM

ETIM 9.0	EC000438
----------	----------

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heavy Duty Power Connectors](#) ***category:***

Click to view products by [Phoenix Contact](#) ***manufacturer:***

Other Similar products are found below :

[6646137-1](#) [6646138-1](#) [6646940-1](#) [6651091-1](#) [6651525-1](#) [6651529-1](#) [73080254296](#) [73080255059](#) [7310205040001](#) [7487](#) [PS25/A0420/63](#)
[AN0024023](#) [1643543-1](#) [1791340000](#) [NLDFT-3-BL-L-S120-M40A](#) [NLDFT-N-W-L-C240-M40B](#) [NLS-2-R-C240-M40B](#) [NLS-3-BL-C240-](#)
[M40B](#) [NLS-N-W-C240-M40B](#) [NPS-3-BL-T6](#) [C148 10A005 000 9](#) [2-1589900-8](#) [9300480317](#) [19000005132](#) [AN0024202](#) [AN0264023](#) [279-](#)
[0841-10100A](#) [281-0334-00100A](#) [419-2083-301](#) [078238-1613](#) [078238-2910](#) [078239-2912](#) [078239-2910](#) [078239-2911](#) [078239-2913](#)
[09370009946](#) [09305160521](#) [09370240318](#) [1-1104457-5](#) [5352I](#) [73000005327](#) [73000005329](#) [73080956756](#) [73080965056](#) [1926075-1](#)
[6646136-1](#) [6646979-1](#) [1103021-2](#) [NPDFT-3-BL-L-T6](#) [46562-1559](#)