



### Features:

- All 12 adapters in kit are direct. **No intermediate couplers.**
- Reduced signal loss in adapters due to absence of couplers.
- Kit includes the most frequently used N Type adapters including N / N, N / SMA, N / BNC, and N Terminations, both 50 and 75 ohm. See complete list in drawing or in table below.
- Rugged, lockable, pistol-grip case.
- All parts precision machined brass with tarnish resistant gold or nickel plating.
- Male center pins are gold plated brass.
- Female contacts are gold plated heat treated beryllium copper.
- Insulation material is high density PTFE.



**Order Example: 72932  
(N Adapter Kit)**

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).  
 All specifications are to the latest revisions. Specifications are subject to change without notice.  
 Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)  
 For "Where to Buy" information, visit the Pomona web site at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)

Item	Description	Pomona Part Number	NOM. IMPEDANCE	FREQ. RANGE	VSWR	OPERATING TEMP
1	TYPE N female/male RA	3843	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C
2	TYPE N Terminator plug	4240-75	75 Ohms	DC to 500 MHz	1.35 at 500 MHz	- 65° to +165° C
3	TYPE N Terminator plug	4240-50	50 OHMS	DC to 500 MHz	1.35 at 500 MHz	- 65° to +165° C
4	TYPE N female/female	3841	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C
5	BNC male/ TYPE N female	3535	50 Ohms	DC to 4 GHz	1.35 to 4 GHz	- 65° to +165° C
6	BNC female, TYPE N male	3288	50 Ohms	DC to 4 GHz	1.35 to 4 GHz	- 65° to +165° C
7	SMA Termination male	4286	50 Ohms	DC to 18GHz	1.25 Max at 18GHz	- 65° to +165° C
8	TYPE N male/ TYPE N male	3842	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C
9	TYPE N female/female/female	5089	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C
10	SMA female/ TYPE N female	4299	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C
11	SMA male/TYPE N female	4298	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C
12	SMA female/TYPE N male	4297	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)

For "Where to Buy" information, visit the Pomona web site at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Adapters - In Series](#) category:*

*Click to view products by [Pomona](#) manufacturer:*

Other Similar products are found below :

[5916-1103-603](#) [5918-1103-000](#) [5919-1503-000](#) [651A505](#) [82-5552](#) [9030-9523-502](#) [A0407000](#) [R114703000W](#) [R125704000](#) [R125771001](#)  
[R141710000W](#) [R141723161](#) [R141730000](#) [R143730700](#) [R143770000](#) [R161703000W](#) [R161730000](#) [R161753000W](#) [R161791500W](#)  
[R161791530W](#) [R201705000](#) [R222705200](#) [R222M40010W](#) [R223703180](#) [R316754000](#) [R405006000](#) [R443162000](#) [AD78TL](#) [HRM-513S](#)  
[1996352-2](#) [2157155-1](#) [252169-75](#) [AD158](#) [2101130-1](#) [252186](#) [R114704000W](#) [R114720000W](#) [R125705001](#) [R125705701](#) [R125771000](#)  
[R125771001W](#) [R125791501W](#) [R127704001](#) [R127.870.001](#) [R127872001](#) [R141717000](#) [R142710000](#) [R142723000](#) [R143703000](#) [R143704000](#)