



ProLED-2W-CC180

Professional Led Modules; **5-15cm** 3D double-sided lightboxes



■ Features:

- luminous efficacy 170 lm/W
- for indoor and outdoor use
- 20 pcs in chain



UK
CA



TECHNICAL DETAILS



MODEL	ProLED-2W-CC180
Supply voltage	12V DC
Power consumption per module	0.72W
Chain power consumption	14.4W
Current consumption per module	60mA
LED diodes	LumiLEDs - 2835
Quantity of LEDs	2
Light color	White (~7000K)
Luminous flux	122lm (W)
Luminous flux density	170lm (W)
Color rendering index - CRI	≥80
Beam angle	175°
Current stabilization	No
Dimming	Yes
Module dimensions (L x W x H)	50 x 16 x 11mm
Cable length	130mm
Number of modules in 1m	5.5
Box weight	17kg
Packing	Chain – 20pcs / Bag – 100pcs / Box – 1600pcs
Montage	Adhesive tape / mounting screw
Lifetime	L70B50 > 50000h
Working temperature	-25°C ÷ 60°C
IP protection	IP67
Warranty	7 years




ProLED-2W-CC180

Professional Led Modules; **5-15cm** 3D double-sided lightboxes



Dimensions



Connection diagram

One-side power input:



Maximum number of modules 20 pcs

Two-side power input:




Maximum number of modules 40 pcs


It is acceptable to connect multiple chains in parallel, as long as the power supply provides sufficient power

Light color / CCT

Light color




Packing



Chain
20 pcs



Bag
100 pcs



Box
2800 pcs




ProLED-2W-CC180




Professional Led Modules; 5-15cm 3D double-sided lightboxes

Application





$$\text{optical performance proportion} = \frac{D}{P} = 1 : 1.3$$

Overall micro lens design can improve the lens uniformity performance.



Energy label / Beam Angle



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LED Bars and Arrays](#) category:

Click to view products by [POS manufacturer](#):

Other Similar products are found below :

[LTL-2755Y](#) [LF2B-D3P-BTHWW2-1M](#) [SSA-LXB10GW-18751](#) [SSA-LXB10YW](#) [SSA-LXH1025I1G7XXD](#) [LTL-2450Y](#) [LTL-2855G](#) [SSB-LX2301SIW](#) [TOS-4102BR-N](#) [SSA-LXB10-IYG8W-1](#) [LPB-R0112051S](#) [SSA-LXB525-I1G3I1D](#) [KB-A100SURKW](#) [MW-MLD-2835-3W-LENS V,2](#) [MW-MLD-2835-1W-LENS](#) [PROLED-MINI-3W-CC100](#) [MW-MLD-2835-3B-LENS](#) [MW-MLD-2835-2W-LENS V,2](#) [OSWSM51006B-5V](#) [PROLED-3W-CC220](#) [MW-MLD-HE-2W-LENS170](#) [AREA 10 CONNECT](#) [SCANGRIP DIFFUSER LARGE](#) [MW-MLD-2835-3WW-LENS V,2](#) [NEVADA-3W V.2](#) [MISSOURI-1W](#) [MW-MLD-FLAT-1W-LENS170](#) [MW-MLD-2835-3R-LENS](#) [PROLED-2W-CC180](#) [TEXAS-3W V.2](#) [MW-MLD-2835-3G-LENS](#) [MW-MLD-HE-2NW-LENS170](#) [ALASKA-1W V.2](#) [MW-MLD-MINI-1W-LENS160](#) [MW-MLD-HE-4W-LENS170](#) [MW-SAMSUNG-3W](#) [LTL-57173HR](#) [1330.0001](#) [1330.0003](#) [1330.0009](#) [KB-2855SGW](#) [KB-B100SURKW](#) [L-1043GDT](#) [L-875/4SRDT](#) [DC10EGWA](#) [LF1B-NA3P-2THWW2-3M](#) [LF1B-NC3P-2THWW2-3M](#) [LF1B-ND3P-2THWW2-3M](#) [LTL-2500G](#) [SSA-LXB10GW](#)