



PUIaudio



Data Sheet

AR03032MR-3


Features:

- Low 160 Hz resonant frequency
- High 133 dB output with 800mV in Artificial Ear (1cm)
- High 25mW max input power


Specifications

Parameters	Values	Units
Rated Input Power	15	mWatts
Max Input Power	25	mWatts
Impedance	$32 \pm 15\%$	Ohms
Sensitivity (SPL @ 1kHz, 1mV)	133 ± 3	dB Pa/V
Resonant Frequency	$160 \pm 20\%$	Hz
Frequency Range	20 ~ 20,000	Hz
Distortion (@ 50 ~ 3000 Hz/ 3mW)	5% Max	-
Frame Material	Plastic	-
Magnet Material	NdFeB	-
Diaphragm Material	PET	-
Weight	2	Grams
Environmental Compliances	ROHS/REACH	-
Buzz, Rattle, etc.	Should not be audible with 693 mV sine wave from 50 Hz to 4 kHz	-
Polarity	When positive voltage is applied to the positive terminal, the diaphragm will move outward	-
Operating Temperature	-20 ~ +60	°C
Storage Temperature	-20 ~ +60	°C

Measurement Method (measured with 1mV, Temperature: 25 ~ 35°C, Relative Humidity: 25%~75%)



Frequency Response (measured at 1mV)




Reliability Testing


Type of Test	Test Specifications
High Temperature Test	48 hours at $+60^{\circ}\text{C} \pm 2^{\circ}\text{C}$
Low Temperature Test	48 hours at $-20^{\circ}\text{C} \pm 2^{\circ}\text{C}$
Humidity Test	24 hours at $+50^{\circ}\text{C} \pm 2^{\circ}\text{C}$ with relative humidity at 90~95% relative humidity
Temperature Cycle Testing	The part shall be subjected to 15 cycles. One cycle shall be 2 hours and consist of: $50^{\circ}\text{C}+1^{\circ}\text{C}/0.5\text{h} \rightarrow 20^{\circ}\text{C}/0.5\text{h} \rightarrow -20^{\circ}\text{C}/0.5\text{h} \rightarrow 20^{\circ}\text{C}/0.5\text{h}$
Vibration Test	Frequency 15~55 Hz, Amplitude 1.5 mm for 2 hours
Drop Test	100 cm free fall on concrete floor, 10 times

After each test, the speaker's SPL shall be ± 4 dB of the original SPL after 1 hour of recovery.

Dimensions



Packaging



Specifications Revisions			
Revision	Description	Date	Approved
A	Released from Engineering	3/21/2025	JD
B	Revised Drawing and Sensitivity	6/13/2025	JD

- Note:
- 1. Unless otherwise specified:
 - A. All dimensions are in millimeters.
 - B. Default tolerances are $\pm 0.5\text{mm}$ and angles are $\pm 3^\circ$.
 - 2. Specifications subject to change or withdrawal without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Speakers & Transducers](#) category:

Click to view products by [PUI Audio](#) manufacturer:

Other Similar products are found below :

[FC-30814-P127](#) [PB-1220PE](#) [AB1541B-LW50-R](#) [AB2025B-LW50-R](#) [PT-2065FW](#) [PT-4175W](#) [AT-1220-TWT-5V-R](#) [FS3020MS0820-H4.7](#)
[FS2515NS0810-H5.5](#) [FS7040DS0450-H16.8](#) [FS3516NS0820-H6.5-R01](#) [GSPK25042PN-8R1.0W-L100](#) [FS7423NB0430-H10.0](#)
[FS66W04100-H31](#) [FS32NS0820-H5.8-R01](#) [FS2112NB0807-H7.0-R01](#) [FS50DS0430-H13.3-R24](#) [FS3411P08-H4.0](#) [FS26NS0820-H4.9-R01](#)
[FS5835DS0850-H19.4-R01](#) [FS28DS0820-H9.4-R01](#) [FS102W0480-H35](#) [FS3525NS0820-H5.5-R01](#) [FS102W04200-H40](#) [FS3232NB0820-](#)
[H15.3-R01](#) [FS3020NB0805-H4.1-R01](#) [FS4020NB0410-H6.6-R01](#) [FS4020NB0820-H8.5-R01](#) [FS50DS0830-H13.3-R24](#) [FS87W08100-H34](#)
[FS87W16120-H32](#) [FS9050W0850-H38.5](#) [FS50MS0820-H7.5-P2.54-L350](#) [FS40MS0820-H5.0-P2.54-L160](#) [FS9050W08100-H38.5](#)
[FS2415NB0808-H5.3-R01](#) [FS23NS0810-H4.8TP](#) [FS2720NS0810-H5.7-P2.54-L170](#) [FS32DS0430-H18.9-BV](#) [FS44DS0450-H25-R01](#)
[FS2323NS0808-H3.3-R01](#) [FS28DS0430-H15.3-BV](#) [GSPK5010TN-8R1W](#) [GSPK1504S-8R0.8W](#) [GSPK5010TN-8R2W](#) [KLJ- 1609030-](#)
[R08W0.5T2](#) [GSPK504522BOX-4R3W-L200-2.0T](#) [FS5045NB0850-H22.0](#) [GSPK2810BOX-4R3W-L100S-2.0T](#) [FS9933NB0450-H15.7-R01](#)