

2x2 MiMo 5G/4G Antenna

Direct mount with SMA-Male cable feed

LPT600-71M2DMG0305: 617-960 and 1710-2690 and 3300-7125MHz



Features & Applications:

- 2x2 MiMo cellular 5G-FR1, 4G LTE
- WiFi6/7, DSRC, ISM compatible
- Indoor and Outdoor rated
- Ommi radiation pattern
- IoT, M2M, industrial metering, base stations

Electrical specifications @ 25° C – Operating Temperatures – 40°C to +85°C							
Frequency Bands – 617-960MHz & 1710-2690MHz & 3300-7125MHz							
Antenna type	Nominal Impedance	Polarization		Radiation pattern	Power withstanding		DC Ground
Monopole	50Ω	Linear		Omni	3W		No
	Frequency (MHz)	617-960	1710-2690	3300-4200	4400-5000	5150-5925	6000-7125
Port 1	VSWR	< 3.5	< 2.5	< 2	< 2	< 2	< 2
	Return Loss(dB)	< -5	< -7	< -10	< -10	< -10	< -10
	Avg. Peak Gain (dBi)	0.2	4.0	7.0	4.3	6.8	4.7
	Avg. Efficiency (%)	40	54	58	55	66	56
Port 2	VSWR	< 3.5	< 2.5	< 2	< 2	< 2	< 2
	Return Loss(dB)	< -5	< -7	< -10	< -10	< -10	< -10
	Avg. Peak Gain (dBi)	0.4	4.1	8.5	6.3	7.3	5.6
	Avg. Efficiency (%)	39	55	64	67	60	57

Mechanical Specifications				
Orderable PN: LPT600-71M2DMG0305				
Dimension with connector (Diameter x Height)	Color	Connector Type	Fixing System	Ingress Protection
Φ44.20 x 115.58 mm	Black	SMA-Male	Direct Mount	IP67
Height installed	Weight	Mounting stud	Cable Style	Cable Length
96.6 mm (After compression)	1.3 kg	Brass	RG316	3048 mm (10 ft)

Notes:


- 1.Mounting hole diameter: > 17.8mm.
- 2.Flame Rating(Radome): UL94-V0.
- 3.Operating temp and Storage temp to be -40°C ~ 85°C.
- 4.Physical: Dimensional stability, Value to be 0.0%, Test method to be ASTM D1042 ISO 2796.

2x2 MiMo 5G/4G Antenna Direct mount with SMA-Male cable feed

LPT600-71M2DMG0305: 617-960 and 1710-2690 and 3300-7125MHz

Mechanical Drawing

LPT600-71M2DMG0305



Testing Setup


LPT600-71M2DMG0305



Radiation element is test on 300*300mm ground plane

Charts- VSWR, Return Loss, Isolation

LPT600-71M2DMG0305



Antenna test with 10ft RG316 cable & SMA connector

2x2 MiMo 5G/4G Antenna

Direct mount with SMA-Male cable feed

LPT600-71M2DMG0305: 617-960 and 1710-2690 and 3300-7125MHz

Charts- Efficiency, and Peak Gain


LPT600-71M2DMG0305



Antenna test with 1 ft RG316 cable & SMA connector


Port1_Charts-XY Gain Plots

LPT600-71M2DMG0305




Port1_Charts – ZX Gain Plots

LPT600-71M2DMG0305




Port1_Charts – ZY Gain Plots

LPT600-71M2DMG0305




Port2_Charts – XY Gain Plots

LPT600-71M2DMG0305




Port2_Charts – ZX Gain Plots

LPT600-71M2DMG0305



Port2_Charts – ZY Gain Plots

LPT600-71M2DMG0305



Antenna test with 1 ft RG316 cable & SMA connector

Packaging

LPT600-71M2DMG0305

1. Antennas packed in a plastic bag.
2. Label on each plastic bag with part number, description, date code.
3. Out box:400X300X300mm, 30Pcs/Box;

For More Information:

Americas - antennas.us@pulseelectronics.com | Europe – antennas.eu@pulseelectronics.com | Asia – antennas.as@pulseelectronics.com | Questions? +1-800-ANTENNA
Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright , 2020. Pulse Electronics, Inc. All rights reserved.
Company address: Pulse Electronics, a YAGEO Company, 15255 Innovation Drive, Suite #100, San Diego, CA 92128

'YAGEO Corporation and its affiliates do not recommend the use of commercial, automotive, and/or COTS grade products for high reliability applications or manned space flight.'

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Antennas](#) category:

Click to view products by [Pulse](#) manufacturer:

Other Similar products are found below :

[930-033-R](#) [108-00014-50](#) [66089-2406](#) [A09-F8NF-M](#) [RGFRA1903041A1T](#) [108-00016-050](#) [W1049B090](#) [WTL2449CQ1-FRSMM](#) [CPL9C](#)
[0600-00060](#) [PAL90209H-FNF](#) [GD53-25](#) [S9025PLSMF](#) [GPSCPMM00](#) [ANTDOM-05-01-WPM](#) [ANT-WP868SMA-Y](#) [CBNC58](#) [MD10-004](#)
[ABFT](#) [LP800NMOW](#) [NMOQ88C](#) [NMOQB](#) [NMOQC](#) [ANT-GSMGPSPUKS](#) [60210](#) [60140](#) [ANT-8WPIG-UFL](#) [ANT-GPSPUKS](#) [A21H0](#)
[29000863](#) [29000848](#) [955179003](#) [22100003](#) [DL-T022-2.4G](#) [DL-T023-4G](#) [T1-915M](#) [DL-T021-2.4GW](#) [DL-T021-2.4G](#) [KH-IPEX-1.13](#)
[BWGNSCNX16-6B1Y2L120](#) [BWGNSCNX15-15B1Y4L120](#) [DL-T023-4GW](#) [J008-GSM](#) [3N0401LG-021](#) [KHA\(RG1.13\)-TX90B-IPEX](#) [KH-](#)
[GPS181804-WY](#) [KHA\(RG1.13\)-TX80B-IPEX](#) [TX5800-JZ-5](#) [KH-137-TX90B-IPEX4](#) [KH-113-TX100B-IPEX4](#)