

Description: LTE Primary + GNSS FPC Antenna

PART NUMBER: W3906B0100

Series: Gemini



Features:

- 2G / 3G / 4G Primary Ant for MiMo
- 698-3600MHz
- Used as pair for W3907B0100
- Global LTE Bands:
 - B1-B23, B25-B29, B33-B42
 - N.A.; Europe, Asia (incl. Jap.)
- GNSS (GPS, Galileo, Glonass)
- · Foldable for tight spaces

Applications:

- Challenging RF Environments Demanding:
 - Highest Peak Gain
 - Lowest ECC (Envelope Correlation Coeff.).
- Matched to Radio Modules from:
 - Sierra Wireless, Telit, Huawei, Gemalto, uBlox, ZTE, and others.
- Security, Video, Graphics
- IoT, SmartGrid, Meters, Remote Monitoring, Sensor Networks
- Transportation, Tracking

All dimensions are in mm / inches

Issue: 2029

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:

Pulse Worldwide Headquarters 15255 Innovation Drive #100 San Diego, CA 92128 USA Tel:1-858-674-8100 Pulse/Larsen Antennas 18110 SE 34th St Bldg 2 Suite 250 Vancouver, WA 98683 USA Tel: 1-360-944-7551

Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



Description: LTE Primary + GNSS FPC Antenna

Series: Gemini

PART NUMBER: W3906B0100

ELECTRICAL SPECIFICATIONS

LTE:

Frequency 698-960/1427.9-1510.9/1559-1610/

1695-2200/2300-2700/3400-3600 MHz

Nominal Impedance 50Ω

Return loss(698-960MHz) -6dB

Return loss(1427.9-1510.9/1559-1610/

1695-2200/2300-2700/3400-3600MHz) -7.5dB

Isolation -10dB

Average Total Efficiency (698-960MHz) 54%

Average Total Efficiency (1427.9-1510.9MHz) 59%

Average Total Efficiency (1559-1610MHz) 59%

Average Total Efficiency (1695-2200MHz) 64%

Average Total Efficiency (2300-2700MHz) 69%

Average Total Efficiency (3400-3600MHz) 64%

Issue: 2029

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:

Tel:1-858-674-8100



Description: LTE Primary + GNSS FPC Antenna

Series: Gemini

PART NUMBER: W3906B0100


ELECTRICAL SPECIFICATIONS

Peak Gain (698-960MHz)	2.7dBi
Peak Gain (1427.9-1510.9MHz)	1.5dBi
Peak Gain (1559-1610MHz)	1.6dBi
Peak Gain (1695-2200MHz)	3.2dBi
Peak Gain (2300-2700MHz)	3.6dBi
Peak Gain (3400-3600MHz)	4.0dBi
GNSS:	
Frequency	1570-1610MHz
Nominal Impedance	50Ω
Return loss (1570-1610MHz)	-10dB
Average Total Efficiency (1570-1610MHz)	35%
Peak Gain (1570-1610MHz)	0.8dBi
Radiation Pattern	Omni
Polarization	Linear
Power withstanding	3W

(*) All RF parameters measured on 2mm thick PC plate

Issue: 2029

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION







Description: LTE Primary + GNSS FPC Antenna

Series: Gemini

PART NUMBER: W3906B0100

MECHANICAL SPECIFICATIONS

Overall Length 120.4x26.8mm

Weight 2.0g

Antenna Color / Material BLACK FPC

Cable type AWG#32 1.13MM

Connector type I-PEX MHF 20278-112R-

13 or compatible

Cable length (LTE) 93mm
Cable length (GPS) 93mm

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature -40~+85° C

Storage Temperature -40~+85° C

RoHS Compliant Yes






Description: LTE Primary + GNSS FPC Antenna

Series: Gemini

PART NUMBER: W3906B0100

MECHANICAL DRAWING



Unit: MM







Description: LTE Primary + GNSS FPC Antenna

Series: Gemini

PART NUMBER: W3906B0100

CHARTS

Return Loss

LTE Return Loss









Description: LTE Primary + GNSS FPC Antenna


Series: Gemini

PART NUMBER: W3906B0100

CHARTS

Return Loss

GNSS Return Loss









Description: LTE Primary + GNSS FPC Antenna


Series: Gemini

PART NUMBER: W3906B0100

CHARTS

Isolation

LTE & GNSS Isolation









Description: LTE Primary + GNSS FPC Antenna


Series: Gemini

PART NUMBER: W3906B0100

CHARTS

Efficiency(%)





Issue: 2029




Description: LTE Primary + GNSS FPC Antenna

Series: Gemini

PART NUMBER: W3906B0100

CHARTS

Efficiency(%)








Description: LTE Primary + GNSS FPC Antenna

Series: Gemini

PART NUMBER: W3906B0100

CHARTS

Peak Gain(dBi)








Description: LTE Primary + GNSS FPC Antenna

Series: Gemini

PART NUMBER: W3906B0100

CHARTS

Peak Gain(dBi)









Description: LTE Primary + GNSS FPC Antenna

Series: Gemini


PART NUMBER: W3906B0100


CHARTS

LTE radiation pattern 698-960MHz (800MHz)

Elevation Plane

Horizontal Plane





13



Description: LTE Primary + GNSS FPC Antenna


Series: Gemini


PART NUMBER: W3906B0100

CHARTS

LTE radiation pattern 1427.9-1510.9MHz (1450MHz)

Elevation Plane







Description: LTE Primary + GNSS FPC Antenna


Series: Gemini


PART NUMBER: W3906B0100

CHARTS

LTE radiation pattern 1559-1610MHz (1570MHz)

Elevation Plane







Description: LTE Primary + GNSS FPC Antenna


Series: Gemini


PART NUMBER: W3906B0100

CHARTS

LTE radiation pattern 1695-2200MHz (1930MHz)

Elevation Plane







Description: LTE Primary + GNSS FPC Antenna


Series: Gemini


PART NUMBER: W3906B0100

CHARTS

LTE radiation pattern 2300-2700MHz (2390MHz)

Elevation Plane







Description: LTE Primary + GNSS FPC Antenna

Series: Gemini


PART NUMBER: W3906B0100


CHARTS

LTE radiation pattern 3400-3600MHz (3400MHz)

Elevation Plane

Horizontal Plane





18



Description: LTE Primary + GNSS FPC Antenna


Series: Gemini

PART NUMBER: W3906B0100

CHARTS

GNSS radiation pattern 1570-1610MHz (1575MHz)

Elevation Plane





Description: LTE Primary + GNSS FPC Antenna

Series: Gemini

PART NUMBER: W3906B0100

PACKAGING

5pcs antenna per PE bag

400pcs PE bags per form bag

2pcs form bag per package box

Total 4000pcs per package box

Package box: 460mm*235mm*140mm

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pulse manufacturer:

Other Similar products are found below:

ICEFIN806DMN ICEFIN698/869DMN PH9085.011NL PE-0603CD060KTT H1086NLT P0182T PA1494.442NL PE-0805CD030KTT PE-53363NLT 23Z106SM-T HX5400NL JXD0-4005NL ST6200QNL T3001NL HX2019 PE-67540NL PE-65968NL PE-65535NL T1142NLT H7019FNL P0841NL P0438T P0584 P0752.474T P1167.154T STQN1553-45 JY0-0016NL JG0-0098NL JG0-0025NL J20-0014NL W1911 HX6101NL JXD1-0025NL RO2408NMD P0469NL P0841SNLT PB2134NL ST2-12B42 PE-0805CM331JTT PE-51509NL 53119 J3026G01DNL P0849SNL W3012-K HX5020NL HX5201NL PE-68210NL T1124NL H5004NL JX30-0005NL