

Technical Data Sheet

SP3T Ramses SMA 18GHz Normally open Indicators 28Vdc Pins Terminals

PAGE 1/2 ISSUE		26-01-17 SERIE : SPnT		PART NUMBER : R573413300				
RF CH	HARACTERIS	STICS						
	Number of wa	avs		:	3			
	Frequency ra				0 - 18 GHz			
	Impedance	0		:	50 Ohms			
	Frequency (C	GHz)	DC - 3	3 - 8	8 - 12.4	12.4 - 18		
	VSWR max		1.20	1.30	1.40	1.50		
	Insertion loss		0.20 dB	0.30 dB	0.40 dB	0.50 dB		
	Isolation min		80 dB	70 dB	60 dB	60 dB		
l	Average pow	er (^)	240 W	150 W	120 W	100 W		
ELEC	TRICAL CHA	RACTERIS	<u>FICS</u>					
	Actuator				NORMALLY	OPEN		
	Nominal curr Actuator volta				102 mA			
	Terminals	age (vcc)			solder pins		IVE COMMON	
	Indicator ratir	าต			1 W / 30 V /	-	,	
MECH	ANICAL CHA		TICS					
MEON			1100					
	Connectors			:	SMA female	e per MIL-C 3	9012	
	Life						cles per position	
	Switching Time***				: < 15 ms			
Construction					Splashproo	f		
	Weight			:	< 180 g			
	0							
	-							
	RONMENTAL	CHARACT	ERISTICS					
ENVIR	RONMENTAL			:	-40°C to +85	5°C		
ENVIR	-	mperature ra	inge	:	-40°C to +85 -55°C to +85			
ENVIR	RONMENTAL Operating ter	mperature ra	inge	:			ROHS	
envir	CONMENTAL Operating ter Storage temp	mperature ra perature ran	inge ge	:			RoHs.	
<u>ENVIR</u> (*	Operating ter Storage temp Average pow	mperature ran perature ran per at 25°C p	inge ge	:			RoHS C	
<u>ENVIR</u> (* (**	Operating ter Storage temp Average pow At 25° C ±10	mperature ran perature ran rer at 25°C p %)	inge ge	:			ROHO COMPLIAN	
<u>ENVIR</u> (* (**	Operating ter Storage temp Average pow	mperature ran perature ran rer at 25°C p %)	inge ge	:			ROHS COMPLIAN	
<u>ENVIR</u> (* (**	Operating ter Storage temp Average pow At 25° C ±10	mperature ran perature ran rer at 25°C p %)	inge ge	:			ROHS COMPLIAN	
<u>ENVIR</u> (* (**	Operating ter Storage temp Average pow At 25° C ±10	mperature ran perature ran rer at 25°C p %)	inge ge	:			ROHS COMPLIAN	
<u>ENVIR</u> (* (**	Operating ter Storage temp Average pow At 25° C ±10	mperature ran perature ran rer at 25°C p %)	inge ge	:			ROHS COMPLIAN	
<u>ENVIR</u> (* (**	Operating ter Storage temp Average pow At 25° C ±10	mperature ran perature ran rer at 25°C p %)	inge ge	:			ROHS COMPLIAN	
<u>ENVIR</u> (* (**	Operating ter Storage temp Average pow At 25° C ±10	mperature ran perature ran rer at 25°C p %)	inge ge	:			ROHS COMPLIAN	



Technical Data Sheet

SP3T Ramses SMA 18GHz Normally open Indicators 28Vdc Pins Terminals



This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Coaxial Switches category:

Click to view products by Radiall manufacturer:

Other Similar products are found below :

 CR-53S10
 R599311000
 R599906000
 R599910000
 CCT-38S150-T
 CR-58S160
 MS180LH3-HRMJ-040V300A
 R599312000
 R512F73417

 R514F73417
 R595333210
 R595F53225
 R591363400
 R595433410
 R595333215
 R595343115
 R595343125
 R591362440

 R593373148
 R595343215
 CCR-33K40
 R595357325
 CCS-18N480-TDS
 R591702640
 R591763600
 CR-33K10
 R599313000
 R516431100

 R591722605
 ARD15105
 MS156LH1-HRMJ-088V300A
 R570412000
 R570412100
 R570413000
 R570422100
 R570423000
 R570432000

 R570433000
 R570442000
 R570412030
 R570423030
 R570433100
 R570443030
 R570463100
 R570442010

 R570413030
 R570452000
 R570452000
 R570452000
 R570442010
 R570442010