



MODEL: CUSA-T80-120-2200-WC

| DESCRIPTION: ULTRASONIC SENSOR

FEATURES

- aluminum housing
- transmitter
- open type
- wire leads w/ 2-pin connector



SPECIFICATIONS


parameter	conditions/description	min	typ	max	units
type	transmitter				
operating voltage				160	Vp-p
frequency		29.5	30.5	31.5	kHz
sound pressure level		100			dB
directivity	at -6 dB	65	80	95	degree
capacitance	at 1 kHz	1,650	2,200	2,750	pF
detectable range		0		12	m
dimensions	Ø9.8 x 7				mm
material	aluminum				
terminal	wire leads with connector				
weight			0.94		g
operating temperature		-20		80	°C
storage temperature		-20		80	°C
RoHS	yes				

MECHANICAL DRAWING

units: mm


wire: UL1571, 30 AWG

connector: JAM JB20-02HG




BEAM PATTERNS

SPL vs. Frequency



Directivity



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Proximity Sensors](#) *category:*

Click to view products by [Same Sky](#) *manufacturer:*

Other Similar products are found below :

[8027AL20NL2CPXX](#) [922AA2W-A9P-L](#) [GL-12F-C2.5X10\(LOT3\)](#) [972AB3XM-A3P-L](#) [980659-1](#) [E2E-X14MD1-G](#) [E2E-X2D1-G](#) [E2E-X4MD1-G](#) [E2E-X5E1-5M-N](#) [EI3010TBOP](#) [MS605AU](#) [EP175-32000](#) [IFRM06P1703/S35L](#) [ILFK12E9189/I02](#) [ILFK12E9193/I02](#) [922AA2XM-B9P-L](#) [922FS0.8-H4P-G-020](#) [SC606ABV0S30](#) [SM552A100](#) [SM851A1200FP](#) [F3S-A162-U](#) [QT-08L](#) [RDS-DIN3-PA-D1](#) [TL-X10F1-G](#) [TL-X5Y1-52](#) [IA12ASF04DOM1](#) [IFFK12P1501/L](#) [IFRM08N1503/S35L](#) [IFRM08N1701/S35L](#) [Y92E-P1D2H5](#) [DR10GTI](#) [DSM2C550](#) [ZS-2065](#) [E2E-X3D1-G](#) [E2QN15E3](#) [EI0801PPOS](#) [TL-X10MF2](#) [SGA8072](#) [SM552A173](#) [E2KC25MY1812M](#) [AIK18F05AN024-2M](#) [SM952A123000](#) [SM850A2400FP](#) [SM956A410002](#) [EI8040NACP](#) [SM801A1200](#) [AC441A](#) [AC441AUS](#) [DCB1C425](#) [DCB3N250](#)