


September 2016



MULTILAYER CERAMIC CAPACITORS



SAMSUNG
ELECTRO-MECHANICS





We declare that all our MLCCs are produced
in accordance with EU RoHS and REACH Directive.



RoHS Compliance and restriction of Br

The following restricted materials are not used in packaging materials as well as products in compliance with the law and restriction.

- Cd, Pb, Hg, Cr6+, As, Br and the compounds, PCB, asbestos

No use of materials breaking Ozone layer

The following ODS materials are not used in our fabrication process.

- ODS material : Freon, Haron, 1-1-1 TCE, CCl4, HCFC

If you want more detailed Information, Please Visit Samsung Electro-mechanics Website
<http://www.semocr.com>

Contents

In order to move to the contents directly, please click each content icon

Part Numbering System	04
Standard & High Capacitors	06
Low Profile Capacitors	34
Super Small Size Capacitors	39
High - Q Capacitors	47
Medium - High Voltage Capacitors	52
Soft - term Capacitors	62
Low Acoustic Noise Capacitors	65
High Effective Capacitance Capacitors	68
Low ESL Capacitors	71
Array Type Capacitors	76
Industrial Capacitors	79
Reliability Test Condition	128
Premium Capacitors for Automotive Applications	132
Packaging Specification	146
Application Manual for Surface Mounting	150
Certifications	154



※ Remarks : Symbols in this catalog have the following definition.

Derating This capacitor with derating is designed for 70% of the rated voltage or less.

dv/dt dv/dt means Pulse(dv/dt) Guarantee Capacitor, 10,000V/us(=10V/ns) max.10,000 cycles guarantee(@Vr, Room temp)

Ref. Reference means that CAP & TCC have the exceptional measurement conditions for Capacitance and Temperature Characteristics of Capacitance.
So please refer to the individual specification for CAP and the individual characteristics data for TCC on Website.

Part Numbering System

CL	10	A	106	M	Q	8	N	N	N	C
1	2	3	4	5	6	7	8	9	10	11

1 SERIES CODE

CL = Multilayer Ceramic Capacitors

2 SIZE CODE

Code	inch(mm)	Code	inch(mm)	Code	inch(mm)	Code	inch(mm)
02	01005(0402)	10	0603(1608)	32	1210(3225)	55	2220(5750)
03	0201(0603)	21	0805(2012)	42	1808(4520)		
05	0402(1005)	31	1206(3216)	43	1812(4532)		

3 DIELECTRIC CODE

Class I (Temperature Compensation)

Symbol	EIA Code	Operation Temperature Range(°C)	Temperature Coeffcient(ppm / °C)
C	C0G	-55 ~ +125	0±30

Class II (High Dielectric Constant)

Symbol	EIA Code	Operation Temperature Range(°C)	Capacitance Change(%)
A	X5R	-55 ~ +85	±15
B	X7R	-55 ~ +125	±15
X	X6S	-55 ~ +105	±22
F	Y5V	-30 ~ +85	-82 ~ +22
Y	X7S	-55 ~ +125	±22
Z	X7T	-55 ~ +125	-33 ~ +22

4 CAPACITANCE CODE

Capacitance expressed in pF. 2 significant digits plus number of zeros.

example) 106=10×10⁶=10,000,000pF

For Values <10pF, Letter R denotes decimal point

example) 1R5 =1.5pF

5 CAPACITANCE TOLERANCE CODE

Code	Tolerance	Code	Tolerance	Code	Tolerance	Code	Tolerance
N	±0.03pF	H	+0.25pF	F*	±1%	V	-5%
A	±0.05pF	L	-0.25pF	G	±2%	K	±10%
B	±0.1pF	D	±0.5pF	J	±5%	M	±20%
C	±0.25pF	F	±1pF	U	+5%	Z	-20, +80%

* For Values <10pF, F=±1pF / Values ≥10pF, F=±1%

Series	Capacitance Step							
	1.0		2.2		4.7			
E-3	1.0		2.2		4.7			
E-6	1.0		2.2		4.7			
E-12	1.0	1.2	1.5	1.8	2.2	2.7	3.3	4.7
E-24	1.0	1.2	1.5	1.8	2.2	2.7	3.3	5.6
	1.1	1.3	1.6	2.0	2.4	3.0	4.3	6.8
						4.7	6.8	8.2
						5.1	6.2	7.5
								9.1

6 RATED VOLTAGE CODE

Code	Voltage	Code	Voltage	Code	Voltage	Code	Voltage
S	2.5Vdc	O	16Vdc	C	100Vdc	H	630Vdc
R	4.0Vdc	A	25Vdc	D	200Vdc	I	1kVdc
Q	6.3Vdc	L	35Vdc	E	250Vdc	J	2kVdc
P	10Vdc	B	50Vdc	G	500Vdc	K	3kVdc

7 THICKNESS CODE

(Unit:mm)							
Size inch(mm)	Code	Thickness	Tolerance	Size inch(mm)	Code	Thickness	Tolerance
01005(0402)	2	0.20	±0.02	1210(3225)	C	0.85	±0.10*
0201(0603)	3	0.30	±0.03		9	0.90	±0.10*
0402(1005)	3	0.30	±0.03*		F	1.25	±0.20
	5	0.50	±0.05		S	1.35	±0.15*
0603(1608)	5	0.50	+0.0/-0.1*		H	1.60	±0.20
	8	0.80	±0.10		U	1.80	±0.20*
0805(2012)	A	0.65	±0.10		I	2.00	±0.20
	C	0.85	±0.10*		J	2.50	±0.20
	C	0.85	±0.10		V	2.50	±0.30
	M	1.15	±0.10		F	1.25	±0.20
	F	1.25	±0.10		G	1.40	±0.20
	Q	1.25	±0.15		I	2.00	±0.20
	Y	1.25	±0.20		F	1.25	±0.20
	C	0.85	±0.15		H	1.60	±0.20
1206(3216)	C	0.85	±0.10*		I	2.00	±0.20
	E	1.10	±0.15		J	2.50	±0.20
	E	1.10	±0.10*		L	3.20	±0.30
	P	1.15	±0.10*		H	1.60	±0.20
	M	1.15	±0.15		I	2.00	±0.20
	F	1.25	±0.15		J	2.50	±0.20
	H	1.60	±0.20		L	3.20	±0.30

* Mark is only applicable to "L", "Y", "F", 12th code in part number.

8 INNER ELECTRODE/TERMINATION/PLATING CODE

Code	Thickness division	Inner electrode	Termination	Plating material
N	Normal	Ni	Cu	Ni / Sn _100%
G	Normal	Cu	Cu	Ni / Sn _100%
S	Normal	Ni	Soft Termination	Ni / Sn _100%
C	Normal	Ni	Control Code	Ni / Sn _100%
L	Low profile	Ni	Cu	Ni / Sn _100%
Y	Low profile	Ni	Soft Termination	Ni / Sn _100%
Z	Normal	Ni	Soft Termination	Ni / Sn _100%
F	Low profile	Ni	Soft Termination	Ni / Sn _100%

9 PRODUCT CODE OR SIZE CONTROL CODE

(Unit:mm)						
Code	01005(0402)	0201(0603)	0402(1005)	0603(1608)	0805(2012)	1206(3216)
S	±0.03	±0.05	±0.07	±0.07		±0.30
Q	±0.05	±0.07	±0.10	±0.15	±0.15	
R	±0.07	±0.09	±0.15	±0.20	±0.20	
U	±0.09		±0.20	±0.25	±0.25	
Z			±0.40	±0.30	±0.30	
9			±0.30			

10 CONTROL CODE

N = Normal
A = Array(2 - element)
B = Array(4 - element)
L = LICC
J = SLIC

11 PACKAGING CODE


Cardboard Tape (Paper)		Embossed Tape (Plastic)	
Code	Taping Type	Code	Taping Type
8 / C / H	Normal, 7" reel (Quantity option)	E / G	Normal, 7" reel (Quantity option)
J	1mm Pitch, 7" reel	R	Chip aligned for horizontal, 7" reel
Z	Chip aligned for horizontal, 7" reel	W	Chip aligned for vertical, 7" reel
Y	Chip aligned for vertical, 7" reel	S	Normal, 10" reel
O	Normal, 10" reel	F	Normal, 13" reel (Quantity option)
3 / D / L	Normal, 13" reel (Quantity option)		
2	1mm Pitch, 13" reel		
7	Chip aligned for vertical, 13" reel		

※ If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Standard & High Capacitors

Feature




- Wide selection of size : from 0402(Inch) to 2220(Inch)
- Highly reliable tolerance and high speed automatic chip placement on PCBs
- Wide capacitance range
- Highly reliable performance
- Highly resistant termination metal
- Tape & reel for surface mount assembly

Application

- | | |
|---|--|
| <ul style="list-style-type: none"> - Mobile Phone - DC - DC Converter - Tablet devices | <ul style="list-style-type: none"> - PC (Laptop, Desktop) - HDD / SSD board - Display |
|---|--|

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
05	0402	1.00±0.05	0.50±0.05	0.0975±0.0125(*)	L	0.25±0.075
		1.00±0.10	0.50±0.05	0.19±0.03(*)	X	0.25±0.10
		1.00±0.05	0.50±0.05	0.30±0.03(*)	3	
		1.00±0.05	0.50±0.05	0.50±0.05	5	
10	0603	1.60±0.10	0.80±0.10	0.50+0.0/-0.1(*)	5	0.30±0.20
		1.60±0.10	0.80±0.10	0.80±0.10	8	
21	0805	2.00±0.10	1.25±0.10	0.70±0.10(*)	7	0.50+0.20/-0.30
		2.00±0.10	1.25±0.10	0.80±0.10(*)	8	
		2.00±0.10	1.25±0.10	0.85±0.10	C	
		2.00±0.10	1.25±0.10	0.90±0.10(*)	9	
		2.00±0.10	1.25±0.10	1.15±0.10	M	
		2.00±0.10	1.25±0.10	1.25±0.10	F	
		2.00±0.15	1.25±0.15	1.25±0.15	Q	
		2.00±0.20	1.25±0.20	1.25±0.20	Y	
		3.20±0.20	1.60±0.20	0.60±0.10(*)	6	
31	1206	3.20±0.15	1.60±0.15	0.85±0.15	C	0.50±0.30
		3.20±0.20	1.60±0.20	0.85±0.10(*)	C	
		3.20±0.20	1.60±0.20	0.90±0.10(*)	9	
		3.20±0.20	1.60±0.20	1.10±0.10(*)	E	
		3.20±0.20	1.60±0.20	1.15±0.10(*)	M	
		3.20±0.20	1.60±0.20	1.15±0.10(*)	P	
		3.20±0.15	1.60±0.15	1.25±0.15	F	
		3.20±0.20	1.60±0.20	1.60±0.20	H	
		3.20±0.30	2.50±0.20	0.85±0.10(*)	C	0.60±0.30
32	1210	3.20±0.30	2.50±0.20	0.90±0.10(*)	9	
		3.20±0.30	2.50±0.20	1.60±0.20	H	
		3.20±0.30	2.50±0.20	1.80±0.20(*)	U	
		3.20±0.30	2.50±0.20	2.00±0.20	I	
		3.20±0.30	2.50±0.20	2.50±0.20	J	
		3.20±0.40	2.50±0.30	2.50±0.30	V	
		4.50±0.40	2.00±0.20	1.25±0.20	F	
42	1808	4.50±0.40	2.00±0.20	1.40±0.20	G	0.80±0.30
		4.50±0.40	2.00±0.20	2.00±0.20	I	
		4.50±0.40	3.20±0.30	1.25±0.20	F	
43	1812	4.50±0.40	3.20±0.30	2.50±0.20	J	0.80±0.30
		4.50±0.40	3.20±0.30	3.20±0.30	L	
		5.70±0.40	5.00±0.40	2.50±0.20	J	
55	2220	5.70±0.40	5.00±0.40	3.20±0.30	L	1.00±0.30

* Mark is only applicable to "L", "F", 12th code in part number.

Standard & High Capacitance Table (COG)

Standard & High Capacitors

Standard & High Capacitance Table (X5R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance									
		nF			uF						
		100	220	470	1.0	2.2	4.7	10	22	47	100
0402 (1005)	4.0										
	6.3										
	10										
	16										
	25										
	35										
0603 (1608)	4.0										
	6.3										
	10										
	16										
	25										
	35										
	50										
0805 (2012)	4.0										
	6.3										
	10										
	16										
	25										
	35										
	50										
1206 (3216)	6.3										150
	10										
	16										
	25										
	35										
	50										
1210 (3225)	6.3										
	10										
	16										
	25										
	35										
	50										
1812(4532)	6.3										
2220(5750)	6.3										
	10										

Standard & High Capacitance Table (X6S)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance									
		nF			uF						
		100	220	470	1.0	2.2	4.7	10	22	47	100
0402 (1005)	2.5										
	4.0										
	6.3										
	10										
	25										
0603 (1608)	4.0										
	6.3										
	10										
	16										
	25										
0805 (2012)	2.5										
	4.0										
	6.3										
	10										
	16										
	25										
1206 (3216)	4.0										
	6.3										
	10										
	16										
	25										
1210 (3225)	4.0										
	6.3										
	10										
	16										
	25										

Standard & High Capacitors

Standard & High Capacitance Table (X7R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance									
		nF					uF				
		47	100	220	330	470	1.0	2.2	3.3	4.7	10
0402 (1005)	6.3						X7S				
	10										
	16										
	25										
	50										
0603 (1608)	6.3									X7S	
	10										
	16										
	25										
	50										
0805 (2012)	6.3										
	10										
	16										
	25										
	35										
1206 (3216)	6.3										
	10										
	16										
	25										
	35										
1210 (3225)	6.3										X7T
	10										
	16										
	25										
	35										
	50										

Product Line Up (COG)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	10Vdc	560pF	±5%	CL05C561JP5NNN□	0.55mm	50Vdc	2.2pF	±0.1pF	CL05C2R2BB5NNN□
		33pF	±5%	CL05C330J05NNN□			2.2pF	±0.25pF	CL05C2R2CB5NNN□
		100pF	±5%	CL05C101J05NNN□			2.4pF	±0.1pF	CL05C2R4BB5NNN□
		150pF	±5%	CL05C151J05NNN□			2.4pF	±0.25pF	CL05C2R4CB5NNN□
		220pF	±5%	CL05C221J05NNN□			2.5pF	±0.1pF	CL05C2R5BB5NNN□
		470pF	±5%	CL05C471J05NNN□			2.5pF	±0.25pF	CL05C2R5CB5NNN□
		1.0nF	±5%	CL05C102J05NNN□			2.7pF	±0.1pF	CL05C2R7BB5NNN□
	25Vdc	10pF	±0.5pF	CL05C100DA5NNN□			2.7pF	±0.25pF	CL05C2R7CB5NNN□
		10pF	±5%	CL05C100JA5NNN□			3.0pF	±0.1pF	CL05C030BB5NNN□
		11pF	±5%	CL05C110JA5NNN□			3.0pF	±0.25pF	CL05C030CB5NNN□
		12pF	±5%	CL05C120JA5NNN□			3.3pF	±0.1pF	CL05C3R3BB5NNN□
		13pF	±5%	CL05C130JA5NNN□			3.3pF	±0.25pF	CL05C3R3CB5NNN□
		15pF	±5%	CL05C150JA5NNN□			3.5pF	±0.25pF	CL05C3R5CB5NNN□
		18pF	±2%	CL05C180GA5NNN□			3.6pF	±0.25pF	CL05C3R6CB5NNN□
		20pF	±5%	CL05C200JA5NNN□			3.9pF	±0.1pF	CL05C3R9BB5NNN□
		22pF	±5%	CL05C220JA5NNN□			3.9pF	±0.25pF	CL05C3R9CB5NNN□
		27pF	±2%	CL05C270GA5NNN□			4.0pF	±0.1pF	CL05C040BB5NNN□
		27pF	±5%	CL05C270JA5NNN□			4.0pF	±0.25pF	CL05C040CB5NNN□
		33pF	±5%	CL05C330JA5NNN□			4.3pF	±0.25pF	CL05C4R3CB5NNN□
		39pF	±5%	CL05C390JA5NNN□			4.7pF	±0.1pF	CL05C4R7BB5NNN□
		43pF	±5%	CL05C430JA5NNN□			4.7pF	±0.25pF	CL05C4R7CB5NNN□
		47pF	±5%	CL05C470JA5NNN□			4.7pF	±0.5pF	CL05C4R7DB5NNN□
		68pF	±5%	CL05C680JA5NNN□			5.0pF	±0.1pF	CL05C050BB5NNN□
		82pF	±5%	CL05C820JA5NNN□			5.0pF	±0.25pF	CL05C050CB5NNN□
		91pF	±5%	CL05C910JA5NNN□			5.0pF	±0.5pF	CL05C050DB5NNN□
		100pF	±5%	CL05C101JA5NNN□			5.1pF	±0.25pF	CL05C5R1CB5NNN□
		100pF	±10%	CL05C101KA5NNN□			5.6pF	±0.1pF	CL05C5R6BB5NNN□
		120pF	±5%	CL05C121JA5NNN□			5.6pF	±0.25pF	CL05C5R6CB5NNN□
		150pF	±5%	CL05C151JA5NNN□			5.6pF	±0.5pF	CL05C5R6DB5NNN□
		180pF	±5%	CL05C181JA5NNN□			6.0pF	±0.25pF	CL05C060CB5NNN□
		220pF	±1%	CL05C221FA5NNN□			6.0pF	±0.5pF	CL05C060DB5NNN□
		220pF	±5%	CL05C221JA5NNN□			6.2pF	±0.25pF	CL05C6R2CB5NNN□
		270pF	±5%	CL05C271JA5NNN□			6.2pF	±0.5pF	CL05C6R2DB5NNN□
		560pF	±5%	CL05C561JA5NNN□			6.8pF	±0.1pF	CL05C6R8BB5NNN□
		1.0nF	±5%	CL05C102JA5NNN□			6.8pF	±0.25pF	CL05C6R8CB5NNN□
	50Vdc	0.2pF	±0.1pF	CL05C0R2BB5NNN□			6.8pF	±0.5pF	CL05C6R8DB5NNN□
		0.3pF	±0.1pF	CL05C0R3BB5NNN□			7.0pF	±0.1pF	CL05C070BB5NNN□
		0.3pF	±0.25pF	CL05C0R3CB5NNN□			7.0pF	±0.25pF	CL05C070CB5NNN□
		0.5pF	±0.1pF	CL05C0R5BB5NNN□			7.0pF	±0.5pF	CL05C070DB5NNN□
		0.5pF	±0.25pF	CL05C0R5CB5NNN□			8.0pF	±0.25pF	CL05C080CB5NNN□
		0.7pF	±0.1pF	CL05C0R7BB5NNN□			8.0pF	±0.5pF	CL05C080DB5NNN□
		0.75pF	±0.1pF	CL05C0R75BB5NNN□			8.2pF	±0.1pF	CL05C8R2BB5NNN□
		0.75pF	±0.25pF	CL05C0R75CB5NNN□			8.2pF	±0.25pF	CL05C8R2CB5NNN□
		1.0pF	±0.1pF	CL05C010BB5NNN□			8.2pF	±0.5pF	CL05C8R2DB5NNN□
		1.0pF	±0.25pF	CL05C010CB5NNN□			9.0pF	±0.25pF	CL05C090CB5NNN□
		1.2pF	±0.1pF	CL05C1R2BB5NNN□			9.0pF	±0.5pF	CL05C090DB5NNN□
		1.2pF	±0.25pF	CL05C1R2CB5NNN□			9.1pF	±0.1pF	CL05C9R1BB5NNN□
		1.3pF	±0.1pF	CL05C1R3BB5NNN□			9.1pF	±0.25pF	CL05C9R1CB5NNN□
		1.5pF	±0.1pF	CL05C1R5BB5NNN□			10pF	±0.25pF	CL05C100CB5NNN□
		1.5pF	±0.25pF	CL05C1R5CB5NNN□			10pF	±0.5pF	CL05C100DB5NNN□
		1.8pF	±0.1pF	CL05C1R8BB5NNN□			10pF	±5%	CL05C100JB5NNN□
		1.8pF	±0.25pF	CL05C1R8CB5NNN□			11pF	±5%	CL05C110JB5NNN□
		2.0pF	±0.1pF	CL05C020BB5NNN□			12pF	±2%	CL05C120GB5NNN□
		2.0pF	±0.25pF	CL05C020CB5NNN□			12pF	±5%	CL05C120JB5NNN□

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Standard & High Capacitors

Product Line Up (COG)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	50Vdc	13pF	±5%	CL05C130JB5NNN □
		14pF	±5%	CL05C140JB5NNN □
		15pF	±5%	CL05C150JB5NNN □
		16pF	±5%	CL05C160JB5NNN □
		17pF	±5%	CL05C170JB5NNN □
		18pF	±2%	CL05C180GB5NNN □
		18pF	±5%	CL05C180JB5NNN □
		20pF	±2%	CL05C200GB5NNN □
		20pF	±5%	CL05C200JB5NNN □
		22pF	±1%	CL05C220FB5NNN □
		22pF	±2%	CL05C220GB5NNN □
		22pF	±5%	CL05C220JB5NNN □
		24pF	±5%	CL05C240JB5NNN □
		26pF	±5%	CL05C260JB5NNN □
		27pF	±1%	CL05C270FB5NNN □
		27pF	±5%	CL05C270JB5NNN □
		30pF	±5%	CL05C300JB5NNN □
		33pF	±1%	CL05C330FB5NNN □
		33pF	±5%	CL05C330JB5NNN □
		36pF	±5%	CL05C360JB5NNN □
		39pF	±2%	CL05C390GB5NNN □
		39pF	±5%	CL05C390JB5NNN □
		43pF	±2%	CL05C430GB5NNN □
		43pF	±5%	CL05C430JB5NNN □
		47pF	±1%	CL05C470FB5NNN □
		47pF	±5%	CL05C470JB5NNN □
		51pF	±5%	CL05C510JB5NNN □
		56pF	±1%	CL05C560FB5NNN □
		56pF	±5%	CL05C560JB5NNN □
		62pF	±2%	CL05C620GB5NNN □
		62pF	±5%	CL05C620JB5NNN □
		68pF	±5%	CL05C680JB5NNN □
		75pF	±5%	CL05C750JB5NNN □
		82pF	±5%	CL05C820JB5NNN □
		91pF	±5%	CL05C910JB5NNN □
		100pF	±1%	CL05C101FB5NNN □
		100pF	±2%	CL05C101GB5NNN □
		100pF	±5%	CL05C101JB5NNN □
		100pF	±10%	CL05C101KB5NNN □
		110pF	±5%	CL05C111JB5NNN □
		120pF	±2%	CL05C121GB5NNN □
		120pF	±5%	CL05C121JB5NNN □
		130pF	±5%	CL05C131JB5NNN □
		150pF	±5%	CL05C151JB5NNN □
		160pF	±5%	CL05C161JB5NNN □
		180pF	±5%	CL05C181JB5NNN □
		200pF	±5%	CL05C201JB5NNN □
		220pF	±1%	CL05C221FB5NNN □
		220pF	±2%	CL05C221GB5NNN □
		220pF	±5%	CL05C221JB5NNN □
		240pF	±5%	CL05C241JB5NNN □
		270pF	±5%	CL05C271JB5NNN □
		300pF	±5%	CL05C301JB5NNN □
		330pF	±5%	CL05C331JB5NNN □

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	50Vdc	390pF	±5%	CL05C391JB5NNN □
		470pF	±1%	CL05C471FB5NNN □
		470pF	±5%	CL05C471JB5NNN □
		560pF	±5%	CL05C561JB5NNN □
		680pF	±5%	CL05C681JB5NNN □
		820pF	±5%	CL05C821JB5NNN □
		1.0nF	±1%	CL05C102FB5NNN □
		1.0nF	±5%	CL05C102JB5NNN □

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.90mm	16Vdc	68pF	±1%	CL10C680FO8NNN □
		68pF	±2%	CL10C680GO8NNN □
		100pF	±2%	CL10C101GO8NNN □
		820pF	±5%	CL10C821JO8NNN □
		1.0nF	±5%	CL10C102JO8NNN □
		2.2nF	±5%	CL10C222JO8NNN □
		3.9nF	±5%	CL10C392JO8NNN □
		10pF	±0.5pF	CL10C100DA8NNN □
		10pF	±5%	CL10C100JA8NNN □
	25Vdc	15pF	±5%	CL10C150JA8NNN □
		20pF	±5%	CL10C200JA8NNN □
		33pF	±5%	CL10C330JA8NNN □
		47pF	±5%	CL10C470JA8NNN □
		68pF	±5%	CL10C680JA8NNN □
		100pF	±5%	CL10C101JA8NNN □
		100pF	±10%	CL10C101KA8NNN □
		120pF	±5%	CL10C121JA8NNN □
		150pF	±5%	CL10C151JA8NNN □
	50Vdc	180pF	±5%	CL10C181JA8NNN □
		270pF	±10%	CL10C271KA8NNN □
		330pF	±10%	CL10C331KA8NNN □
		390pF	±5%	CL10C391JA8NNN □
		470pF	±5%	CL10C471JA8NNN □
		560pF	±5%	CL10C561JA8NNN □
		680pF	±5%	CL10C681JA8NNN □
		820pF	±5%	CL10C821JA8NNN □
		1.5nF	±2%	CL10C152GA8NNN □
		1.5nF	±5%	CL10C152JA8NNN □
	50Vdc	1.8nF	±5%	CL10C182JA8NNN □
		10nF	±5%	CL10C102GA8NNN □
		1.0nF	±2%	CL10C102JA8NNN □
		1.0nF	±5%	CL10C102KA8NNN □
		2.2nF	±2%	CL10C222GA8NNN □
		2.2nF	±5%	CL10C222JA8NNN □
		3.3nF	±2%	CL10C332GA8NNN □
		3.3nF	±5%	CL10C332JA8NNN □
		3.9nF	±5%	CL10C392JA8NNN □

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (COG)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.90mm	50Vdc	0.47pF	±0.1pF	CL10CR47BB8NNN□	0.90mm	50Vdc	6.8pF	±0.25pF	CL10C6R8CB8NNN□
		0.5pF	±0.1pF	CL10COR5BB8NNN□			6.8pF	±0.5pF	CL10C6R8DB8NNN□
		0.5pF	±0.25pF	CL10COR5CB8NNN□			7.0pF	±0.1pF	CL10C070BB8NNN□
		0.56pF	±0.1pF	CL10CR56BB8NNN□			7.0pF	±0.25pF	CL10C070CB8NNN□
		0.68pF	±0.1pF	CL10CR68BB8NNN□			7.0pF	±0.5pF	CL10C070DB8NNN□
		0.75pF	±0.1pF	CL10CR75BB8NNN□			7.5pF	±0.1pF	CL10C7R5BB8NNN□
		0.75pF	±0.25pF	CL10CR75CB8NNN□			7.5pF	±0.25pF	CL10C7R5CB8NNN□
		0.8pF	±0.1pF	CL10COR8BB8NNN□			7.5pF	±0.5pF	CL10C7R5DB8NNN□
		0.82pF	±0.1pF	CL10CR82BB8NNN□			8.0pF	±0.25pF	CL10C080CB8NNN□
		1.0pF	±0.1pF	CL10C010BB8NNN□			8.0pF	±0.5pF	CL10C080DB8NNN□
		1.0pF	±0.25pF	CL10C010CB8NNN□			8.2pF	±0.1pF	CL10C8R2BB8NNN□
		1.2pF	±0.1pF	CL10C1R2BB8NNN□			8.2pF	±0.25pF	CL10C8R2CB8NNN□
		1.2pF	±0.25pF	CL10C1R2CB8NNN□			8.2pF	±0.5pF	CL10C8R2DB8NNN□
		1.5pF	±0.1pF	CL10C1R5BB8NNN□			9.0pF	±0.25pF	CL10C090CB8NNN□
		1.5pF	±0.25pF	CL10C1R5CB8NNN□			9.0pF	±0.5pF	CL10C090DB8NNN□
		1.8pF	±0.1pF	CL10C1R8BB8NNN□			9.1pF	±0.25pF	CL10C9R1CB8NNN□
		1.8pF	±0.25pF	CL10C1R8CB8NNN□			9.1pF	±0.5pF	CL10C9R1DB8NNN□
		2.0pF	±0.1pF	CL10C020BB8NNN□			10pF	±0.1pF	CL10C100BB8NNN□
		2.0pF	±0.25pF	CL10C020CB8NNN□			10pF	±0.25pF	CL10C100CB8NNN□
		2.2pF	±0.1pF	CL10C2R2BB8NNN□			10pF	±0.5pF	CL10C100DB8NNN□
		2.2pF	±0.25pF	CL10C2R2CB8NNN□			10pF	±1%	CL10C100FB8NNN□
		2.4pF	±0.1pF	CL10C2R4BB8NNN□			10pF	±2%	CL10C100GB8NNN□
		2.4pF	±0.25pF	CL10C2R4CB8NNN□			10pF	±5%	CL10C100JB8NNN□
		2.5pF	±0.1pF	CL10C2R5BB8NNN□			10pF	±10%	CL10C100KB8NNN□
		2.5pF	±0.25pF	CL10C2R5CB8NNN□			11pF	±2%	CL10C110GB8NNN□
		2.7pF	±0.1pF	CL10C2R7BB8NNN□			11pF	±5%	CL10C110JB8NNN□
		2.7pF	±0.25pF	CL10C2R7CB8NNN□			12pF	±1%	CL10C120FB8NNN□
		3.0pF	±0.1pF	CL10C030BB8NNN□			12pF	±2%	CL10C120GB8NNN□
		3.0pF	±0.25pF	CL10C030CB8NNN□			12pF	±5%	CL10C120JB8NNN□
		3.3pF	±0.1pF	CL10C3R3BB8NNN□			13pF	±2%	CL10C130GB8NNN□
		3.3pF	±0.25pF	CL10C3R3CB8NNN□			13pF	±5%	CL10C130JB8NNN□
		3.5pF	±0.25pF	CL10C3R5CB8NNN□			14pF	±5%	CL10C140JB8NNN□
		3.6pF	±0.1pF	CL10C3R6BB8NNN□			15pF	±1%	CL10C150FB8NNN□
		3.6pF	±0.25pF	CL10C3R6CB8NNN□			15pF	±2%	CL10C150GB8NNN□
		3.9pF	±0.1pF	CL10C3R9BB8NNN□			15pF	±5%	CL10C150JB8NNN□
		3.9pF	±0.25pF	CL10C3R9CB8NNN□			15pF	±10%	CL10C150KB8NNN□
		4.0pF	±0.1pF	CL10C040BB8NNN□			16pF	±5%	CL10C160JB8NNN□
		4.0pF	±0.25pF	CL10C040CB8NNN□			17pF	±5%	CL10C170JB8NNN□
		4.3pF	±0.1pF	CL10C4R3BB8NNN□			18pF	±1%	CL10C180FB8NNN□
		4.3pF	±0.25pF	CL10C4R3CB8NNN□			18pF	±2%	CL10C180GB8NNN□
		4.7pF	±0.1pF	CL10C4R7BB8NNN□			18pF	±5%	CL10C180JB8NNN□
		4.7pF	±0.25pF	CL10C4R7CB8NNN□			19pF	±5%	CL10C190JB8NNN□
		5.0pF	±0.1pF	CL10C050BB8NNN□			20pF	±1%	CL10C200FB8NNN□
		5.0pF	±0.25pF	CL10C050CB8NNN□			20pF	±2%	CL10C200GB8NNN□
		5.0pF	±0.5pF	CL10C050DB8NNN□			20pF	±5%	CL10C200JB8NNN□
		5.1pF	±0.25pF	CL10C5R1CB8NNN□			21pF	±5%	CL10C210JB8NNN□
		5.6pF	±0.1pF	CL10C5R6BB8NNN□			22pF	±1%	CL10C220FB8NNN□
		5.6pF	±0.25pF	CL10C5R6CB8NNN□			22pF	±2%	CL10C220GB8NNN□
		5.6pF	±0.5pF	CL10C5R6DB8NNN□			22pF	±5%	CL10C220JB8NNN□
		6.0pF	±0.25pF	CL10C060CB8NNN□			22pF	±10%	CL10C220KB8NNN□
		6.0pF	±0.5pF	CL10C060DB8NNN□			23pF	±5%	CL10C230JB8NNN□
		6.2pF	±0.25pF	CL10C6R2CB8NNN□			24pF	±2%	CL10C240GB8NNN□
		6.2pF	±0.5pF	CL10C6R2DB8NNN□			24pF	±5%	CL10C240JB8NNN□
		6.8pF	±0.1pF	CL10C6R8BB8NNN□			25pF	±5%	CL10C250JB8NNN□

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Standard & High Capacitors

Product Line Up (COG)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.90mm	50Vdc	26pF	±5%	CL10C260JB8NNN□	0.90mm	50Vdc	91pF	±5%	CL10C910JB8NNN□
		27pF	±1%	CL10C270FB8NNN□			95pF	±5%	CL10C950JB8NNN□
		27pF	±2%	CL10C270GB8NNN□			100pF	±1%	CL10C101FB8NNN□
		27pF	±5%	CL10C270JB8NNN□			100pF	±2%	CL10C101GB8NNN□
		28pF	±2%	CL10C280GB8NNN□			100pF	±5%	CL10C101JB8NNN□
		28pF	±5%	CL10C280JB8NNN□			100pF	±10%	CL10C101KB8NNN□
		30pF	±1%	CL10C300FB8NNN□			110pF	±5%	CL10C111JB8NNN□
		30pF	±5%	CL10C300JB8NNN□			120pF	±1%	CL10C121FB8NNN□
		32pF	±2%	CL10C320GB8NNN□			120pF	±2%	CL10C121GB8NNN□
		32pF	±5%	CL10C320JB8NNN□			120pF	±5%	CL10C121JB8NNN□
		33pF	±1%	CL10C330FB8NNN□			120pF	±10%	CL10C121KB8NNN□
		33pF	±2%	CL10C330GB8NNN□			130pF	±1%	CL10C131FB8NNN□
		33pF	±5%	CL10C330JB8NNN□			130pF	±5%	CL10C131JB8NNN□
		33pF	±10%	CL10C330KB8NNN□			140pF	±5%	CL10C141JB8NNN□
		35pF	±2%	CL10C350GB8NNN□			150pF	±2%	CL10C151GB8NNN□
		35pF	±5%	CL10C350JB8NNN□			150pF	±5%	CL10C151JB8NNN□
		36pF	±2%	CL10C360GB8NNN□			160pF	±5%	CL10C161JB8NNN□
		36pF	±5%	CL10C360JB8NNN□			170pF	±2%	CL10C171GB8NNN□
		39pF	±1%	CL10C390FB8NNN□			170pF	±5%	CL10C171JB8NNN□
		39pF	±2%	CL10C390GB8NNN□			180pF	±1%	CL10C181FB8NNN□
		39pF	±5%	CL10C390JB8NNN□			180pF	±2%	CL10C181GB8NNN□
		41pF	±2%	CL10C410GB8NNN□			180pF	±5%	CL10C181JB8NNN□
		41pF	±5%	CL10C410JB8NNN□			190pF	±5%	CL10C191JB8NNN□
		42pF	±5%	CL10C420JB8NNN□			200pF	±1%	CL10C201FB8NNN□
		43pF	±5%	CL10C430JB8NNN□			200pF	±5%	CL10C201JB8NNN□
		47pF	±1%	CL10C470FB8NNN□			220pF	±1%	CL10C221FB8NNN□
		47pF	±2%	CL10C470GB8NNN□			220pF	±2%	CL10C221GB8NNN□
		47pF	±5%	CL10C470JB8NNN□			220pF	±5%	CL10C221JB8NNN□
		47pF	±10%	CL10C470KB8NNN□			220pF	±10%	CL10C221KB8NNN□
		50pF	±5%	CL10C500JB8NNN□			240pF	±5%	CL10C241JB8NNN□
		51pF	±2%	CL10C510GB8NNN□			250pF	±5%	CL10C251JB8NNN□
		51pF	±5%	CL10C510JB8NNN□			270pF	±1%	CL10C271FB8NNN□
		56pF	±1%	CL10C560FB8NNN□			270pF	±2%	CL10C271JB8NNN□
		56pF	±2%	CL10C560GB8NNN□			270pF	±5%	CL10C271KB8NNN□
		56pF	±5%	CL10C560JB8NNN□			280pF	±5%	CL10C281JB8NNN□
		56pF	±10%	CL10C560KB8NNN□			300pF	±5%	CL10C301JB8NNN□
		60pF	±5%	CL10C600JB8NNN□			330pF	±0.25pF	CL10C331CB8NNN□
		62pF	±2%	CL10C620GB8NNN□			330pF	±1%	CL10C331FB8NNN□
		62pF	±5%	CL10C620JB8NNN□			330pF	±2%	CL10C331GB8NNN□
		68pF	±1%	CL10C680FB8NNN□			330pF	±5%	CL10C331JB8NNN□
		68pF	±2%	CL10C680GB8NNN□			350pF	±5%	CL10C351JB8NNN□
		68pF	±5%	CL10C680JB8NNN□			360pF	±5%	CL10C361JB8NNN□
		68pF	±10%	CL10C680KB8NNN□			390pF	±1%	CL10C391FB8NNN□
		70pF	±2%	CL10C700FB8NNN□			390pF	±2%	CL10C391GB8NNN□
		70pF	±5%	CL10C700JB8NNN□			390pF	±5%	CL10C391JB8NNN□
		75pF	±2%	CL10C750GB8NNN□			390pF	±10%	CL10C391KB8NNN□
		75pF	±5%	CL10C750JB8NNN□			430pF	±5%	CL10C431JB8NNN□
		80pF	±2%	CL10C800FB8NNN□			470pF	±1%	CL10C471FB8NNN□
		80pF	±5%	CL10C800JB8NNN□			470pF	±2%	CL10C471GB8NNN□
		82pF	±1%	CL10C820FB8NNN□			470pF	±5%	CL10C471JB8NNN□
		82pF	±2%	CL10C820GB8NNN□			470pF	±10%	CL10C471KB8NNN□
		82pF	±5%	CL10C820JB8NNN□			500pF	±5%	CL10C501JB8NNN□
		90pF	±5%	CL10C900JB8NNN□			510pF	±5%	CL10C511JB8NNN□
		91pF	±2%	CL10C910FB8NNN□			560pF	±1%	CL10C561FB8NNN□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (COG)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.90mm	50Vdc	560pF	±2%	CL10C561GB8NNN□	0.75mm	50Vdc	2.0pF	±0.25pF	CL21C020CBANNNN□
		560pF	±5%	CL10C561JB8NNN□			2.2pF	±0.1pF	CL21C2R2BBANNNN□
		560pF	±10%	CL10C561KB8NNN□			2.2pF	±0.25pF	CL21C2R2CBANNNN□
		620pF	±5%	CL10C621JB8NNN□			2.4pF	±0.25pF	CL21C2R4CBANNNN□
		680pF	±1%	CL10C681FB8NNN□			2.5pF	±0.25pF	CL21C2R5CBANNNN□
		680pF	±2%	CL10C681GB8NNN□			2.7pF	±0.1pF	CL21C2R7BBANNNN□
		680pF	±5%	CL10C681JB8NNN□			2.7pF	±0.25pF	CL21C2R7CBANNNN□
		680pF	±10%	CL10C681KB8NNN□			3.0pF	±0.1pF	CL21C030BBANNNN□
		720pF	±5%	CL10C721JB8NNN□			3.0pF	±0.25pF	CL21C030CBANNNN□
		750pF	±5%	CL10C751JB8NNN□			3.2pF	±0.25pF	CL21C3R2CBANNNN□
		820pF	±1%	CL10C821FB8NNN□			3.3pF	±0.1pF	CL21C3R3BBANNNN□
		820pF	±2%	CL10C821GB8NNN□			3.3pF	±0.25pF	CL21C3R3CBANNNN□
		820pF	±5%	CL10C821JB8NNN□			3.6pF	±0.1pF	CL21C3R6BBANNNN□
		820pF	±10%	CL10C821KB8NNN□			3.6pF	±0.25pF	CL21C3R6CBANNNN□
		910pF	±5%	CL10C911JB8NNN□			3.9pF	±0.1pF	CL21C3R9BBANNNN□
		1.0nF	±1%	CL10C102FB8NNN□			3.9pF	±0.25pF	CL21C3R9CBANNNN□
		1.0nF	±2%	CL10C102GB8NNN□			4.0pF	±0.1pF	CL21C040BBANNNN□
		1.0nF	±5%	CL10C102JB8NNN□			4.0pF	±0.25pF	CL21C040CBANNNN□
		1.2nF	±5%	CL10C122JB8NNN□			4.7pF	±0.1pF	CL21C4R7BBANNNN□
		1.5nF	±5%	CL10C152JB8NNN□			4.7pF	±0.25pF	CL21C4R7CBANNNN□
		1.8nF	±5%	CL10C182JB8NNN□			5.0pF	±0.1pF	CL21C050BBANNNN□
		2.2nF	±5%	CL10C222JB8NNN□			5.0pF	±0.25pF	CL21C050CBANNNN□
		2.7nF	±5%	CL10C272JB8NNN□			5.1pF	±0.25pF	CL21C5R1CBANNNN□
		3.3nF	±5%	CL10C332JB8NNN□			5.6pF	±0.25pF	CL21C5R6CBANNNN□
		4.7nF	±5%	CL10C472JB8NNN□			5.6pF	±0.5pF	CL21C5R6DBANNNN□
		5.6nF	±5%	CL10C562JB8NNN□			6.0pF	±0.25pF	CL21C060CBANNNN□
							6.0pF	±0.5pF	CL21C060DBANNNN□
							6.2pF	±0.25pF	CL21C6R2CBANNNN□
							6.8pF	±0.25pF	CL21C6R8CBANNNN□
							6.8pF	±0.5pF	CL21C6R8DBANNNN□
							7.0pF	±0.25pF	CL21C070CBANNNN□
							7.0pF	±0.5pF	CL21C070DBANNNN□
							7.5pF	±0.25pF	CL21C7R5CBANNNN□
							7.5pF	±0.5pF	CL21C7R5DBANNNN□
							8.0pF	±0.25pF	CL21C080CBANNNN□
							8.0pF	±0.5pF	CL21C080DBANNNN□
							8.2pF	±0.1pF	CL21C8R2BBANNNN□
							8.2pF	±0.25pF	CL21C8R2CBANNNN□
							8.2pF	±0.5pF	CL21C8R2DBANNNN□
							9.0pF	±0.25pF	CL21C090CBANNNN□
							9.0pF	±0.5pF	CL21C090DBANNNN□
							10pF	±0.1pF	CL21C100BBANNNN□
							10pF	±0.25pF	CL21C100CBANNNN□
							10pF	±0.5pF	CL21C100DBANNNN□
							10pF	±1%	CL21C100FBANNNN□
							10pF	±2%	CL21C100GBANNNN□
							10pF	±5%	CL21C100JBANNNN□
							12pF	±1%	CL21C120FBANNNN□
							12pF	±2%	CL21C120GBANNNN□
							12pF	±5%	CL21C120JBANNNN□
							13pF	±5%	CL21C130JBANNNN□
							14pF	±5%	CL21C140JBANNNN□
							15pF	±2%	CL21C150GBANNNN□
							15pF	±5%	CL21C150JBANNNN□

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.75mm	25Vdc	220pF	±2%	CL21C221GAANNNN□
		220pF	±5%	CL21C221JAANNNN□
		270pF	±5%	CL21C271JAANNNN□
		680pF	±5%	CL21C681JAANNNN□
		1.5nF	±5%	CL21C152JAANNNN□
		3.9nF	±5%	CL21C392JAANNNN□
	50Vdc	0.47pF	±0.1pF	CL21CR47BBANNNN□
		0.47pF	±0.25pF	CL21CR47CBANNNN□
		0.5pF	±0.1pF	CL21COR55BANNNN□
		0.5pF	±0.25pF	CL21COR55CBANNNN□
		0.68pF	±0.1pF	CL21CR68BBANNNN□
		0.75pF	±0.1pF	CL21CR75BBANNNN□
		0.82pF	±0.1pF	CL21CR82BBANNNN□
		0.82pF	±0.25pF	CL21CR82CBANNNN□
		1.0pF	±0.1pF	CL21C010BBANNNN□
		1.0pF	±0.25pF	CL21C010CBANNNN□
		1.2pF	±0.1pF	CL21C1R2BBANNNN□
		1.2pF	±0.25pF	CL21C1R2CBANNNN□
		1.5pF	±0.1pF	CL21C1R5BBANNNN□
		1.5pF	±0.25pF	CL21C1R5CBANNNN□
		1.8pF	±0.1pF	CL21C1R8BBANNNN□
		1.8pF	±0.25pF	CL21C1R8CBANNNN□
		1.8pF	±0.5pF	CL21C1R8DBANNNN□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Standard & High Capacitors

Product Line Up (COG)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.75mm	50Vdc	15pF	±10%	CL21C150KBANNNN □	0.75mm	50Vdc	75pF	±5%	CL21C750JBANNNN □
		16pF	±5%	CL21C160JBANNNN □			80pF	±2%	CL21C800GBANNNN □
		17pF	±5%	CL21C170JBANNNN □			80pF	±5%	CL21C800JBANNNN □
		18pF	±1%	CL21C180FBANNNN □			82pF	±1%	CL21C820FBANNNN □
		18pF	±2%	CL21C180GBANNNN □			82pF	±2%	CL21C820GBANNNN □
		18pF	±5%	CL21C180JBANNNN □			82pF	±5%	CL21C820JBANNNN □
		20pF	±2%	CL21C200GBANNNN □			90pF	±5%	CL21C900JBANNNN □
		20pF	±5%	CL21C200JBANNNN □			91pF	±5%	CL21C910JBANNNN □
		22pF	±1%	CL21C220FBANNNN □			100pF	±1%	CL21C101FBANNNN □
		22pF	±2%	CL21C220GBANNNN □			100pF	±2%	CL21C101GBANNNN □
		22pF	±5%	CL21C220JBANNNN □			100pF	±5%	CL21C101JBANNNN □
		22pF	±10%	CL21C220KBANNNN □			100pF	±10%	CL21C101KBANNNN □
		23pF	±5%	CL21C230JBANNNN □			110pF	±5%	CL21C111JBANNNN □
		24pF	±2%	CL21C240GBANNNN □			120pF	±1%	CL21C121FBANNNN □
		24pF	±5%	CL21C240JBANNNN □			120pF	±2%	CL21C121GBANNNN □
		25pF	±5%	CL21C250JBANNNN □			120pF	±5%	CL21C121JBANNNN □
		27pF	±1%	CL21C270FBANNNN □			130pF	±5%	CL21C131JBANNNN □
		27pF	±2%	CL21C270GBANNNN □			150pF	±1%	CL21C151FBANNNN □
		27pF	±5%	CL21C270JBANNNN □			150pF	±2%	CL21C151GBANNNN □
		28pF	±5%	CL21C280JBANNNN □			150pF	±5%	CL21C151JBANNNN □
		30pF	±5%	CL21C300JBANNNN □			160pF	±5%	CL21C161JBANNNN □
		32pF	±2%	CL21C320GBANNNN □			180pF	±1%	CL21C181FBANNNN □
		32pF	±5%	CL21C320JBANNNN □			180pF	±2%	CL21C181GBANNNN □
		33pF	±1%	CL21C330FBANNNN □			180pF	±5%	CL21C181JBANNNN □
		33pF	±2%	CL21C330GBANNNN □			200pF	±5%	CL21C201JBANNNN □
		33pF	±5%	CL21C330JBANNNN □			220pF	±1%	CL21C221FBANNNN □
		33pF	±10%	CL21C330KBANNNN □			220pF	±2%	CL21C221GBANNNN □
		36pF	±5%	CL21C360JBANNNN □			220pF	±5%	CL21C221JBANNNN □
		38pF	±2%	CL21C380GBANNNN □			220pF	±10%	CL21C221KBANNNN □
		38pF	±5%	CL21C380JBANNNN □			240pF	±5%	CL21C241JBANNNN □
		39pF	±2%	CL21C390GBANNNN □			250pF	±5%	CL21C251JBANNNN □
		39pF	±5%	CL21C390JBANNNN □			260pF	±5%	CL21C261JBANNNN □
		40pF	±2%	CL21C400GBANNNN □			270pF	±1%	CL21C271FBANNNN □
		40pF	±5%	CL21C400JBANNNN □			270pF	±2%	CL21C271GBANNNN □
		43pF	±5%	CL21C430JBANNNN □			300pF	±5%	CL21C301JBANNNN □
		47pF	±1%	CL21C470FBANNNN □			330pF	±1%	CL21C331FBANNNN □
		47pF	±2%	CL21C470GBANNNN □			330pF	±2%	CL21C331GBANNNN □
		47pF	±5%	CL21C470JBANNNN □			330pF	±5%	CL21C331JBANNNN □
		47pF	±10%	CL21C470KBANNNN □			360pF	±5%	CL21C361JBANNNN □
		50pF	±5%	CL21C500JBANNNN □			390pF	±1%	CL21C391FBANNNN □
		51pF	±2%	CL21C510GBANNNN □			390pF	±2%	CL21C391GBANNNN □
		51pF	±5%	CL21C510JBANNNN □			390pF	±5%	CL21C391JBANNNN □
		56pF	±1%	CL21C560FBANNNN □			430pF	±5%	CL21C431JBANNNN □
		56pF	±2%	CL21C560GBANNNN □			470pF	±1%	CL21C471FBANNNN □
		56pF	±5%	CL21C560JBANNNN □			470pF	±2%	CL21C471GBANNNN □
		60pF	±5%	CL21C600JBANNNN □			470pF	±5%	CL21C471JBANNNN □
		62pF	±5%	CL21C620JBANNNN □			470pF	±10%	CL21C471KBANNNN □
		68pF	±1%	CL21C680FBANNNN □			510pF	±5%	CL21C511JBANNNN □
		68pF	±2%	CL21C680GBANNNN □			560pF	±1%	CL21C561FBANNNN □
		68pF	±5%	CL21C680JBANNNN □			560pF	±2%	CL21C561GBANNNN □
		68pF	±10%	CL21C680KBANNNN □			560pF	±5%	CL21C561JBANNNN □
		70pF	±5%	CL21C700JBANNNN □			680pF	±5%	CL21C681JBANNNN □
		70pF	±10%	CL21C700KBANNNN □					
		75pF	±2%	CL21C750GBANNNN □	0.95mm	50Vdc	5.0pF	±0.25pF	CL21C050CBNNNN □

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (COG)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.95mm	50Vdc	10pF	±0.1pF	CL21C100BBCNNN□	0.95mm	50Vdc	1.0nF	±2%	CL21C102GBCNNN□
		10pF	±5%	CL21C100JBCNNN□			1.0nF	±5%	CL21C102JBCNNN□
		11pF	±2%	CL21C110GBCNNN□			1.0nF	±10%	CL21C102KBCNNN□
		11pF	±5%	CL21C110JBCNNN□	1.35mm	25Vdc	270pF	±5%	CL21C271JAFNNN□
		12pF	±2%	CL21C120GBCNNN□			2.7nF	±5%	CL21C272JAFNNN□
		12pF	±5%	CL21C120JBCNNN□			3.3nF	±5%	CL21C332JAFNNN□
		13pF	±2%	CL21C130GBCNNN□			3.9nF	±5%	CL21C392JAFNNN□
		15pF	±2%	CL21C150GBCNNN□			4.7nF	±5%	CL21C472JAFNNN□
		15pF	±5%	CL21C150JBCNNN□			4.7nF	±10%	CL21C472KAFNNN□
		16pF	±2%	CL21C160GBCNNN□			8.2nF	±5%	CL21C822JAFNNN□
		18pF	±2%	CL21C180GBCNNN□			10nF	±2%	CL21C103GAFNNN□
		18pF	±5%	CL21C180JBCNNN□			10nF	±5%	CL21C103JAFNNN□
		20pF	±2%	CL21C200GBCNNN□		50Vdc	1.2nF	±1%	CL21C122FBFNNN□
		20pF	±5%	CL21C200JBCNNN□			1.2nF	±2%	CL21C122GBFNNN□
		22pF	±2%	CL21C220GBCNNN□			1.2nF	±5%	CL21C122JBFNNN□
		22pF	±5%	CL21C220JBCNNN□			1.3nF	±5%	CL21C132JBFNNN□
		24pF	±2%	CL21C240GBCNNN□			1.5nF	±1%	CL21C152FBFNNN□
		30pF	±2%	CL21C300GBCNNN□			1.5nF	±2%	CL21C152GBFNNN□
		30pF	±5%	CL21C300JBCNNN□			1.5nF	±5%	CL21C152JBFNNN□
		36pF	±2%	CL21C360GBCNNN□			1.6nF	±5%	CL21C162JBFNNN□
		36pF	±5%	CL21C360JBCNNN□			1.8nF	±2%	CL21C182GBFNNN□
		39pF	±5%	CL21C390JBCNNN□			1.8nF	±5%	CL21C182JBFNNN□
		43pF	±2%	CL21C430GBCNNN□			2.0nF	±5%	CL21C202JBFNNN□
		43pF	±5%	CL21C430JBCNNN□			2.2nF	±2%	CL21C222GBFNNN□
		47pF	±5%	CL21C470JBCNNN□			2.2nF	±5%	CL21C222JBFNNN□
		51pF	±5%	CL21C510JBCNNN□			2.7nF	±5%	CL21C272JBFNNN□
		51pF	±10%	CL21C510KBCNNN□			3.3nF	±5%	CL21C332JBFNNN□
		56pF	±2%	CL21C560GBCNNN□			3.9nF	±5%	CL21C392JBFNNN□
		56pF	±5%	CL21C560JBCNNN□			4.7nF	±5%	CL21C472JBFNNN□
		68pF	±5%	CL21C680JBCNNN□			5.6nF	±5%	CL21C562JBFNNN□
		82pF	±5%	CL21C820JBCNNN□			6.8nF	±5%	CL21C682JBFNNN□
		100pF	±5%	CL21C101JBCNNN□			10nF	±5%	CL21C103JBFNNN□
		120pF	±1%	CL21C121FBCNNN□	1.00mm	25Vdc	330pF	±5%	CL31C331JACNNN□
		120pF	±5%	CL21C121JBCNNN□			470pF	±10%	CL31C471KACNNN□
		120pF	±10%	CL21C121KBCNNN□			0.5pF	±0.25pF	CL31C0R5CBCNNN□
		150pF	±5%	CL21C151JBCNNN□			1.0pF	±0.25pF	CL31C0102CBCNNN□
		180pF	±5%	CL21C181JBCNNN□			1.2pF	±0.25pF	CL31C1R2CBCNNN□
		220pF	±5%	CL21C221JBCNNN□			1.8pF	±0.25pF	CL31C1R8CBCNNN□
		300pF	±5%	CL21C301JBCNNN□			2.0pF	±0.25pF	CL31C0202CBCNNN□
		330pF	±2%	CL21C331GBCNNN□			2.2pF	±0.25pF	CL31C2R2CBCNNN□
		470pF	±5%	CL21C471JBCNNN□			2.7pF	±0.1pF	CL31C2R7BCNNN□
		510pF	±5%	CL21C511JBCNNN□			2.7pF	±0.25pF	CL31C2R7CBCNNN□
		560pF	±5%	CL21C561JBCNNN□			3.0pF	±0.25pF	CL31C0302CBCNNN□
		600pF	±5%	CL21C601JBCNNN□			3.3pF	±0.25pF	CL31C3R3CBCNNN□
		620pF	±5%	CL21C621JBCNNN□			3.9pF	±0.1pF	CL31C3R9BBCNNN□
		680pF	±1%	CL21C681FBCNNN□			4.3pF	±0.1pF	CL31C4R3BBCNNN□
		680pF	±2%	CL21C681GBCNNN□			4.7pF	±0.25pF	CL31C4R7CBCNNN□
		680pF	±5%	CL21C681JBCNNN□			5.6pF	±0.25pF	CL31C5R6CBCNNN□
		750pF	±5%	CL21C751JBCNNN□			5.6pF	±0.5pF	CL31C5R6DBCNNN□
		820pF	±1%	CL21C821FBCNNN□					
		820pF	±2%	CL21C821GBCNNN□					
		820pF	±5%	CL21C821JBCNNN□					
		910pF	±5%	CL21C911JBCNNN□					
		1.0nF	±1%	CL21C102FBCNNN□					

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Standard & High Capacitors

Product Line Up (COG)

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
1.00mm	50Vdc	6.0pF	±0.5pF	CL31C060DBCNNN □	1.00mm	50Vdc	200pF	±5%	CL31C201JBCNNN □
		6.8pF	±0.25pF	CL31C6R8CBCNNN □			220pF	±1%	CL31C221FBCNNN □
		8.0pF	±0.25pF	CL31C080CBCNNN □			220pF	±2%	CL31C221GBCNNN □
		8.2pF	±0.25pF	CL31C8R2CBCNNN □			220pF	±5%	CL31C221JBCNNN □
		10pF	±0.5pF	CL31C100DBCNNN □			240pF	±5%	CL31C241JBCNNN □
		10pF	±5%	CL31C100JBCNNN □			270pF	±5%	CL31C271JBCNNN □
		11pF	±5%	CL31C110JBCNNN □			300pF	±5%	CL31C301JBCNNN □
		12pF	±5%	CL31C120JBCNNN □			330pF	±1%	CL31C331FBCNNN □
		13pF	±5%	CL31C130JBCNNN □			330pF	±2%	CL31C331GBCNNN □
		15pF	±5%	CL31C150JBCNNN □			330pF	±5%	CL31C331JBCNNN □
		15pF	±10%	CL31C150KBCNNN □			360pF	±1%	CL31C361FBCNNN □
		16pF	±5%	CL31C160JBCNNN □			360pF	±5%	CL31C361JBCNNN □
		18pF	±5%	CL31C180JBCNNN □			390pF	±1%	CL31C391FBCNNN □
		20pF	±2%	CL31C200GBCNNN □			390pF	±2%	CL31C391GBCNNN □
		20pF	±5%	CL31C200JBCNNN □			390pF	±5%	CL31C391JBCNNN □
		22pF	±1%	CL31C220FBCNNN □			430pF	±5%	CL31C431JBCNNN □
		22pF	±5%	CL31C220JBCNNN □			470pF	±1%	CL31C471FBCNNN □
		24pF	±2%	CL31C240GBCNNN □			470pF	±2%	CL31C471GBCNNN □
		24pF	±5%	CL31C240JBCNNN □			470pF	±5%	CL31C471JBCNNN □
		25pF	±5%	CL31C250JBCNNN □			470pF	±10%	CL31C471KBCNNN □
		27pF	±1%	CL31C270FBCNNN □			510pF	±5%	CL31C511JBCNNN □
		27pF	±2%	CL31C270GBCNNN □			560pF	±1%	CL31C561FBCNNN □
		27pF	±5%	CL31C270JBCNNN □			560pF	±5%	CL31C561JBCNNN □
		30pF	±5%	CL31C300JBCNNN □			620pF	±5%	CL31C621JBCNNN □
		33pF	±1%	CL31C330FBCNNN □			680pF	±1%	CL31C681FBCNNN □
		33pF	±5%	CL31C330JBCNNN □			680pF	±2%	CL31C681GBCNNN □
		36pF	±5%	CL31C360JBCNNN □			680pF	±5%	CL31C681JBCNNN □
		38pF	±2%	CL31C380GBCNNN □			750pF	±5%	CL31C751JBCNNN □
		39pF	±2%	CL31C390GBCNNN □			820pF	±5%	CL31C821JBCNNN □
		39pF	±5%	CL31C390JBCNNN □			910pF	±5%	CL31C911JBCNNN □
		43pF	±2%	CL31C430GBCNNN □	1.40mm	25Vdc	1.0nF	±1%	CL31C102FBCNNN □
		43pF	±5%	CL31C430JBCNNN □			1.0nF	±2%	CL31C102GBCNNN □
		47pF	±5%	CL31C470JBCNNN □			1.0nF	±5%	CL31C102JBCNNN □
		47pF	±10%	CL31C470KBCNNN □			1.2nF	±2%	CL31C122GBCNNN □
		51pF	±5%	CL31C510JBCNNN □			1.2nF	±5%	CL31C122JBCNNN □
		56pF	±2%	CL31C560GBCNNN □			1.5nF	±2%	CL31C152GBCNNN □
		56pF	±5%	CL31C560JBCNNN □			1.5nF	±5%	CL31C152JBCNNN □
		62pF	±5%	CL31C620JBCNNN □			1.8nF	±2%	CL31C182GBCNNN □
		68pF	±2%	CL31C680GBCNNN □			1.8nF	±5%	CL31C182JBCNNN □
		68pF	±5%	CL31C680JBCNNN □			2.0nF	±5%	CL31C202JBCNNN □
		82pF	±5%	CL31C820JBCNNN □	50Vdc	50Vdc	2.2nF	±1%	CL31C222FBCNNN □
		91pF	±5%	CL31C910JBCNNN □			2.2nF	±2%	CL31C222GBCNNN □
		100pF	±2%	CL31C101GBCNNN □			2.2nF	±5%	CL31C222JBCNNN □
		100pF	±5%	CL31C101JBCNNN □			4.7nF	±2%	CL31C472GAFNNN □
		100pF	±10%	CL31C101KBCNNN □			8.2nF	±2%	CL31C822GAFNNN □
		110pF	±5%	CL31C111JBCNNN □			8.2nF	±5%	CL31C822JAFNNN □
		120pF	±5%	CL31C121JBCNNN □			10nF	±2%	CL31C103GAFNNN □
		130pF	±5%	CL31C131JBCNNN □			10nF	±5%	CL31C103JAFNNN □
		150pF	±5%	CL31C151JBCNNN □			2.7nF	±5%	CL31C272JBFNNN □
		160pF	±5%	CL31C161JBCNNN □			3.0nF	±5%	CL31C302JBFNNN □
		160pF	±10%	CL31C161KBCNNN □			3.3nF	±1%	CL31C332FBFNNN □
		180pF	±1%	CL31C181FBCNNN □			3.3nF	±2%	CL31C332GBFNNN □
		180pF	±2%	CL31C181GBCNNN □			3.3nF	±5%	CL31C332JBFNNN □
		180pF	±5%	CL31C181JBCNNN □			3.3nF	±10%	CL31C332KBFNNN □

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (COG)

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
1.40mm	50Vdc	3.6nF	±5%	CL31C362JBFNNN□
		3.9nF	±5%	CL31C392JBFNNN□
		4.7nF	±1%	CL31C472FBFNNN□
		4.7nF	±2%	CL31C472GBFNNN□
		4.7nF	±5%	CL31C472JBFNNN□
1.80mm	16Vdc	120nF	±5%	CL31C124J0HNNN□
		6.8nF	±2%	CL31C682GAHNNN□
		8.2nF	±5%	CL31C822JAHNNN□
		10nF	±5%	CL31C103JAHNNN□
		39nF	±5%	CL31C393JAHNNN□
		47nF	±5%	CL31C473JAHNNN□
		56nF	±5%	CL31C563JAHNNN□
		68nF	±5%	CL31C683JAHNNN□
		82nF	±5%	CL31C823JAHNNN□
		100nF	±5%	CL31C104JAHNNN□
	25Vdc	5.6nF	±5%	CL31C562JBHNNN□
		6.8nF	±5%	CL31C682JBHNNN□
		10nF	±2%	CL31C103GBHNNN□
		15nF	±5%	CL31C153JBHNNN□
		18nF	±5%	CL31C183JBHNNN□
	50Vdc	22nF	±5%	CL31C223JBHNNN□
		27nF	±5%	CL31C273JBHNNN□
		33nF	±5%	CL31C333JBHNNN□
		47nF	±5%	CL31C473JBHNNN□

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
1.45mm	25Vdc	10nF	±5%	CL32C103JAFNNN□
		1.0nF	±5%	CL32C102JBFNNN□
		1.2nF	±5%	CL32C122JBFNNN□
		1.5nF	±5%	CL32C152JBFNNN□
		1.8nF	±5%	CL32C182JBFNNN□
		2.7nF	±5%	CL32C272JBFNNN□
		3.9nF	±5%	CL32C392JBFNNN□
		4.7nF	±5%	CL32C472JBFNNN□
		5.6nF	±5%	CL32C562JBFNNN□
		6.8nF	±5%	CL32C682JBFNNN□
		8.2nF	±1%	CL32C822FBFNNN□
		8.2nF	±5%	CL32C822JBFNNN□
		10nF	±1%	CL32C103FBFNNN□
		10nF	±2%	CL32C103GBFNNN□
		10nF	±5%	CL32C103JBFNNN□
	1.80mm	50Vdc	11nF	CL32C113JBHNNN□

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Standard & High Capacitors

Product Line Up (X5R)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark		
0.11mm	6.3Vdc	220nF	±20%	CL05A224MQLHEC □	Derating Ref.	0.55mm	16Vdc	100nF	±5%	CL05A104J05NNNN □			
0.22mm	6.3Vdc	470nF	±20%	CL05A474MQXLNN □	Derating Ref.			100nF	±10%	CL05A104K05NNNN □			
		1.0uF	±20%	CL05A105MQXLNN □	Derating Ref.			100nF	±20%	CL05A104M05NNNN □			
0.33mm	4.0Vdc	2.2uF	±20%	CL05A225MR3LRN □	Derating Ref.			220nF	±10%	CL05A224KO5NNNN □			
		1.0uF	±20%	CL05A105MQ3LNN □	Derating			470nF	±10%	CL05A474KO5NNNN □	Derating		
	6.3Vdc	2.2uF	±20%	CL05A225MQ3LRN □	Derating Ref.			1.0uF	±10%	CL05A105KO5NNNN □	Derating		
0.35mm	6.3Vdc	4.7uF	±20%	CL05A475MQ3LUN □	Derating Ref.			4.2uF	±10%	CL05A425KO5LUN □	Derating Ref.		
0.55mm	4.0Vdc	100nF	±20%	CL05A104MR5NNNN □				100nF	±10%	CL05A104KA5NNNN □			
		1.0uF	±20%	CL05A105MR5NNNN □	Derating			220nF	±10%	CL05A224KA5NNNN □			
		1.3uF	±10%	CL05A135KR5NNNN □	Derating			330nF	±10%	CL05A334KA5NNNN □			
		1.4uF	±10%	CL05A145KR5NNNN □	Derating			330nF	±20%	CL05A334MA5NNNN □			
		1.5uF	±10%	CL05A155KR5NNNN □	Derating			470nF	±10%	CL05A474KA5NNNN □			
		1.7uF	±10%	CL05A175KR5NNNN □	Derating			1.0uF	±10%	CL05A105KA5NNNN □	Derating		
		1.8uF	±10%	CL05A185KR5NNNN □	Derating			10Vdc	2.2uF	±10%	CL05A225KP5NSN □	Derating Ref.	
		2.2uF	±20%	CL05A225MR5NNNN □	Derating Ref.			2.2uF	±20%	CL05A225MP5NSN □	Derating Ref.		
		3.3uF	±20%	CL05A335MR5NNNN □	Derating Ref.			25Vdc	2.2uF	±10%	CL05A225MQ5NSN □	Ref.	
	6.3Vdc	100nF	±10%	CL05A104KQ5NNNN □				2.2uF	±20%	CL05A225KP5NSN □	Derating Ref.		
		100nF	±20%	CL05A104MQ5NNNN □				2.2uF	±20%	CL05A225MP5NSN □	Derating Ref.		
		120nF	±10%	CL05A124KQ5NNNN □				10Vdc	2.2uF	±10%	CL05A225KP5NSN □	Derating Ref.	
		150nF	±10%	CL05A154KQ5NNNN □				2.2uF	±20%	CL05A225MP5NSN □	Derating Ref.		
		220nF	±5%	CL05A224JQ5NNNN □				25Vdc	1uF	±10%	CL05A105KA5NQN □	Derating	
		220nF	±10%	CL05A224KQ5NNNN □				1uF	±20%	CL05A105MA5NQN □	Derating		
		220nF	±20%	CL05A224MQ5NNNN □				0.60mm	4.0Vdc	4.7uF	±20%	CL05A475MR5NQN □	Derating Ref.
		330nF	±10%	CL05A334KQ5NNNN □				4.0Vdc	4.7uF	±20%	CL05A475MQ5NQN □	Derating Ref.	
		330nF	±20%	CL05A334MQ5NNNN □				6.3Vdc	4.7uF	±20%	CL05A475MR5NQN □	Derating Ref.	
		470nF	±10%	CL05A474KQ5NNNN □				16Vdc	2.2uF	±10%	CL05A225KO5NQN □	Derating Ref.	
		680nF	±10%	CL05A684KQ5NNNN □				2.2uF	±20%	CL05A225MO5NQN □	Derating Ref.		
		1.0uF	±5%	CL05A105JQ5NNNN □	Derating			25Vdc	1uF	±10%	CL05A105KA5NQN □	Derating	
		1.0uF	±10%	CL05A105KQ5NNNN □	Derating			10Vdc	4.7uF	±10%	CL05A475KP5NQN □	Derating Ref.	
10Vdc	10Vdc	1.0uF	±20%	CL05A105MQ5NNNN □	Derating			4.7uF	±20%	CL05A475MP5NQN □	Derating Ref.		
		1.0uF	±10%	CL05A225KQ5NNNN □	Derating Ref.			4.7uF	±20%	CL05A106MP5NQN □	Derating Ref.		
		2.2uF	±10%	CL05A225MQ5NNNN □	Derating Ref.			10uF	±20%	CL05A106MP5NQN □	Derating Ref.		
		2.2uF	±20%	CL05A225MR5NNNN □	Derating Ref.			35Vdc	1uF	±10%	CL05A105KL5NQN □	Derating	
		10nF	±10%	CL05A103KP5NNNN □				2.2uF	±20%	CL05A225MR5NUN □	Derating		
		47nF	±10%	CL05A473KP5NNNN □				10uF	±20%	CL05A106MR5NUN □	Derating Ref.		
		47nF	±20%	CL05A473MP5NNNN □				10Vdc	10uF	±20%	CL05A106MP5NUN □	Derating Ref.	
		68nF	±10%	CL05A683KP5NNNN □				22uF	±20%	CL05A226MQ5QUN □	Derating		
		82nF	±10%	CL05A823KP5NNNN □				10Vdc	10uF	±20%	CL05A106MP5NUN □	Derating Ref.	
		100nF	±10%	CL05A104KP5NNNN □				16Vdc	4.7uF	±20%	CL05A475MO5NUN □	Derating Ref.	
		100nF	±20%	CL05A104MP5NNNN □				25Vdc	2.2uF	±10%	CL05A225KA5NUN □	Derating Ref.	
		150nF	±10%	CL05A154KP5NNNN □				2.2uF	±20%	CL05A225MA5NUN □	Derating Ref.		
		220nF	±10%	CL05A224KP5NNNN □				25Vdc	2.2uF	±20%	CL05A226MQ5N6J □	Derating	
		220nF	±20%	CL05A224MP5NNNN □				0.75mm	6.3Vdc	22uF	±20%	CL05A226MQ5N6J □	Derating
		330nF	±10%	CL05A334KP5NNNN □				0.80mm	6.3Vdc	22uF	±20%	CL05A226MQ6NUN □	Derating
		330nF	±20%	CL05A334MP5NNNN □				10Vdc	10uF	±20%	CL05A106MP6NUN □	Derating Ref.	
		470nF	±10%	CL05A474KP5NNNN □				0.85mm	6.3Vdc	22uF	±20%	CL05A226MQ6N6J □	Derating
		1.0uF	±5%	CL05A105JP5NNNN □				0.90mm	4.0Vdc	22uF	±20%	CL05A226MR5NZN □	Derating Ref.
		1.0uF	±10%	CL05A105KP5NNNN □									
		1.0uF	±20%	CL05A105MP5NNNN □									
		2.2uF	±10%	CL05A225KP5NNNN □	Derating Ref.								
		2.2uF	±20%	CL05A225MP5NNNN □	Derating Ref.								
16Vdc	16Vdc	4.7nF	±10%	CL05A472K05NNNN □									
		22nF	±10%	CL05A223K05NNNN □									
		47nF	±10%	CL05A473K05NNNN □									
		47nF	±20%	CL05A473M05NNNN □									

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (X5R)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark		
0.50mm	4.0Vdc	10uF	±20%	CL10A106MR5LQN □		0.90mm	16Vdc	1.0uF	±10%	CL10A105KQ8NNN □			
	6.3Vdc	2.2uF	±10%	CL10A225KQ5LNN □				1.0uF	±20%	CL10A105M08NNN □			
		4.7uF	±10%	CL10A475KQ5LNN □				2.2uF	±10%	CL10A225KQ8NNN □			
		4.7uF	±20%	CL10A475MQ5LNN □				4.7uF	±10%	CL10A475KQ8NNN □			
		10uF	±20%	CL10A106MQ5LRN □				4.7uF	±20%	CL10A475M08NNN □			
	10Vdc	1.0uF	±10%	CL10A105KP5LNN □				100nF	±10%	CL10A104KA8NNN □			
		2.2uF	±10%	CL10A225KP5LNN □				220nF	±10%	CL10A224KA8NNN □			
		4.7uF	±10%	CL10A475KP5LNN □				220nF	±20%	CL10A224MA8NNN □			
		4.7uF	±20%	CL10A475MP5LNN □				330nF	±10%	CL10A334KA8NNN □			
0.60mm	16Vdc	1.0uF	±10%	CL10A105K05LNN □				470nF	±10%	CL10A474KA8NNN □			
		2.2uF	±10%	CL10A225K05LNN □				1.0uF	±10%	CL10A105KA8NNN □			
	25Vdc	1.0uF	±10%	CL10A105KA5LNN □				2.2uF	±10%	CL10A225KA8NNN □			
		2.2uF	±10%	CL10A225KA5LNN □				35Vdc	1.0uF	±10%	CL10A105KL8NNN □		
	6.3Vdc	4.7uF	±10%	CL10A475KQ5NNN □				2.2uF	±10%	CL10A225KL8NNN □			
		4.7uF	±20%	CL10A475MQ5NNN □				100nF	±10%	CL10A104KB8NNN □			
0.80mm	6.3Vdc	22uF	±20%	CL10A226MQ7LUN □		0.95mm	220nF	±20%	CL10A226MR8NQN □				
		22uF	±20%	CL10A226MP7LUN □			4.7uF	±20%	CL10A475MQ8NQN □				
		22uF	±20%	CL10A226M07JZN □			10uF	±20%	CL10A106MQ8NQN □				
0.90mm	4.0Vdc	2.2uF	±20%	CL10A225MR8NNN □			4.7uF	±10%	CL10A475KQ8NQN □				
		4.7uF	±20%	CL10A475MR8NNN □			10uF	±10%	CL10A106K08NQN □				
		10uF	±10%	CL10A106KR8NNN □			470nF	±10%	CL10A474KQ8NQN □				
		10uF	±20%	CL10A106MR8NNN □			10uF	±10%	CL10A106K08NQN □				
		22uF	±20%	CL10A226MR8NNN □			470nF	±20%	CL10A474KQ8NQN □				
	6.3Vdc	470nF	±10%	CL10A474KQ8NNN □			10uF	±20%	CL10A106M08NQN □				
		470nF	±20%	CL10A474MQ8NNN □			10uF	±20%	CL10A475KA8NQN □				
		680nF	±10%	CL10A684KQ8NNN □			470nF	±10%	CL10A475KA8NQN □				
		1.0uF	±10%	CL10A105KQ8NNN □			10uF	±10%	CL10A475MA8NQN □				
		1.0uF	±20%	CL10A105MQ8NNN □			470nF	±20%	CL10A475MA8NQN □				
		2.2uF	±10%	CL10A225KQ8NNN □			10uF	±10%	CL10A475KL8NQN □				
		2.2uF	±20%	CL10A225MQ8NNN □			22uF	±10%	CL10A226MQ8NQN □				
		3.3uF	±10%	CL10A335KQ8NNN □			22uF	±20%	CL10A476MQ8QRN □				
		3.3uF	±20%	CL10A335MQ8NNN □			47uF	±20%	CL10A476MQ8QRN □				
		4.7uF	±10%	CL10A475KQ8NNN □			10Vdc	22uF	±20%	CL10A226MP8NQN □			
10Vdc	10Vdc	4.7uF	±20%	CL10A475MQ8NNN □			25Vdc	10uF	±20%	CL10A475KL8NQN □			
		10uF	±10%	CL10A106KQ8NNN □			35Vdc	4.7uF	±10%	CL10A475KL8NQN □			
		10uF	±20%	CL10A106MQ8NNN □			1.00mm	4.0Vdc	47uF	±20%	CL10A476MR8NQN □		
		22uF	±20%	CL10A226MQ8NNN □			6.3Vdc	10uF	±20%	CL10A226MQ8NQN □			
		22uF	±10%	CL10A226MP8NNN □			4.0Vdc	47uF	±20%	CL10A476MR8NQN □			
		330nF	±10%	CL10A334KQ8NNN □			6.3Vdc	22uF	±20%	CL10A226MQ8NQN □			
		470nF	±10%	CL10A474KQ8NNN □			10Vdc	22uF	±20%	CL10A226MP8NQN □			
		680nF	±10%	CL10A684KQ8NNN □			25Vdc	10uF	±20%	CL10A476MQ8NQN □			
		820nF	±10%	CL10A824KQ8NNN □			35Vdc	4.7uF	±20%	CL10A476MQ8NQN □			
		1.0uF	±10%	CL10A105KQ8NNN □			4.0Vdc	47uF	±20%	CL10A476MR8NQN □			
16Vdc	16Vdc	1.0uF	±20%	CL10A105MP8NNN □			6.3Vdc	10uF	±20%	CL10A476MR8NQN □			
		2.2uF	±10%	CL10A225KP8NNN □			10Vdc	22uF	±20%	CL10A476MR8NQN □			
		2.2uF	±20%	CL10A225MP8NNN □			25Vdc	10uF	±20%	CL10A476MR8NQN □			
		3.3uF	±10%	CL10A335KP8NNN □			35Vdc	4.7uF	±20%	CL10A476MR8NQN □			
16Vdc	16Vdc	3.3uF	±20%	CL10A335MP8NNN □			1.05mm	6.3Vdc	22uF	±20%	CL10A226MQ8NQN □		
		4.7uF	±10%	CL10A475KP8NNN □			10.0mm	4.0Vdc	47uF	±20%	CL10A476MR8NQN □		
		4.7uF	±20%	CL10A475MP8NNN □			6.3Vdc	47uF	±20%	CL10A476MR8NQN □			
		10uF	±10%	CL10A106KP8NNN □			1.10mm	4.0Vdc	47uF	±20%	CL10A476MR8NQN □		
16Vdc	16Vdc	10uF	±20%	CL10A106MP8NNN □			6.3Vdc	47uF	±20%	CL10A476MQ8CZN □			
		330nF	±10%	CL10A334KO8NNN □									
		470nF	±10%	CL10A474KO8NNN □									

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Standard & High Capacitors

Product Line Up (X5R)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.70mm	10Vdc	2.2uF	±10%	CL21A225KP6LNN □		1.35mm	6.3Vdc	2.2uF	±20%	CL21A225MQFNNN □	
	16Vdc	1.0uF	±20%	CL21A105M06LNN □				3.3uF	±10%	CL21A335KQFNNN □	
		2.2uF	±10%	CL21A225KO6LNN □				3.3uF	±20%	CL21A335MQFNNN □	
0.80mm	6.3Vdc	10uF	±10%	CL21A106KQ7LQN □			4.7uF	±10%	CL21A475KQFNNN □		
		47uF	±20%	CL21A476MQ7FRN □	Derating			4.7uF	±20%	CL21A475MQFNNN □	
		47uF	±20%	CL21A476MQ7LRN □	Derating		6.8uF	±10%	CL21A685KQFNNN □		
	10Vdc	10uF	±10%	CL21A106KP7LQN □	Derating			10uF	±10%	CL21A106KQFNNN □	
0.90mm	6.3Vdc	47uF	±20%	CL21A476MQ8LRN □	Derating		10uF	±20%	CL21A106MQFNNN □		
0.95mm	4.0Vdc	22uF	±20%	CL21A226MRCLRN □	Derating			10uF	±20%	CL21A226MQFNNN □	
		47uF	±20%	CL21A476MRCLRP □	Derating		10Vdc	1.0uF	±10%	CL21A105KPFNNN □	
		1.0uF	±10%	CL21A105KQCLNN □				2.2uF	±10%	CL21A225KPFNNN □	
		1.0uF	±10%	CL21A105KQCNNN □				2.2uF	±20%	CL21A225MPFNNN □	
		4.7uF	±10%	CL21A475KQCLNN □				3.3uF	±10%	CL21A335KPFNNN □	
	6.3Vdc	4.7uF	±20%	CL21A475MQCLNN □				4.7uF	±10%	CL21A475KPFNNN □	
		10uF	±10%	CL21A106KQCLNN □				4.7uF	±20%	CL21A475MPFNNN □	
		10uF	±10%	CL21A106KQCLR □				10uF	±10%	CL21A106KPFNNN □	
		10uF	±20%	CL21A106MQCLNN □				10uF	±20%	CL21A106MPFNNN □	
		22uF	±10%	CL21A226KQCLR □	Derating		16Vdc	680nF	±10%	CL21A684KOFNNN □	
10Vdc	10Vdc	22uF	±20%	CL21A226MQCLQN □	Derating			1.0uF	±10%	CL21A105KOFNNN □	
		22uF	±20%	CL21A226MQCLRN □	Derating			2.2uF	±10%	CL21A225KOFNNN □	
		22uF	±20%	CL21A226MQCLR □	Derating			2.2uF	±20%	CL21A225MOFNNN □	
		47uF	±20%	CL21A476MQCLR □	Derating			3.3uF	±10%	CL21A335KOFNNN □	
		2.2uF	±10%	CL21A225KPCLNN □				4.7uF	±10%	CL21A475KOFNNN □	
		4.7uF	±10%	CL21A475KPCLNN □				10uF	±10%	CL21A106KOFNNN □	Derating
		4.7uF	±20%	CL21A475MPCLNN □	Derating		25Vdc	470nF	±20%	CL21A474MAFNNN □	
		10uF	±10%	CL21A106KPCLQN □	Derating			1.0uF	±10%	CL21A105KAFNNN □	
		10uF	±20%	CL21A106MPCLNN □	Derating			2.2uF	±10%	CL21A225KAFNNN □	
	25Vdc	10uF	±20%	CL21A106MPCLQN □	Derating	50Vdc	1.0uF	±10%	CL21A105KBFNNN □	Derating	
		22uF	±10%	CL21A226KPCLRN □	Derating		2.2uF	±10%	CL21A225KBFNNN □	Derating	
16Vdc	25Vdc	22uF	±10%	CL21A226ZPCLRN □	Derating	1.40mm	4.0Vdc	22uF	±20%	CL21A226MRQNNN □	
		47uF	±10%	CL21A226ZPCLQN □	Derating			47uF	±20%	CL21A476MRQNNN □	Derating
		4.7uF	±10%	CL21A476ZPCLRN □	Derating		6.3Vdc	4.7uF	±10%	CL21A475KQQNNN □	Derating
		10uF	±10%	CL21A106ZPCLNN □	Derating			10uF	±10%	CL21A106KQQNNN □	Derating
		10uF	±10%	CL21A106ZPCLR □	Derating			22uF	±10%	CL21A226KQQNNN □	
		10uF	±10%	CL21A106ZPCLSN □	Derating			22uF	±20%	CL21A226MQQNNN □	
		22uF	±20%	CL21A226MOCLR □	Derating		10Vdc	22uF	±20%	CL21A226MPQNNN □	
25Vdc	35Vdc	1.0uF	±10%	CL21A105KACLNN □				10uF	±10%	CL21A106KOQNNN □	Derating
		1.0uF	±10%	CL21A105KACNNN □				22uF	±10%	CL21A226KOQNNN □	Derating
		2.2uF	±10%	CL21A225KACLNN □	Derating			22uF	±20%	CL21A226MOQNNN □	Derating
		4.7uF	±10%	CL21A475KACLNN □	Derating		16Vdc	4.7uF	±10%	CL21A475KAQNNN □	Derating
		10uF	±10%	CL21A106KACLNN □	Derating			4.7uF	±20%	CL21A475MAQNNN □	Derating
50Vdc	35Vdc	4.7uF	±10%	CL21A475KLCLQN □	Derating			22uF	±20%	CL21A226MAQNNN □	Derating
		2.2uF	±10%	CL21A105KBCFNN □				2.2uF	±10%	CL21A225KBQNNN □	Derating
		1.0uF	±10%	CL21A105KBCLNN □				4.7uF	±10%	CL21A475KBQNNN □	Derating
		1.0uF	±10%	CL21A105KBCLQN □			25Vdc	47uF	±20%	CL21A476MRYNNN □	
		2.2uF	±10%	CL21A225KB9LNN □	Derating			47uF	±20%	CL21A476MQYNNN □	Derating
1.00mm	6.3Vdc	33uF	±20%	CL21A336MQ9LRN □	Derating			47uF	±20%	CL21A476MQYNNN □	Derating
		47uF	±20%	CL21A476MQ9LRN □	Derating	4.0Vdc	47uF	±20%	CL21A476MRYNNN □		
		50Vdc	2.2uF	±10%	CL21A225KB9LNN □	Derating	47uF	±20%	CL21A476MQYNNN □	Derating	
	6.3Vdc	33uF	±20%	CL21A336MQELRN □	Derating	6.3Vdc	47uF	±20%	CL21A476MQYNNN □	Derating	
		10Vdc	2.2uF	±10%	CL21A225KPENNN □			47uF	±20%	CL21A476MQYNNN □	Derating
		12.5mm	6.3Vdc	47uF	±20%	CL21A476MQMNRN □	Derating	10uF	±10%	CL21A106KAYNNN □	Derating
1.35mm	4.0Vdc	10uF	±20%	CL21A106MRFNNN □							
	6.3Vdc	2.2uF	±10%	CL21A225KQFNNN □							

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (X5R)

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	6.3Vdc	10uF	±20%	CL31A106MQCLNN□	
		22uF	±10%	CL31A226KQCLNN□	Derating
		22uF	±20%	CL31A226MQCLNN□	Derating
	10Vdc	10uF	±10%	CL31A106KPCCLNN□	
		10uF	±20%	CL31A106MPCLNN□	
	16Vdc	2.2uF	±10%	CL31A225KOCLNN□	
		4.7uF	±10%	CL31A475KOCLNN□	
		4.7uF	±20%	CL31A475MOCLNN□	
		10uF	±10%	CL31A106KOCLNN□	
		22uF	±10%	CL31A226KOCLNN□	Derating
		22uF	±20%	CL31A226MOCLNN□	Derating
	25Vdc	4.7uF	±10%	CL31A475KACLNN□	
		10uF	±10%	CL31A106KACLNN□	Derating
1.00mm	35Vdc	4.7uF	±10%	CL31A475KL9LNN□	Derating
	50Vdc	1.0uF	±10%	CL31A105KB9LNN□	
		2.2uF	±10%	CL31A225KB9LNN□	
		4.7uF	±10%	CL31A475KB9LNN□	Derating
	100Vdc	2.2uF	±10%	CL31A225KC9LNN□	Derating
1.20mm	16Vdc	4.7uF	±10%	CL31A475KOELNN□	
1.25mm	10Vdc	10uF	±10%	CL31A106KPPLNN□	
		10uF	±20%	CL31A106MPPLNN□	
	16Vdc	4.7uF	±10%	CL31A475KOPLNN□	
		4.7uF	±20%	CL31A475MOPLNN□	
	25Vdc	1.0uF	±10%	CL31A105KAPLNN□	
		2.2uF	±10%	CL31A225KAPLNN□	
		4.7uF	±10%	CL31A475KAPLNN□	
1.70mm	50Vdc	2.2uF	±10%	CL31A225KBTLNN□	
1.80mm	6.3Vdc	3.3uF	±10%	CL31A335KQHNNN□	
		10uF	±10%	CL31A106KQHNNN□	
		10uF	±20%	CL31A106MQHNNN□	
		15uF	±10%	CL31A156KQHNNN□	
		15uF	±20%	CL31A156MQHNNN□	
		22uF	±10%	CL31A226KQHNNN□	
		22uF	±20%	CL31A226MQHNNN□	
		33uF	±20%	CL31A336MQHNNN□	
		47uF	±10%	CL31A476KQHNNN□	
		47uF	±20%	CL31A476MQHNNN□	
	10Vdc	100uF	±20%	CL31A107MQHNNN□	Derating
		3.3uF	±10%	CL31A335KPHNNN□	
		4.7uF	±10%	CL31A475KPHNNN□	
		10uF	±10%	CL31A106KPHNNN□	
		10uF	±20%	CL31A106MPHNNN□	
		22uF	±10%	CL31A226KPHNNN□	
		22uF	±20%	CL31A226MPHNNN□	
		47uF	±20%	CL31A476MPHNNN□	Derating
	16Vdc	100uF	±20%	CL31A107MPHNNN□	Derating
		2.2uF	±10%	CL31A225KOHNNN□	
		3.3uF	±10%	CL31A335KOHNNN□	
		3.3uF	±20%	CL31A335MOHNNN□	
		4.7uF	±10%	CL31A475KOHNNN□	
		4.7uF	±20%	CL31A475MOHNNN□	
		10uF	±10%	CL31A106KOHNNN□	
		10uF	±20%	CL31A106MOHNNN□	
		22uF	±10%	CL31A226KOHNNN□	Derating

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.80mm	16Vdc	22uF	±20%	CL31A226MOHNNN□	
		2.2uF	±10%	CL31A225KAHNNN□	
		3.3uF	±10%	CL31A335KAHNNN□	
	25Vdc	4.7uF	±10%	CL31A475KAHNNN□	
		10uF	±10%	CL31A106KAHNNN□	
		10uF	±20%	CL31A106MAHNNN□	
	35Vdc	22uF	±10%	CL31A226MAHNNN□	
		22uF	±20%	CL31A226MHNNN□	Derating
		22uF	±20%	CL31A226MBHNNN□	Derating
	50Vdc	2.2uF	±10%	CL31A225KLBHNNN□	
		2.2uF	±20%	CL31A225KBHNNN□	
		4.7uF	±10%	CL31A475KBHNNN□	
		10uF	±10%	CL31A106KBHNNN□	
		10uF	±20%	CL31A106MBHNNN□	

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	16Vdc	10uF	±10%	CL32A106KOCLNN□	
		22uF	±20%	CL32A226MOCLNN□	Derating
	25Vdc	10uF	±10%	CL32A106KA9LNN□	
		22uF	±20%	CL32A226MATLNN□	
	35Vdc	4.7uF	±10%	CL32A475KALUJNN□	
		10uF	±10%	CL32A106KALUJNN□	
	50Vdc	4.7uF	±10%	CL32A475KLULNN□	
		10uF	±10%	CL32A106KLULNN□	
	6.3Vdc	22uF	±10%	CL32A226KOTFNN□	
		22uF	±20%	CL32A226MOTLNN□	Derating
	10Vdc	10uF	±10%	CL32A106KATLNN□	
		10uF	±20%	CL32A106MATLNN□	
1.00mm	25Vdc	4.7uF	±10%	CL32A475KULNN□	
		10uF	±10%	CL32A106KULNN□	
	35Vdc	4.7uF	±10%	CL32A475KLULNN□	
		10uF	±10%	CL32A106KLULNN□	
	50Vdc	4.7uF	±10%	CL32A475MLULNN□	
		10uF	±10%	CL32A106MLULNN□	
	6.3Vdc	10uF	±10%	CL32A106KPINNN□	
		10uF	±20%	CL32A106KOILNN□	
	10Vdc	2.2uF	±20%	CL32A225MAINNN□	
		4.7uF	±10%	CL32A475KAINNN□	
	16Vdc	10uF	±10%	CL32A106KAILNN□	
		10uF	±20%	CL32A106MAILNN□	
1.20mm	25Vdc	22uF	±10%	CL32A226KQJNNNN□	
		22uF	±20%	CL32A226MQJNNNN□	
	35Vdc	33uF	±20%	CL32A336MQJNNNN□	
		47uF	±10%	CL32A476KQJNNNN□	
	50Vdc	47uF	±10%	CL32A476MQJNNNN□	
		47uF	±20%	CL32A476KQJNNNN□	
	6.3Vdc	22uF	±10%	CL32A226KPJNNNN□	
		22uF	±20%	CL32A226MPJNNNN□	Derating
	10Vdc	47uF	±10%	CL32A476KPJNNNN□	Derating
		47uF	±20%	CL32A476MPJNNNN□	
	16Vdc	10uF	±10%	CL32A106KOJNNNN□	
		10uF	±20%	CL32A106MOJNNNN□	
		22uF	±10%	CL32A226KOJNNNN□	
		22uF	±20%	CL32A226MOJNNNN□	
		47uF	±10%	CL32A476KOJNNNN□	

Standard & High Capacitors

Product Line Up (X5R)

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.70mm	16Vdc	47uF	±20%	CL32A476MQJNNN □	
	25Vdc	10uF	±10%	CL32A106KAJNNN □	
		10uF	±20%	CL32A106MAJNNN □	
		22uF	±10%	CL32A226KAJNNN □	
		22uF	±20%	CL32A226MAJNNN □	
	35Vdc	10uF	±10%	CL32A106KLJNNN □	
		2.2uF	±10%	CL32A225KBJNNN □	
		10uF	±10%	CL32A106KBJNNN □	
	50Vdc	10uF	±20%	CL32A106MBJNNN □	
		100uF	±20%	CL32A107MQVNNN □	Derating
		150uF	±20%	CL32A157MQVNNN □	Derating
		220uF	±20%	CL32A227MQVNNN □	Derating
	10Vdc	100uF	±20%	CL32A107MPVNNN □	Derating

■ Size : 4.50 X 3.20mm (inch : 1812)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.70mm	6.3Vdc	33uF	±20%	CL43A336MQJNNN □	
		47uF	±10%	CL43A476KQJNNN □	
		47uF	±20%	CL43A476MQJNNN □	
3.50mm	6.3Vdc	100uF	±20%	CL43A107MQLNNN □	

■ Size : 5.70 X 5.00mm (inch : 2220)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.70mm	6.3Vdc	47uF	±20%	CL55A476MQJNNN □	
		68uF	±20%	CL55A686MQJNNN □	
		100uF	±20%	CL55A107MQJNNN □	
	10Vdc	47uF	±10%	CL55A476KPJNNN □	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Product Line Up (X6S)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.55mm	4.0Vdc	1.0uF	±20%	CL05X105MQ3LNN □	
		2.2nF	±20%	CL05X222MR5NNN □	
		15nF	±20%	CL05X153MR5NNN □	
		47nF	±20%	CL05X473MR5NNN □	
		220nF	±20%	CL05X224MR5NNN □	
	6.3Vdc	2.2uF	±20%	CL05X225MR5NNN □	
		680nF	±5%	CL05X684JQ5NNN □	
		1.0uF	±10%	CL05X105KQ5NNN □	
		10Vdc	±10%	CL05X105KP5NNN □	
		2.2uF	±20%	CL05X225MS5NSN □	
0.57mm	2.5Vdc	1.0uF	±10%	CL05X105KA5NQN □	
0.60mm	25Vdc	1.0uF	±10%	CL05X105KA8NQN □	
0.70mm	4.0Vdc	4.7uF	±20%	CL05X475MR5NUN □	
		10uF	±20%	CL05X106MR5NUN □	

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	
1.35mm	4.0Vdc	22uF	±20%	CL21X226MSCLRN □		
		4.0Vdc	10uF	±10%	CL21X106KRCLRN □	
		10Vdc	10uF	±10%	CL21X106KPCLRN □	
		4.7uF	±10%	CL21X475KRFNNN □		
		10uF	±10%	CL21X106KRFNNN □		
	16Vdc	10uF	±20%	CL21X106MRFNNN □		
		2.2uF	±10%	CL21X225KOFNNN □		
		4.0Vdc	22uF	±20%	CL21X226MRQNNN □	
		6.3Vdc	10uF	±10%	CL21X106KQQNNN □	
		22uF	±20%	CL21X226MQQNNN □		
1.40mm	16Vdc	10uF	±10%	CL21X106KOQNNN □		
		10uF	±20%	CL21X106MOQNNN □		
		4.7uF	±10%	CL21X475KAQNNN □		
		4.7uF	±20%	CL21X475MAQNNN □		
		2.5Vdc	47uF	±20%	CL21X476MSYNNN □	
	25Vdc	47uF	±20%	CL21X476MRYNNN □		
		10Vdc	10uF	±10%	CL21X106KPYNNN □	
		10uF	±10%	CL21X106KAYNNN □		
		10uF	±20%	CL21X106MAYNNN □		
		4.0Vdc	47uF	±20%	CL21X476MRQNNN □	

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	4.0Vdc	1.0uF	±20%	CL10X105MR8NNN □	
		4.7uF	±20%	CL10X475MR8NNN □	
		10uF	±10%	CL10X106KR8NNN □	
		10uF	±20%	CL10X106MR8NNN □	
	6.3Vdc	1.0uF	±20%	CL10X105MQ8NNN □	
		2.2uF	±10%	CL10X225KQ8NNN □	
		2.2uF	±20%	CL10X225MQ8NNN □	
		4.7uF	±10%	CL10X475KQ8NNN □	
		4.7uF	±20%	CL10X475MQ8NNN □	
		10uF	±10%	CL10X106KQ8NNN □	
0.95mm	10Vdc	2.2uF	±10%	CL10X225KP8NNN □	
	25Vdc	1.0uF	±10%	CL10X105KA8NNN □	
	25Vdc	4.7uF	±10%	CL10X475KA8NNN □	
	100mm	10uF	±20%	CL10X106MP8NRN □	
	16Vdc	4.7uF	±10%	CL10X475KO8NRN □	
1.00mm	10Vdc	10uF	±20%	CL10X106M08NRN □	
	16Vdc	10uF	±20%	CL10X106M08NRN □	

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.80mm	4.0Vdc	4.7uF	±10%	CL31X475KACLNN □	
		10uF	±10%	CL31X106KRHNNN □	
		10uF	±20%	CL31X106MRHNNN □	
		22uF	±10%	CL31X226KRHNNN □	
		22uF	±20%	CL31X226MRHNNN □	
	6.3Vdc	47uF	±20%	CL31X476MRHNNN □	
		10uF	±10%	CL31X106KQHNNN □	
		10uF	±20%	CL31X106MQHNNN □	
		22uF	±10%	CL31X226KQHNNN □	
		47uF	±20%	CL31X476MQHNNN □	
2.70mm	16Vdc	22uF	±10%	CL31X226KOHNNN □	
	25Vdc	10uF	±10%	CL31X106KAHNNN □	
	25Vdc	47uF	±20%	CL31X476KAHNNN □	
	25Vdc	10uF	±10%	CL31X226KQHNNN □	
	25Vdc	10uF	±10%	CL31X106KQHNNN □	

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.80mm	4.0Vdc	22uF	±20%	CL32X226MQJNNN □	
		47uF	±10%	CL32X476KPJNNN □	
		10uF	±10%	CL32X106KOJNNN □	
	6.3Vdc	100uF	±10%	CL32X107KRVNNN □	
		100uF	±20%	CL32X107MQVNNN □	
		100uF	±20%	CL32X107MQVNNN □	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Standard & High Capacitors

Product Line Up (X7R)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.33mm	16Vdc	100nF	±10%	CL05B104K03LNN □		0.55mm	16Vdc	47nF	±20%	CL05B473M05NNNN □	
0.55mm	6.3Vdc	68nF	±10%	CL05B683KQ5NNNN □		0.55mm	16Vdc	56nF	±10%	CL05B563K05NNNN □	
		100nF	±10%	CL05B104KQ5NNNN □				68nF	±10%	CL05B683K05NNNN □	
		470nF	±10%	CL05B474KQ5NNNN □	Ref.			82nF	±10%	CL05B823K05NNNN □	
	10Vdc	1.0nF	±10%	CL05B102KP5NNNN □			25Vdc	100nF	±5%	CL05B104J05NNNN □	
		2.2nF	±20%	CL05B222MP5NNNN □				100nF	±10%	CL05B104K05NNNN □	
		6.8nF	±20%	CL05B682MP5NNNN □				100nF	±20%	CL05B104M05NNNN □	
		10nF	±10%	CL05B103KP5NNNN □				150nF	±10%	CL05B154K05NNNN □	
		15nF	±20%	CL05B153MP5NNNN □				220nF	±10%	CL05B224K05NNNN □	Ref.
		18nF	±10%	CL05B183KP5NNNN □				220pF	±10%	CL05B221KA5NNNN □	
		22nF	±10%	CL05B223KP5NNNN □				270pF	±10%	CL05B271KA5NNNN □	
16Vdc	10Vdc	27nF	±10%	CL05B273KP5NNNN □				330pF	±10%	CL05B331KA5NNNN □	
		33nF	±10%	CL05B333KP5NNNN □				470pF	±10%	CL05B471KA5NNNN □	
		47nF	±10%	CL05B473KP5NNNN □				560pF	±10%	CL05B561KA5NNNN □	
		47nF	±20%	CL05B473MP5NNNN □				1.0nF	±10%	CL05B102KA5NNNN □	
		56nF	±10%	CL05B563KP5NNNN □				1.5nF	±10%	CL05B152KA5NNNN □	
		68nF	±10%	CL05B683KP5NNNN □				1.8nF	±10%	CL05B182KA5NNNN □	
		82nF	±10%	CL05B823KP5NNNN □				2.2nF	±10%	CL05B222KA5NNNN □	
		100nF	±5%	CL05B104JP5NNNN □				2.2nF	±20%	CL05B222MA5NNNN □	
		100nF	±10%	CL05B104KP5NNNN □				3.3nF	±5%	CL05B332JA5NNNN □	
		100nF	±20%	CL05B104MP5NNNN □				3.3nF	±10%	CL05B332KA5NNNN □	
	16Vdc	220nF	±10%	CL05B224KP5NNNN □	Ref.			3.9nF	±10%	CL05B392KA5NNNN □	
		470nF	±10%	CL05B474KP5NNNN □				4.7nF	±5%	CL05B472JA5NNNN □	
		220pF	±10%	CL05B221K05NNNN □				4.7nF	±10%	CL05B472KA5NNNN □	
		330pF	±10%	CL05B331K05NNNN □				5.6nF	±10%	CL05B562KA5NNNN □	
		820pF	±10%	CL05B821K05NNNN □				6.8nF	±10%	CL05B682KA5NNNN □	
		1.0nF	±10%	CL05B102K05NNNN □				8.2nF	±10%	CL05B822KA5NNNN □	
		2.2nF	±10%	CL05B222K05NNNN □				10nF	±5%	CL05B103JA5NNNN □	
		2.7nF	±10%	CL05B272K05NNNN □				10nF	±10%	CL05B103KA5NNNN □	
		3.9nF	±10%	CL05B392K05NNNN □				10nF	±20%	CL05B103MA5NNNN □	
		4.7nF	±10%	CL05B472K05NNNN □				12nF	±10%	CL05B123KA5NNNN □	
25Vdc	16Vdc	4.7nF	±20%	CL05B472MO5NNNN □				15nF	±10%	CL05B153KA5NNNN □	
		5.6nF	±10%	CL05B562K05NNNN □				18nF	±10%	CL05B183KA5NNNN □	
		6.8nF	±10%	CL05B682K05NNNN □				22nF	±10%	CL05B223KA5NNNN □	
		8.2nF	±10%	CL05B822K05NNNN □				33nF	±10%	CL05B333KA5NNNN □	
		10nF	±5%	CL05B103JA5NNNN □				47nF	±10%	CL05B473KA5NNNN □	
		10nF	±10%	CL05B103K05NNNN □				100nF	±10%	CL05B104KA5NNNN □	
		10nF	±20%	CL05B103MO5NNNN □				12pF	±5%	CL05B120JB5NNNN □	
		12nF	±10%	CL05B123K05NNNN □				47pF	±5%	CL05B470JB5NNNN □	
		15nF	±5%	CL05B153J05NNNN □				100pF	±10%	CL05B101KB5NNNN □	
		15nF	±10%	CL05B153K05NNNN □				120pF	±10%	CL05B121KB5NNNN □	
50Vdc	25Vdc	18nF	±5%	CL05B183J05NNNN □				150pF	±10%	CL05B151KB5NNNN □	
		18nF	±10%	CL05B183KO5NNNN □				180pF	±10%	CL05B181KB5NNNN □	
		22nF	±5%	CL05B223J05NNNN □				200pF	±10%	CL05B201KB5NNNN □	
		22nF	±10%	CL05B223K05NNNN □				220pF	±5%	CL05B221JB5NNNN □	
		22nF	±20%	CL05B223MO5NNNN □				220pF	±10%	CL05B221KB5NNNN □	
		27nF	±5%	CL05B273J05NNNN □				240pF	±10%	CL05B241KB5NNNN □	
		27nF	±10%	CL05B273K05NNNN □				270pF	±5%	CL05B271JB5NNNN □	
		33nF	±5%	CL05B333J05NNNN □				270pF	±10%	CL05B271KB5NNNN □	
		33nF	±10%	CL05B333K05NNNN □				300pF	±10%	CL05B301KB5NNNN □	
		33nF	±20%	CL05B333MO5NNNN □				320pF	±10%	CL05B321KB5NNNN □	
		39nF	±10%	CL05B393K05NNNN □				330pF	±5%	CL05B331JB5NNNN □	
		47nF	±5%	CL05B473J05NNNN □				330pF	±10%	CL05B331KB5NNNN □	
		47nF	±10%	CL05B473K05NNNN □				360pF	±10%	CL05B361KB5NNNN □	

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (X7R)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.55mm	50Vdc	390pF	±5%	CL05B391JB5NNN□		0.90mm	10Vdc	100nF	±10%	CL10B104KP8NNN□	
		390pF	±10%	CL05B391KB5NNN□				150nF	±10%	CL10B154KP8NNN□	
		470pF	±5%	CL05B471JB5NNN□				220nF	±5%	CL10B224JP8NNN□	
		470pF	±10%	CL05B471KB5NNN□				220nF	±10%	CL10B224KP8NNN□	
		510pF	±10%	CL05B511KB5NNN□				330nF	±10%	CL10B334KP8NNN□	
		560pF	±5%	CL05B561JB5NNN□				470nF	±10%	CL10B474KP8NNN□	
		560pF	±10%	CL05B561KB5NNN□				1.0uF	±10%	CL10B105KP8NNN□	
		620pF	±10%	CL05B621KB5NNN□				2.2uF	±10%	CL10B225KP8NNN□	Ref.
		680pF	±5%	CL05B681JB5NNN□			16Vdc	470pF	±10%	CL10B471KO8NNN□	
		680pF	±10%	CL05B681KB5NNN□				820pF	±10%	CL10B821KO8NNN□	
		750pF	±10%	CL05B751KB5NNN□				1.0nF	±10%	CL10B102KO8NNN□	
		820pF	±10%	CL05B821KB5NNN□				2.2nF	±10%	CL10B222KO8NNN□	
		1.0nF	±5%	CL05B102JB5NNN□				3.3nF	±10%	CL10B332KO8NNN□	
		1.0nF	±10%	CL05B102KB5NNN□				3.9nF	±10%	CL10B392KO8NNN□	
		1.2nF	±5%	CL05B122JB5NNN□				10nF	±10%	CL10B103KO8NNN□	
		1.2nF	±10%	CL05B122KB5NNN□				15nF	±10%	CL10B153KO8NNN□	
		1.5nF	±5%	CL05B152JB5NNN□				16nF	±10%	CL10B163KO8NNN□	
		1.5nF	±10%	CL05B152KB5NNN□				18nF	±10%	CL10B183KO8NNN□	
		1.8nF	±10%	CL05B182KB5NNN□				22nF	±10%	CL10B223KO8NNN□	
		2.0nF	±10%	CL05B202KB5NNN□				27nF	±10%	CL10B273KO8NNN□	
		2.2nF	±5%	CL05B222JB5NNN□				33nF	±10%	CL10B333KO8NNN□	
		2.2nF	±10%	CL05B222KB5NNN□				39nF	±10%	CL10B393KO8NNN□	
		2.4nF	±10%	CL05B242KB5NNN□				47nF	±10%	CL10B473KO8NNN□	
		2.7nF	±10%	CL05B272KB5NNN□				56nF	±10%	CL10B563KO8NNN□	
		3.0nF	±10%	CL05B302KB5NNN□				68nF	±10%	CL10B683KO8NNN□	
		3.3nF	±5%	CL05B332JB5NNN□				68nF	±20%	CL10B683MO8NNN□	
		3.3nF	±10%	CL05B332KB5NNN□				75nF	±10%	CL10B753KO8NNN□	
		3.9nF	±5%	CL05B392JB5NNN□				82nF	±10%	CL10B823KO8NNN□	
		3.9nF	±10%	CL05B392KB5NNN□				100nF	±5%	CL10B104JO8NNN□	
		4.7nF	±5%	CL05B472JB5NNN□				100nF	±10%	CL10B104K08NNN□	
		4.7nF	±10%	CL05B472KB5NNN□				120nF	±10%	CL10B124K08NNN□	
		4.7nF	±20%	CL05B472MB5NNN□				150nF	±10%	CL10B154K08NNN□	
		5.6nF	±10%	CL05B562KB5NNN□				180nF	±10%	CL10B184K08NNN□	
		6.8nF	±5%	CL05B682JB5NNN□				220nF	±5%	CL10B224JO8NNN□	
		6.8nF	±10%	CL05B682KB5NNN□				220nF	±10%	CL10B224K08NNN□	
		8.2nF	±10%	CL05B822KB5NNN□				220nF	±20%	CL10B224MO8NNN□	
		10nF	±5%	CL05B103JB5NNN□				330nF	±10%	CL10B334JO8NNN□	
		10nF	±10%	CL05B103KB5NNN□				470nF	±10%	CL10B474JO8NNN□	
		10nF	±20%	CL05B103MB5NNN□				470nF	±20%	CL10B474MO8NNN□	
		15nF	±10%	CL05B153KB5NNN□				680nF	±10%	CL10B684K08NNN□	
		22nF	±10%	CL05B223KB5NNN□				1.0uF	±10%	CL10B105K08NNN□	
	25Vdc	220pF	±10%	CL10B221KA8NNN□		25Vdc	25Vdc	390pF	±10%	CL10B391KA8NNN□	
		390pF	±10%	CL10B471KA8NNN□				470pF	±10%	CL10B471KA8NNN□	
		470pF	±5%	CL10B102JA8NNN□				1.0nF	±5%	CL10B102KA8NNN□	
		1.0nF	±10%	CL10B102KA8NNN□				2.2nF	±10%	CL10B222KA8NNN□	
		2.2nF	±10%	CL10B222KA8NNN□				4.7nF	±10%	CL10B472KA8NNN□	
		4.7nF	±10%	CL10B472KA8NNN□				5.6nF	±10%	CL10B562KA8NNN□	
		5.6nF	±10%	CL10B562KA8NNN□				6.8nF	±10%	CL10B682KA8NNN□	
		6.8nF	±10%	CL10B682KA8NNN□				8.2nF	±10%	CL10B822KA8NNN□	
		8.2nF	±10%	CL10B822KA8NNN□				10nF	±10%	CL10B103KA8NNN□	
		10nF	±10%	CL10B103KA8NNN□				12nF	±10%	CL10B123KA8NNN□	

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	6.3Vdc	4.7nF	±10%	CL10B472KQ8NNN□	
		470nF	±10%	CL10B474KQ8NNN□	
		680nF	±10%	CL10B684KQ8NNN□	
		820nF	±10%	CL10B824KQ8NNN□	
		1.0uF	±10%	CL10B105KQ8NNN□	
		1.0uF	±20%	CL10B105MQ8NNN□	
		2.2uF	±10%	CL10B225KQ8NNN□	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Standard & High Capacitors

Product Line Up (X7R)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	25Vdc	15nF	±5%	CL10B153JA8NNN□		0.90mm	50Vdc	1.4nF	±5%	CL10B142JB8NNN□	
		15nF	±10%	CL10B153KA8NNN□				1.5nF	±5%	CL10B152JB8NNN□	
		18nF	±10%	CL10B183KA8NNN□				1.5nF	±10%	CL10B152KB8NNN□	
		18nF	±20%	CL10B183MA8NNN□				1.8nF	±5%	CL10B182JB8NNN□	
		22nF	±5%	CL10B223JA8NNN□				1.8nF	±10%	CL10B182KB8NNN□	
		22nF	±10%	CL10B223KA8NNN□				2.0nF	±10%	CL10B202KB8NNN□	
		27nF	±10%	CL10B273KA8NNN□				2.2nF	±5%	CL10B222JB8NNN□	
		33nF	±5%	CL10B333JA8NNN□				2.2nF	±10%	CL10B222KB8NNN□	
		33nF	±10%	CL10B333KA8NNN□				2.2nF	±20%	CL10B222MB8NNN□	
		39nF	±10%	CL10B393KA8NNN□				2.4nF	±10%	CL10B242KB8NNN□	
		47nF	±10%	CL10B473KA8NNN□				2.7nF	±5%	CL10B272JB8NNN□	
		56nF	±5%	CL10B563JA8NNN□				2.7nF	±10%	CL10B272KB8NNN□	
		56nF	±10%	CL10B563KA8NNN□				2.9nF	±10%	CL10B292KB8NNN□	
		68nF	±10%	CL10B683KA8NNN□				3.0nF	±10%	CL10B302KB8NNN□	
		82nF	±10%	CL10B823KA8NNN□				3.0nF	±20%	CL10B302MB8NNN□	
		100nF	±5%	CL10B104JA8NNN□				3.3nF	±5%	CL10B332JB8NNN□	
		100nF	±10%	CL10B104KA8NNN□				3.3nF	±10%	CL10B332KB8NNN□	
		100nF	±20%	CL10B104MA8NNN□				3.3nF	±20%	CL10B332MB8NNN□	
		150nF	±10%	CL10B154KA8NNN□				3.6nF	±5%	CL10B362JB8NNN□	
		220nF	±10%	CL10B224KA8NNN□				3.6nF	±10%	CL10B362KB8NNN□	
		470nF	±10%	CL10B474KA8NNN□				3.9nF	±10%	CL10B392KB8NNN□	
		1.0uF	±10%	CL10B105KA8NNN□				4.7nF	±5%	CL10B472JB8NNN□	
50Vdc	50Vdc	100pF	±10%	CL10B101KB8NNN□				4.7nF	±10%	CL10B472KB8NNN□	
		120pF	±10%	CL10B121KB8NNN□				4.7nF	±20%	CL10B472MB8NNN□	
		150pF	±10%	CL10B151KB8NNN□				5.1nF	±10%	CL10B512KB8NNN□	
		180pF	±10%	CL10B181KB8NNN□				5.6nF	±5%	CL10B562JB8NNN□	
		200pF	±10%	CL10B201KB8NNN□				5.6nF	±10%	CL10B562KB8NNN□	
		220pF	±5%	CL10B221JB8NNN□				5.6nF	±20%	CL10B562MB8NNN□	
		220pF	±10%	CL10B221KB8NNN□				6.2nF	±5%	CL10B622JB8NNN□	
		270pF	±%	CL10B271JB8NNN□				6.2nF	±10%	CL10B622KB8NNN□	
		270pF	±10%	CL10B271KB8NNN□				6.8nF	±5%	CL10B682JB8NNN□	
		300pF	±10%	CL10B301KB8NNN□				6.8nF	±10%	CL10B682KB8NNN□	
		330pF	±5%	CL10B331JB8NNN□				6.8nF	±20%	CL10B682MB8NNN□	
		330pF	±10%	CL10B331KB8NNN□				7.5nF	±5%	CL10B752JB8NNN□	
		360pF	±10%	CL10B361KB8NNN□				8.2nF	±5%	CL10B822JB8NNN□	
		390pF	±10%	CL10B391KB8NNN□				8.2nF	±10%	CL10B822KB8NNN□	
		430pF	±10%	CL10B431KB8NNN□				9.1nF	±5%	CL10B912JB8NNN□	
		470pF	±5%	CL10B471JB8NNN□				10nF	±5%	CL10B103JB8NNN□	
		470pF	±10%	CL10B471KB8NNN□				10nF	±10%	CL10B103KB8NNN□	
		500pF	±10%	CL10B501KB8NNN□				10nF	±20%	CL10B103MB8NNN□	
		510pF	±10%	CL10B511KB8NNN□				12nF	±5%	CL10B123JB8NNN□	
		560pF	±5%	CL10B561JB8NNN□				12nF	±10%	CL10B123KB8NNN□	
		560pF	±10%	CL10B561KB8NNN□				15nF	±5%	CL10B153JB8NNN□	
		620pF	±5%	CL10B621JB8NNN□				15nF	±10%	CL10B153KB8NNN□	
		680pF	±5%	CL10B681JB8NNN□				15nF	±20%	CL10B153MB8NNN□	
		680pF	±10%	CL10B681KB8NNN□				18nF	±5%	CL10B183JB8NNN□	
		750pF	±10%	CL10B751KB8NNN□				18nF	±10%	CL10B183KB8NNN□	
		820pF	±5%	CL10B821JB8NNN□				20nF	±10%	CL10B203KB8NNN□	
		820pF	±10%	CL10B821KB8NNN□				22nF	±5%	CL10B223JB8NNN□	
		910pF	±5%	CL10B911JB8NNN□				22nF	±10%	CL10B223KB8NNN□	
		1.0nF	±10%	CL10B102KB8NNN□				22nF	±20%	CL10B223MB8NNN□	
		1.0nF	±20%	CL10B102MB8NNN□				27nF	±10%	CL10B273KB8NNN□	
		1.2nF	±5%	CL10B122JB8NNN□				33nF	±5%	CL10B333JB8NNN□	
		1.2nF	±10%	CL10B122KB8NNN□				33nF	±10%	CL10B333KB8NNN□	

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Product Line Up (X7R)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	50Vdc	39nF	±5%	CL10B393JB8NNN□		0.75mm	25Vdc	68nF	±10%	CL21B683KAANNN□	
		39nF	±10%	CL10B393KB8NNN□				18pF	±5%	CL21B180JBANNN□	
		47nF	±5%	CL10B473JB8NNN□				22pF	±5%	CL21B220JBANNN□	
		47nF	±10%	CL10B473KB8NNN□				56pF	±5%	CL21B560JBANNN□	
		47nF	±20%	CL10B473MB8NNN□				100pF	±5%	CL21B101KBANNN□	
		56nF	±5%	CL10B563JB8NNN□				100pF	±10%	CL21B101KBANNN□	
		56nF	±10%	CL10B563KB8NNN□				150pF	±10%	CL21B151KBANNN□	
		68nF	±5%	CL10B683JB8NNN□				180pF	±10%	CL21B181KBANNN□	
		68nF	±10%	CL10B683KB8NNN□				200pF	±10%	CL21B201KBANNN□	
		82nF	±5%	CL10B823JB8NNN□				220pF	±5%	CL21B221JBANNN□	
		82nF	±10%	CL10B823KB8NNN□				220pF	±10%	CL21B221KBANNN□	
		100nF	±5%	CL10B104JB8NNN□				270pF	±10%	CL21B271KBANNN□	
		100nF	±10%	CL10B104KB8NNN□				300pF	±10%	CL21B301KBANNN□	
		100nF	±20%	CL10B104MB8NNN□				330pF	±5%	CL21B331JBANNN□	
		220nF	±10%	CL10B224KB8NNN□				330pF	±10%	CL21B331KBANNN□	
		330nF	±10%	CL10B334KB8NNN□				360pF	±10%	CL21B361KBANNN□	
								390pF	±5%	CL21B391JBANNN□	
								390pF	±10%	CL21B391KBANNN□	
								470pF	±5%	CL21B471JBANNN□	
								470pF	±10%	CL21B471KBANNN□	
								500pF	±10%	CL21B501KBANNN□	

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.75mm	16Vdc	15nF	±10%	CL21B153KOANNN□	
		22nF	±10%	CL21B223KOANNN□	
		33nF	±10%	CL21B333KOANNN□	
		39nF	±10%	CL21B393KOANNN□	
		47nF	±10%	CL21B473KOANNN□	
		56nF	±10%	CL21B563KOANNN□	
		68nF	±10%	CL21B683KOANNN□	
		100nF	±5%	CL21B104JOANNN□	
		100nF	±10%	CL21B104KOANNN□	
		100nF	±20%	CL21B104MOANNN□	
		120nF	±5%	CL21B124JOANNN□	
		150nF	±10%	CL21B154KOANNN□	
		180nF	±10%	CL21B184KOANNN□	
		220pF	±20%	CL21B221MAANNN□	
		1.0nF	±10%	CL21B102KAANNN□	
		1.0nF	±20%	CL21B102MAANNN□	
	25Vdc	2.2nF	±10%	CL21B222KAANNN□	
		2.2nF	±20%	CL21B222MAANNN□	
		4.7nF	±10%	CL21B472KAANNN□	
		5.6nF	±10%	CL21B562KAANNN□	
		6.8nF	±10%	CL21B682KAANNN□	
		6.8nF	±20%	CL21B682MAANNN□	
		10nF	±10%	CL21B103KAANNN□	
		12nF	±10%	CL21B123KAANNN□	
		15nF	±5%	CL21B153JAANNN□	
		15nF	±10%	CL21B153KAANNN□	
		18nF	±10%	CL21B183KAANNN□	
		22nF	±10%	CL21B223KAANNN□	
		27nF	±10%	CL21B273KAANNN□	
		33nF	±10%	CL21B333KAANNN□	
		39nF	±10%	CL21B393KAANNN□	
		47nF	±10%	CL21B473KAANNN□	
		56nF	±10%	CL21B563KAANNN□	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Standard & High Capacitors

Product Line Up (X7R)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.75mm	50Vdc	3.9nF	±10%	CL21B392KBANNN □		0.95mm	50Vdc	2.7nF	±10%	CL21B272KBCNNN □	
		4.7nF	±5%	CL21B472JBANNN □				3.3nF	±10%	CL21B332KBCNNN □	
		4.7nF	±10%	CL21B472KBANNN □				4.7nF	±5%	CL21B472JBCNNN □	
		5.0nF	±10%	CL21B502KBANNN □				6.8nF	±10%	CL21B682KBCNNN □	
		5.1nF	±10%	CL21B512KBANNN □				10nF	±5%	CL21B103JBCNNN □	
		5.6nF	±5%	CL21B562JBANNN □				10nF	±10%	CL21B103KBCNNN □	
		5.6nF	±10%	CL21B562KBANNN □				18nF	±5%	CL21B183JBCNNN □	
		6.8nF	±5%	CL21B682JBANNN □				22nF	±10%	CL21B223KBCNNN □	
		6.8nF	±10%	CL21B682KBANNN □				24nF	±5%	CL21B243JBCNNN □	
		7.5nF	±10%	CL21B752KBANNN □				33nF	±5%	CL21B333JBCNNN □	
		8.2nF	±5%	CL21B822JBANNN □				39nF	±5%	CL21B393JBCNNN □	
		8.2nF	±10%	CL21B822KBANNN □				39nF	±10%	CL21B393KBCNNN □	
		9.1nF	±10%	CL21B912KBANNN □				47nF	±5%	CL21B473JBCNNN □	
		10nF	±5%	CL21B103JBANNN □				47nF	±10%	CL21B473KBCNNN □	
		10nF	±10%	CL21B103KBANNN □				47nF	±20%	CL21B473MBCNNN □	
		10nF	±20%	CL21B103MBANNN □				51nF	±10%	CL21B513KBCNNN □	
		12nF	±5%	CL21B123JBANNN □				56nF	±5%	CL21B563JBCNNN □	
		12nF	±10%	CL21B123KBANNN □				56nF	±10%	CL21B563KBCNNN □	
		12nF	±20%	CL21B123MBANNN □				68nF	±5%	CL21B683JBCNNN □	
		15nF	±5%	CL21B153JBANNN □				68nF	±10%	CL21B683KBCNNN □	
		15nF	±10%	CL21B153KBANNN □				82nF	±5%	CL21B823JBCNNN □	
		15nF	±20%	CL21B153MBANNN □				82nF	±10%	CL21B823KBCNNN □	
		18nF	±10%	CL21B183KBANNN □				100nF	±5%	CL21B104JBCNNN □	
		20nF	±10%	CL21B203KBANNN □				100nF	±10%	CL21B104KBCNNN □	
		22nF	±5%	CL21B223JBANNN □				100nF	±20%	CL21B104MBCNNN □	
		22nF	±10%	CL21B223KBANNN □		1.35mm	6.3Vdc	1.0uF	±10%	CL21B105KQFNNN □	
		27nF	±5%	CL21B273JBANNN □				2.2uF	±5%	CL21B225JQFNNN □	
		27nF	±10%	CL21B273KBANNN □				2.2uF	±10%	CL21B225KQFNNN □	
		33nF	±5%	CL21B333JBANNN □				3.3uF	±10%	CL21B335KQFNNN □	
		33nF	±10%	CL21B333KBANNN □				3.3uF	±20%	CL21B335MQFNNN □	
		33nF	±20%	CL21B333MBANNN □				4.7uF	±10%	CL21B475KQFNNN □	Ref.
0.95mm	16Vdc	39nF	±5%	CL21B393JBANNN □		10Vdc	470nF	470nF	±10%	CL21B474KPFNNN □	
		39nF	±10%	CL21B393KBANNN □				680nF	±10%	CL21B684KPFNNN □	
		47nF	±10%	CL21B473KBANNN □				820nF	±10%	CL21B824KPFNNN □	
		150nF	±10%	CL21B154KOCNNN □				1.0uF	±5%	CL21B105JPFNNN □	
		220nF	±5%	CL21B224JOCNNN □				1.0uF	±10%	CL21B105KPFNNN □	
		220nF	±10%	CL21B224KOCNNN □				1.0uF	±20%	CL21B105MPFNNN □	
		220nF	±20%	CL21B224MOCNNN □				2.2uF	±10%	CL21B225KPFNNN □	
		270nF	±5%	CL21B274JOCNNN □				2.2uF	±20%	CL21B225MPFNNN □	
		270nF	±10%	CL21B274KOCNNN □				3.3uF	±10%	CL21B335KPFNNN □	
	25Vdc	330nF	±5%	CL21B334JOCNNN □				4.7uF	±10%	CL21B475KPFNNN □	Ref.
		330nF	±10%	CL21B334KOCNNN □		16Vdc	150nF	150nF	±10%	CL21B154KOFNNN □	
		1.0uF	±10%	CL21B105KOCNNN □				220nF	±10%	CL21B224KOFNNN □	
		47nF	±10%	CL21B473KACNNN □				330nF	±10%	CL21B334KOFNNN □	
		68nF	±10%	CL21B683KACNNN □				390nF	±10%	CL21B394KOFNNN □	
		82nF	±10%	CL21B823KACNNN □				470nF	±5%	CL21B474JOFNNN □	
		100nF	±5%	CL21B104JACNNN □				470nF	±10%	CL21B474KOFNNN □	
		100nF	±10%	CL21B104KACNNN □				470nF	±20%	CL21B474MOFNNN □	
		100nF	±20%	CL21B104MACNNN □				680nF	±5%	CL21B684JOFNNN □	
		120nF	±5%	CL21B124JACNNN □				680nF	±10%	CL21B684KOFNNN □	
50Vdc	50Vdc	120nF	±10%	CL21B124KACNNN □				1.0uF	±10%	CL21B105KOFNNN □	
		120nF	±10%	CL21B124KACNNN □				2.2uF	±10%	CL21B225KOFNNN □	
		150nF	±10%	CL21B154KACNNN □				2.2uF	±20%	CL21B225MOFNNN □	
		1.0nF	±10%	CL21B102KBCNNN □				4.7uF	±10%	CL21B475KOFNNN □	Ref.
		2.2nF	±10%	CL21B222KBCNNN □							

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (X7R)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	
1.35mm	25Vdc	18nF	±10%	CL21B183KAFNNN □		1.00mm	16Vdc	270nF	±20%	CL31B274MOCNNN □		
		47nF	±10%	CL21B473KAFNNN □				330nF	±10%	CL31B334KOCNNN □		
		100nF	±10%	CL21B104KAFNNN □				330nF	±20%	CL31B334MOCNNN □		
		150nF	±10%	CL21B154KAFNNN □				390nF	±10%	CL31B394KOCNNN □		
		180nF	±10%	CL21B184KAFNNN □				470nF	±10%	CL31B474KOCNNN □		
		220nF	±5%	CL21B224JAFNNN □				560nF	±10%	CL31B564KOCNNN □		
		220nF	±10%	CL21B224KAFNNN □				680nF	±10%	CL31B684KOCNNN □		
		220nF	±20%	CL21B224MAFNNN □			25Vdc	4.7nF	±10%	CL31B472KACNNN □		
		270nF	±10%	CL21B274KAFNNN □				22nF	±10%	CL31B223KACNNN □		
		330nF	±10%	CL21B334KAFNNN □				47nF	±10%	CL31B473KACNNN □		
		390nF	±10%	CL21B394KAFNNN □				68nF	±10%	CL31B683KACNNN □		
		470nF	±5%	CL21B474JAFNNN □				100nF	±10%	CL31B104KACNNN □		
		470nF	±10%	CL21B474KAFNNN □				120nF	±10%	CL31B124KACNNN □		
		1.0uF	±10%	CL21B105KAFNNN □				150nF	±10%	CL31B154KACNNN □		
		1.5uF	±10%	CL21B155KAFNNN □				180nF	±10%	CL31B184KACNNN □		
		2.2uF	±10%	CL21B225KAFNNN □				220nF	±5%	CL31B224JACNNN □		
		4.7uF	±10%	CL21B475KAFNNN □	Ref. □			220nF	±10%	CL31B224KACNNN □		
50Vdc	35Vdc	1.0uF	±10%	CL21B105KLFNNN □		25Vdc	270nF	±10%	CL31B274KACNNN □			
	560pF	±10%	CL21B561KBFNNN □		330nF			±10%	CL31B334KACNNN □			
	47nF	±10%	CL21B473KBFNNN □		390nF			±10%	CL31B394KACNNN □			
	68nF	±5%	CL21B683JBFNNN □		120pF			±10%	CL31B121KBCNNN □			
	68nF	±10%	CL21B683KBFNNN □		180pF			±10%	CL31B181KBCNNN □			
	75nF	±10%	CL21B753KBFNNN □		220pF			±10%	CL31B221KBCNNN □			
	82nF	±10%	CL21B823KBFNNN □		270pF			±10%	CL31B271KBCNNN □			
	100nF	±5%	CL21B104KBFNNN □		330pF			±10%	CL31B331KBCNNN □			
	100nF	±10%	CL21B104KBFNNN □		390pF			±5%	CL31B391KBCNNN □			
	100nF	±20%	CL21B104MBFNNN □		390pF			±10%	CL31B391KBCNNN □			
	120nF	±10%	CL21B124KBFNNN □		470pF			±10%	CL31B471KBCNNN □			
	150nF	±10%	CL21B154KBFNNN □		560pF			±10%	CL31B561KBCNNN □			
	220nF	±5%	CL21B224JBFNNN □		680pF			±10%	CL31B681KBCNNN □			
	220nF	±10%	CL21B224KBFNNN □		820pF			±10%	CL31B821KBCNNN □			
	270nF	±10%	CL21B274KBFNNN □		1.0nF			±5%	CL31B102JBCNNN □			
	330nF	±10%	CL21B334KBFNNN □		1.0nF			±10%	CL31B102KBCNNN □			
	470nF	±10%	CL21B474KBFNNN □		1.0nF			±20%	CL31B102MBCNNN □			
	680nF	±10%	CL21B684KBFNNN □		1.2nF			±10%	CL31B122KBCNNN □			
	1.0uF	±10%	CL21B105KBFNNN □		1.5nF			±5%	CL31B152JBCNNN □			
	1.0uF	±20%	CL21B105MBFNNN □		1.5nF			±10%	CL31B152KBCNNN □			
1.40mm	6.3Vdc	4.7uF	±10%	CL21B475KQQNNN □	Ref. □			1.8nF	±10%	CL31B182KBCNNN □		
		10uF	±10%	CL21B106KQQNNN □				2.0nF	±10%	CL31B202KBCNNN □		
	10Vdc	4.7uF	±10%	CL21B475KPQNNN □	Ref. □			2.2nF	±10%	CL31B222KBCNNN □		
		10uF	±10%	CL21B106KPQNNN □				2.4nF	±10%	CL31B242KBCNNN □		
	16Vdc	10uF	±10%	CL21B106KOQNNN □				3.0nF	±10%	CL31B302KBCNNN □		
	1.0uF	±10%	CL21B106KOQNNN □		3.3nF			±5%	CL31B332JBCNNN □			
	1.0uF	±20%	CL21B106KOQNNN □		3.3nF			±10%	CL31B332KBCNNN □			
	1.8nF	±10%	CL21B182KBCNNN □		3.9nF			±5%	CL31B392JBCNNN □			

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.00mm	10Vdc	1.0uF	±10%	CL31B105KPCNNN □	
		1.2uF	±10%	CL31B125KPCNNN □	
	16Vdc	22nF	±5%	CL31B223JOCNNN □	
		100nF	±10%	CL31B104KOCNNN □	
		220nF	±10%	CL31B224KOCNNN □	
		270nF	±10%	CL31B274KOCNNN □	
		4.7nF	±10%	CL31B472KBCNNN □	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Standard & High Capacitors

Product Line Up (X7R)

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.00mm	50Vdc	10nF	±5%	CL31B103JBCNNN□		1.80mm	6.3Vdc	10uF	±10%	CL31B106KQHNNN□	
		10nF	±10%	CL31B103KBCNNN□				10uF	±20%	CL31B106MQHNNN□	
		10nF	±20%	CL31B103MBCNNN□				22uF	±10%	CL31B226KQHNNN□	
		15nF	±5%	CL31B153JBCNNN□			10Vdc	4.7uF	±10%	CL31B475KPHNNN□	
		15nF	±10%	CL31B153KBCNNN□				6.8uF	+80/-20%	CL31B685ZPHNNN□	
		18nF	±10%	CL31B183KBCNNN□				10uF	±10%	CL31B106KPHNNN□	
		22nF	±5%	CL31B223JBCNNN□				22uF	±10%	CL31B226KPHNNN□	
		22nF	±10%	CL31B223KBCNNN□				22uF	±20%	CL31B226MPHNNN□	
		27nF	±5%	CL31B273JBCNNN□		16Vdc	1.0uF	±20%	CL31B105MOHNNN□		
		27nF	±10%	CL31B273KBCNNN□			2.2uF	±10%	CL31B225KOHNNN□		
		33nF	±5%	CL31B333JBCNNN□			2.2uF	±20%	CL31B225MOHNNN□		
		33nF	±10%	CL31B333KBCNNN□			3.3uF	±10%	CL31B335KOHNNN□		
		39nF	±5%	CL31B393JBCNNN□			4.7uF	±10%	CL31B475KOHNNN□		
		39nF	±10%	CL31B393KBCNNN□			10uF	±10%	CL31B106KOHNNN□		
		47nF	±5%	CL31B473JBCNNN□			10uF	±20%	CL31B106MOHNNN□		
		47nF	±10%	CL31B473KBCNNN□			680nF	±10%	CL31B684KAHNNN□		
		56nF	±5%	CL31B563JBCNNN□			1.0uF	±5%	CL31B105JAHNNN□		
		56nF	±10%	CL31B563KBCNNN□			1.0uF	±10%	CL31B105KAHNNN□		
1.20mm	16Vdc	4.7uF	±10%	CL31B475KOELNNN□			1.0uF	±20%	CL31B105MAHNNN□		
		2.2uF	±10%	CL31B225KPENNNN□			1.2uF	±20%	CL31B125MAHNNN□		
1.25mm	10Vdc	2.2uF	±20%	CL31B225MPENNNN□			2.2uF	±10%	CL31B225KAHNNN□		
		25Vdc	1.0uF	± 10 %	CL31B105KAPLNNN□		2.2uF	±20%	CL31B225MAHNNN□		
1.40mm	10Vdc	1.5uF	±10%	CL31B155KPFNNN□		4.7uF	±10%	CL31B475KAHNNN□			
		2.2uF	±10%	CL31B225KPFNNN□		390nF	±10%	CL31B394KBHNNN□			
		2.2uF	±20%	CL31B225MPFNNN□		470nF	±5%	CL31B474JBHNNN□			
	16Vdc	820nF	±10%	CL31B824KOFNNN□		470nF	±10%	CL31B474KBHNNN□			
		1.0uF	±5%	CL31B105JOFNNN□		680nF	±10%	CL31B684KBHNNN□			
		1.0uF	±10%	CL31B105KOFNNN□		1.0uF	±10%	CL31B105KBHNNN□			
		1.0uF	±20%	CL31B105MOFNNN□		2.2uF	±10%	CL31B225KBHNNN□			
		1.5uF	±10%	CL31B155KOFNNN□		4.7uF	±10%	CL31B475KBHNNN□			
	25Vdc	10nF	±2%	CL31B103GAFNNN□		10uF	±10%	CL31B106KBHNNN□	Ref.		
		470nF	±5%	CL31B474JAFNNN□		4.7nF	±10%	CL31B472KBHNNN□			
		470nF	±10%	CL31B474KAFNNN□		390nF	±10%	CL31B394KBHNNN□			
		470nF	±20%	CL31B474MAFNNN□		470nF	±10%	CL31B474KBHNNN□			
		560nF	±10%	CL31B564KAFNNN□		680nF	±10%	CL31B684KBHNNN□			
1.80mm	50Vdc	100nF	±10%	CL31B104KBFNNN□		1.0uF	±10%	CL31B105KBHNNN□			
		180nF	±10%	CL31B184KBFNNN□		2.2uF	±10%	CL31B225KBHNNN□			
		200nF	±10%	CL31B204KBFNNN□		4.7uF	±10%	CL31B475KBHNNN□			
		220nF	±5%	CL31B224JBFNNN□		10uF	±10%	CL31B106KBHNNN□			
		220nF	±10%	CL31B224KBFNNN□		4.7nF	±10%	CL31B472KBHNNN□			
		220nF	±20%	CL31B224MBFNNN□		390nF	±10%	CL31B394KBHNNN□			
		270nF	±10%	CL31B274KBFNNN□		470nF	±5%	CL31B474JBHNNN□			
		330nF	±5%	CL31B334JBFNNN□		680nF	±10%	CL31B684KBHNNN□			
		330nF	±10%	CL31B334KBFNNN□		1.0uF	±10%	CL31B105KBHNNN□			
		3.3uF	±10%	CL31B335QHNNNN□		2.2uF	±10%	CL31B225KBHNNN□			
		6.8uF	±10%	CL31B685QHNNNN□		4.7uF	±10%	CL31B475KBHNNN□			

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (X7R)

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.45mm	16Vdc	100nF	±10%	CL32B104K0FNNN □		2.70mm	50Vdc	4.7uF	±10%	CL32B475KBJNNN □	
		220nF	±10%	CL32B224K0FNNN □				10uF	±10%	CL32B106KBJNNN □	
		470nF	±10%	CL32B474K0FNNN □							
		680nF	±10%	CL32B684K0FNNN □							
		1.0uF	±10%	CL32B105K0FNNN □							
		2.2uF	±10%	CL32B225K0FNNN □							
	25Vdc	220nF	±5%	CL32B224JAFNNN □							
		220nF	±10%	CL32B224KAFNNN □							
		470nF	±20%	CL32B474MAFNNN □							
		560nF	±5%	CL32B564JAFNNN □							
		1.0uF	±10%	CL32B105KAFNNN □							
	50Vdc	47nF	±10%	CL32B473KBFNNN □							
		100nF	±5%	CL32B104JBFNNN □							
		100nF	±10%	CL32B104KBFNNN □							
		100nF	±20%	CL32B104MBFNNN □							
		120nF	±5%	CL32B124JBFNNN □							
		120nF	±10%	CL32B124KBFNNN □							
		120nF	±20%	CL32B124MBFNNN □							
		150nF	±5%	CL32B154JBFNNN □							
		150nF	±10%	CL32B154KBFNNN □							
		220nF	±5%	CL32B224JBFNNN □							
		220nF	±10%	CL32B224KBFNNN □							
		270nF	±10%	CL32B274KBFNNN □							
		330nF	±5%	CL32B334JBFNNN □							
		330nF	±10%	CL32B334KBFNNN □							
		390nF	±10%	CL32B394KBFNNN □							
		470nF	±5%	CL32B474JBFNNN □							
		470nF	±10%	CL32B474KBFNNN □							
1.80mm	16Vdc	3.3uF	±10%	CL32B335KOHNNN □							
	25Vdc	330nF	±10%	CL32B334KAHNNN □							
		2.2uF	±10%	CL32B225KAHNNN □							
	50Vdc	820nF	±10%	CL32B824KBHNNN □							
		1.0uF	±10%	CL32B105KBHNNN □							
		1.0uF	±20%	CL32B105MBHNNN □							
2.00mm	16Vdc	10uF	±10%	CL32B106KOULNN □							
	25Vdc	10uF	±10%	CL32B106KAULNN □							
	35Vdc	4.7uF	±10%	CL32B475KLULNN □							
		10uF	±10%	CL32B106KLULNN □							
2.20mm	10Vdc	4.7uF	±10%	CL32B475KPINNN □							
		10uF	±10%	CL32B106KPINNN □							
	16Vdc	4.7uF	±10%	CL32B475KOINNN □							
	25Vdc	2.2uF	±10%	CL32B225KA1NNN □							
2.70mm	6.3Vdc	22uF	±20%	CL32B226MQJNNN □							
		47uF	±20%	CL32B476MQJNNN □	Ref.						
	10Vdc	22uF	±10%	CL32B226KPJNNN □							
		47uF	±20%	CL32B476MPJNNN □	Ref.						
	16Vdc	10uF	±10%	CL32B106KOJNNN □							
		22uF	±10%	CL32B226KOJNNN □							
		22uF	±20%	CL32B226MOJNNN □							
	25Vdc	3.3uF	±10%	CL32B335KAJNNN □							
		10uF	±10%	CL32B106KAJNNN □							
		22uF	±10%	CL32B226KAJNNN □							
	35Vdc	10uF	±10%	CL32B106KLJNNN □							
	50Vdc	2.2uF	±10%	CL32B225KBJNNN □							

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Low Profile Capacitors

Feature




- Decoupling and filtering application where the thickness is limited
- A range of low-profile products as thin as 0.11mm in 1005mm

Application

- Mobile phone
- Smart watch
- IC Package

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
05	0402	1.00±0.05	0.50±0.05	0.0975±0.0125	L	0.25±0.075
		1.00±0.10	0.50±0.05	0.19±0.03	X	0.25±0.10
		1.00±0.05	0.50±0.05	0.30±0.03	3	
10	0603	1.60±0.10	0.80±0.10	0.50+0.0/-0.10	5	
		1.60±0.10	0.80±0.10	0.60±0.10	6	0.30±0.20
		1.60±0.10	0.80±0.10	0.70±0.10	7	
21	0805	2.00±0.10	1.25±0.10	0.60±0.10	6	
		2.00±0.10	1.25±0.10	0.70±0.10	7	
		2.00±0.10	1.25±0.10	0.80±0.10	8	0.50+0.20/-0.30
		2.00±0.10	1.25±0.10	0.85±0.10	C	
		2.00±0.10	1.25±0.10	0.90±0.10	9	
		2.00±0.10	1.25±0.10	1.10±0.10	E	
31	1206	3.20±0.20	1.60±0.20	0.85±0.10	C	
		3.20±0.20	1.60±0.20	0.90±0.10	9	0.50±0.30
		3.20±0.20	1.60±0.20	1.10±0.10	E	
		3.20±0.20	1.60±0.20	1.15±0.10	M	
32	1210	3.20±0.30	2.50±0.20	0.85±0.10	C	
		3.20±0.30	2.50±0.20	0.90±0.10	9	
		3.20±0.30	2.50±0.20	1.15±0.10	M	0.60±0.30
		3.20±0.30	2.50±0.20	1.35±0.15	S	
		3.20±0.30	2.50±0.20	1.60±0.10	T	
		3.20±0.30	2.50±0.20	1.80±0.20	U	
		3.20±0.30	2.50±0.20	2.00±0.20	I	

Low Profile Capacitance Table (X5R)

Size inch (mm)	T max. (mm)	Rated Voltage (Vdc)	Capacitance(uF)								
			0.22	0.47	1.0	2.2	4.7	10	22	47	68
0402 (1005)	0.11	6.3									
	0.22	6.3									
	0.33	4.0									
		6.3						0.35 T max.			
0603 (1608)		4.0									
		6.3									
	0.50	10									
		16									
		25									
	0.60	6.3									
		6.3									
	0.80	10									
		16									
		10									
0805 (2012)	0.70	16									
		6.3									
	0.80	10									
		6.3									
	0.90	16									
		25									
	0.95	35									
		50									
	1.00	6.3									
		50									
	1.20	6.3							33uF		
1206 (3216)	0.95	6.3									
		10									
		16									
		25									
	1.00	35									
		50									
		100									
	1.20	16									
		10									
	1.25	16									
		25									

Low Profile Capacitors

Low Profile Capacitance Table (X5R)

Size inch (mm)	T max. (mm)	Rated Voltage (Vdc)	Capacitance(uF)								
			0.22	0.47	1.0	2.2	4.7	10	22	47	68
1210 (3225)	0.95	16									
	1.00	25									
	1.25	16									
	1.50	10									
		25					6.8uF				
	1.70	16									
		25									
	2.00	25									
		35									
	2.20	10									
		16									
		25									

Low Profile Capacitance Table (X6S)

Size inch (mm)	T max. (mm)	Rated Voltage (Vdc)	Capacitance(uF)								
			0.22	0.47	1.0	2.2	4.7	10	22	47	68
0402(1005)	0.33	6.3			X6S						
0805 (2012)	0.95	2.5							X6S		
		4.0						X6S			
		10						X6S			
1206(3216)	0.95	25					X6S				

Product Line Up (X5R)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.11mm	6.3Vdc	220nF	±20%	CL05A224MQXLHEC □	<small>Derating Ref.</small>
0.22mm	6.3Vdc	470nF	±20%	CL05A474MQXLNN □	<small>Derating Ref.</small>
		1.0uF	±20%	CL05A105MQXLNN □	<small>Derating Ref.</small>
0.33mm	4.0Vdc	2.2uF	±20%	CL05A225MR3LRN □	<small>Derating Ref.</small>
	6.3Vdc	1.0uF	±20%	CL05A105MQ3LRN □	<small>Derating</small>
		2.2uF	±20%	CL05A225MQ3LRN □	<small>Derating Ref.</small>
0.35mm	6.3Vdc	4.7uF	±20%	CL05A475MQ3LUN □	<small>Derating Ref.</small>

■ Size: 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.50mm	4.0Vdc	10uF	±20%	CL10A106MR5LQN □	<small>Derating Ref.</small>
	6.3Vdc	2.2uF	±10%	CL10A225KQ5LNN □	
		4.7uF	±10%	CL10A475KQ5LNN □	
		4.7uF	±20%	CL10A475MQ5LNN □	
		10uF	±20%	CL10A106MQ5LRN □	<small>Derating Ref.</small>
	10Vdc	1.0uF	±10%	CL10A105KP5LNN □	
		2.2uF	±10%	CL10A225KP5LNN □	
		4.7uF	±10%	CL10A475KP5LNN □	<small>Derating</small>
		4.7uF	±20%	CL10A475MP5LNN □	<small>Derating</small>
	16Vdc	1.0uF	±10%	CL10A105K05LNN □	
		2.2uF	±10%	CL10A225K05LNN □	<small>Derating</small>
		1.0uF	±10%	CL10A105KA5LNN □	<small>Derating</small>
		2.2uF	±10%	CL10A225KA5LNN □	<small>Derating</small>
0.60mm	6.3Vdc	4.7uF	±10%	CL10A475KQ5NNN □	
		4.7uF	±20%	CL10A475MQ5NNN □	
	6.3Vdc	22uF	±20%	CL10A226MQ7LUN □	<small>Derating</small>
		22uF	±20%	CL10A226MP7LUN □	<small>Derating</small>
0.80mm	6.3Vdc	22uF	±20%	CL10A226M07JZN □	<small>Derating</small>
		22uF	±20%	CL10A226M07JZN □	<small>Derating</small>

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.70mm	10Vdc	2.2uF	±10%	CL21A225KP6LNN □	
	16Vdc	1.0uF	±20%	CL21A105M06LNN □	
		2.2uF	±10%	CL21A225K06LNN □	
0.80mm	6.3Vdc	10uF	±10%	CL21A106KQ7LQN □	
	6.3Vdc	47uF	±20%	CL21A476MQ7FRN □	<small>Derating</small>
		47uF	±20%	CL21A476MQ7LRN □	<small>Derating</small>
		10uF	±10%	CL21A106KP7LQN □	<small>Derating</small>
	9.0mm	47uF	±20%	CL21A476MQ8LRN □	<small>Derating</small>
		22uF	±20%	CL21A226MRCLRN □	<small>Derating</small>
		47uF	±20%	CL21A476MRCLRP □	<small>Derating</small>
	6.3Vdc	1.0uF	±10%	CL21A105KQCLNN □	
		1.0uF	±10%	CL21A105KQCNNN □	
		4.7uF	±10%	CL21A475KQCLNN □	
		4.7uF	±20%	CL21A475MQCLNN □	
		10uF	±10%	CL21A106KQCLNN □	
		10uF	±10%	CL21A106KQCLRN □	
		10uF	±20%	CL21A106MQCLNN □	
		22uF	±10%	CL21A226KQCLRN □	<small>Derating</small>
		22uF	±20%	CL21A226MQCLQN □	<small>Derating</small>
		22uF	±20%	CL21A226MQCLRN □	<small>Derating</small>
	10Vdc	47uF	±20%	CL21A476MQCLRN □	<small>Derating</small>
		2.2uF	±10%	CL21A225KPCLNN □	
		4.7uF	±10%	CL21A475KPCLNN □	
		4.7uF	±20%	CL21A475MPCLNN □	
		10uF	±10%	CL21A106KPCLNN □	<small>Derating</small>
	16Vdc	10uF	±10%	CL21A106KPCLQN □	<small>Derating</small>
		10uF	±20%	CL21A106MPCLNN □	<small>Derating</small>
		10uF	±20%	CL21A106MPCLQN □	<small>Derating</small>
		22uF	±10%	CL21A226KPCLRN □	<small>Derating</small>
		22uF	±20%	CL21A226MPCLRN □	<small>Derating</small>
	25Vdc	22uF	±20%	CL21A226ZPCLRN □	<small>Derating</small>
		2.2uF	±10%	CL21A225KOCLNN □	
		4.7uF	±10%	CL21A475KOCLNN □	
		4.7uF	±20%	CL21A475KOCLRN □	
		10uF	±10%	CL21A106KOCLNN □	<small>Derating</small>
		10uF	±10%	CL21A106KOCLRN □	<small>Derating</small>
		10uF	±20%	CL21A106KOCLSN □	<small>Derating</small>
	35Vdc	22uF	±20%	CL21A226MOCLRN □	<small>Derating</small>
		1.0uF	±10%	CL21A105KACLNN □	
		1.0uF	±10%	CL21A105KACNNN □	
		2.2uF	±10%	CL21A225KACLNN □	<small>Derating</small>
		4.7uF	±10%	CL21A475KACLNN □	<small>Derating</small>
	50Vdc	10uF	±10%	CL21A106KACLNN □	<small>Derating</small>
		4.7uF	±10%	CL21A475KACLQN □	<small>Derating</small>
		1.0uF	±10%	CL21A105KBCLNN □	
1.00mm	6.3Vdc	33uF	±20%	CL21A336MQ9LRN □	<small>Derating</small>
	6.3Vdc	47uF	±20%	CL21A476MQ9LRN □	<small>Derating</small>
		2.2uF	±10%	CL21A225KB9LNN □	<small>Derating</small>
	50Vdc	33uF	±20%	CL21A336MQELRN □	<small>Derating</small>
1.20mm	6.3Vdc	33uF	±20%	CL21A336MQELRN □	<small>Derating</small>

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Low Profile Capacitors

Product Line Up (X5R)

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	6.3Vdc	10uF	±20%	CL31A106MQCLNN □	
		22uF	±10%	CL31A226KQCLNN □	Derating
		22uF	±20%	CL31A226MQCLNN □	Derating
	10Vdc	10uF	±10%	CL31A106KPCLNN □	
		10uF	±20%	CL31A106MPCLNN □	
	16Vdc	2.2uF	±10%	CL31A225KOCLNN □	
		4.7uF	±10%	CL31A475KOCLNN □	
		4.7uF	±20%	CL31A475MOCLNN □	
		10uF	±10%	CL31A106KOCLNN □	
		22uF	±10%	CL31A226KOCLNN □	Derating
		22uF	±20%	CL31A226MOCLNN □	Derating
	25Vdc	4.7uF	±10%	CL31A475KACLNN □	
		10uF	±10%	CL31A106KACLNN □	Derating
1.00mm	35Vdc	4.7uF	±10%	CL31A475KL9LNN □	Derating
	50Vdc	1.0uF	±10%	CL31A105KB9LNN □	
		2.2uF	±10%	CL31A225KB9LNN □	
		4.7uF	±10%	CL31A475KB9LNN □	Derating
1.20mm	16Vdc	4.7uF	±10%	CL31A475KOELNN □	
1.25mm	10Vdc	10uF	±10%	CL31A106KPPLNN □	
		10uF	±20%	CL31A106MPPLNN □	
	16Vdc	4.7uF	±10%	CL31A475KOPLNN □	
		4.7uF	±20%	CL31A475MOPLNN □	
	25Vdc	1.0uF	±10%	CL31A105KAPLNN □	
		2.2uF	±10%	CL31A225KAPLNN □	
		4.7uF	±10%	CL31A475KAPLNN □	

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	16Vdc	10uF	±10%	CL32A106KOCLNN □	
		22uF	±20%	CL32A226MOCLNN □	Derating
1.00mm	25Vdc	10uF	±10%	CL32A106KA9LNN □	
1.25mm	16Vdc	10uF	±10%	CL32A106KOMLNN □	
1.50mm	10Vdc	22uF	±10%	CL32A226KPSLNN □	
		22uF	±20%	CL32A226MPSLNN □	
	25Vdc	6.8uF	±10%	CL32A685KASLNN □	
1.70mm	16Vdc	22uF	±10%	CL32A226KOTFNN □	Derating
		22uF	±20%	CL32A226MOTLNN □	Derating
	25Vdc	10uF	±10%	CL32A106KATLNN □	
		10uF	±20%	CL32A106MATLNN □	
2.00mm	25Vdc	4.7uF	±10%	CL32A475KAULNN □	
		10uF	±10%	CL32A106KAULNN □	
	35Vdc	4.7uF	±10%	CL32A475KLULNN □	
		10uF	±10%	CL32A106KLULNN □	
		10uF	±20%	CL32A106MLULNN □	
2.20mm	10Vdc	10uF	±10%	CL32A106KPINNN □	
	16Vdc	10uF	±10%	CL32A106KOILNN □	
	25Vdc	2.2uF	±20%	CL32A225MAINNN □	
		4.7uF	±10%	CL32A475KAINNN □	
		10uF	±10%	CL32A106KAILNN □	
		10uF	±20%	CL32A106MAILNN □	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (X6S)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.33mm	6.3Vdc	1.0uF	±20%	CL05X105MQ3LNN □	Derating

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	2.5Vdc	22uF	±20%	CL21X226MSCLRN □	Derating
	4.0Vdc	10uF	±10%	CL21X106KRCLRN □	Derating
	10Vdc	10uF	±10%	CL21X106KPCLRN □	Derating

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	25Vdc	4.7uF	±10%	CL31X475KACLNN □	

Super Small Size Capacitors

Feature





- Small size chip
- 02 and 03 Series (High - Q) MLCC shows very low ESR value
- 02 and 03 Series are suited to only reflow soldering
- 02 and 03 Series are suited to miniature RF module, portable equipment and high frequency circuit

Application

- DC – DC Converter
- Mobile phone, Tablet devices
- PC (Laptop, Desktop)
- HDD / SSD Board

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
02	01005	0.40±0.02	0.20±0.02	0.20±0.02	2	0.10±0.03
03	0201	0.60±0.03	0.30±0.03	0.30±0.03	3	0.15±0.05

Super Small Size Capacitors

Super Small Size Capacitance Table (C0G)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance(pF)							
		0.2	0.5	1.0	10	22	47	100	
01005 (0402)	6.3								
	16								
	25					27pF			
0201 (0603)	6.3								
	25								
	50								

Super Small Size Capacitance Table (X5R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance														uF		
		pF				nF										1.0	2.2	
220	330	470	680	1.0	2.2	3.3	4.7	10	15	22	33	47	68	100	220	470	1.0	2.2
01005 (0402)	4.0																	
	6.3																	
	10																	
0201 (0603)	4.0																	
	6.3																	
	10																	
	16																	
	25																	

Super Small Size Capacitance Table (X7R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance														
		pF					nF									
100	220	330	470	680	1.0	2.2	3.3	4.7	6.8	10						
01005(0402)	10															
0201 (0603)	6.3															
	10															
	16															
	25															
	50															

Super Small Size Capacitance Table (X6S)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance(nF)							
		2.2	3.3	4.7	6.8	10	22	47	100
01005(0402)	2.5								
0201(0603)	4.0								
0201(0603)	6.3								

Product Line Up (COG)

■ Size : 0.40 X 0.20mm (inch : 01005)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.22mm	16Vdc	0.2pF	±0.1pF	CL02C0R2B02GNN□	0.22mm	16Vdc	5.1pF	±0.25pF	CL02C5R1C02GNN□
		0.3pF	±0.1pF	CL02C0R3B02GNN□			5.2pF	±0.1pF	CL02C5R2B02GNN□
		0.4pF	±0.1pF	CL02C0R4B02GNN□			5.3pF	±0.1pF	CL02C5R3B02GNN□
		0.5pF	±0.1pF	CL02C0R5B02GNN□			5.4pF	±0.1pF	CL02C5R4B02GNN□
		0.6pF	±0.1pF	CL02C0R6B02GNN□			5.5pF	±0.1pF	CL02C5R5B02GNN□
		0.7pF	±0.1pF	CL02C0R7B02GNN□			5.6pF	±0.1pF	CL02C5R6B02GNN□
		0.8pF	±0.1pF	CL02C0R8B02GNN□			5.6pF	±0.25pF	CL02C5R6C02GNN□
		0.9pF	±0.1pF	CL02C0R9B02GNN□			5.7pF	±0.1pF	CL02C5R7B02GNN□
		1.0pF	±0.1pF	CL02C010B02GNN□			5.7pF	±0.25pF	CL02C5R7C02GNN□
		1.1pF	±0.1pF	CL02C1R1B02GNN□			5.8pF	±0.1pF	CL02C5R8B02GNN□
		1.2pF	±0.1pF	CL02C1R2B02GNN□			5.9pF	±0.1pF	CL02C5R9B02GNN□
		1.3pF	±0.1pF	CL02C1R3B02GNN□			6.0pF	±0.1pF	CL02C060B02GNN□
		1.4pF	±0.1pF	CL02C1R4B02GNN□			6.1pF	±0.1pF	CL02C6R1B02GNN□
		1.5pF	±0.1pF	CL02C1R5B02GNN□			6.2pF	±0.1pF	CL02C6R2B02GNN□
		1.6pF	±0.1pF	CL02C1R6B02GNN□			6.3pF	±0.1pF	CL02C6R3B02GNN□
		1.7pF	±0.1pF	CL02C1R7B02GNN□			6.4pF	±0.1pF	CL02C6R4B02GNN□
		1.8pF	±0.1pF	CL02C1R8B02GNN□			6.5pF	±0.1pF	CL02C6R5B02GNN□
		1.9pF	±0.1pF	CL02C1R9B02GNN□			6.6pF	±0.1pF	CL02C6R6B02GNN□
		2.0pF	±0.1pF	CL02C20B02GNN□			6.7pF	±0.1pF	CL02C6R7B02GNN□
		2.1pF	±0.1pF	CL02C2R1B02GNN□			6.8pF	±0.1pF	CL02C6R8B02GNN□
		2.2pF	±0.1pF	CL02C2R2B02GNN□			6.9pF	±0.1pF	CL02C6R9B02GNN□
		2.3pF	±0.1pF	CL02C2R3B02GNN□			7.0pF	±0.1pF	CL02C070B02GNN□
		2.4pF	±0.1pF	CL02C2R4B02GNN□			7.1pF	±0.1pF	CL02C7R1B02GNN□
		2.5pF	±0.1pF	CL02C2R5B02GNN□			7.2pF	±0.1pF	CL02C7R2B02GNN□
		2.6pF	±0.1pF	CL02C2R6B02GNN□			7.3pF	±0.1pF	CL02C7R3B02GNN□
		2.7pF	±0.1pF	CL02C2R7B02GNN□			7.4pF	±0.1pF	CL02C7R4B02GNN□
		2.8pF	±0.1pF	CL02C2R8B02GNN□			7.5pF	±0.1pF	CL02C7R5B02GNN□
		2.9pF	±0.1pF	CL02C2R9B02GNN□			7.6pF	±0.1pF	CL02C7R6B02GNN□
		3.0pF	±0.1pF	CL02C30B02GNN□			7.7pF	±0.1pF	CL02C7R7B02GNN□
		3.1pF	±0.1pF	CL02C3R1B02GNN□			7.8pF	±0.1pF	CL02C7R8B02GNN□
		3.2pF	±0.1pF	CL02C3R2B02GNN□			7.9pF	±0.1pF	CL02C7R9B02GNN□
		3.3pF	±0.1pF	CL02C3R3B02GNN□			8.0pF	±0.1pF	CL02C080B02GNN□
		3.3pF	±0.25pF	CL02C3R3C02GNN□			8.0pF	±0.25pF	CL02C080C02GNN□
		3.4pF	±0.1pF	CL02C3R4B02GNN□			8.1pF	±0.1pF	CL02C8R1B02GNN□
		3.5pF	±0.1pF	CL02C3R5B02GNN□			8.2pF	±0.1pF	CL02C8R2B02GNN□
		3.5pF	±0.25pF	CL02C3R5C02GNN□			8.2pF	±0.25pF	CL02C8R2C02GNN□
		3.6pF	±0.1pF	CL02C3R6B02GNN□			8.3pF	±0.1pF	CL02C8R3B02GNN□
		3.7pF	±0.1pF	CL02C3R7B02GNN□			8.4pF	±0.1pF	CL02C8R4B02GNN□
		3.7pF	±0.25pF	CL02C3R7C02GNN□			8.4pF	±0.25pF	CL02C8R4C02GNN□
		3.8pF	±0.1pF	CL02C3R8B02GNN□			8.5pF	±0.1pF	CL02C8R5B02GNN□
		3.9pF	±0.1pF	CL02C3R9B02GNN□			8.6pF	±0.1pF	CL02C8R6B02GNN□
		4.0pF	±0.1pF	CL02C40B02GNN□			8.7pF	±0.1pF	CL02C8R7B02GNN□
		4.1pF	±0.1pF	CL02C4R1B02GNN□			8.8pF	±0.1pF	CL02C8R8B02GNN□
		4.2pF	±0.1pF	CL02C4R2B02GNN□			8.9pF	±0.1pF	CL02C8R9B02GNN□
		4.3pF	±0.1pF	CL02C4R3B02GNN□			9.0pF	±0.1pF	CL02C090B02GNN□
		4.4pF	±0.1pF	CL02C4R4B02GNN□			9.1pF	±0.1pF	CL02C9R1B02GNN□
		4.5pF	±0.1pF	CL02C4R5B02GNN□			9.2pF	±0.1pF	CL02C9R2B02GNN□
		4.6pF	±0.1pF	CL02C4R6B02GNN□			9.3pF	±0.1pF	CL02C9R3B02GNN□
		4.7pF	±0.1pF	CL02C4R7B02GNN□			9.4pF	±0.1pF	CL02C9R4B02GNN□
		4.8pF	±0.1pF	CL02C4R8B02GNN□			9.5pF	±0.1pF	CL02C9R5B02GNN□
		4.9pF	±0.1pF	CL02C4R9B02GNN□			9.5pF	±0.25pF	CL02C9R5C02GNN□
		5.0pF	±0.1pF	CL02C050B02GNN□			9.6pF	±0.1pF	CL02C9R6B02GNN□
		5.0pF	±0.25pF	CL02C050C02GNN□			9.7pF	±0.1pF	CL02C9R7B02GNN□
		5.1pF	±0.1pF	CL02C5R1B02GNN□			9.8pF	±0.1pF	CL02C9R8B02GNN□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Super Small Size Capacitors

Product Line Up (COG)

■ Size : 0.40 X 0.20mm (inch : 01005)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.22mm	16Vdc	9.9pF	±0.1pF	CL02C9R9B02GNN □
		10pF	±5%	CL02C100J02GNN □
		18pF	±2%	CL02C180G02GNN □
		22pF	±2%	CL02C220G02GNN □

■ Size : 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.33mm	16Vdc	33pF	±5%	CL03C330J03GNN □
		33pF	±5%	CL03C330J03GNNN □
	25Vdc	0.2pF	±0.1pF	CL03C0R2BA3GNN □
		0.2pF	±0.25pF	CL03C0R2CA3GNN □
		0.2pF	±0.03pF	CL03C0R2NA3GNN □
		0.3pF	±0.1pF	CL03C0R3BA3GNN □
		0.3pF	±0.25pF	CL03C0R3CA3GNN □
		0.3pF	±0.03pF	CL03C0R3NA3GNN □
		0.4pF	±0.1pF	CL03C0R4BA3GNN □
		0.4pF	±0.25pF	CL03C0R4CA3GNN □
		0.4pF	±0.03pF	CL03C0R4NA3GNN □
		0.5pF	±0.1pF	CL03C0R5BA3GNN □
		0.5pF	±0.25pF	CL03C0R5CA3GNN □
		0.5pF	±0.03pF	CL03C0R5NA3GNN □
		0.6pF	±0.1pF	CL03C0R6BA3GNN □
		0.6pF	±0.25pF	CL03C0R6CA3GNN □
		0.6pF	±0.03pF	CL03C0R6NA3GNN □
		0.7pF	±0.1pF	CL03C0R7BA3GNN □
		0.7pF	±0.03pF	CL03C0R7NA3GNN □
		0.75pF	±0.1pF	CL03C0R75BA3GNN □
		0.8pF	±0.1pF	CL03C0R8BA3GNN □
		0.8pF	±0.25pF	CL03C0R8CA3GNN □
		0.8pF	±0.03pF	CL03C0R8NA3GNN □
		0.9pF	±0.1pF	CL03C0R9BA3GNN □
		0.9pF	±0.25pF	CL03C0R9CA3GNN □
		0.9pF	±0.03pF	CL03C0R9NA3GNN □
		1.0pF	±0.1pF	CL03C010BA3GNN □
		1.0pF	±0.25pF	CL03C010CA3GNN □
		1.0pF	±0.03pF	CL03C010NA3GNN □
		1.1pF	±0.1pF	CL03C1R1BA3GNN □
		1.1pF	±0.03pF	CL03C1R1NA3GNN □
		1.2pF	±0.1pF	CL03C1R2BA3GNN □
		1.2pF	±0.25pF	CL03C1R2CA3GNN □
		1.2pF	±0.03pF	CL03C1R2NA3GNN □
		1.3pF	±0.1pF	CL03C1R3BA3GNN □
		1.3pF	±0.25pF	CL03C1R3CA3GNN □
		1.3pF	±0.03pF	CL03C1R3NA3GNN □
		1.4pF	±0.03pF	CL03C1R4NA3GNN □
		1.5pF	±0.1pF	CL03C1R5BA3GNN □
		1.5pF	±0.25pF	CL03C1R5CA3GNN □
		1.5pF	±0.03pF	CL03C1R5NA3GNN □
		1.6pF	±0.05pF	CL03C1R6AA3GNN □
		1.6pF	±0.1pF	CL03C1R6BA3GNN □
		1.6pF	±0.25pF	CL03C1R6CA3GNN □
		1.7pF	±0.05pF	CL03C1R7AA3GNN □

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.33mm	25Vdc	1.7pF	±0.1pF	CL03C1R7BA3GNN □
		1.7pF	±0.25pF	CL03C1R7CA3GNN □
		1.8pF	±0.05pF	CL03C1R8AA3GNN □
		1.8pF	±0.1pF	CL03C1R8BA3GNN □
		1.8pF	±0.25pF	CL03C1R8CA3GNN □
		1.9pF	±0.05pF	CL03C1R9AA3GNN □
		1.9pF	±0.1pF	CL03C1R9CA3GNN □
		1.9pF	±0.25pF	CL03C020AA3GNN □
		2.0pF	±0.05pF	CL03C020BA3GNN □
		2.0pF	±0.25pF	CL03C020CA3GNN □
		2.0pF	±0.1pF	CL03C2R0BA3GNN □
		2.1pF	±0.05pF	CL03C2R1AA3GNN □
		2.1pF	±0.1pF	CL03C2R1BA3GNN □
		2.2pF	±0.05pF	CL03C2R2AA3GNN □
		2.2pF	±0.1pF	CL03C2R2BA3GNN □
		2.2pF	±0.25pF	CL03C2R2CA3GNN □
		2.3pF	±0.05pF	CL03C2R3AA3GNN □
		2.3pF	±0.1pF	CL03C2R3BA3GNN □
		2.4pF	±0.05pF	CL03C2R4AA3GNN □
		2.4pF	±0.1pF	CL03C2R4BA3GNN □
		2.4pF	±0.25pF	CL03C2R4CA3GNN □
		2.5pF	±0.05pF	CL03C2R5AA3GNN □
		2.5pF	±0.1pF	CL03C2R5BA3GNN □
		2.6pF	±0.05pF	CL03C2R6AA3GNN □
		2.6pF	±0.1pF	CL03C2R6BA3GNN □
		2.7pF	±0.05pF	CL03C2R7AA3GNN □
		2.7pF	±0.1pF	CL03C2R7BA3GNN □
		2.7pF	±0.25pF	CL03C2R7CA3GNN □
		2.8pF	±0.05pF	CL03C2R8AA3GNN □
		2.8pF	±0.1pF	CL03C2R8BA3GNN □
		2.9pF	±0.05pF	CL03C2R9AA3GNN □
		2.9pF	±0.1pF	CL03C2R9BA3GNN □
		3.0pF	±0.05pF	CL03C030AA3GNN □
		3.0pF	±0.1pF	CL03C030BA3GNN □
		3.0pF	±0.25pF	CL03C030CA3GNN □
		3.1pF	±0.05pF	CL03C3R1AA3GNN □
		3.1pF	±0.1pF	CL03C3R1BA3GNN □
		3.2pF	±0.05pF	CL03C3R2AA3GNN □
		3.2pF	±0.1pF	CL03C3R2BA3GNN □
		3.2pF	±0.25pF	CL03C3R2CA3GNN □
		3.3pF	±0.05pF	CL03C3R3AA3GNN □
		3.3pF	±0.1pF	CL03C3R3BA3GNN □
		3.3pF	±0.25pF	CL03C3R3CA3GNN □
		3.4pF	±0.05pF	CL03C3R4AA3GNN □
		3.4pF	±0.1pF	CL03C3R4BA3GNN □
		3.4pF	±0.25pF	CL03C3R4CA3GNN □
		3.5pF	±0.05pF	CL03C3R5AA3GNN □
		3.6pF	±0.05pF	CL03C3R6AA3GNN □
		3.6pF	±0.1pF	CL03C3R6BA3GNN □
		3.6pF	±0.25pF	CL03C3R6CA3GNN □
		3.7pF	±0.05pF	CL03C3R7AA3GNN □
		3.8pF	±0.05pF	CL03C3R8AA3GNN □
		3.8pF	±0.1pF	CL03C3R8BA3GNN □

Product Line Up (COG)

■ Size : 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.33mm	25Vdc	3.8pF	±0.25pF	CL03C3R8CA3GNN□	0.33mm	25Vdc	6.8pF	±0.25pF	CL03C6R8CA3GNN□
		3.9pF	±0.05pF	CL03C3R9AA3GNN□			6.9pF	±0.05pF	CL03C6R9AA3GNN□
		3.9pF	±0.1pF	CL03C3R9BA3GNN□			7.0pF	±0.05pF	CL03C070AA3GNN□
		3.9pF	±0.25pF	CL03C3R9CA3GNN□			7.0pF	±0.1pF	CL03C070BA3GNN□
		4.0pF	±0.05pF	CL03C040AA3GNN□			7.0pF	±0.25pF	CL03C070CA3GNN□
		4.0pF	±0.1pF	CL03C040BA3GNN□			7.1pF	±0.05pF	CL03C7R1AA3GNN□
		4.0pF	±0.25pF	CL03C040CA3GNN□			7.2pF	±0.05pF	CL03C7R2AA3GNN□
		4.1pF	±0.05pF	CL03C4R1AA3GNN□			7.2pF	±0.1pF	CL03C7R2BA3GNN□
		4.2pF	±0.05pF	CL03C4R2AA3GNN□			7.3pF	±0.05pF	CL03C7R3AA3GNN□
		4.3pF	±0.05pF	CL03C4R3AA3GNN□			7.4pF	±0.05pF	CL03C7R4AA3GNN□
		4.3pF	±0.1pF	CL03C4R3BA3GNN□			7.5pF	±0.05pF	CL03C7R5AA3GNN□
		4.3pF	±0.25pF	CL03C4R3CA3GNN□			7.5pF	±0.1pF	CL03C7R5BA3GNN□
		4.4pF	±0.05pF	CL03C4R4AA3GNN□			7.5pF	±0.25pF	CL03C7R5CA3GNN□
		4.5pF	±0.05pF	CL03C4R5AA3GNN□			7.6pF	±0.05pF	CL03C7R6AA3GNN□
		4.6pF	±0.05pF	CL03C4R6AA3GNN□			7.7pF	±0.05pF	CL03C7R7AA3GNN□
		4.7pF	±0.05pF	CL03C4R7AA3GNN□			7.8pF	±0.05pF	CL03C7R8AA3GNN□
		4.7pF	±0.1pF	CL03C4R7BA3GNN□			7.9pF	±0.05pF	CL03C7R9AA3GNN□
		4.7pF	±0.25pF	CL03C4R7CA3GNN□			8.0pF	±0.05pF	CL03C080AA3GNN□
		4.8pF	±0.05pF	CL03C4R8AA3GNN□			8.0pF	±0.25pF	CL03C080CA3GNN□
		4.9pF	±0.05pF	CL03C4R9AA3GNN□			8.0pF	±0.5pF	CL03C080DA3GNN□
		5.0pF	±0.05pF	CL03C050AA3GNN□			8.1pF	±0.05pF	CL03C8R1AA3GNN□
		5.0pF	±0.1pF	CL03C050BA3GNN□			8.2pF	±0.05pF	CL03C8R2AA3GNN□
		5.0pF	±0.25pF	CL03C050CA3GNN□			8.2pF	±0.1pF	CL03C8R2BA3GNN□
		5.1pF	±0.05pF	CL03C5R1AA3GNN□			8.2pF	±0.25pF	CL03C8R2CA3GNN□
		5.1pF	±0.1pF	CL03C5R1BA3GNN□			8.2pF	±0.5pF	CL03C8R2DA3GNN□
		5.1pF	±0.25pF	CL03C5R1CA3GNN□			8.3pF	±0.05pF	CL03C8R3AA3GNN□
		5.1pF	±0.25pF	CL03C5R1CA3NNN□			8.4pF	±0.05pF	CL03C8R4AA3GNN□
		5.2pF	±0.05pF	CL03C5R2AA3GNN□			8.5pF	±0.05pF	CL03C8R5AA3GNN□
		5.3pF	±0.05pF	CL03C5R3AA3GNN□			8.5pF	±0.25pF	CL03C8R5CA3GNN□
		5.4pF	±0.05pF	CL03C5R4AA3GNN□			8.6pF	±0.05pF	CL03C8R6AA3GNN□
		5.5pF	±0.05pF	CL03C5R5AA3GNN□			8.7pF	±0.05pF	CL03C8R7AA3GNN□
		5.6pF	±0.05pF	CL03C5R6AA3GNN□			8.8pF	±0.05pF	CL03C8R8AA3GNN□
		5.6pF	±0.1pF	CL03C5R6BA3GNN□			8.9pF	±0.05pF	CL03C8R9AA3GNN□
		5.6pF	±0.25pF	CL03C5R6CA3GNN□			9.0pF	±0.05pF	CL03C090AA3GNN□
		5.7pF	±0.05pF	CL03C5R7AA3GNN□			9.0pF	±0.1pF	CL03C090BA3GNN□
		5.8pF	±0.05pF	CL03C5R8AA3GNN□			9.0pF	±0.25pF	CL03C090CA3GNN□
		5.9pF	±0.05pF	CL03C5R9AA3GNN□			9.0pF	±0.5pF	CL03C090DA3GNN□
		6.0pF	±0.05pF	CL03C060AA3GNN□			9.1pF	±0.05pF	CL03C9R1AA3GNN□
		6.0pF	±0.1pF	CL03C060BA3GNN□			9.1pF	±0.1pF	CL03C9R1BA3GNN□
		6.0pF	±0.25pF	CL03C060CA3GNN□			9.1pF	±0.25pF	CL03C9R1CA3GNN□
		6.0pF	±0.5pF	CL03C060DA3GNN□			9.1pF	±0.5pF	CL03C9R1DA3GNN□
		6.1pF	±0.05pF	CL03C6R1AA3GNN□			9.2pF	±0.05pF	CL03C9R2AA3GNN□
		6.2pF	±0.05pF	CL03C6R2AA3GNN□			9.3pF	±0.05pF	CL03C9R3AA3GNN□
		6.2pF	±0.1pF	CL03C6R2BA3GNN□			9.4pF	±0.05pF	CL03C9R4AA3GNN□
		6.2pF	±0.25pF	CL03C6R2CA3GNN□			9.5pF	±0.05pF	CL03C9R5AA3GNN□
		6.3pF	±0.05pF	CL03C6R3AA3GNN□			9.6pF	±0.05pF	CL03C9R6AA3GNN□
		6.4pF	±0.05pF	CL03C6R4AA3GNN□			9.7pF	±0.05pF	CL03C9R7AA3GNN□
		6.4pF	±0.25pF	CL03C6R4CA3GNN□			9.8pF	±0.05pF	CL03C9R8AA3GNN□
		6.5pF	±0.05pF	CL03C6R5AA3GNN□			9.9pF	±0.05pF	CL03C9R9AA3GNN□
		6.6pF	±0.05pF	CL03C6R6AA3GNN□			10pF	±0.05pF	CL03C100AA3GNN□
		6.7pF	±0.05pF	CL03C6R7AA3GNN□			10pF	±0.25pF	CL03C100CA3GNN□
		6.8pF	±0.05pF	CL03C6R8AA3GNN□			10pF	±0.5pF	CL03C100DA3GNN□
		6.8pF	±0.1pF	CL03C6R8BA3GNN□			10pF	±2%	CL03C100GA3GNN□
		6.8pF	±0.1pF	CL03C6R8BA3NNN□			10pF	±5%	CL03C100JA3GNN□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Super Small Size Capacitors

Product Line Up (COG)

■ Size : 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.33mm	25Vdc	11pF	±2%	CL03C110GA3GNN□	0.33mm	50Vdc	6.0pF	±0.5pF	CL03C060DB3GNN□
		11pF	±5%	CL03C110JA3GNN□			6.2pF	±0.1pF	CL03C6R2BB3GNN□
		12pF	±2%	CL03C120GA3GNN□			6.5pF	±0.1pF	CL03C6R5BB3GNN□
		12pF	±5%	CL03C120JA3GNN□			7.0pF	±0.1pF	CL03C070BB3GNN□
		12pF	±5%	CL03C120JA3NNN□			7.0pF	±0.5pF	CL03C070DB3GNN□
		13pF	±2%	CL03C130GA3GNN□			7.5pF	±0.1pF	CL03C7R5BB3GNN□
		13pF	±5%	CL03C130JA3GNN□			8.0pF	±0.1pF	CL03C080BB3GNN□
		15pF	±2%	CL03C150GA3GNN□			8.0pF	±0.5pF	CL03C080DB3GNN□
		15pF	±5%	CL03C150JA3GNN□			8.2pF	±0.1pF	CL03C8R2BB3GNN□
		15pF	±5%	CL03C150JA3NNN□			8.2pF	±0.5pF	CL03C8R2DB3GNN□
		16pF	±2%	CL03C160GA3GNN□			10pF	±5%	CL03C100JB3GNN□
		16pF	±5%	CL03C160JA3GNN□			10pF	±5%	CL03C100JB3NNN□
		16pF	+5%	CL03C160UA3GNN□			12pF	±5%	CL03C120JB3NNN□
		18pF	±2%	CL03C180GA3GNN□			15pF	±5%	CL03C150JB3NNN□
		18pF	±5%	CL03C180JA3GNN□			33pF	±5%	CL03C330JB3NNN□
		18pF	±5%	CL03C180JA3NNN□			100pF	±5%	CL03C101JB3NNN□
	50Vdc	20pF	±2%	CL03C200GA3GNN□					
		20pF	±5%	CL03C200JA3GNN□					
		22pF	±2%	CL03C220GA3GNN□					
		22pF	±5%	CL03C220JA3GNN□					
		22pF	±5%	CL03C220JA3NNN□					
		24pF	±5%	CL03C240JA3GNN□					
		27pF	±5%	CL03C270JA3GNN□					
		27pF	±5%	CL03C270JA3NNN□					
		30pF	±5%	CL03C300JA3GNN□					
		33pF	±5%	CL03C330JA3GNN□					
		33pF	±5%	CL03C330JA3NNN□					
		39pF	±5%	CL03C390JA3NNN□					
		47pF	±5%	CL03C470JA3NNN□					
		56pF	±5%	CL03C560JA3NNN□					
		68pF	±5%	CL03C680JA3NNN□					
		82pF	±5%	CL03C820JA3NNN□					
		100pF	±5%	CL03C101JA3NNN□					
		0.5pF	±0.25pF	CL03C05CB3GNN□					
		0.75pF	±0.1pF	CL03CR75BB3GNN□					
		0.8pF	±0.25pF	CL03C0R8CB3GNN□					
		1.0pF	±0.1pF	CL03C010BB3GNN□					
		1.2pF	±0.1pF	CL03C1R2BB3GNN□					
		1.2pF	±0.25pF	CL03C1R2CB3GNN□					
		1.5pF	±0.1pF	CL03C1R5BB3GNN□					
		1.5pF	±0.25pF	CL03C1R5CB3GNN□					
		1.8pF	±0.1pF	CL03C1R8BB3GNN□					
		2.0pF	±0.1pF	CL03C020BB3GNN□					
		2.0pF	±0.25pF	CL03C020CB3GNN□					
		2.2pF	±0.05pF	CL03C2R2AB3GNN□					
		2.7pF	±0.1pF	CL03C2R7BB3GNN□					
		3.0pF	±0.1pF	CL03C030BB3GNN□					
		3.0pF	±0.25pF	CL03C030CB3GNN□					
		3.3pF	±0.1pF	CL03C3R3BB3GNN□					
		4.0pF	±0.1pF	CL03C040BB3GNN□					
		4.7pF	±0.1pF	CL03C4R7BB3GNN□					
		5.0pF	±0.1pF	CL03C050BB3GNN□					
		5.6pF	±0.1pF	CL03C5R6BB3GNN□					
		6.0pF	±0.1pF	CL03C060BB3GNN□					

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (X5R)

■ Size : 0.40 X 0.20mm (inch : 01005)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.22mm	4.0Vdc	15nF	±10%	CL02A153KR2NNN □		0.33mm	6.3Vdc	1.0uF	±10%	CL03A105KQ3CNN □	Operating Ref.
		33nF	±10%	CL02A333KR2NNN □				1.0uF	±10%	CL03A105MQ3CNN □	Operating Ref.
		47nF	±10%	CL02A473KR2NNN □			10Vdc	330pF	±20%	CL03A331KP3NNN □	
		100nF	±10%	CL02A104KR2NNN □	Derating			1.5nF	±10%	CL03A152KP3NNN □	
		100nF	±20%	CL02A104MR2NNN □	Derating			2.2nF	±20%	CL03A222KP3NNN □	
	6.3Vdc	680pF	±10%	CL02A681KQ2NNN □				3.3nF	±5%	CL03A332KP3NNN □	
		820pF	±10%	CL02A821KQ2NNN □				4.7nF	±10%	CL03A472KP3NNN □	
		1.0nF	±10%	CL02A102KQ2NNN □				8.2nF	±20%	CL03A822KP3NNN □	
		1.2nF	±10%	CL02A122KQ2NNN □				10nF	±10%	CL03A103KP3NNN □	
		1.8nF	±10%	CL02A182KQ2NNN □				15nF	±10%	CL03A153KP3NNN □	
		2.2nF	±10%	CL02A222KQ2NNN □				22nF	±10%	CL03A223KP3NNN □	Operating
		2.7nF	±10%	CL02A272KQ2NNN □				33nF	±10%	CL03A333KP3NNN □	Operating
		3.9nF	±10%	CL02A392KQ2NNN □				47nF	±20%	CL03A473KP3NNN □	Operating
		5.6nF	±10%	CL02A562KQ2NNN □				100nF	±5%	CL03A104KP3NNN □	Operating
		10nF	±10%	CL02A103KQ2NNN □				100nF	±10%	CL03A104MP3NNN □	Operating
		15nF	±10%	CL02A153KQ2NNN □	Derating			220nF	±10%	CL03A224KP3NNN □	Operating Ref.
		33nF	±10%	CL02A333KQ2NNN □	Derating			220nF	±5%	CL03A224MP3NNN □	Operating Ref.
		47nF	±10%	CL02A473KQ2NNN □	Derating			470nF	±10%	CL03A474KP3NNN □	Operating Ref.
		68nF	±10%	CL02A683KQ2NNN □	Derating			470nF	±20%	CL03A474MP3NNN □	Operating Ref.
		100nF	±10%	CL02A104KQ2NNN □	Derating		16Vdc	220pF	±10%	CL03A221KO3NNN □	Operating
		100nF	±20%	CL02A104MQ2NNN □	Derating			330pF	±10%	CL03A331KO3NNN □	Operating
	10Vdc	470pF	±10%	CL02A471KP2NNN □				470pF	±10%	CL03A471KO3NNN □	Operating
		820pF	±10%	CL02A821KP2NNN □				10nF	±10%	CL03A103KO3NNN □	Operating
		1.0nF	±10%	CL02A102KP2NNN □				22nF	±10%	CL03A223KO3NNN □	Operating
		2.2nF	±10%	CL02A222KP2NNN □				47nF	±20%	CL03A473KO3NNN □	Operating
		5.6nF	±10%	CL02A562KP2NNN □				100nF	±10%	CL03A104KO3NNN □	Operating
		10nF	±10%	CL02A103KP2NNN □				100nF	±10%	CL03A104MO3NNN □	Operating

■ Size : 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.33mm	4.0Vdc	100nF	±10%	CL03A104KR3NNN □		0.35mm	4.0Vdc	1.0uF	±20%	CL03A105MR3CSN □	Operating Ref.
		470nF	±10%	CL03A474KR3NNN □	Ref.			1.0uF	±10%	CL03A105KQ3CSN □	Operating Ref.
		470nF	±20%	CL03A474MR3NNN □	Ref.		6.3Vdc	1.0uF	±20%	CL03A105MQ3NSN □	Operating Ref.
		330pF	±10%	CL03A331KQ3NNN □				2.2uF	±20%	CL03A225MQ3CSN □	Operating Ref.
		10nF	±10%	CL03A103KQ3NNN □				1.0uF	±20%	CL03A105MP3NSN □	Operating Ref.
		12nF	±10%	CL03A123KQ3NNN □				2.2uF	±20%	CL03A225KA3CRN □	Operating Ref.
		15nF	±10%	CL03A153KQ3NNN □				2.2uF	±20%	CL03A225MQ3CR6 □	Operating Ref.
		22nF	±5%	CL03A223JQ3NNN □			10Vdc	2.2uF	±20%	CL03A225MP3CRN □	Operating Ref.
		22nF	±10%	CL03A223KQ3NNN □				2.2uF	±20%	CL03A105MO3RN □	Operating Ref.
		33nF	±10%	CL03A333KQ3NNN □				1.0uF	±20%	CL03A105MR3CRN □	Operating Ref.
		47nF	±10%	CL03A473KQ3NNN □				1.0uF	±20%	CL03A225KQ3CRN □	Operating Ref.
	6.3Vdc	82nF	±10%	CL03A823KQ3NNN □			16Vdc	2.2uF	±20%	CL03A225MP3CRN □	Operating Ref.
		100nF	±5%	CL03A104JQ3NNN □	Derating			2.2uF	±20%	CL03A225MQ3CRN □	Operating Ref.
		100nF	±10%	CL03A104KQ3NNN □	Derating			2.2uF	±20%	CL03A225MP3CRN □	Operating Ref.
		100nF	±20%	CL03A104MQ3NNN □	Derating			1.0uF	±20%	CL03A105MO3RN □	Operating Ref.
		220nF	±10%	CL03A224KQ3NNN □	Derating			1.0uF	±20%	CL03A225KQ3CRN □	Operating Ref.
		220nF	±20%	CL03A224MQ3NNN □	Derating			1.0uF	±20%	CL03A225MP3CRN □	Operating Ref.
		470nF	±5%	CL03A474JQ3NNN □	Derating			1.0uF	±20%	CL03A225KQ3CRN □	Operating Ref.
		470nF	±10%	CL03A474KQ3NNN □	Derating			1.0uF	±20%	CL03A225MQ3CRN □	Operating Ref.
		470nF	±20%	CL03A474MQ3NNN □	Derating			1.0uF	±20%	CL03A225MP3CRN □	Operating Ref.
		1.5uF	±20%	CL03A155MQ3NNN □	Derating			1.0uF	±20%	CL03A225KQ3CRN □	Operating Ref.

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Super Small Size Capacitors

Product Line Up (X6S)

■ Size : 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.33mm	4.0Vdc	2.2nF	±20%	CL03X222MR3NNN □	
		4.7nF	±20%	CL03X472MR3NNN □	
		6.8nF	±20%	CL03X682MR3NNN □	
		15nF	±20%	CL03X153MR3NNN □	
		22nF	±20%	CL03X223MR3NNN □	
		47nF	±20%	CL03X473MR3NNN □	
		100nF	±10%	CL03X104KR3NNN □	Derating Ref.
	6.3Vdc	100nF	±10%	CL03X104KQ3NNN □	Derating Ref.
0.39mm	4.0Vdc	1.0uF	±20%	CL03X105MR3RN □	Derating Ref.

Product Line Up (X7R)

■ Size : 0.40 X 0.20mm (inch : 01005)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.22mm	6.3Vdc	1.0nF	±10%	CL02B102KQ2NNN □	
		100pF	±10%	CL02B101KP2NNN □	
		120pF	±10%	CL02B121KP2NNN □	
		180pF	±10%	CL02B181KP2NNN □	
		220pF	±10%	CL02B221KP2NNN □	
		330pF	±10%	CL02B331KP2NNN □	
		390pF	±10%	CL02B391KP2NNN □	
	1.0nF	±10%	CL02B102KP2NNN □		

■ Size : 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.33mm	6.3Vdc	2.2nF	±10%	CL03B222KQ3NNN □	
		3.3nF	±10%	CL03B332KQ3NNN □	
		4.7nF	±10%	CL03B472KQ3NNN □	
		6.8nF	±10%	CL03B682KQ3NNN □	
		10nF	±10%	CL03B103KQ3NNN □	
	10Vdc	470pF	±10%	CL03B471KP3NNN □	
		1.5nF	±10%	CL03B152KP3NNN □	
		2.2nF	±10%	CL03B222KP3NNN □	
		3.3nF	±10%	CL03B332KP3NNN □	
16Vdc	10Vdc	4.7nF	±10%	CL03B472KP3NNN □	
		6.8nF	±10%	CL03B682KP3NNN □	
		10nF	±10%	CL03B103KP3NNN □	
		10nF	±20%	CL03B103MP3NNN □	
		100pF	±10%	CL03B101KO3NNN □	
		120pF	±10%	CL03B121KO3NNN □	
		150pF	±10%	CL03B151KO3NNN □	
		180pF	±10%	CL03B181KO3NNN □	
	220pF	±10%	CL03B221KO3NNN □		
	270pF	±10%	CL03B271KO3NNN □		
	330pF	±10%	CL03B331KO3NNN □		

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

High Q Capacitors

Feature




- High Q and low ESR in high frequency range
- Tight tolerance available
- High efficiency and low power consumption in RF circuit

Application

- Mobile Phone
- Set Top Box
- Wireless Equipment
- GPS, Bluetooth

Structure and Dimensions



Size Code	EIA Code	Rated Voltage (Vdc)	Dimension(mm)						
			L	W	T	BW			
02	01005	16	0.40±0.02	0.20±0.02	0.20±0.02	0.10±0.03			
03	0201	25 / 50	0.60±0.03	0.30±0.03	0.30±0.03	0.15±0.05			

High Q Capacitance Table (C0G)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance(pF)																		
		0.2	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8
01005(0402)	16																			
0201 (0603)	25																			
	50																			
Size inch (mm)	Rated Voltage (Vdc)	Capacitance(pF)																		
		4.2	4.4	4.6	4.8	5.0	5.2	5.4	5.6	5.8	6.0	6.2	6.4	6.6	6.8	7.0	7.2	7.4	7.6	7.8
01005(0402)	16																			
0201 (0603)	25																			
	50																			
Size inch (mm)	Rated Voltage (Vdc)	Capacitance(pF)																		
		8.2	8.4	8.6	8.8	9.0	9.2	9.4	9.7	10	11	12	14	16	18	20	22	24	27	30
01005(0402)	16																			
0201 (0603)	25																			
	50																			

High Q Capacitors

Product Line Up (COG)

■ Size : 0.40 X 0.20mm (inch : 01005)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.22mm	16Vdc	0.2pF	±0.1pF	CL02C0R2B02GNN □	0.22mm	16Vdc	5.1pF	±0.25pF	CL02C5R1CO2GNN □
		0.3pF	±0.1pF	CL02C0R3B02GNN □			5.2pF	±0.1pF	CL02C5R2B02GNN □
		0.4pF	±0.1pF	CL02C0R4B02GNN □			5.3pF	±0.1pF	CL02C5R3B02GNN □
		0.5pF	±0.1pF	CL02C0R5B02GNN □			5.4pF	±0.1pF	CL02C5R4B02GNN □
		0.6pF	±0.1pF	CL02C0R6B02GNN □			5.5pF	±0.1pF	CL02C5R5B02GNN □
		0.7pF	±0.1pF	CL02C0R7B02GNN □			5.6pF	±0.1pF	CL02C5R6B02GNN □
		0.8pF	±0.1pF	CL02C0R8B02GNN □			5.6pF	±0.25pF	CL02C5R6CO2GNN □
		0.9pF	±0.1pF	CL02C0R9B02GNN □			5.7pF	±0.1pF	CL02C5R7B02GNN □
		1.0pF	±0.1pF	CL02C010B02GNN □			5.7pF	±0.25pF	CL02C5R7CO2GNN □
		1.1pF	±0.1pF	CL02C1R1B02GNN □			5.8pF	±0.1pF	CL02C5R8B02GNN □
		1.2pF	±0.1pF	CL02C1R2B02GNN □			5.9pF	±0.1pF	CL02C5R9B02GNN □
		1.3pF	±0.1pF	CL02C1R3B02GNN □			6.0pF	±0.1pF	CL02C060B02GNN □
		1.4pF	±0.1pF	CL02C1R4B02GNN □			6.1pF	±0.1pF	CL02C6R1B02GNN □
		1.5pF	±0.1pF	CL02C1R5B02GNN □			6.2pF	±0.1pF	CL02C6R2B02GNN □
		1.6pF	±0.1pF	CL02C1R6B02GNN □			6.3pF	±0.1pF	CL02C6R3B02GNN □
		1.7pF	±0.1pF	CL02C1R7B02GNN □			6.4pF	±0.1pF	CL02C6R4B02GNN □
		1.8pF	±0.1pF	CL02C1R8B02GNN □			6.5pF	±0.1pF	CL02C6R5B02GNN □
		1.9pF	±0.1pF	CL02C1R9B02GNN □			6.6pF	±0.1pF	CL02C6R6B02GNN □
		2.0pF	±0.1pF	CL02C020B02GNN □			6.7pF	±0.1pF	CL02C6R7B02GNN □
		2.1pF	±0.1pF	CL02C2R1B02GNN □			6.8pF	±0.1pF	CL02C6R8B02GNN □
		2.2pF	±0.1pF	CL02C2R2B02GNN □			6.9pF	±0.1pF	CL02C6R9B02GNN □
		2.3pF	±0.1pF	CL02C2R3B02GNN □			7.0pF	±0.1pF	CL02C070B02GNN □
		2.4pF	±0.1pF	CL02C2R4B02GNN □			7.1pF	±0.1pF	CL02C7R1B02GNN □
		2.5pF	±0.1pF	CL02C2R5B02GNN □			7.2pF	±0.1pF	CL02C7R2B02GNN □
		2.6pF	±0.1pF	CL02C2R6B02GNN □			7.3pF	±0.1pF	CL02C7R3B02GNN □
		2.7pF	±0.1pF	CL02C2R7B02GNN □			7.4pF	±0.1pF	CL02C7R4B02GNN □
		2.8pF	±0.1pF	CL02C2R8B02GNN □			7.5pF	±0.1pF	CL02C7R5B02GNN □
		2.9pF	±0.1pF	CL02C2R9B02GNN □			7.6pF	±0.1pF	CL02C7R6B02GNN □
		3.0pF	±0.1pF	CL02C030B02GNN □			7.7pF	±0.1pF	CL02C7R7B02GNN □
		3.1pF	±0.1pF	CL02C3R1B02GNN □			7.8pF	±0.1pF	CL02C7R8B02GNN □
		3.2pF	±0.1pF	CL02C3R2B02GNN □			7.9pF	±0.1pF	CL02C7R9B02GNN □
		3.3pF	±0.1pF	CL02C3R3B02GNN □			8.0pF	±0.1pF	CL02C080B02GNN □
		3.3pF	±0.25pF	CL02C3R3C02GNN □			8.0pF	±0.25pF	CL02C080CO2GNN □
		3.4pF	±0.1pF	CL02C3R4B02GNN □			8.1pF	±0.1pF	CL02C8R1B02GNN □
		3.5pF	±0.1pF	CL02C3R5B02GNN □			8.2pF	±0.1pF	CL02C8R2B02GNN □
		3.5pF	±0.25pF	CL02C3R5C02GNN □			8.2pF	±0.25pF	CL02C8R2CO2GNN □
		3.6pF	±0.1pF	CL02C3R6B02GNN □			8.3pF	±0.1pF	CL02C8R3B02GNN □
		3.7pF	±0.1pF	CL02C3R7B02GNN □			8.4pF	±0.1pF	CL02C8R4B02GNN □
		3.7pF	±0.25pF	CL02C3R7C02GNN □			8.4pF	±0.25pF	CL02C8R4CO2GNN □
		3.8pF	±0.1pF	CL02C3R8B02GNN □			8.5pF	±0.1pF	CL02C8R5B02GNN □
		3.9pF	±0.1pF	CL02C3R9B02GNN □			8.6pF	±0.1pF	CL02C8R6B02GNN □
		4.0pF	±0.1pF	CL02C040B02GNN □			8.7pF	±0.1pF	CL02C8R7B02GNN □
		4.1pF	±0.1pF	CL02C4R1B02GNN □			8.8pF	±0.1pF	CL02C8R8B02GNN □
		4.2pF	±0.1pF	CL02C4R2B02GNN □			8.9pF	±0.1pF	CL02C8R9B02GNN □
		4.3pF	±0.1pF	CL02C4R3B02GNN □			9.0pF	±0.1pF	CL02C090B02GNN □
		4.4pF	±0.1pF	CL02C4R4B02GNN □			9.1pF	±0.1pF	CL02C9R1B02GNN □
		4.5pF	±0.1pF	CL02C4R5B02GNN □			9.2pF	±0.1pF	CL02C9R2B02GNN □
		4.6pF	±0.1pF	CL02C4R6B02GNN □			9.3pF	±0.1pF	CL02C9R3B02GNN □
		4.7pF	±0.1pF	CL02C4R7B02GNN □			9.4pF	±0.1pF	CL02C9R4B02GNN □
		4.8pF	±0.1pF	CL02C4R8B02GNN □			9.5pF	±0.1pF	CL02C9R5B02GNN □
		4.9pF	±0.1pF	CL02C4R9B02GNN □			9.5pF	±0.25pF	CL02C9R5CO2GNN □
		5.0pF	±0.1pF	CL02C050B02GNN □			9.6pF	±0.1pF	CL02C9R6B02GNN □
		5.0pF	±0.25pF	CL02C050C02GNN □			9.7pF	±0.1pF	CL02C9R7B02GNN □
		5.1pF	±0.1pF	CL02C5R1B02GNN □			9.8pF	±0.1pF	CL02C9R8B02GNN □

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (COG)

■ Size : 0.40 X 0.20mm (inch : 01005)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.22mm	16Vdc	9.9pF	±0.1pF	CL02C9R9B02GNN□	0.33mm	25Vdc	1.8pF	±0.05pF	CL03C1R8AA3GNN□
		10pF	±5%	CL02C100J02GNN□			1.8pF	±0.1pF	CL03C1R8BA3GNN□
		18pF	±2%	CL02C180G02GNN□			1.8pF	±0.25pF	CL03C1R8CA3GNN□
		22pF	±2%	CL02C220G02GNN□			1.9pF	±0.05pF	CL03C1R9AA3GNN□
0.33mm	25Vdc	1.9pF	±0.1pF	CL03C1R9BA3GNN□			1.9pF	±0.1pF	CL03C1R9CA3GNN□
		2.0pF	±0.05pF	CL03C200AA3GNN□			2.0pF	±0.1pF	CL03C200BA3GNN□
		2.0pF	±0.25pF	CL03C200CA3GNN□			2.0pF	±0.25pF	CL03C2020AA3GNN□
		2.0pF	±0.25pF	CL03C2020BA3GNN□			2.0pF	±0.25pF	CL03C2020CA3GNN□
		2.0pF	±0.1pF	CL03C2R0BA3GNN□			2.1pF	±0.05pF	CL03C2R1AA3GNN□
		2.1pF	±0.1pF	CL03C2R1BA3GNN□			2.1pF	±0.1pF	CL03C2R1BA3GNN□
		2.2pF	±0.05pF	CL03C2R2AA3GNN□			2.2pF	±0.1pF	CL03C2R2BA3GNN□
		2.2pF	±0.25pF	CL03C2R2CA3GNN□			2.2pF	±0.25pF	CL03C2R2CA3GNN□
		2.3pF	±0.05pF	CL03C2R3AA3GNN□			2.3pF	±0.1pF	CL03C2R3BA3GNN□
		2.3pF	±0.1pF	CL03C2R3BA3GNN□			2.4pF	±0.05pF	CL03C2R4AA3GNN□
		2.4pF	±0.1pF	CL03C2R4BA3GNN□			2.4pF	±0.1pF	CL03C2R4BA3GNN□
		2.4pF	±0.25pF	CL03C2R4CA3GNN□			2.4pF	±0.25pF	CL03C2R4CA3GNN□
		2.5pF	±0.05pF	CL03C2R5AA3GNN□			2.5pF	±0.1pF	CL03C2R5BA3GNN□
		2.5pF	±0.1pF	CL03C2R5BA3GNN□			2.6pF	±0.05pF	CL03C2R6AA3GNN□
		2.6pF	±0.1pF	CL03C2R6BA3GNN□			2.6pF	±0.1pF	CL03C2R6BA3GNN□
		2.7pF	±0.05pF	CL03C2R7AA3GNN□			2.7pF	±0.1pF	CL03C2R7BA3GNN□
		2.7pF	±0.25pF	CL03C2R7CA3GNN□			2.7pF	±0.25pF	CL03C2R7CA3GNN□
		2.8pF	±0.05pF	CL03C2R8AA3GNN□			2.8pF	±0.1pF	CL03C2R8BA3GNN□
		2.8pF	±0.1pF	CL03C2R8BA3GNN□			2.9pF	±0.05pF	CL03C2R9AA3GNN□
		2.9pF	±0.1pF	CL03C2R9BA3GNN□			2.9pF	±0.1pF	CL03C2R9BA3GNN□
		3.0pF	±0.05pF	CL03C030AA3GNN□			3.0pF	±0.1pF	CL03C030BA3GNN□
		3.0pF	±0.1pF	CL03C030BA3GNN□			3.0pF	±0.25pF	CL03C030CA3GNN□
		3.1pF	±0.05pF	CL03C3R1AA3GNN□			3.1pF	±0.1pF	CL03C3R1BA3GNN□
		3.1pF	±0.1pF	CL03C3R1BA3GNN□			3.2pF	±0.05pF	CL03C3R2AA3GNN□
		3.2pF	±0.05pF	CL03C3R2AA3GNN□			3.2pF	±0.1pF	CL03C3R2BA3GNN□
		3.2pF	±0.25pF	CL03C3R2CA3GNN□			3.3pF	±0.05pF	CL03C3R3AA3GNN□
		3.3pF	±0.1pF	CL03C3R3BA3GNN□			3.3pF	±0.25pF	CL03C3R3CA3GNN□
		3.3pF	±0.25pF	CL03C3R4AA3GNN□			3.4pF	±0.05pF	CL03C3R4BA3GNN□
		3.4pF	±0.1pF	CL03C3R4BA3GNN□			3.4pF	±0.25pF	CL03C3R4CA3GNN□
		3.4pF	±0.25pF	CL03C3R5AA3GNN□			3.5pF	±0.05pF	CL03C3R5BA3GNN□
		3.5pF	±0.1pF	CL03C3R6AA3GNN□			3.6pF	±0.05pF	CL03C3R6BA3GNN□
		3.6pF	±0.1pF	CL03C3R6BA3GNN□			3.6pF	±0.25pF	CL03C3R6CA3GNN□
		3.6pF	±0.25pF	CL03C3R7AA3GNN□			3.7pF	±0.05pF	CL03C3R7AA3GNN□
		3.7pF	±0.05pF	CL03C3R8AA3GNN□			3.8pF	±0.05pF	CL03C3R8BA3GNN□
		3.8pF	±0.1pF	CL03C3R8BA3GNN□			3.8pF	±0.25pF	CL03C3R8CA3GNN□
		3.8pF	±0.25pF	CL03C3R9AA3GNN□			3.9pF	±0.05pF	CL03C3R9BA3GNN□
		3.9pF	±0.1pF	CL03C3R9BA3GNN□			3.9pF	±0.25pF	CL03C3R9CA3GNN□
		3.9pF	±0.25pF	CL03C3R9AA3GNN□			3.9pF	±0.05pF	CL03C3R9BA3GNN□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

High Q Capacitors

Product Line Up (COG)

■ Size : 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.33mm	25Vdc	3.9pF	±0.1pF	CL03C3R9BA3GNN □	0.33mm	25Vdc	7.0pF	±0.25pF	CL03C070CA3GNN □
		3.9pF	±0.25pF	CL03C3R9CA3GNN □			7.1pF	±0.05pF	CL03C7R1AA3GNN □
		4.0pF	±0.05pF	CL03C040AA3GNN □			7.2pF	±0.05pF	CL03C7R2AA3GNN □
		4.0pF	±0.1pF	CL03C040BA3GNN □			7.2pF	±0.1pF	CL03C7R2BA3GNN □
		4.0pF	±0.25pF	CL03C040CA3GNN □			7.3pF	±0.05pF	CL03C7R3AA3GNN □
		4.1pF	±0.05pF	CL03C4R1AA3GNN □			7.4pF	±0.05pF	CL03C7R4AA3GNN □
		4.2pF	±0.05pF	CL03C4R2AA3GNN □			7.5pF	±0.05pF	CL03C7R5AA3GNN □
		4.3pF	±0.05pF	CL03C4R3AA3GNN □			7.5pF	±0.1pF	CL03C7R5BA3GNN □
		4.3pF	±0.1pF	CL03C4R3BA3GNN □			7.5pF	±0.25pF	CL03C7R5CA3GNN □
		4.3pF	±0.25pF	CL03C4R3CA3GNN □			7.6pF	±0.05pF	CL03C7R6AA3GNN □
		4.4pF	±0.05pF	CL03C4R4AA3GNN □			7.7pF	±0.05pF	CL03C7R7AA3GNN □
		4.5pF	±0.05pF	CL03C4R5AA3GNN □			7.8pF	±0.05pF	CL03C7R8AA3GNN □
		4.6pF	±0.05pF	CL03C4R6AA3GNN □			7.9pF	±0.05pF	CL03C7R9AA3GNN □
		4.7pF	±0.05pF	CL03C4R7AA3GNN □			8.0pF	±0.05pF	CL03C080AA3GNN □
		4.7pF	±0.1pF	CL03C4R7BA3GNN □			8.0pF	±0.25pF	CL03C080CA3GNN □
		4.7pF	±0.25pF	CL03C4R7CA3GNN □			8.0pF	±0.5pF	CL03C080DA3GNN □
		4.8pF	±0.05pF	CL03C4R8AA3GNN □			8.1pF	±0.05pF	CL03C8R1AA3GNN □
		4.9pF	±0.05pF	CL03C4R9AA3GNN □			8.2pF	±0.05pF	CL03C8R2AA3GNN □
		5.0pF	±0.05pF	CL03C050AA3GNN □			8.2pF	±0.1pF	CL03C8R2BA3GNN □
		5.0pF	±0.1pF	CL03C050BA3GNN □			8.2pF	±0.25pF	CL03C8R2CA3GNN □
		5.0pF	±0.25pF	CL03C050CA3GNN □			8.2pF	±0.5pF	CL03C8R2DA3GNN □
		5.1pF	±0.05pF	CL03C5R1AA3GNN □			8.3pF	±0.05pF	CL03C8R3AA3GNN □
		5.1pF	±0.1pF	CL03C5R1BA3GNN □			8.4pF	±0.05pF	CL03C8R4AA3GNN □
		5.1pF	±0.25pF	CL03C5R1CA3GNN □			8.5pF	±0.05pF	CL03C8R5AA3GNN □
		5.2pF	±0.05pF	CL03C5R2AA3GNN □			8.5pF	±0.25pF	CL03C8R5CA3GNN □
		5.3pF	±0.05pF	CL03C5R3AA3GNN □			8.6pF	±0.05pF	CL03C8R6AA3GNN □
		5.4pF	±0.05pF	CL03C5R4AA3GNN □			8.7pF	±0.05pF	CL03C8R7AA3GNN □
		5.5pF	±0.05pF	CL03C5R5AA3GNN □			8.8pF	±0.05pF	CL03C8R8AA3GNN □
		5.6pF	±0.05pF	CL03C5R6AA3GNN □			8.9pF	±0.05pF	CL03C8R9AA3GNN □
		5.6pF	±0.1pF	CL03C5R6BA3GNN □			9.0pF	±0.05pF	CL03C090AA3GNN □
		5.6pF	±0.25pF	CL03C5R6CA3GNN □			9.0pF	±0.1pF	CL03C090BA3GNN □
		5.7pF	±0.05pF	CL03C5R7AA3GNN □			9.0pF	±0.25pF	CL03C090CA3GNN □
		5.8pF	±0.05pF	CL03C5R8AA3GNN □			9.0pF	±0.5pF	CL03C090DA3GNN □
		5.9pF	±0.05pF	CL03C5R9AA3GNN □			9.1pF	±0.05pF	CL03C9R1AA3GNN □
		6.0pF	±0.05pF	CL03C060AA3GNN □			9.1pF	±0.1pF	CL03C9R1BA3GNN □
		6.0pF	±0.1pF	CL03C060BA3GNN □			9.1pF	±0.25pF	CL03C9R1CA3GNN □
		6.0pF	±0.25pF	CL03C060CA3GNN □			9.1pF	±0.5pF	CL03C9R1DA3GNN □
		6.0pF	±0.5pF	CL03C060DA3GNN □			9.2pF	±0.05pF	CL03C9R2AA3GNN □
		6.1pF	±0.05pF	CL03C6R1AA3GNN □			9.3pF	±0.05pF	CL03C9R3AA3GNN □
		6.2pF	±0.05pF	CL03C6R2AA3GNN □			9.4pF	±0.05pF	CL03C9R4AA3GNN □
		6.2pF	±0.1pF	CL03C6R2BA3GNN □			9.5pF	±0.05pF	CL03C9R5AA3GNN □
		6.2pF	±0.25pF	CL03C6R2CA3GNN □			9.6pF	±0.05pF	CL03C9R6AA3GNN □
		6.3pF	±0.05pF	CL03C6R3AA3GNN □			9.7pF	±0.05pF	CL03C9R7AA3GNN □
		6.4pF	±0.05pF	CL03C6R4AA3GNN □			9.8pF	±0.05pF	CL03C9R8AA3GNN □
		6.4pF	±0.25pF	CL03C6R4CA3GNN □			9.9pF	±0.05pF	CL03C9R9AA3GNN □
		6.5pF	±0.05pF	CL03C6R5AA3GNN □			10pF	±0.05pF	CL03C100AA3GNN □
		6.6pF	±0.05pF	CL03C6R6AA3GNN □			10pF	±0.25pF	CL03C100CA3GNN □
		6.7pF	±0.05pF	CL03C6R7AA3GNN □			10pF	±0.5pF	CL03C100DA3GNN □
		6.8pF	±0.05pF	CL03C6R8AA3GNN □			10pF	±2%	CL03C100GA3GNN □
		6.8pF	±0.1pF	CL03C6R8BA3GNN □			10pF	±5%	CL03C100JA3GNN □
		6.8pF	±0.25pF	CL03C6R8CA3GNN □			11pF	±2%	CL03C110GA3GNN □
		6.9pF	±0.05pF	CL03C6R9AA3GNN □			11pF	±5%	CL03C110JA3GNN □
		7.0pF	±0.05pF	CL03C070AA3GNN □			12pF	±2%	CL03C120GA3GNN □
		7.0pF	±0.1pF	CL03C070BA3GNN □			12pF	±5%	CL03C120JA3GNN □

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (COG)

■ Size : 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.33mm	25Vdc	13pF	±2%	CL03C130GA3GNN□
		13pF	±5%	CL03C130JA3GNN□
		15pF	±2%	CL03C150GA3GNN□
		15pF	±5%	CL03C150JA3GNN□
		16pF	±2%	CL03C160GA3GNN□
		16pF	±5%	CL03C160JA3GNN□
		16pF	±5%	CL03C160UA3GNN□
		18pF	±2%	CL03C180GA3GNN□
		18pF	±5%	CL03C180JA3GNN□
		20pF	±2%	CL03C200GA3GNN□
		20pF	±5%	CL03C200JA3GNN□
		22pF	±2%	CL03C220GA3GNN□
		22pF	±5%	CL03C220JA3GNN□
		24pF	±5%	CL03C240JA3GNN□
		27pF	±5%	CL03C270JA3GNN□
		30pF	±5%	CL03C300JA3GNN□
		33pF	±5%	CL03C330JA3GNN□
	50Vdc	0.5pF	±0.25pF	CL03C0R5CB3GNN□
		0.75pF	±0.1pF	CL03CR75BB3GNN□
		0.8pF	±0.25pF	CL03C0R8CB3GNN□
		1.0pF	±0.1pF	CL03C010BB3GNN□
		1.2pF	±0.1pF	CL03C1R2BB3GNN□
		1.2pF	±0.25pF	CL03C1R2CB3GNN□
		1.5pF	±0.1pF	CL03C1R5BB3GNN□
		1.5pF	±0.25pF	CL03C1R5CB3GNN□
		1.8pF	±0.1pF	CL03C1R8BB3GNN□
		2.0pF	±0.1pF	CL03C020BB3GNN□
		2.0pF	±0.25pF	CL03C020CB3GNN□
		2.2pF	±0.05pF	CL03C2R2AB3GNN□
		2.7pF	±0.1pF	CL03C2R7BB3GNN□
		3.0pF	±0.1pF	CL03C030BB3GNN□
		3.0pF	±0.25pF	CL03C030CB3GNN□
		3.3pF	±0.1pF	CL03C3R3BB3GNN□
		4.0pF	±0.1pF	CL03C040BB3GNN□
		4.7pF	±0.1pF	CL03C4R7BB3GNN□
		5.0pF	±0.1pF	CL03C050BB3GNN□
		5.6pF	±0.1pF	CL03C5R6BB3GNN□
		6.0pF	±0.1pF	CL03C060BB3GNN□
		6.0pF	±0.5pF	CL03C060DB3GNN□
		6.2pF	±0.1pF	CL03C6R2BB3GNN□
		6.5pF	±0.1pF	CL03C6R5BB3GNN□
		7.0pF	±0.1pF	CL03C070BB3GNN□
		7.0pF	±0.5pF	CL03C070DB3GNN□
		7.5pF	±0.1pF	CL03C7R5BB3GNN□
		8.0pF	±0.1pF	CL03C080BB3GNN□
		8.0pF	±0.5pF	CL03C080DB3GNN□
		8.2pF	±0.1pF	CL03C8R2BB3GNN□
		8.2pF	±0.5pF	CL03C8R2DB3GNN□
		10pF	±5%	CL03C100JB3GNN□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
 In order to move to the page directly, please click the here. ↑

Medium – High Voltage Capacitors

Feature




- Highly reliable performance
- Operating at high voltage level
- Wide voltage level : from 100V to 3kV
- High withstanding voltage
- Tape & reel surface mount assembly

Application

- Switching Power Circuit (SMPS)
- Lighting Ballast, LCD Back Lighting Inverter
- DC – DC converter input filter, Snubber Circuit
- Network (IEEE802.3)

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
05	0402	1.00±0.05	0.50±0.05	0.50±0.05	5	0.25±0.10
10	0603	1.60±0.10	0.80±0.10	0.80±0.10	8	0.30±0.20
21	0805	2.00±0.10	1.25±0.10	0.65±0.10	A	0.50+0.20/-0.30
		2.00±0.10	1.25±0.10	0.85±0.10	C	
		2.00±0.10	1.25±0.10	1.15±0.10	M	
		2.00±0.10	1.25±0.10	1.25±0.10	F	
31	1206	3.20±0.15	1.60±0.15	0.85±0.15	C	0.50±0.30
		3.20±0.15	1.60±0.15	1.25±0.15	F	
		3.20±0.20	1.60±0.20	1.60±0.20	H	
32	1210	3.20±0.30	2.50±0.20	1.25±0.20	F	0.60±0.30
		3.20±0.30	2.50±0.20	1.60±0.20	H	
		3.20±0.30	2.50±0.20	2.00±0.20	I	
		3.20±0.30	2.50±0.20	2.50±0.20	J	
42	1808	4.50±0.40	2.00±0.20	1.25±0.20	F	0.80±0.30
		4.50±0.40	2.00±0.20	1.60±0.20	H	
		4.50±0.40	2.00±0.20	2.00±0.20	I	
43	1812	4.50±0.40	3.20±0.30	1.25±0.20	F	0.80±0.30
		4.50±0.40	3.20±0.30	1.60±0.20	H	
		4.50±0.40	3.20±0.30	2.00±0.20	I	
		4.50±0.40	3.20±0.30	2.50±0.20	J	
55	2220	5.70±0.40	5.00±0.40	2.50±0.20	J	1.00±0.30

Medium - High Voltage Capacitance Table (C0G)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance																																		
		pF												nF																						
		47	100	120	150	180	220	270	330	390	470	560	680	820	1.0	1.2	1.5	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	12	15	18	22	27	33	47	56	68
0402(1005)	100																																			
0603 (1608)	100																																			
	200																																			
	250																																			
	100																																			
0805 (2012)	200																																			
	250																																			
	500																																			
	630																																			
	100																																			
1206 (3216)	200																																			
	250																																			
	500																																			
	630																																			
	1k																																			
	2k																																			
	100																																			
1210 (3225)	200																																			
	250																																			
	500																																			
	630																																			
	1k																																			
	2k																																			
1808 (4520)	2k																																			
	3k																																			
1812 (4532)	100																																			
	200																																			
	250																																			
	500																																			
	630																																			
	1k																																			
	2k																																			
	3k																																			
2220 (5750)	100																																			
	200																																			
	250																																			
	500																																			
	630																																			
	1k																																			
	2k																																			
	3k																																			

Medium – High Voltage Capacitors

Medium – High Voltage Capacitance Table (X7R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance																	
		nF														uF			
		1.0	1.5	2.2	3.3	4.7	6.8	10	15	22	33	47	68	100	150	220	330	470	680
0603(1608)	100																		
0805 (2012)	100																		
	200																		
1206 (3216)	250																		
	100																		
	200																		
	250																		
	350																		
	500																		
	630																		
	1k																		
1210 (3225)	2k																		
	100																		
	200																		
	250																		
	500																		
	630																		
	1k																		
1808 (4520)	2k																		
	3k																		
	100																		
1812 (4532)	200																		
	250																		
	500																		
	630																		
	1k																		
	2k																		
	100																		
2220 (5750)	200																		
	250																		
	500																		
	630																		
	1k																		
	2k																		

Product Line Up (COG)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	100Vdc	1.8pF	±0.25pF	CL05C1R8CC5NNN□	0.90mm	100Vdc	270pF	±5%	CL10C271JC8NNN□
		2.2pF	±0.25pF	CL05C2R2CC5NNN□			330pF	±5%	CL10C331JC8NNN□
		3.0pF	±0.25pF	CL05C030CC5NNN□			390pF	±5%	CL10C391JC8NNN□
		3.3pF	±0.25pF	CL05C3R3CC5NNN□			470pF	±5%	CL10C471JC8NNN□
		4.0pF	±0.25pF	CL05C040CC5NNN□			1.0nF	±5%	CL10C102JC8NNN□
		15pF	±5%	CL05C150JC5NNN□			220pF	±10%	CL10C221KD8NNN□
		33pF	±5%	CL05C330JC5NNN□			250Vdc	470pF	±5%
		39pF	±5%	CL05C390JC5NNN□					CL10C471JE8NNN□
		47pF	±5%	CL05C470JC5NNN□					
		82pF	±5%	CL05C820JC5NNN□					
		100pF	±5%	CL05C101JC5NNN□					

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.90mm	100Vdc	10pF	±0.25pF	CL10C100CC8NNN□	0.75mm	100Vdc	2.7pF	±0.25pF	CL21C2R7CCANNNN□
		10pF	±0.5pF	CL10C100DC8NNN□			4.7pF	±0.1pF	CL21C4R7BCANNNN□
		10pF	±5%	CL10C100JC8NNN□			10pF	±0.25pF	CL21C100CCANNNN□
		12pF	±5%	CL10C120JC8NNN□			10pF	±5%	CL21C100JCANNNN□
		13pF	±5%	CL10C130JC8NNN□			11pF	±2%	CL21C110GCANNNN□
		15pF	±5%	CL10C150JC8NNN□			11pF	±5%	CL21C110JCANNNN□
		18pF	±5%	CL10C180JC8NNN□			12pF	±2%	CL21C120GCANNNN□
		20pF	±5%	CL10C200JC8NNN□			13pF	±2%	CL21C130GCANNNN□
		22pF	±5%	CL10C220JC8NNN□			13pF	±5%	CL21C130JCANNNN□
		24pF	±5%	CL10C240JC8NNN□			14pF	±5%	CL21C140JCANNNN□
		27pF	±5%	CL10C270JC8NNN□			15pF	±5%	CL21C150JCANNNN□
		30pF	±5%	CL10C300JC8NNN□			16pF	±2%	CL21C160GCANNNN□
		32pF	±2%	CL10C320GC8NNN□			16pF	±5%	CL21C160JCANNNN□
		33pF	±1%	CL10C330FC8NNN□			17pF	±5%	CL21C170JCANNNN□
		33pF	±5%	CL10C330JC8NNN□			18pF	±2%	CL21C180GCANNNN□
		39pF	±1%	CL10C390FC8NNN□			18pF	±5%	CL21C180JCANNNN□
		39pF	±5%	CL10C390JC8NNN□			20pF	±5%	CL21C200JCANNNN□
		47pF	±5%	CL10C470JC8NNN□			22pF	±5%	CL21C220JCANNNN□
		50pF	±5%	CL10C500JC8NNN□			24pF	±2%	CL21C240GCANNNN□
		52pF	±5%	CL10C520JC8NNN□			24pF	±5%	CL21C240JCANNNN□
		56pF	±5%	CL10C560JC8NNN□			25pF	±5%	CL21C250JCANNNN□
		62pF	±5%	CL10C620JC8NNN□			27pF	±5%	CL21C270JCANNNN□
		62pF	±10%	CL10C620KC8NNN□			30pF	±5%	CL21C300JCANNNN□
		68pF	±2%	CL10C680GC8NNN□			33pF	±2%	CL21C330GCANNNN□
		68pF	±5%	CL10C680JC8NNN□			33pF	±5%	CL21C330JCANNNN□
		82pF	±5%	CL10C820JC8NNN□			36pF	±5%	CL21C360JCANNNN□
		91pF	±5%	CL10C910JC8NNN□			38pF	±2%	CL21C380GCANNNN□
		95pF	±5%	CL10C950JC8NNN□			39pF	±2%	CL21C390GCANNNN□
		100pF	±5%	CL10C101JC8NNN□			39pF	±5%	CL21C390JCANNNN□
		110pF	±5%	CL10C111JC8NNN□			39pF	±10%	CL21C390KCANNNN□
		120pF	±5%	CL10C121JC8NNN□			40pF	±2%	CL21C400GCANNNN□
		150pF	±5%	CL10C151JC8NNN□			43pF	±2%	CL21C430GCANNNN□
		180pF	±5%	CL10C181JC8NNN□			43pF	±5%	CL21C430JCANNNN□
		180pF	±10%	CL10C181KC8NNN□			47pF	±5%	CL21C470JCANNNN□
		190pF	±5%	CL10C191JC8NNN□			51pF	±2%	CL21C510GCANNNN□
		200pF	±5%	CL10C201JC8NNN□			51pF	±5%	CL21C510JCANNNN□
		220pF	±5%	CL10C221JC8NNN□			56pF	±5%	CL21C560JCANNNN□
		220pF	±10%	CL10C221KC8NNN□			62pF	±5%	CL21C620JCANNNN□
							68pF	±5%	CL21C680JCANNNN□
							75pF	±5%	CL21C750JCANNNN□
							82pF	±5%	CL21C820JCANNNN□
							91pF	±2%	CL21C910GCANNNN□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Medium – High Voltage Capacitors

Product Line Up (COG)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.75mm	100Vdc	91pF	±5%	CL21C910JCANNN □
		100pF	±5%	CL21C101JCANNN □
		110pF	±5%	CL21C111JCANNN □
		120pF	±5%	CL21C121JCANNN □
		130pF	±5%	CL21C131JCANNN □
		150pF	±1%	CL21C151FCANNN □
		150pF	±5%	CL21C151JCANNN □
		160pF	±5%	CL21C161JCANNN □
		180pF	±2%	CL21C181GCANNN □
		180pF	±5%	CL21C181JCANNN □
		200pF	±5%	CL21C201JCANNN □
		220pF	±5%	CL21C221JCANNN □
		240pF	±5%	CL21C241JCANNN □
		270pF	±5%	CL21C271JCANNN □
		270pF	±10%	CL21C271KCANNN □
		300pF	±5%	CL21C301JCANNN □
		330pF	±5%	CL21C331JCANNN □
		360pF	±5%	CL21C361JCANNN □
		390pF	±5%	CL21C391JCANNN □
	200Vdc	100pF	±5%	CL21C101JDANN □
0.95mm	100Vdc	15pF	±5%	CL21C150JCCNNN □
		470pF	±2%	CL21C471GCCNNN □
		470pF	±5%	CL21C471JCCNNN □
		510pF	±5%	CL21C511JCCNNN □
		560pF	±1%	CL21C561FCCNNN □
		620pF	±5%	CL21C621JCCNNN □
		680pF	±5%	CL21C681JCCNNN □
	200Vdc	10pF	±0.5pF	CL21C100DDCCNNN □
		15pF	±5%	CL21C150JDCNNN □
		18pF	±2%	CL21C180GDCNNN □
		18pF	±5%	CL21C180JDCNNN □
		20pF	±2%	CL21C200GDCNNN □
		36pF	±2%	CL21C360GDCNNN □
		39pF	±2%	CL21C390GDCNNN □
		43pF	±2%	CL21C430GDCNNN □
		47pF	±5%	CL21C470JDCNNN □
		51pF	±5%	CL21C510JDCNNN □
		56pF	±2%	CL21C560GDCNNN □
		56pF	±5%	CL21C560JDCNNN □
		62pF	±2%	CL21C620GDCNNN □
		100pF	±2%	CL21C101GDCNNN □
		100pF	±5%	CL21C101JDCNNN □
		120pF	±5%	CL21C121JDCNNN □
		150pF	±5%	CL21C151JDCNNN □
		200pF	±5%	CL21C201JDCNNN □
		220pF	±5%	CL21C221JDCNNN □
	250Vdc	100pF	±10%	CL21C101KECNNN □
1.35mm	100Vdc	100pF	±5%	CL21C101JCFNNN □
		1.0nF	±2%	CL21C102GCFNNN □
		1.0nF	±5%	CL21C102JCFNNN □
		1.2nF	±5%	CL21C122JCFNNN □
		2.2nF	±5%	CL21C222JCFNNN □
	200Vdc	470pF	±5%	CL21C471JDFFNNN □
		1.0nF	±5%	CL21C102JDFNNN □

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
1.35mm	250Vdc	1.0nF	±5%	CL21C102JEFNNN □
		27pF	±5%	CL21C270JHFNNN □
		33pF	±5%	CL21C330JHFNNN □
		68pF	±5%	CL21C680JHFNNN □
		150pF	±5%	CL21C151JHFNNN □
		560pF	±5%	CL21C561JHFNNN □

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
1.00mm	100Vdc	10pF	±0.25pF	CL31C100CCCNNN □
		10pF	±0.5pF	CL31C100DCCNNN □
		10pF	±5%	CL31C100JCCNNN □
		11pF	±5%	CL31C110JCCNNN □
		12pF	±2%	CL31C120GCCNNN □
		12pF	±5%	CL31C120JCCNNN □
		15pF	±2%	CL31C150GCCNNN □
		15pF	±5%	CL31C150JCCNNN □
		18pF	±2%	CL31C180GCCNNN □
		18pF	±5%	CL31C180JCCNNN □
		20pF	±5%	CL31C200JCCNNN □
		22pF	±5%	CL31C220JCCNNN □
		24pF	±5%	CL31C240JCCNNN □
		27pF	±1%	CL31C270FCCNNN □
		27pF	±2%	CL31C270GCCNNN □
		27pF	±5%	CL31C270JCCNNN □
		30pF	±2%	CL31C300GCCNNN □
		30pF	±5%	CL31C300JCCNNN □
		30pF	±10%	CL31C300KCCNNN □
		33pF	±5%	CL31C330JCCNNN □
		36pF	±5%	CL31C360JCCNNN □
		39pF	±5%	CL31C390JCCNNN □
		43pF	±5%	CL31C430JCCNNN □
		51pF	±5%	CL31C510JCCNNN □
		56pF	±5%	CL31C560JCCNNN □
		62pF	±5%	CL31C620JCCNNN □
		68pF	±5%	CL31C680JCCNNN □
		75pF	±5%	CL31C750JCCNNN □
		82pF	±5%	CL31C820JCCNNN □
		91pF	±1%	CL31C910FCCNNN □
		91pF	±2%	CL31C910GCCNNN □
		91pF	±5%	CL31C910JCCNNN □
		100pF	±5%	CL31C101JCCNNN □
		110pF	±5%	CL31C111JCCNNN □
		120pF	±5%	CL31C121JCCNNN □
		130pF	±5%	CL31C131JCCNNN □
		180pF	±1%	CL31C181FCCNNN □
		180pF	±5%	CL31C181JCCNNN □
		200pF	±5%	CL31C201JCCNNN □
		220pF	±5%	CL31C221JCCNNN □
		240pF	±5%	CL31C241JCCNNN □
		270pF	±5%	CL31C271JCCNNN □
		300pF	±5%	CL31C301JCCNNN □

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (COG)

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.00mm	100Vdc	330pF	±1%	CL31C331FCCNNN □		1.40mm	500Vdc	470pF	±10%	CL31C471KGFNNN □	
		330pF	±5%	CL31C331JCCNNN □				560pF	±2%	CL31C561GGFNNN □	
		360pF	±5%	CL31C361JCCNNN □				560pF	±5%	CL31C561JGFNNN □	
		390pF	±5%	CL31C391JCCNNN □			630Vdc	10pF	±5%	CL31C100JHFNNN □	
		390pF	±10%	CL31C391KCCNNN □				12pF	±5%	CL31C120JHFNNN □	
		470pF	±1%	CL31C471FCCNNN □				15pF	±5%	CL31C150JHFNNN □	
		470pF	±2%	CL31C471GCCNNN □				18pF	±5%	CL31C180JHFNNN □	
		470pF	±5%	CL31C471JCCNNN □				22pF	±5%	CL31C220JHFNNN □	
		470pF	±10%	CL31C471KCCNNN □				22pF	±5%	CL31C220JHFNNC □	dv/dt
		510pF	±5%	CL31C511JCCNNN □				27pF	±5%	CL31C270JHFNNN □	
		560pF	±5%	CL31C561JCCNNN □				33pF	±5%	CL31C330JHFNNN □	
		680pF	±5%	CL31C681JCCNNN □				39pF	±5%	CL31C390JHFNNN □	
		750pF	±5%	CL31C751JCCNNN □				47pF	±2%	CL31C470GHFNNN □	
		820pF	±1%	CL31C821FCCNNN □				47pF	±5%	CL31C470JHFNNN □	
		910pF	±5%	CL31C911JCCNNN □				47pF	±5%	CL31C470JHFNNC □	dv/dt
		1.0nF	±5%	CL31C102JCCNNN □				47pF	±10%	CL31C470KHFNNN □	
		1.2nF	±5%	CL31C122JCCNNN □				56pF	±5%	CL31C560JHFNNN □	
		1.5nF	±5%	CL31C152JCCNNN □				68pF	±5%	CL31C680JHFNNN □	
		1.8nF	±5%	CL31C182JCCNNN □				82pF	±5%	CL31C820JHFNNN □	
		2.2nF	±5%	CL31C222JCCNNN □				100pF	±5%	CL31C101JHFNNN □	
	200Vdc	10pF	±0.5pF	CL31C100DDCNNN □				120pF	±5%	CL31C121JHFNNN □	
		15pF	±5%	CL31C150JDCNNN □				150pF	±5%	CL31C151JHFNNN □	
		36pF	±5%	CL31C360JDCNNN □				180pF	±5%	CL31C181JHFNNN □	
		51pF	±5%	CL31C510JDCNNN □				220pF	±5%	CL31C221JHFNNN □	
		100pF	±5%	CL31C101JDCNNN □				220pF	±10%	CL31C221KHFNNN □	
		200pF	±5%	CL31C201JDCNNN □				330pF	±5%	CL31C331JHFNNN □	
		220pF	±5%	CL31C221JDCNNN □				390pF	±5%	CL31C391JHFNNN □	
1.30mm	630Vdc	1.0nF	±5%	CL31C102JHMLNN □				470pF	±5%	CL31C471JHFNNN □	
1.40mm	200Vdc	1.0nF	±5%	CL31C102JDFNNN □		1kVdc	10pF	±5%	CL31C100JFNNN □		
		1.5nF	±5%	CL31C152JDFNNN □			12pF	±5%	CL31C120JFNNN □		
500Vdc	500Vdc	10pF	±5%	CL31C100JGFNNN □			15pF	±5%	CL31C150JFNNN □		
		15pF	±2%	CL31C150GGFNNN □			18pF	±5%	CL31C180JFNNN □		
		15pF	±5%	CL31C150JGFNNN □			22pF	±5%	CL31C220JFNNN □		
		20pF	±5%	CL31C200JGFNNN □			33pF	±5%	CL31C330JFNNN □		
		22pF	±5%	CL31C220JGFNNN □			39pF	±5%	CL31C390JFNNN □		
		39pF	±2%	CL31C390GGFNNN □			47pF	±5%	CL31C470JFNNN □		
		39pF	±5%	CL31C390JGFNNN □			56pF	±5%	CL31C560JFNNN □		
		47pF	±2%	CL31C470GGFNNN □			68pF	±5%	CL31C680JFNNN □		
		47pF	±5%	CL31C470JGFNNN □			82pF	±5%	CL31C820JFNNN □		
		68pF	±2%	CL31C680GGFNNN □			100pF	±5%	CL31C101JFNNN □		
		68pF	±5%	CL31C680JGFNNN □			100pF	±5%	CL31C101JFNNC □	dv/dt	
		82pF	±5%	CL31C820JGFNNN □			120pF	±5%	CL31C121JFNNN □		
		100pF	±2%	CL31C101GGFNNN □			150pF	±5%	CL31C151JFNNN □		
		100pF	±5%	CL31C101JGFNNN □			170pF	±5%	CL31C170JFNNN □		
		100pF	±10%	CL31C101KGFNNN □			200pF	±5%	CL31C200JFNNN □		
		150pF	±5%	CL31C151JGFNNN □			220pF	±5%	CL31C220JFNNN □		
		220pF	±2%	CL31C221GGFNNN □			250pF	±5%	CL31C250JFNNN □		
		220pF	±5%	CL31C221JGFNNN □			270pF	±5%	CL31C270JFNNN □		
		270pF	±2%	CL31C271GGFNNN □			300pF	±5%	CL31C300JFNNN □		
		270pF	±5%	CL31C271JGFNNN □			330pF	±5%	CL31C330JFNNN □		
		330pF	±5%	CL31C331JGFNNN □			360pF	±5%	CL31C360JFNNN □		
		470pF	±2%	CL31C471GGFNNN □			400pF	±5%	CL31C400JFNNN □		
		470pF	±5%	CL31C471JGFNNN □			430pF	±5%	CL31C430JFNNN □		
		470pF	±10%	CL31C471KGFNNN □			460pF	±5%	CL31C460JFNNN □		
		470pF	±15%	CL31C471LGFNNN □			490pF	±5%	CL31C490JFNNN □		
		470pF	±20%	CL31C471MGFNNN □			520pF	±5%	CL31C520JFNNN □		
		470pF	±25%	CL31C471NGFNNN □			550pF	±5%	CL31C550JFNNN □		
		470pF	±30%	CL31C471QGFNNN □			580pF	±5%	CL31C580JFNNN □		
		470pF	±35%	CL31C471RGFNNN □			610pF	±5%	CL31C610JFNNN □		
		470pF	±40%	CL31C471TGFNNN □			640pF	±5%	CL31C640JFNNN □		
		470pF	±45%	CL31C471VGFNNN □			670pF	±5%	CL31C670JFNNN □		
		470pF	±50%	CL31C471WGFNNN □			700pF	±5%	CL31C700JFNNN □		
		470pF	±55%	CL31C471XGFNNN □			730pF	±5%	CL31C730JFNNN □		
		470pF	±60%	CL31C471YGFNNN □			760pF	±5%	CL31C760JFNNN □		
		470pF	±65%	CL31C471ZGFNNN □			790pF	±5%	CL31C790JFNNN □		
		470pF	±70%	CL31C471AGFNNN □			820pF	±5%	CL31C820JFNNN □		
		470pF	±75%	CL31C471BGFNNN □			850pF	±5%	CL31C850JFNNN □		
		470pF	±80%	CL31C471CGFNNN □			880pF	±5%	CL31C880JFNNN □		
		470pF	±85%	CL31C471DGFNNN □			910pF	±5%	CL31C910JFNNN □		
		470pF	±90%	CL31C471EGFNNN □			940pF	±5%	CL31C940JFNNN □		
		470pF	±95%	CL31C471FGFNNN □			970pF	±5%	CL31C970JFNNN □		
		470pF	±100%	CL31C471GGFNNN □			1.0nF	±5%	CL31C101JHFNNN □		
		470pF	±110%	CL31C471HGFNNN □			1.2nF	±5%	CL31C122JHFNNN □		
		470pF	±120%	CL31C471IGFNNN □			1.5nF	±5%	CL31C152JHFNNN □		
		470pF	±130%	CL31C471JGFNNN □			1.8nF	±5%	CL31C182JHFNNN □		
		470pF	±140%	CL31C471KGFNNN □			2.0nF	±5%	CL31C202JHFNNN □		
		470pF	±150%	CL31C471LGFNNN □			2.2nF	±5%	CL31C222JHFNNN □		
		470pF	±160%	CL31C471MGFNNN □			2.4nF	±5%	CL31C242JHFNNN □		
		470pF	±170%	CL31C471NGFNNN □			2.6nF	±5%	CL31C262JHFNNN □		
		470pF	±180%	CL31C471QGFNNN □			2.8nF	±5%	CL31C282JHFNNN □		
		470pF	±190%	CL31C471RGFNNN □			3.0nF	±5%	CL31C302JHFNNN □		
		470pF	±200%	CL31C471TGFNNN □			3.2nF	±5%	CL31C322JHFNNN □		
		470pF	±210%	CL31C471VGFNNN □			3.4nF	±5%	CL31C342JHFNNN □		
		470pF	±220%	CL31C471WGFNNN □			3.6nF	±5%	CL31C362JHFNNN □		
		470pF	±230%	CL31C471XGFNNN □			3.8nF	±5%	CL31C382JHFNNN □		
		470pF	±240%	CL31C471ZGFNNN □			4.0nF	±5%	CL31C402JHFNNN □		
		470pF	±250%	CL31C471AGFNNN □			4.2nF	±5%	CL31C422JHFNNN □		
		470pF	±260%	CL31C471BGFNNN □			4.4nF	±5%	CL31C442JHFNNN □		
		470pF	±270%	CL31C471CGFNNN □			4.6nF	±5%	CL31C462JHFNNN □		
		470pF	±280%	CL31C471DGFNNN □			4.8nF	±5%	CL31C482JHFNNN □		
		470pF	±290%	CL31C471EGFNNN □			5.0nF	±5%	CL31C502JHFNNN □		
		470pF	±300%	CL31C471FGFNNN □			5.2nF	±5%	CL31C522JHFNNN □		
		470pF	±310%	CL31C471GGFNNN □			5.4nF	±5%	CL31C542JHFNNN □		
		470pF	±320%	CL31C471HGFNNN □			5.6nF	±5%	CL31C562JHFNNN □		
		470pF	±330%	CL31C471IGFNNN □			5.8nF	±5%	CL31C582JHFNNN □		
		470pF	±340%	CL31C471KGFNNN □			6.0nF	±5%	CL31C		

Medium – High Voltage Capacitors

Product Line Up (C0G)

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.80mm	250Vdc	8.2nF	±5%	CL31C822JEHNNN□	
	500Vdc	1.0nF	±2%	CL31C102GGHNNN□	
		1.0nF	±5%	CL31C102JGHNNN□	
		1.5nF	±5%	CL31C152JGHNNN□	
		2.2nF	±5%	CL31C222JGHNNN□	
	630Vdc	680pF	±5%	CL31C681JHHNNN□	
		1.0nF	±5%	CL31C102JHHNNN□	
		1.0nF	±5%	CL31C102JJHNNNC□	dv/dt
		1.2nF	±5%	CL31C122JHHNNN□	
		1.5nF	±5%	CL31C152JHHNNN□	
1kVdc		2.2nF	±5%	CL31C222JHHNNN□	
		2.7nF	±5%	CL31C272JHHNNN□	
		3.3nF	±5%	CL31C332JHHNNN□	
		33pF	±5%	CL31C330JIHNNN□	
		150pF	±5%	CL31C151JIHNNN□	
		180pF	±5%	CL31C181JIHNNN□	
		220pF	±5%	CL31C221JIHNNN□	
		220pF	±5%	CL31C221JIHNNC□	dv/dt
		270pF	±5%	CL31C271JIHNNN□	
		270pF	±5%	CL31C271JIHNNC□	dv/dt
2kVdc		330pF	±5%	CL31C331JIHNNN□	
		330pF	±5%	CL31C331JIHNNC□	dv/dt
		470pF	±5%	CL31C471JIHNNN□	
		470pF	±5%	CL31C471JIHNNC□	dv/dt
		10pF	±5%	CL31C100JJHNNN□	
		10pF	±5%	CL31C100JJHNNC□	dv/dt
		15pF	±5%	CL31C150JJHNNN□	
		22pF	±5%	CL31C220JJHNNN□	
		33pF	±5%	CL31C330JJHNNN□	
		47pF	±5%	CL31C470JJHNNN□	

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.45mm	100Vdc	1.0nF	±10%	CL32C102KCFNNN□	
		1.5nF	±10%	CL32C152KCFNNN□	
		4.7nF	±5%	CL32C472JCFNNN□	
	500Vdc	680pF	±5%	CL32C681JGFNNN□	
		330pF	±5%	CL32C331JIFNNN□	
		100pF	±5%	CL32C101JJFNNN□	
	2kVdc	100pF	±10%	CL32C101KJFNNN□	
		150pF	±5%	CL32C151JJFNNN□	
		1.8nF	±5%	CL32C182JJHNNN□	
1.80mm	630Vdc	470pF	±5%	CL32C471JIHNNN□	
	1kVdc	220pF	±5%	CL32C221JJHNNN□	
	2kVdc	330pF	±5%	CL32C331JJINNN□	
	2.20mm	6.8nF	±10%	CL32C682KHJNNN□	
		8.2nF	±5%	CL32C822JHJNNN□	
		470pF	±5%	CL32C471JJJNNN□	

■ Size : 4.50 X 2.00mm (inch : 1808)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.45mm	3kVdc	5pF	±5%	CL42C050JKFNNN□	
		10pF	±5%	CL42C100JKFNNN□	
		12pF	±5%	CL42C120JKFNNN□	
		15pF	±5%	CL42C150JKFNNN□	
		18pF	±5%	CL42C180JKFNNN□	
		22pF	±5%	CL42C220JKFNNN□	
		27pF	±5%	CL42C270JKFNNN□	
		33pF	±5%	CL42C330JKFNNN□	
		47pF	±5%	CL42C470JKFNNN□	
		68pF	±5%	CL42C680JKFNNN□	
1.80mm	2kVdc	220pF	±5%	CL42C221JJHNNN□	
	3kVdc	150pF	±5%	CL42C151JKINNN□	

■ Size : 4.50 X 3.20mm (inch : 1812)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.45mm	100Vdc	10nF	±5%	CL43C103JCFNNN□	
	1kVdc	820pF	±5%	CL43C821JIHNNN□	
		1.0nF	±5%	CL43C102JIHNNN□	
	2.20mm	1.2nF	±5%	CL43C122JJINNN□	
		22nF	±5%	CL43C223JHJNNN□	
		1.3nF	±5%	CL43C132JJJNNN□	
	2.70mm	1.5nF	±5%	CL43C152JJJNNN□	
		1.6nF	±5%	CL43C162JJJNNN□	
		1.8nF	±5%	CL43C182JJJNNN□	

■ Size : 5.70 X 5.00mm (inch : 2220)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.70mm	3kVdc	1.0nF	±5%	CL55C102JKJNNN□	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (X7R)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	100Vdc	220pF	±10%	CL10B221KC8NNN□	
		470pF	±10%	CL10B471KC8NNN□	
		680pF	±5%	CL10B681JC8NNN□	
		1.0nF	±10%	CL10B102KC8NNN□	
		1.5nF	±10%	CL10B152KC8NNN□	
		1.8nF	±10%	CL10B182KC8NNN□	
		2.2nF	±10%	CL10B222KC8NNN□	
		2.7nF	±10%	CL10B272KC8NNN□	
		3.3nF	±5%	CL10B332JC8NNN□	
		3.3nF	±10%	CL10B332KC8NNN□	
		3.9nF	±10%	CL10B392KC8NNN□	
		4.7nF	±10%	CL10B472KC8NNN□	
		10nF	±10%	CL10B103KC8NNN□	
		100nF	±10%	CL10B104KC8NNN□	

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.75mm	100Vdc	100pF	±5%	CL21B101JCANNN□	
		220pF	±10%	CL21B221KCANNN□	
		270pF	±10%	CL21B271KCANNN□	
		330pF	±5%	CL21B331JCANNN□	
		330pF	±10%	CL21B331KCANNN□	
		470pF	±10%	CL21B471KCANNN□	
		1.0nF	±5%	CL21B102JCANNN□	
		1.0nF	±10%	CL21B102KCANNN□	
		1.5nF	±10%	CL21B152KCANNN□	
		2.2nF	±10%	CL21B222KCANNN□	
		3.3nF	±10%	CL21B332KCANNN□	
		3.9nF	±10%	CL21B392KCANNN□	
		4.7nF	±10%	CL21B472KCANNN□	
		6.8nF	±10%	CL21B682KCANNN□	
		8.2nF	±10%	CL21B822KCANNN□	
		10nF	±5%	CL21B103JCANNN□	
		10nF	±10%	CL21B103KCANNN□	
		15nF	±10%	CL21B153KCANNN□	
		18nF	±10%	CL21B183KCANNN□	
		22nF	±5%	CL21B223KCANNN□	
		22nF	±10%	CL21B223KDCNNN□	
0.95mm	100Vdc	15nF	±10%	CL21B153KCCNNN□	
		330pF	±10%	CL21B331KDCNNN□	
		470pF	±10%	CL21B471KDCNNN□	
		560pF	±10%	CL21B561KDCNNN□	
		1.0nF	±5%	CL21B102JDCNNN□	
		1.0nF	±10%	CL21B102KDCNNN□	
		1.5nF	±10%	CL21B152KDCNNN□	
		2.2nF	±10%	CL21B222KDCNNN□	
		3.3nF	±10%	CL21B332KDCNNN□	
		4.7nF	±10%	CL21B472KDCNNN□	
1.35mm	100Vdc	6.8nF	±10%	CL21B682KDCNNN□	
		10nF	±10%	CL21B103KDCNNN□	
		560pF	±10%	CL21B561KECNNN□	
		22nF	±10%	CL21B223KCFNNN□	
		27nF	±10%	CL21B273KCFNNN□	
		33nF	±10%	CL21B333KCFNNN□	
		47nF	±10%	CL21B473KCFNNN□	
		68nF	±10%	CL21B683KCFNNN□	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.00mm	100Vdc	330pF	±10%	CL31B331KCCNNN□	
		470pF	±10%	CL31B471KCCNNN□	
		1.0nF	±10%	CL31B102KCCNNN□	
		1.5nF	±10%	CL31B152KCCNNN□	
		2.2nF	±10%	CL31B222KCCNNN□	
		2.7nF	±5%	CL31B272JCCNNN□	
		3.3nF	±10%	CL31B332KCCNNN□	
		3.9nF	±10%	CL31B392KCCNNN□	
		4.7nF	±10%	CL31B472KCCNNN□	
		6.8nF	±10%	CL31B682KCCNNN□	
		10nF	±10%	CL31B103KCCNNN□	
		18nF	±10%	CL31B183KCCNNN□	
		22nF	±10%	CL31B223KCCNNN□	
		22nF	±20%	CL31B473MCCNNN□	
		47nF	±10%	CL31B471KDCNNN□	
		680pF	±10%	CL31B681KDCNNN□	
1.40mm	100Vdc	1.0nF	±10%	CL31B102KDCNNN□	
		2.2nF	±10%	CL31B222KDCNNN□	
		3.3nF	±10%	CL31B332KDCNNN□	
		4.7nF	±10%	CL31B472KDCNNN□	
		6.8nF	±10%	CL31B682KDCNNN□	
		10nF	±10%	CL31B103KDCNNN□	
		15nF	±10%	CL31B153KDCNNN□	
		18nF	±10%	CL31B183KDCNNN□	
		22nF	±5%	CL31B223JDCNNN□	
		22nF	±10%	CL31B223KDCNNN□	
1.40mm	200Vdc	470pF	±10%	CL31B471KDFNNN□	
		680pF	±10%	CL31B681KDFNNN□	
		100nF	±10%	CL31B104KDFNNN□	
		100nF	±5%	CL31B104KCFNNN□	
		33nF	±10%	CL31B333KDFNNN□	
		47nF	±10%	CL31B473KDFNNN□	
		22nF	±10%	CL31B223KEFNNN□	
		220pF	±10%	CL31B221KGFFNNN□	
		470pF	±10%	CL31B471KGFFNNN□	
		470pF	±20%	CL31B471MGFNNN□	
1.40mm	500Vdc	560pF	±10%	CL31B561KGFFNNN□	
		680pF	±10%	CL31B681KGFFNNN□	
		1.0nF	±10%	CL31B102KGFFNNN□	
		1.0nF	±20%	CL31B102MGFNNN□	
		1.0nF	±10%	CL31B103KGFFNNN□	
		1.5nF	±10%	CL31B152KGFFNNN□	
		1.8nF	±5%	CL31B182JGFNNN□	

Medium – High Voltage Capacitors

Product Line Up (X7R)

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.40mm	500Vdc	1.8nF	±10%	CL31B182KGFNNN □	
		2.2nF	±10%	CL31B222KGFNNN □	
		2.2nF	±20%	CL31B222MGFNNN □	
		2.7nF	±10%	CL31B272KGFNNN □	
		3.3nF	±10%	CL31B332KGFNNN □	
		4.7nF	±10%	CL31B472KGFNNN □	
		6.8nF	±10%	CL31B682KGFNNN □	
		8.2nF	±10%	CL31B822KGFNNN □	
		10nF	±10%	CL31B103KGFNNN □	
		12nF	±10%	CL31B123KGFNNN □	
	630Vdc	15nF	±10%	CL31B153KGFNNN □	
		220pF	±10%	CL31B221KHFNNN □	
		330pF	±10%	CL31B331KHFNNN □	
		470pF	±10%	CL31B471KHFNNN □	
		560pF	±10%	CL31B561KHFNNN □	
		680pF	±10%	CL31B681KHFNNN □	
		1.0nF	±10%	CL31B102KHFNNN □	
		1.5nF	±10%	CL31B152KHFNNN □	
		2.2nF	±10%	CL31B222KHFNNN □	
		3.3nF	±10%	CL31B332KHFNNN □	
		4.7nF	±10%	CL31B472KHFNNN □	
		6.8nF	±10%	CL31B682KHFNNN □	
		8.2nF	±5%	CL31B822JHFNNN □	
		10nF	±10%	CL31B103KHFNNN □	
		15nF	±10%	CL31B153KHFNNN □	
1.80mm	1kVdc	680pF	±10%	CL31B681KIFNNN □	Derating
		1.0nF	±10%	CL31B102KIFNNN □	Derating
		2.2nF	±10%	CL31B222KIFNNN □	Derating
		2.5nF	±10%	CL31B252KIFNNN □	Derating
		3.3nF	±5%	CL31B332JIFNNN □	Derating
		4.7nF	±10%	CL31B472KIFNNN □	Derating
	2kVdc	150nF	±10%	CL31B154KCHNNN □	
		220nF	±10%	CL31B224KCHNNN □	
		470nF	±10%	CL31B474KCHNNN □	
		1.0uF	±10%	CL31B105KCHNNN □	
		68nF	±10%	CL31B683KDHNNN □	
1.45mm	2kVdc	100nF	±10%	CL31B104KDHNNN □	
		33nF	±10%	CL31B333KEHNNN □	
		39nF	±10%	CL31B393KEHNNN □	
		47nF	±10%	CL31B473KEHNNN □	
		100nF	±10%	CL31B104KEHNNN □	
	3kVdc	33nF	±10%	CL31B333KGHNNN □	
		22nF	±10%	CL31B223KHHNNN □	
		220pF	±10%	CL31B221KJHNNN □	Derating
		470pF	±10%	CL31B471KJHNNN □	Derating
		1.0nF	±10%	CL31B102KJHNNN □	Derating
		1.0nF	±20%	CL31B102MJHNNN □	Derating
		1.5nF	±10%	CL31B152KJHNNN □	Derating
1.80mm	3kVdc	47nF	±10%	CL31B473KJHNNN □	Derating
		100nF	±10%	CL32B222KCFNNN □	
		150nF	±10%	CL32B222KCFNNN □	
		220nF	±10%	CL32B222KCFNNN □	
		330nF	±10%	CL32B222KCFNNN □	
	4kVdc	47nF	±20%	CL32B472MHFNNN □	
		1.0uF	±10%	CL32B472KIFNNN □	Derating
		1.0uF	±20%	CL32B102KJFNNN □	
		220nF	±10%	CL32B224JCHNNN □	
		330nF	±10%	CL32B224KCHNNN □	
1.80mm	4kVdc	47nF	±10%	CL32B473KEHNNN □	
		1.0uF	±10%	CL32B473KGHNNN □	
		33nF	±10%	CL32B333KHHNNN □	
		33nF	±20%	CL32B334KCINNN □	
		470nF	±10%	CL32B474KCINNN □	
	5kVdc	33nF	±10%	CL32B334KCINNN □	
		1.0uF	±10%	CL32B105KCJNNN □	
		1.0uF	±20%	CL32B434KCJNNN □	
		430nF	±10%	CL32B434MCJNNN □	
		430nF	±20%	CL32B474KCJNNN □	
1.80mm	5kVdc	470nF	±10%	CL32B104KEJNNN □	
		1.0uF	±10%	CL32B154KEJNNN □	
		1.0uF	±20%	CL32B434KEJNNN □	
		150nF	±10%	CL32B154KEJNNN □	
		150nF	±20%	CL32B474KEJNNN □	
	6kVdc	1.0uF	±10%	CL32B104KEJNNN □	
		1.0uF	±20%	CL32B434KEJNNN □	
		1.0uF	±30%	CL32B474KEJNNN □	
		1.0uF	±40%	CL32B154KEJNNN □	
		1.0uF	±50%	CL32B474KEJNNN □	

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.45mm	500Vdc	2.2nF	±10%	CL32B222KCFNNN □	
		4.7nF	±10%	CL32B472KCFNNN □	
		10nF	±10%	CL32B103KCFNNN □	
		47nF	±10%	CL32B473KCFNNN □	
		100nF	±5%	CL32B104JCFNNN □	
		100nF	±10%	CL32B104KCFNNN □	
		150nF	±10%	CL32B154KCFNNN □	
		10nF	±10%	CL32B103KDFNNN □	
		1.8nF	±5%	CL32B182JGFNNN □	
		10nF	±10%	CL32B103KGFNNN □	
	630Vdc	10nF	±20%	CL32B103MGFNNN □	
		15nF	±20%	CL32B153MGFNNN □	
		22nF	±10%	CL32B223KGFNNN □	
		4.7nF	±20%	CL32B472MHFNNN □	
		1.0nF	±10%	CL32B472KIFNNN □	Derating
1.80mm	1kVdc	1.0nF	±10%	CL32B102KJFNNN □	
		220nF	±10%	CL32B224KCHNNN □	
		330nF	±10%	CL32B334KCHNNN □	
		47nF	±10%	CL32B473KEHNNN □	
		47nF	±10%	CL32B473KGHNNN □	
	2kVdc	33nF	±10%	CL32B333KHHNNN □	
		33nF	±20%	CL32B334KCINNN □	
		470nF	±10%	CL32B474KCINNN □	
		1.0uF	±10%	CL32B105KCJNNN □	
		1.0uF	±20%	CL32B434KCJNNN □	
1.80mm	2kVdc	430nF	±10%	CL32B434MCJNNN □	
		430nF	±20%	CL32B474KCJNNN □	
		1.0uF	±10%	CL32B105KEJNNN □	
		1.0uF	±20%	CL32B434KEJNNN □	
		1.0uF	±30%	CL32B474KEJNNN □	
	3kVdc	1.0uF	±10%	CL32B104KEJNNN □	
		1.0uF	±20%	CL32B434KEJNNN □	
		1.0uF	±30%	CL32B474KEJNNN □	
		1.0uF	±40%	CL32B154KEJNNN □	
		1.0uF	±50%	CL32B474KEJNNN □	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (X7R)

■ Size : 4.50 X 2.00mm (inch : 1808)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.45mm	1kVdc	1.0nF	±10%	CL42B102KIFNNN □	
	2kVdc	1.0nF	±10%	CL42B102KJFNNN □	

■ Size : 5.70 X 5.00mm (inch : 2220)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.70mm	100Vdc	1.80mm	100Vdc	820nF	±10%
		2kVdc	10nF	±10%	CL55B103KJHNNN □
		470nF	±10%	CL55B474KCJNNN □	
		2.2uF	±10%	CL55B225KCJNNN □	
		3.3uF	±10%	CL55B335KCJNNN □	
		4.7uF	±10%	CL55B475KCJNNN □	
		630Vdc	220nF	±10%	CL55B224KHJNNN □

■ Size : 4.50 X 3.20mm (inch : 1812)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.45mm	100Vdc	100nF	±10%	CL43B104KCFNNN □	
		100nF	±20%	CL43B104MCFNNN □	
		220nF	±10%	CL43B224KCFNNN □	
		330nF	±10%	CL43B334KCFNNN □	
	200Vdc	1.0nF	±10%	CL43B102KDFNNN □	
		47nF	±10%	CL43B473KDFNNN □	
		47nF	±20%	CL43B473MDFN NN □	
		100nF	±10%	CL43B104KDFNNN □	
	500Vdc	3.3nF	±10%	CL43B332KGFFNNN □	
		10nF	±10%	CL43B103KGFFNNN □	
		22nF	±10%	CL43B223KGFFNNN □	
		33nF	±10%	CL43B333KGFFNNN □	
		47nF	±10%	CL43B473KGFFNNN □	
	1kVdc	1.0nF	±10%	CL43B102KIFNNN □	
		1.5nF	±10%	CL43B152KIFNNN □	
		2.2nF	±10%	CL43B222KIFNNN □	
		2.7nF	±10%	CL43B272KIFNNN □	
		3.3nF	±10%	CL43B332KIFNNN □	
		4.7nF	±10%	CL43B472KIFNNN □	
		5.0nF	±10%	CL43B502KIFNNN □	
		10nF	±10%	CL43B103KIFNNN □	
		10nF	±20%	CL43B103MIFNNN □	
	2kVdc	1.0nF	±10%	CL43B102KJFNNN □	
		1.5nF	±10%	CL43B152KJFNNN □	
		2.2nF	±10%	CL43B222KJFNNN □	
1.80mm	100Vdc	470nF	±10%	CL43B474KCHNNN □	
		470nF	±20%	CL43B474MCHNNN □	
2.20mm	500Vdc	100nF	±10%	CL43B104KGJNNN □	
2.70mm	100Vdc	680nF	±10%	CL43B684KCJNNN □	
		820nF	±10%	CL43B824KCJNNN □	
		1.0uF	±10%	CL43B105KCJNNN □	
	200Vdc	470nF	±10%	CL43B474KDJNNN □	
		220nF	±10%	CL43B224KEJNNN □	
		220nF	±20%	CL43B224MEJNNN □	
		470nF	±10%	CL43B474KEJNNN □	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Soft – term Capacitors

Feature





- Soft – Termination relaxes the applied thermal/mechanical stresses by ductile properties of metal-polymer composites.
- Excellent bending strength
- Durability against thermal shock / cycles.

Application

- | | |
|---|--|
| <ul style="list-style-type: none"> - Mobile Phone - DC – DC Converter - Tablet devices | <ul style="list-style-type: none"> - PC (Laptop, Desktop) - HDD / SSD board - Display |
|---|--|

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
03	0201	0.60±0.03	0.30±0.03	0.30±0.03	3	0.15±0.05
05	0402	1.00±0.05	0.50±0.05	0.50±0.05	5	
		1.00±0.05	0.50±0.05	0.60±0.10	6	0.25±0.10
10	0603	1.00±0.05	0.50±0.05	0.70±0.10	7	
		1.60±0.10	0.80±0.10	0.80±0.10	8	0.30±0.20
21	0805	2.00±0.10	1.25±0.10	0.60±0.10	6	
		2.00±0.10	1.25±0.10	0.85±0.10	C	
		2.00±0.10	1.25±0.10	1.25±0.10	F	
		2.00±0.15	1.25±0.15	1.25±0.15	Q	
		2.00±0.20	1.25±0.20	1.25±0.20	Y	
31	1206	3.20±0.15	1.60±0.15	0.85±0.15	C	
		3.20±0.15	1.60±0.15	1.10±0.15	E	
		3.20±0.15	1.60±0.15	1.25±0.15	F	
		3.20±0.20	1.60±0.20	1.60±0.20	H	
		3.20±0.15	1.60±0.15	1.15±0.10	P	0.50±0.30

Soft – term Capacitance Table (X5R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance																		
		nF						uF												
		100	150	220	330	470	680	1.0	1.5	2.2	3.3	4.7	6.8	10	15	22	33	47	68	100
0201 (0603)	6.3																			
	10																			
0402 (1005)	6.3																			
	10																			
0603 (1608)	6.3																			
	10																			
1206(3216)	25																			

Soft – term Capacitance Table (X7R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance																			
		nF										uF									
		1.0	1.5	6.8	10	15	22	33	47	68	100	150	220	330	470	680	1.0	1.5	2.2	3.3	4.7
0805(2012)	250																				
	25																				
	50																				
	100																				
	250																				
	350																				
1206 (3216)	35																				
	50																				
	100																				
1210 (3225)	35																				
	50																				
	100																				

Soft - term Capacitors

Product Line Up (X5R)

■ Size : 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.33mm	10Vdc	100nF	±10%	CL03A104KP3ZNN □	Derating Ref.
0.35mm	6.3Vdc	1.0uF	±20%	CL03A105MQ3ZSN □	Derating Ref.
	10Vdc	1.0uF	±20%	CL03A105MP3ZSN □	Derating Ref.
0.39mm	6.3Vdc	2.2uF	±20%	CL03A225MQ3ZRN □	Derating Ref.

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.57mm	10Vdc	2.2uF	±10%	CL05A225KP5ZSN □	Derating Ref.
0.65mm	6.3Vdc	4.7uF	±20%	CL05A475MQ5ZRN □	Derating Ref.
	10Vdc	4.7uF	±10%	CL05A475KP5ZRN □	Derating Ref.
0.70mm	6.3Vdc	10uF	±20%	CL05A106MQ5ZUN □	Derating Ref.
	10Vdc	10uF	±20%	CL05A106MP5ZUN □	Derating Ref.
0.80mm	6.3Vdc	22uF	±20%	CL05A226MQ6ZUN □	Derating
0.90mm	6.3Vdc	22uF	±20%	CL05A226MQ7ZUN □	Derating

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	6.3Vdc	10uF	±20%	CL10A106MQ8ZQN □	Ref.
1.05mm	6.3Vdc	22uF	±20%	CL10A226MQ8ZUN □	Derating
	10Vdc	22uF	±20%	CL10A226MP8ZUN □	Derating

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.80mm	25Vdc	22uF	±10%	CL31A226KAHZNN □	
	25Vdc	22uF	±10%	CL31A226KAHZUN □	

Product Line Up (X7R)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	250Vdc	1.0nF	±10%	CL21B102KECSNN □	

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.00mm	350Vdc	10nF	±10%	CL31B103KFCSNN □	
	350Vdc	22nF	±10%	CL31B223KFCSNN □	
1.25mm	350Vdc	33nF	±10%	CL31B333KFESEN □	
	25Vdc	10uF	±10%	CL31B106KAHSNN □	
	50Vdc	1.0uF	±10%	CL31B105KBHSNN □	
	100Vdc	220nF	±10%	CL31B224KCHSNN □	
	100Vdc	1.0uF	±10%	CL31B105KCHSNN □	
1.80mm	25Vdc	2.2uF	±10%	CL31B225KCHSNN □	
	250Vdc	100nF	±10%	CL31B104KEHSNN □	

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.00mm	35Vdc	4.7uF	±10%	CL32B475KLUYNN □	
	50Vdc	4.7uF	±10%	CL32B475KBUYNN □	
2.70mm	100Vdc	1.0uF	±10%	CL32B105KCJSNN □	
	100Vdc	2.2uF	±10%	CL32B225KCJSNN □	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Low Acoustic Noise Capacitor

Feature




- Equivalent electrical characteristics as general products.
- Reduced acoustic noise due to the thick bottom cover.
- Pin-to-pin replacement without changing the substrate land pattern.

Application

- | | |
|---|---|
| <ul style="list-style-type: none"> - PAM (GSM / TD-SCDMA / TDD-LTE) - PMIC - DC-DC Converter | <ul style="list-style-type: none"> - Tablet devices - PC (Laptop, Desktop) - HDD / SSD board |
|---|---|

Structure and Dimensions




Structure (Size & Thickness)

- | | |
|--|---|
| Same Dielectric Thickness
as Standard MLCC
Normal Bottom Cover | Same Dielectric Thickness
as Standard MLCC
Thick Bottom Cover |
|--|---|

Performance

- | | |
|---|---|
| Acoustic Noise Reduction
without Changing Layout | Significant Acoustic Noise Reduction
without Changing Layout |
|---|---|



Size Code	EIA Code	Dimension(mm)					
		L	W	T	Thickness Code	Size Tol. Code	BW
03	0201	0.60±0.05	0.30±0.05	0.30±0.05	3	S	0.15±0.05
		1.00±0.07	0.50±0.07	0.50±0.07	5	S	0.25±0.10
		1.00±0.15	0.50±0.15	0.50±0.15	5	R	
		1.00±0.20	0.50±0.20	0.50±0.20	5	U	
		1.00±0.07	0.50±0.07	0.70±0.10	7	S	
		1.00±0.15	0.50±0.15	0.70±0.10	7	R	
		1.00±0.20	0.50±0.20	0.80±0.10	8	U	
05	0402	1.60±0.10	0.80±0.10	0.80±0.10	8	N	0.30±0.20
		1.60±0.20	0.80±0.20	0.80±0.20	8	R	
		1.60±0.25	0.80±0.25	0.80±0.25	8	U	
		1.60±0.10	0.80±0.10	0.90±0.10	9	H	
		1.60±0.20	0.80±0.20	0.85±0.10	C	R	
		1.60±0.25	0.80±0.25	0.85±0.10	C	U	
		1.60±0.10	0.80±0.10	0.95±0.10	N	H	
		1.60±0.25	0.80±0.25	1.05±0.10	O	U	
		1.60±0.20	0.80±0.20	1.10±0.10	E	R	0.50 +0.20 / -0.30
		1.60±0.25	0.80±0.25	1.15±0.10	M	U	
21	0805	2.00±0.20	1.25±0.20	1.10±0.10	E	R	
		2.00±0.20	1.25±0.20	1.15±0.10	M	R	
		2.00±0.15	1.25±0.15	1.25±0.15	Q	N	

Low Acoustic Noise Capacitor

Low Acoustic Noise Capacitance Table (HMC* / X5R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance(uF)				
		2.2	4.7	10	22	47
0402 (1005)	6.3					
	10					
0603 (1608)	6.3					
	10					
0805 (2012)	6.3					
	25					

* HMC : Horizontally Mounted Capacitor

Low Acoustic Noise Capacitance Table (T - HMC* / X5R)

Size inch (mm)	T max. (mm)	Rated Voltage (Vdc)	Capacitance(uF)				
			2.2	4.7	10	22	47
0402 (1005)	0.8	6.3					
		10					
	0.9	6.3					
		10					
0603 (1608)	0.95	10					
	1.0	10					
	1.05	6.3					
		10					
	1.2	6.3					
0805 (2012)	1.25	10					
	1.2	25					
	1.7	25					

* T- HMC : Thick & Horizontally Mounted Capacitor

Product Line Up (HMC* / X5R)

Size L × W (mm / inch)	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	
0.6 × 0.3 (0201)	0.35mm	10Vdc	1.0uF	±20%	CL03A105MP3NSNZ	<small>Derating Ref.</small>	
1.0 × 0.5 (0402)	0.57mm	6.3Vdc	2.2uF	±20%	CL05A225MQ5NSNZ	<small>Ref.</small>	
		10Vdc	2.2uF	±10%	CL05A225KP5NSNZ	<small>Derating Ref.</small>	
	0.65mm	6.3Vdc	4.7uF	±20%	CL05A475MQ5NRNZ	<small>Derating Ref.</small>	
		10Vdc	4.7uF	±10%	CL05A475KP5NRNZ	<small>Derating Ref.</small>	
	0.70mm	6.3Vdc	10uF	±20%	CL05A106MQ5NUNZ	<small>Derating Ref.</small>	
		10Vdc	10uF	±20%	CL05A106MP5NUNZ	<small>Derating Ref.</small>	
		25Vdc	2.2uF	±20%	CL05A225MA5NUNZ	<small>Derating Ref.</small>	
1.6 × 0.8 (0603)	0.90mm	6.3Vdc	2.2uF	±10%	CL10A225KQ8NNNNZ		
			4.7uF	±10%	CL10A475KQ8NNNNZ		
		10Vdc	2.2uF	±10%	CL10A225KP8NNNNZ		
			4.7uF	±10%	CL10A475KP8NNNNZ		
			10uF	±10%	CL10A106KP8NNNNZ	<small>Derating Ref.</small>	
			10uF	±20%	CL10A106MP8NNNNZ	<small>Derating Ref.</small>	
		1.00mm	6.3Vdc	22uF	±20%	CL10A226MQ8NRRN	<small>Derating</small>
		1.05mm	10Vdc	22uF	±20%	CL10A226MP8NUNR	<small>Derating</small>
2.0 × 1.25 (0805)	1.35mm	6.3Vdc	47uF	±20%	CL21A476MQMNRN	<small>Derating</small>	
		6.3Vdc	22uF	±20%	CL21A226MQQNNNR		
	1.40mm	25Vdc	4.7uF	±10%	CL21A475KAQNNNR	<small>Derating</small>	

* HMC : Horizontally Mounted Capacitor

Product Line Up (T - HMC* / X5R)

Size L × W (mm / inch)	Thickness Max. (mm)	Rated Voltage (Vdc)	Capacitance	Capacitance Tolerance	Part Number	Remark	
1.0 × 0.5 (0402)	0.80mm	6.3Vdc	2.2uF	±10%	CL05A225KQ7NSB8	<small>Ref.</small>	
			4.7uF	±20%	CL05A475MQ7NRB8	<small>Derating Ref.</small>	
		10Vdc	2.2uF	±10%	CL05A225KP7NSB8	<small>Derating Ref.</small>	
			4.7uF	±20%	CL05A475MP7NRB8	<small>Derating Ref.</small>	
	0.90mm	6.3Vdc	10uF	±20%	CL05A106MQ8NUB8	<small>Derating Ref.</small>	
			10uF	±20%	CL05A106MP8NUB8	<small>Derating Ref.</small>	
	1.6 × 0.8 (0603)	0.95mm	22uF	±20%	CL10A226MQCNRBE	<small>Derating</small>	
			22uF	±20%	CL10A226MPCNUBE	<small>Derating</small>	
		1.00mm	10Vdc	4.7uF	±10%	CL10A475KP9NHBC	
		1.05mm	6.3Vdc	10uF	±20%	CL10A106MQNNHBC	<small>Ref.</small>
			10Vdc	10uF	±20%	CL10A106MPNNHBC	<small>Derating Ref.</small>
		1.15mm	6.3Vdc	22uF	±20%	CL10A226MQONUBE	<small>Derating</small>
		1.20mm	6.3Vdc	47uF	±20%	CL10A476MQENRBE	<small>Derating</small>
		1.25mm	10Vdc	22uF	±20%	CL10A226MPMNUBE	<small>Derating</small>
			6.3Vdc	22uF	±20%	CL10A226MQMNUBE	<small>Derating</small>
2.0 × 1.25 (0805)	1.20mm	25Vdc	10uF	±10%	CL21A106KAENRBE	<small>Derating</small>	

* T-HMC : Thick & Horizontally Mounted Capacitor

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148


In order to move to the page directly, please click the here. ↑

High Effective Capacitance Capacitors

Feature




- Wide selection of size : from 0402(inch) to 1210(inch)
- When a DC bias is applied, a capacitance is higher than conventional products.
- Highly reliable performance
- Reduced capacitance degradation by bias and aging
- DC - bias performance (Graph) :



Application

- | | |
|--|--|
| <ul style="list-style-type: none"> - HDD / SSD board - Display - Digital Camera | <ul style="list-style-type: none"> - Lighting - Mobile Phone - PC (Laptop, Desktop) |
|--|--|

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
05	0402	1.00 ± 0.05	0.50 ± 0.05	0.50 ± 0.05	5	0.25 ± 0.10
10	0603	1.60 ± 0.10	0.80 ± 0.10	0.80 ± 0.10	8	0.30 ± 0.20
21	0805	2.00 ± 0.20	1.25 ± 0.20	$0.85 \pm 0.10(*)$	C	$0.50+0.2/-0.30$
		2.00 ± 0.10	1.25 ± 0.10	1.25 ± 0.10	F	
		2.00 ± 0.15	1.25 ± 0.15	1.25 ± 0.15	Q	
31	1206	3.20 ± 0.20	1.60 ± 0.20	$0.85 \pm 0.10(*)$	C	0.50 ± 0.30
		3.20 ± 0.20	1.60 ± 0.20	1.60 ± 0.20	H	
32	1210	3.20 ± 0.30	2.50 ± 0.20	$1.80 \pm 0.20(*)$	U	0.60 ± 0.30
		3.20 ± 0.30	2.50 ± 0.20	2.50 ± 0.20	J	

* Mark is only applicable to "L", "Y", "F", 12th code in part number.

High Effective Capacitance Table (X5R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance(nF)		Capacitance(uF)				
		680	820	1.0	2.2	4.7	10	22
0402 (1005)	6.3							
	16							
0603 (1608)	6.3							
	10							
	16							
	25							
0805 (2012)	4.0							
	6.3							
	10							
	16							
	25							
1206 (3216)	16							
	25							

High Effective Capacitance Table (X6S)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance(uF)				
		1.0	2.2	4.7	10	22
0402(1005)	10					
	6.3					
0603 (1608)	10					
	16					
	25					
	10					
1206 (3216)	16					
	25					

High Effective Capacitance Table (X7R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance(uF)				
		1.0	2.2	4.7	10	22
0805 (2012)	10					
	25					
	50					
1206 (3216)	10					
	50					
1210 (3225)	25					
	50					

High Effective Capacitance Capacitors

Product Line Up (X5R)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	6.3Vdc	1.0uF	±10%	CL10A105KQ8N3N □	
	10Vdc	680nF	±10%	CL10A684KP8N3N □	
		820nF	±10%	CL10A824KP8N3N □	
	16Vdc	1.0uF	±10%	CL10A105KO8N3N □	
		2.2uF	±10%	CL10A225KO8N3N □	

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	6.3Vdc	10uF	±10%	CL21A106KQCL3R □	
	10Vdc	10uF	±10%	CL21A106KPCL3R □	Derating
	16Vdc	10uF	±10%	CL21A106KOCL3R □	Derating
1.35mm	6.3Vdc	10uF	±10%	CL21A106KQFN3N □	
	10Vdc	10uF	±10%	CL21A106KP FN3N □	
	16Vdc	10uF	±10%	CL21A106KO FN3N □	Derating
	25Vdc	4.7uF	±10%	CL21A475KAFN3N □	Derating
		10uF	±10%	CL21A106KAFN3N □	Derating
1.40mm	4.0Vdc	10uF	±10%	CL21A106KRQN3N □	
	6.3Vdc	4.7uF	±10%	CL21A475KQQN3N □	Ref.
		10uF	±10%	CL21A106KQQN3N □	Ref.

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	16Vdc	10uF	±10%	CL31A106KOCL3N □	Derating
	25Vdc	4.7uF	±10%	CL31A475KACL3N □	
		10uF	±10%	CL31A106KACL3N □	Derating
1.80mm	25Vdc	22uF	±10%	CL31A226KAHN3N □	Derating

Product Line Up (X7R)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.35mm	10Vdc	4.7uF	±10%	CL21B475KPFN3N □	Ref.
	25Vdc	1.0uF	±10%	CL21B105KAFN3N □	
		2.2uF	±10%	CL21B225KAFN3N □	
	50Vdc	1.0uF	±10%	CL21B105KB FN3N □	

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.80mm	10Vdc	10uF	±10%	CL31B106KPHN3N □	
	50Vdc	4.7uF	±10%	CL31B475KBHN3N □	

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.00mm	25Vdc	10uF	±10%	CL32B106KAUL3N □	
2.70mm	50Vdc	4.7uF	±10%	CL32B475KBJN3N □	

Product Line Up (X6S)

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	25Vdc	10uF	±10%	CL31X106KACL3N □	Derating
	10Vdc	22uF	±10%	CL31X226KPHN3N □	Derating
	16Vdc	22uF	±10%	CL31X226KOHN3N □	Derating
	25Vdc	22uF	±10%	CL31X226KAHN3N □	Derating

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Low ESL Capacitors _ LICC

Low Inductance Ceramic Capacitor

Feature




- Low ESL, good for noise reduction for high frequency
- Highly reliable performance
- Tape & reel for surface mount assembly

Application

- High Speed Microprocessor
- High Frequency Digital Equipment

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
L5	0204	0.52±0.05	1.00±0.05	0.30±0.05	3	0.18±0.06
L6	0304	0.60±0.05	1.00±0.05	0.40±0.05	4	0.18±0.10
01	0306	0.80±0.05	1.60±0.20	0.50±0.05/-0.10	5	0.25±0.15

Low ESL Capacitance Table

Size inch (mm)	Rated Voltage (Vdc)	Capacitance(uF)						
		0.01	0.1	0.22	0.47	1.0	2.2	4.3
0204 (0510)	2.5					X7S		
	4.0				X6S			
	6.3		X7T					
0304(0610)	4.0						X5R	
	4.0			X7S				
0306 (0816)	6.3		X7R					
	10		X7R					
	25	X7R						

Product Line Up

EIA Code	Size L x W	Thickness Max.	Rated Voltage	TC Code	Capacitance	Capacitance Tolerance	Part Number	Remark
0204	0.50mm x 1.00mm	0.35mm	2.5Vdc	X7T	1.0uF	±20%	CLL5Z105MS3NLN□	
			4.0Vdc	X6S	470nF	±20%	CLL5X474MR3NLN□	
				X6S	1.0uF	±20%	CLL5X105MR3NLN□	
			6.3Vdc	X7S	100nF	±20%	CLL5Y104MQ3NLN□	
0304	0.60mm x 1.00mm	0.45mm	4.0Vdc	X5R	4.3uF	±20%	CLL6A435MR4NLN□	
0306	0.80mm x 1.60mm	0.55mm	4.0Vdc	X7S	100nF	±20%	CL01Y104MR5NLN□	
				X7S	1.0uF	±20%	CL01Y105MR5NLN□	
			6.3Vdc	X7R	100nF	±10%	CL01B104KQ5NLN□	
			10Vdc	X7R	100nF	±10%	CL01B104KP5NLN□	
			25Vdc	X7R	10nF	±10%	CL01B103KA5NLN□	

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Low ESL Capacitors _ SLIC

Super Low Inductance Capacitor

Feature




- Low ESL, good for noise reduction for high frequency
- Highly reliable performance
- Tape & reel for surface mount assembly

Application

- High Speed Microprocessor
- High Frequency Digital Equipment

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)						
		L	W	T	Thickness Code	BW	SW	P
10	0603	1.60±0.10	0.80±0.10	0.50+0.05/-0.10	5	0.25±0.10	0.15±0.10	0.40±0.10
21	0805	2.00±0.10	1.25±0.10	0.50+0.05/-0.10	5	0.25+0.15/-0.10	0.20+0.15/-0.10	0.50±0.10

Low ESL Capacitance Table

Size inch (mm)	T max. (mm)	Rated Voltage (Vdc)	Capacitance(uF)						
			0.1	0.22	0.47	0.68	1.0	2.2	4.3
0603(1608)	0.55	4.0		X7S				X7S	
0805(2012)	0.55	4.0			X7R			X7S	

Product Line Up

EIA Code	Size L x W	Thickness Max.	Rated Voltage	TC Code	Capacitance	Capacitance Tolerance	Part Number
0603	1.60mm x 0.80mm	0.55mm	4.0Vdc	X7S	100nF	±20%	CL10Y104MR5NJJ □
				X7S	470nF	±20%	CL10Y474MR5NJJ □
				X7S	1.0uF	±20%	CL10Y105MR5NJJ □
				X7S	2.2uF	±20%	CL10Y225MR5NJJ □
0805	2.00mm x 1.25mm	0.55mm	4.0Vdc	X7S	2.2uF	±20%	CL21Y225MR5NJJ □
				X7R	470nF	±20%	CL21B474MQ5NJJ □
				X7R	680nF	±20%	CL21B684MQ5NJJ □

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Low ESL Capacitors _ 3T

3-Terminal Capacitor

Feature





- Low ESL, good for noise reduction for high frequency
- Highly reliable performance
- Tape & reel for surface mount assembly

Application

- High Speed Microprocessor
 - CPU / GPU for PC & Game console
 - AP for Smartphone
 - Network IC
- High Frequency Digital Equipment

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)						
		L	W	T	Thickness Code	BW		
						A	B	C
05	0402	1.05±0.05	0.65±0.05	0.45±0.05	5	0.17±0.10	0.35±0.10	0.15±0.10
19	0503	1.20±0.05	0.90±0.05	0.75±0.05	7	0.15±0.10	0.50±0.10	0.20±0.10

Low ESL Capacitance Table

Size inch (mm)	T max. (mm)	Rated Voltage (Vdc)	Capacitance(uF)					
			1.0	2.2	4.3	10	22	47
0402(1005)	0.5	4.0			X5R			
0503(1209)	0.8	4.0					X5R	

Product Line Up

EIA Code	Size L x W	Thickness Max.	Rated Voltage	TC Code	Capacitance	Capacitance Tolerance	Part Number
0402	1.00mm x 0.50mm	0.50mm	4.0Vdc	X5R	4.3uF	±20%	CL05A435MR5NWN□
0503	1.20mm x 0.90mm	0.80mm	4.0Vdc	X5R	22uF	±20%	CL19A226MR7NWN□


※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Low ESL Capacitors _ VLC

Vertically Laminated Capacitor

Feature




- Lowest ESL, good for noise reduction for high frequency
- Highly reliable performance
- Tape & reel for surface mount assembly

Application

- High Speed Microprocessor
 - CPU / GPU for PC & Game console
 - AP for Smartphone
 - Network IC
- High Frequency Digital Equipment

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)						Band Gap
		L	W	T	Thickness Code	Band Width		
21	0805	2.00 ± 0.10	1.25 ± 0.10	0.70 ± 0.10	7	0.42 ± 0.10	0.74 ± 0.10	0.21 ± 0.05
				0.90 ± 0.10	9			

Low ESL Capacitance Table

Size inch (mm)	T max. (mm)	Rated Voltage (Vdc)	Capacitance(uF)						
			1.0	2.2	3.3	4.7	10	22	47
0805(2012)	0.8	4.0							X5R
	1.0	4.0							X5R

Product Line Up

EIA Code	Size L x W	Thickness Max.	Rated Voltage	TC Code	Capacitance	Capacitance Tolerance	Part Number
0805	2.00mm x 1.25mm	0.80mm	4.0Vdc	X5R	47uF	±20%	CL21A476MR7NVN□
		1.00mm		X5R	47uF	±20%	CL21A476MR9NVN□

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Low ESL Capacitors _ X2Y®

Feature





- One device for EMI suppression or decoupling
- Differential and common mode attenuation
- Matched capacitance line to ground, both lines

Application

- Amplifier Filter & Decoupling
- High Speed Data Filtering
- EMC I / O Filtering
- FPGA / ASIC / u - P Decoupling
- DDR Memory Decoupling

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)					
		L	W	T	Thickness Code	e1	e2
10	0603	1.60±0.15	0.80±0.10	0.60±0.10	6	0.25±0.15	0.45±0.15

Low ESL Capacitance Table

Size inch (mm)	T max. (mm)	Rated Voltage (Vdc)	Capacitance							
			nF			uF				
			1.0	2.2	4.7	0.1	0.22	0.47	1.0	
0603 (1608)	0.7	6.3	6.3			X7R			X5R	
			10						X5R	
			16			X7R				
			25							
			50	X7R						
			100		X7R					

Product Line Up

EIA Code	Size L x W	Thickness Max.	Rated Voltage	TC Code	Capacitance	Capacitance Tolerance	Part Number
0603	1.60mm x 0.80mm	0.70mm	6.3Vdc	X7R	220nF	±20%	CL10B224MQ6NXN□
				X5R	1.0uF	±20%	CL10A105MQ6NXN□
			10Vdc	X5R	470nF	±20%	CL10A474MP6NXN□
				X5R	1.0uF	±20%	CL10A105MP6NXN□
			16Vdc	X7R	100nF	±20%	CL10B104M06NXN□
				X7R	220nF	±20%	CL10B224M06NXN□
			50Vdc	X7R	1.0nF	±20%	CL10B102MB6NXN□
				X7R	2.2nF	±20%	CL10B222MC6NXN□
			100Vdc	X7R	4.7nF	±20%	CL10B472MC6NXN□
				X7R			

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Array Type Capacitors

Feature



- Reduction in required space (more than 50%)
- Reduction in cost and time for replacement of PCB
- Reduction in amount of solder joints
- Easier PCB design
- Reduced waste from tape and reel packaging process
- It protect EMI bypassing digital signal line noise


Application

- A bypass for digital and analog signal line noise generated by telecommunication equipment and other common electronic circuits


Structure and Dimensions

CL	14	A	105	M	A	5	N	A	N	C
1	2	3	4	5	6	7	8	9	10	11

■ A : ARRAY (2 -element)



■ B : ARRAY (4 -element)



Code	Size (mm)	EIA Code	Dimension(mm)					
			L	W	T	BW	SW	P
A	0906	0302	0.90±0.05	0.60±0.05	0.45±0.05	0.25±0.05	0.15±0.10	0.45±0.05
A	1410	0504	1.37±0.15	1.00±0.15	0.35±0.05	0.36±0.10	0.20±0.10	0.64±0.10
					0.50±0.05			
					0.60±0.06			
					0.80±0.08			
A	2012	0805	2.00±0.15	1.25±0.15	0.85±0.10	0.50±0.20	0.25±0.15	1.00±0.10
B	2012	0805	2.00±0.15	1.25±0.15	0.85±0.10	0.25±0.10	0.25±0.15	0.50±0.10
B	3216	1206	3.20±0.15	1.60±0.15	0.85±0.15	0.40±0.20	0.30±0.15	0.80±0.20

Array Type capacitance Table (C0G / X5R / X7R)

TC	Size inch (mm)	Type	Rated Voltage (Vdc)	T max. (mm)	Capacitance(pF)										
					10	22	27	47	100	470					
C0G	0504(1410)	2 - element	25	0.88				47							
	1206(3216)	4 - element	50	1.00											
X5R	0504(1410)	2 - element	25	0.95	Capacitance(nF)										
					1.0	2.2	4.7	10	22	47	100	220	470	1000	2200
					4.0										
					6.3										
					10										
					16										
					25										
					35										
					50										
					70										
X7R	0805(2012)	4 - element	10	0.95					47						
					16				47						
	1206(3216)	4 - element	25	1.00					47						
					50				47						
					70				47						

Array Type Capacitors

Product Line Up (C0G / X5R)

■ Size : 0.90 X 0.60mm (inch : 0302)

Element Type	Thickness Max.	Rated Voltage	TC Code	Capacitance	Capacitance Tolerance	Part Number	Remark
2 - Array	0.50mm	4.0Vdc	X5R	1.0uF	±20%	CL09A105MR4NAN □	Derating
		6.3Vdc	X5R	100nF	±10%	CL09A104KQ4SAN □	Derating
		10Vdc	X5R	1.0uF	±20%	CL09A105MQ4NAN □	Derating

■ Size : 1.40 X 1.00mm (inch : 0504)

Element Type	Thickness Max.	Rated Voltage	TC Code	Capacitance	Capacitance Tolerance	Part Number	Remark
2 - Array	0.66mm	25Vdc	C0G	27pF	±10%	CL14C270KA6NAN □	
	0.40mm	10Vdc	X5R	1.0uF	±20%	CL14A105MP3NAN □	Derating
		16Vdc	X5R	1.0uF	±20%	CL14A105M03NAN □	Derating
	0.55mm	25Vdc	X5R	1.0uF	±20%	CL14A105MA5NAN □	Derating
	0.66mm	10Vdc	X5R	100nF	±10%	CL14A104KP6NAN □	
		25Vdc	X5R	100nF	±10%	CL14A104KA6NAN □	
	0.88mm	10Vdc	X5R	1.0uF	±10%	CL14A105KP8NAN □	Derating
		X5R		2.2uF	±10%	CL14A225KP8NAN □	Derating
		16Vdc	X5R	1.0uF	±20%	CL14A105M08NAN □	Derating

Product Line Up (C0G / X5R / X7R)

■ Size : 2.00 X 1.25mm (inch : 0805)

Element Type	Thickness Max.	Rated Voltage	TC Code	Capacitance	Capacitance Tolerance	Part Number	Remark
2 - Array	0.95mm	10Vdc	X5R	1.0uF	±20%	CL21A105MPCNAN □	
		16Vdc	X5R	1.0uF	±10%	CL21A105KOCNAN □	
4 - Array	0.95mm	10Vdc	X7R	100nF	±20%	CL21B104MPCNBN □	
		16Vdc	X7R	100nF	±10%	CL21B104KOCNBN □	
		50Vdc	X7R	470pF	±10%	CL21B471KBCNBN □	

■ Size : 3.20 X 1.60mm (inch : 1206)

Element Type	Thickness Max.	Rated Voltage	TC Code	Capacitance	Capacitance Tolerance	Part Number	Remark
4 - Array	1.00mm	50Vdc	COG	10pF	±5%	CL31C100JBCNBN □	
			COG	15pF	±5%	CL31C150JBCNBN □	
			COG	22pF	±5%	CL31C220JBCNBN □	
			COG	27pF	±5%	CL31C270JBCNBN □	
			COG	33pF	±10%	CL31C330KBCNBN □	
			COG	39pF	±10%	CL31C390KBCNBN □	
			COG	68pF	±5%	CL31C680JBCNBN □	
			COG	82pF	±5%	CL31C820JBCNBN □	
			COG	100pF	±5%	CL31C101JBCNBN □	
			COG	150pF	±10%	CL31C151KBCNBN □	
			COG	180pF	±5%	CL31C181JBCNBN □	
			COG	330pF	±5%	CL31C331JBCNBN □	
			COG	470pF	±5%	CL31C471JBCNBN □	
	1.00mm	16Vdc	X7R	100nF	±10%	CL31B104KOCNBN □	
		25Vdc	X7R	47nF	±10%	CL31B473KACNBN □	
			X7R	100nF	±10%	CL31B104KACNBN □	
	50Vdc	X7R		1.0nF	±20%	CL31B102MBCNBN □	
		X7R	10nF	±20%	CL31B103MBCNBN □		
		X7R	15nF	±10%	CL31B153KBCNBN □		

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Industrial Capacitors Part Numbering System

CL	32	B	106	K	A	J	N	N	W	E
1	2	3	4	5	6	7	8	9	10	11

* SEMCO MLCC use 15 – digit Part Numbering system.

	8 9 10 Code	Meaning
Standard Termination	NNW	Industrial Capacitors (Networks, Power, etc)
	NFN	Industrial Capacitors for Power Application
	GQW / GNW	High Q Industrial Capacitors
	N3W	High Effective Capacitance Industrial Capacitors
Soft Termination	ZW6 / SW6	Soft – Termination(3mm) Industrial Capacitors
	ZNW / SNW	Soft – termination Industrial Capacitors
	ZFN / SFN / YFN	Soft – termination Capacitors for Power Application
Reinforced Soft Termination	Z46	Reinforced Soft – Termination(3mm) Industrial Capacitors
	Z4J	Reinforced Soft – Termination(5mm) Industrial Capacitors

* For the meaning of 8 (N, G, S, Z, and Y), please refer to the Page 05 (Part Numbering System).

Feature




- Rated voltage 6.3V~250V
- temperature range -55°C to +125°C (X7R / C0G), -55°C to +85°C (X5R), case size 0201 to 2220
- Special outgoing inspection for industrial application (HALT, etc)

Application

- Network, Power application and etc.
- Ideal for decoupling and filtering applications (Class II : X5R/X7R/X6S)
- Impedance matching, tuning, coupling in high frequency circuit (Class I : C0G)

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
03	0201	0.60±0.03	0.30±0.03	0.30±0.03	3	0.15±0.05
05	0402	1.00±0.05	0.50±0.05	0.50±0.05	5	0.25±0.10
10	0603	1.60±0.10	0.80±0.10	0.80±0.10	8	0.30±0.20
21	0805	2.00±0.10	1.25±0.10	0.65±0.10	A	0.50+0.20/-0.30
				0.85±0.10	C	
				1.15±0.10	M	
				1.25±0.10	F	
31	1206	3.20±0.15	1.60±0.15	0.85±0.15	C	0.50±0.30
				1.25±0.15	F	
				1.60±0.20	H	
32	1210	3.20±0.30	2.50±0.20	1.25±0.20	F	0.60±0.30
				1.60±0.20	H	
				2.00±0.20	I	
				2.50±0.20	J	
42	1808	4.50±0.40	2.00±0.20	1.25±0.20	F	0.80±0.30
				1.60±0.20	H	
				2.00±0.20	I	
43	1812	4.50±0.40	3.20±0.30	1.25±0.20	F	0.80±0.30
				1.60±0.20	H	
				2.00±0.20	I	
				2.50±0.20	J	
55	2220	5.70±0.40	5.00±0.40	2.50±0.20	J	1.00±0.30

Industrial Capacitors

NNW – C0G / X5R / X6S / X7R / X7S

Industrial Capacitance Table (C0G)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance(pF)						
		0.2	0.5	1.0	10	22	47	100
0201(0603)	25							

Size inch (mm)	Rated Voltage (Vdc)	Capacitance																	
		pF									nF								
1.0, 1.0, 10, 12, 15, 18, 22, 33, 47, 56, 91, 100, 120, 180, 220, 240, 270, 330, 390, 470, 560, 680, 910	1.0, 1.2, 1.8, 2.2, 2.7, 4.7, 5.6, 8.2, 10, 27, 33, 47, 68, 100																		
0402 (1005)	25																		
	50																		
	100																		
0603 (1608)	25																		
	50																		
	100																		
0805 (2012)	25																		
	50																		
	100																		
	200																		
	250																		
1206 (3216)	25																		
	50																		
	100																		
	200																		
	500																		
1210 (3225)	2k																		
	50																		
	100																		
1812(4532)	1k																		
1812(4532)	50																		

Industrial Capacitance Table (X5R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance																				
		pF				nF								uF								
		220	330	470	680	1.0	2.2	3.3	4.7	10	15	22	33	47	68	100	220	470	1.0	2.2	3.3	4.7
0201 (0603)	4.0															80	120					
	6.3																120	180				
	10															120	180					

Size inch (mm)	Rated Voltage (Vdc)	Capacitance											
		nF			uF								
		100	220	470	1.0	2.2	4.7	10	22	47	100	220	
0402 (1005)	4.0												
	6.3												
	10			20									
	16		10										
0603 (1608)	4.0												
	6.3												
	10												
	16												
	25												
0805 (2012)	4.0												
	6.3												
	10												
	16												
	25												
1206 (3216)	6.3												
	10												
	16												
	25												
1210 (3225)	6.3												
	10												
	16												
	25												

Industrial Capacitors

NNW – COG / X5R / X6S / X7R / X7S

Industrial Capacitance Table (X6S)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance(uF)										
		0.1	0.22	0.47	1.0	2.2	4.7	10	22	47	100	220
0402 (1005)	4.0											
	6.3											
	10											
0603 (1608)	4.0											
	6.3											
	10											
0805 (2012)	4.0											
	6.3											
1206(3216)	4.0											
1210 (3225)	6.3											
	10											
	16											

Industrial Capacitance Table (X7R / X7S)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance												
		pF					nF							
		100	220	330	470	680	1.0	2.2	3.3	4.7	6.8	10	22	47
0201 (0603)	10													
	16													
	25													

Size inch (mm)	Rated Voltage (Vdc)	Capacitance																							
		nF										uF													
		4.7	10	15	22	33	47	68	100	120	150	220	330	470	680	1.0	2.2	3.3	4.7	6.8	10	22	47	100	
0402 (1005)	6.3														X7S										
	10																								
	16																								
	25																								
	50																								
0603 (1608)	6.3																								X7S
	10																								
	16																								
	25																								
	50																								
	100																								

Industrial Capacitance Table (X7R / X7S)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance																					
		nF												uF									
		4.7	10	15	22	33	47	68	100	120	150	220	330	470	680	1.0	2.2	3.3	4.7	6.8	10	22	47
0805 (2012)	6.3																						
	10																						
	16																						
	25																						
	50																						
	100																						
	200																						
1206 (3216)	6.3																						
	10																						
	16																						
	25																						
	35																						
	50																						
	100																						
	200																						
	250																						
	500	6.8																					
1210 (3225)	2k	2.2																					
	6.3																						
	10																						
	16																						
	25																						
	50																						
	100																						
	200																						
	500																						
	630																						
1812 (4532)	2k	1																					
	100																						
	200																						
	500																						
	630																						
2220(5750)	1k																						
	100																						

Industrial Capacitors

NNW - COG / X5R / X65 / X7R / X7S

Product Line Up (COG)

■ Size : 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.33mm	25Vdc	4.7pF	±0.25pF	CL03C4R7CA3GNW□
		10pF	±0.50pF	CL03C100DA3GNW□
		12pF	±5%	CL03C120JA3NNW□
		15pF	±5%	CL03C150JA3NNW□
		27pF	±5%	CL03C270JA3NNW□
		33pF	±5%	CL03C330JA3NNW□
		47pF	±5%	CL03C470JA3NNW□
		56pF	±5%	CL03C560JA3NNW□
		68pF	±5%	CL03C680JA3NNW□
		82pF	±5%	CL03C820JA3NNW□
		100pF	±5%	CL03C101JA3NNW□

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	25Vdc	82pF	±10%	CL05C820KA5NNW□
		150pF	±5%	CL05C151JA5NNW□
		220pF	±5%	CL05C221JA5NNW□
	50Vdc	0.1pF	±0.05pF	CL05C0R1AB5GNW□
		0.1pF	±0.1pF	CL05C0R1BB5GNW□
		0.2pF	±0.05pF	CL05C0R2AB5GNW□
		0.2pF	±0.1pF	CL05C0R2BB5GNW□
		0.3pF	±0.05pF	CL05C0R3AB5GNW□
		0.3pF	±0.1pF	CL05C0R3BB5GNW□
		0.4pF	±0.05pF	CL05C0R4AB5GNW□
		0.4pF	±0.1pF	CL05C0R4BB5GNW□
		0.5pF	±0.05pF	CL05C0R5AB5GNW□
		0.5pF	±0.1pF	CL05C0R5BB5GNW□
		0.6pF	±0.05pF	CL05C0R6AB5GNW□
		0.6pF	±0.1pF	CL05C0R6BB5GNW□
		0.7pF	±0.05pF	CL05C0R7AB5GNW□
		0.7pF	±0.1pF	CL05C0R7BB5GNW□
		0.8pF	±0.05pF	CL05C0R8AB5GNW□
		0.8pF	±0.1pF	CL05C0R8BB5GNW□
		0.9pF	±0.05pF	CL05C0R9AB5GNW□
		0.9pF	±0.1pF	CL05C0R9BB5GNW□
		1.0pF	±0.05pF	CL05C010AB5GNW□
		1.0pF	±0.1pF	CL05C010BB5GNW□
		1.0pF	±0.25pF	CL05C010CB5NNW□
		1.0pF	±0.25pF	CL05C010CB5GNW□
		1.1pF	±0.05pF	CL05C1R1AB5GNW□
		1.1pF	±0.1pF	CL05C1R1BB5GNW□
		1.1pF	±0.25pF	CL05C1R1CB5GNW□
		1.2pF	±0.05pF	CL05C1R2AB5GNW□
		1.2pF	±0.1pF	CL05C1R2BB5GNW□
		1.2pF	±0.25pF	CL05C1R2CB5GNW□
		1.3pF	±0.05pF	CL05C1R3AB5GNW□
		1.3pF	±0.1pF	CL05C1R3BB5GNW□
		1.3pF	±0.25pF	CL05C1R3CB5GNW□
		1.5pF	±0.05pF	CL05C1R5AB5GNW□
		1.5pF	±0.1pF	CL05C1R5BB5GNW□
		1.5pF	±0.25pF	CL05C1R5CB5GNW□
		1.6pF	±0.05pF	CL05C1R6AB5GNW□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (COG)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	50Vdc	5.6pF	±0.05pF	CL05C5R6AB5GNW□	0.55mm	50Vdc	12pF	±5%	CL05C120JB5NNW□
		5.6pF	±0.1pF	CL05C5R6BB5GNW□			12pF	±5%	CL05C120JB5GNW□
		5.6pF	±0.25pF	CL05C5R6CB5NNW□			15pF	±1%	CL05C150FB5GNW□
		5.6pF	±0.25pF	CL05C5R6CB5GNW□			15pF	±2%	CL05C150GB5GNW□
		5.6pF	±0.5pF	CL05C5R6DB5GNW□			15pF	±5%	CL05C150JB5GNW□
		6.0pF	±0.05pF	CL05C060AB5GNW□			18pF	±1%	CL05C180FB5GNW□
		6.0pF	±0.1pF	CL05C060BB5GNW□			18pF	±2%	CL05C180GB5GNW□
		6.0pF	±0.25pF	CL05C060CB5GNW□			18pF	±5%	CL05C180JB5NNW□
		6.0pF	±0.5pF	CL05C060DB5GNW□			18pF	±5%	CL05C180JB5GNW□
		6.2pF	±0.05pF	CL05C6R2AB5GNW□			20pF	±1%	CL05C200FB5GNW□
		6.2pF	±0.1pF	CL05C6R2BB5GNW□			20pF	±2%	CL05C200GB5GNW□
		6.2pF	±0.25pF	CL05C6R2CB5GNW□			20pF	±5%	CL05C200JB5GNW□
		6.2pF	±0.5pF	CL05C6R2DB5GNW□			22pF	±1%	CL05C220FB5GNW□
		6.8pF	±0.05pF	CL05C6R8AB5GNW□			22pF	±2%	CL05C220GB5GNW□
		6.8pF	±0.1pF	CL05C6R8BB5NNW□			22pF	±5%	CL05C220JB5NNW□
		6.8pF	±0.1pF	CL05C6R8BB5GNW□			22pF	±5%	CL05C220JB5GNW□
		6.8pF	±0.25pF	CL05C6R8CB5NNW□			24pF	±1%	CL05C240FB5GNW□
		6.8pF	±0.25pF	CL05C6R8CB5GNW□			24pF	±2%	CL05C240GB5GNW□
		6.8pF	±0.5pF	CL05C6R8DB5GNW□			24pF	±5%	CL05C240JB5NNW□
		7.0pF	±0.05pF	CL05C070AB5GNW□			24pF	±5%	CL05C240JB5GNW□
		7.0pF	±0.1pF	CL05C070BB5GNW□			27pF	±1%	CL05C270FB5GNW□
		7.0pF	±0.25pF	CL05C070CB5GNW□			27pF	±2%	CL05C270GB5GNW□
		7.0pF	±0.5pF	CL05C070DB5GNW□			27pF	±5%	CL05C270JB5NNW□
		7.5pF	±0.05pF	CL05C7R5AB5GNW□			27pF	±5%	CL05C270JB5GNW□
		7.5pF	±0.1pF	CL05C7R5BB5GNW□			33pF	±1%	CL05C330FB5GNW□
		7.5pF	±0.25pF	CL05C7R5CB5GNW□			33pF	±2%	CL05C330GB5GNW□
		7.5pF	±0.5pF	CL05C7R5DB5GNW□			33pF	±5%	CL05C330JB5NNW□
		8.0pF	±0.05pF	CL05C080AB5GNW□			33pF	±5%	CL05C330JB5GNW□
		8.0pF	±0.1pF	CL05C080BB5GNW□			39pF	±1%	CL05C390FB5GNW□
		8.0pF	±0.25pF	CL05C080CB5GNW□			39pF	±2%	CL05C390GB5GNW□
		8.0pF	±0.5pF	CL05C080DB5GNW□			39pF	±5%	CL05C390JB5NNW□
		8.2pF	±0.05pF	CL05C8R2AB5GNW□			39pF	±5%	CL05C390JB5GNW□
		8.2pF	±0.1pF	CL05C8R2BB5NNW□			47pF	±1%	CL05C470FB5GNW□
		8.2pF	±0.1pF	CL05C8R2BB5GNW□			47pF	±2%	CL05C470GB5GNW□
		8.2pF	±0.25pF	CL05C8R2CB5GNW□			47pF	±5%	CL05C470JB5NNW□
		8.2pF	±0.5pF	CL05C8R2DB5GNW□			47pF	±5%	CL05C470JB5GNW□
		9.0pF	±0.05pF	CL05C090AB5GNW□			51pF	±5%	CL05C510JB5NNW□
		9.0pF	±0.1pF	CL05C090BB5GNW□			56pF	±5%	CL05C560JB5NNW□
		9.0pF	±0.25pF	CL05C090CB5GNW□			68pF	±5%	CL05C680JB5NNW□
		9.0pF	±0.5pF	CL05C090DB5GNW□			82pF	±5%	CL05C820JB5NNW□
		9.1pF	±0.05pF	CL05C9R1AB5GNW□			82pF	±10%	CL05C820KB5NNW□
		9.1pF	±0.1pF	CL05C9R1BB5GNW□			100pF	±5%	CL05C101JB5NNW□
		9.1pF	±0.25pF	CL05C9R1CB5GNW□			120pF	±5%	CL05C121JB5NNW□
		9.1pF	±0.5pF	CL05C9R1DB5GNW□			150pF	±5%	CL05C151JB5NNW□
		10pF	±1%	CL05C100FB5GNW□			180pF	±5%	CL05C181JB5NNW□
		10pF	±2%	CL05C100GB5GNW□			270pF	±1%	CL05C271FB5NNW□
		10pF	±5%	CL05C100JB5NNW□			270pF	±5%	CL05C271JB5NNW□
		10pF	±5%	CL05C100JB5GNW□			330pF	±5%	CL05C331JB5NNW□
		11pF	±1%	CL05C110FB5GNW□			390pF	±1%	CL05C391FB5NNW□
		11pF	±2%	CL05C110GB5GNW□			390pF	±5%	CL05C391JB5NNW□
		11pF	±5%	CL05C110JB5GNW□			470pF	±1%	CL05C471FB5NNW□
		12pF	±1%	CL05C120FB5GNW□			470pF	±5%	CL05C471JB5NNW□
		12pF	±2%	CL05C120GB5NNW□			560pF	±5%	CL05C561JB5NNW□
		12pF	±2%	CL05C120GB5GNW□			680pF	±5%	CL05C681JB5NNW□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Industrial Capacitors

NNW – COG / X5R / X6S / X7R / X7S

Product Line Up (COG)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	50Vdc	820pF	±5%	CL05C821JB5NNW□
		1.0nF	±5%	CL05C102JB5NNW□
	100Vdc	47pF	±5%	CL05C470JC5NNW□

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.90mm	50Vdc	1.0pF	±0.25pF	CL10C010CB8NNW□
		1.2pF	±0.25pF	CL10C1R2CB8NNW□
		1.5pF	±0.1pF	CL10C1R5BB8NNW□
		1.5pF	±0.25pF	CL10C1R5CB8NNW□
		2.2pF	±0.1pF	CL10C2R2BB8NNW□
		2.2pF	±0.25pF	CL10C2R2CB8NNW□
		2.7pF	±0.1pF	CL10C2R7BB8NNW□
		2.7pF	±0.25pF	CL10C2R7CB8NNW□
		3.3pF	±0.1pF	CL10C3R3BB8NNW□
		3.3pF	±0.25pF	CL10C3R3CB8NNW□
		3.3pF	±0.5pF	CL10C3R3DB8NNW□
		3.6pF	±0.25pF	CL10C3R6CB8NNW□
		3.9pF	±0.1pF	CL10C3R9BB8NNW□
		3.9pF	±0.25pF	CL10C3R9CB8NNW□
		4.7pF	±0.1pF	CL10C4R7BB8NNW□
		4.7pF	±0.25pF	CL10C4R7CB8NNW□
		4.7pF	±0.5pF	CL10C4R7DB8NNW□
		5.0pF	±0.1pF	CL10C50BB8NNW□
		5.6pF	±0.25pF	CL10C5R6CB8NNW□
		6.2pF	±0.25pF	CL10C6R2CB8NNW□
		6.8pF	±0.25pF	CL10C6R8CB8NNW□
		6.8pF	±0.5pF	CL10C6R8DB8NNW□
		8.2pF	±0.25pF	CL10C8R2CB8NNW□
		9.0pF	±5%	CL10C90JB8NNW□
		10pF	±0.25pF	CL10C100CB8NNW□
		10pF	±5%	CL10C100JB8NNW□
		15pF	±1%	CL10C150FB8NNW□
		15pF	±5%	CL10C150JB8NNW□
		20pF	±5%	CL10C200JB8NNW□
		22pF	±1%	CL10C220FB8NNW□
		22pF	±2%	CL10C220GB8NNW□
		22pF	±5%	CL10C220JB8NNW□
		27pF	±5%	CL10C270JB8NNW□
		30pF	±5%	CL10C300JB8NNW□
		33pF	±5%	CL10C330JB8NNW□
		33pF	±10%	CL10C330KB8NNW□
		47pF	±5%	CL10C470JB8NNW□
		47pF	±10%	CL10C470KB8NNW□
		56pF	±5%	CL10C560JB8NNW□
		68pF	±5%	CL10C680JB8NNW□
		82pF	±1%	CL10C820FB8NNW□
		82pF	±5%	CL10C820JB8NNW□
		100pF	±1%	CL10C101FB8NNW□
		100pF	±5%	CL10C101JB8NNW□
		100pF	±10%	CL10C101KB8NNW□
		120pF	±5%	CL10C121JB8NNW□

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.90mm	50Vdc	150pF	±1%	CL10C151FB8NNW□
		150pF	±2%	CL10C151GB8NNW□
		150pF	±5%	CL10C151JB8NNW□
		180pF	±5%	CL10C181JB8NNW□
		220pF	±2%	CL10C221GB8NNW□
		220pF	±5%	CL10C221JB8NNW□
		270pF	±1%	CL10C271FB8NNW□
		270pF	±5%	CL10C271JB8NNW□
		330pF	±5%	CL10C331JB8NNW□
		390pF	±5%	CL10C391JB8NNW□
		390pF	±10%	CL10C391KB8NNW□
		470pF	±5%	CL10C471JB8NNW□
		680pF	±5%	CL10C681JB8NNW□
		820pF	±10%	CL10C821KB8NNW□
		1.0nF	±5%	CL10C102JB8NNW□
		1.2nF	±5%	CL10C122JB8NNW□
		1.5nF	±5%	CL10C152JB8NNW□
100Vdc	100Vdc	10pF	±5%	CL10C100JC8NNW□
		33pF	±5%	CL10C330JC8NNW□
		47pF	±5%	CL10C470JC8NNW□
		82pF	±5%	CL10C820JC8NNW□
		100pF	±5%	CL10C101JC8NNW□
		150pF	±5%	CL10C151JC8NNW□
		220pF	±5%	CL10C221JC8NNW□
		270pF	±5%	CL10C271JC8NNW□
		330pF	±5%	CL10C331JC8NNW□

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.75mm	50Vdc	1.0pF	±0.25pF	CL21C010CBANNW□
		1.5pF	±0.1pF	CL21C1R5BBANNW□
		10pF	±0.5pF	CL21C100DBANNW□
		10pF	±5%	CL21C100JBANNW□
		15pF	±5%	CL21C150JBANNW□
		22pF	±1%	CL21C220FBANNW□
		22pF	±5%	CL21C220JBANNW□
		33pF	±5%	CL21C330JBANNW□
		47pF	±5%	CL21C470JBANNW□
		47pF	±10%	CL21C470KBANNW□
		100pF	±2%	CL21C101GBANNW□
		100pF	±5%	CL21C121JBANNW□
		120pF	±5%	CL21C121JBANNW□
		150pF	±5%	CL21C151JBANNW□
		220pF	±5%	CL21C221JBANNW□
		220pF	±10%	CL21C221KBANNW□
		330pF	±1%	CL21C331FBANNW□
		1.0nF	±5%	CL21C102JBANNW□
100Vdc	100Vdc	15pF	±5%	CL21C150JCANNW□
		100pF	±5%	CL21C101JCANNW□
		150pF	±5%	CL21C151JCANNW□
0.95mm	50Vdc	680pF	±5%	CL21C681BCNNW□
		1.0nF	±5%	CL21C102BCNNW□

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (COG)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.95mm	100Vdc	470pF	±5%	CL21C471JCCNNW□	0.95mm	250Vdc	3.3pF	±0.05pF	CL21C3R3AECGNW□
		680pF	±5%	CL21C681JCCNNW□			3.3pF	±0.1pF	CL21C3R3BECGNW□
	200Vdc	220pF	±5%	CL21C221JDCNNW□			3.3pF	±0.25pF	CL21C3R3CECGNW□
		0.5pF	±0.05pF	CL21C0R5AECGNW□			3.6pF	±0.05pF	CL21C3R6AECGNW□
		0.5pF	±0.1pF	CL21C0R5BECGNW□			3.6pF	±0.1pF	CL21C3R6BECGNW□
		0.5pF	±0.25pF	CL21C0R5CECGNW□			3.6pF	±0.25pF	CL21C3R6CECGNW□
		0.6pF	±0.05pF	CL21C0R6AECGNW□			3.9pF	±0.05pF	CL21C3R9AECGNW□
		0.6pF	±0.1pF	CL21C0R6BECGNW□			3.9pF	±0.1pF	CL21C3R9BECGNW□
		0.6pF	±0.25pF	CL21C0R6CECGNW□			3.9pF	±0.25pF	CL21C3R9CECGNW□
		0.7pF	±0.05pF	CL21C0R7AECGNW□			4.0pF	±0.05pF	CL21C040AECGNW□
		0.7pF	±0.1pF	CL21C0R7BECGNW□			4.0pF	±0.1pF	CL21C040BECGNW□
		0.7pF	±0.25pF	CL21C0R7CECGNW□			4.0pF	±0.25pF	CL21C040CECGNW□
		0.8pF	±0.05pF	CL21C0R8AECGNW□			4.3pF	±0.05pF	CL21C4R3AECGNW□
		0.8pF	±0.1pF	CL21C0R8BECGNW□			4.3pF	±0.1pF	CL21C4R3BECGNW□
		0.8pF	±0.25pF	CL21C0R8CECGNW□			4.3pF	±0.25pF	CL21C4R3CECGNW□
		0.9pF	±0.05pF	CL21C0R9AECGNW□			4.7pF	±0.05pF	CL21C4R7AECGNW□
		0.9pF	±0.1pF	CL21C0R9BECGNW□			4.7pF	±0.1pF	CL21C4R7BECGNW□
		0.9pF	±0.25pF	CL21C0R9CECGNW□			4.7pF	±0.25pF	CL21C4R7CECGNW□
		1.0pF	±0.05pF	CL21C010AECGNW□			5.0pF	±0.05pF	CL21C050AECGNW□
		1.0pF	±0.1pF	CL21C010BECGNW□			5.0pF	±0.1pF	CL21C050BECGNW□
		1.0pF	±0.25pF	CL21C010CECGNW□			5.0pF	±0.25pF	CL21C050CECGNW□
		1.1pF	±0.05pF	CL21C1R1AECGNW□			5.1pF	±0.05pF	CL21C5R1AECGNW□
		1.1pF	±0.1pF	CL21C1R1BECGNW□			5.1pF	±0.1pF	CL21C5R1BECGNW□
		1.1pF	±0.25pF	CL21C1R1CECGNW□			5.1pF	±0.25pF	CL21C5R1CECGNW□
		1.2pF	±0.05pF	CL21C1R2AECGNW□			5.1pF	±0.5pF	CL21C5R1DECWNW□
		1.2pF	±0.1pF	CL21C1R2BECGNW□			5.6pF	±0.05pF	CL21C5R6AECGNW□
		1.2pF	±0.25pF	CL21C1R2CECGNW□			5.6pF	±0.1pF	CL21C5R6BECGNW□
		1.3pF	±0.05pF	CL21C1R3AECGNW□			5.6pF	±0.25pF	CL21C5R6CECGNW□
		1.3pF	±0.1pF	CL21C1R3BECGNW□			5.6pF	±0.5pF	CL21C5R6DECWNW□
		1.3pF	±0.25pF	CL21C1R3CECGNW□			6.0pF	±0.05pF	CL21C060AECGNW□
		1.5pF	±0.05pF	CL21C1R5AECGNW□			6.0pF	±0.1pF	CL21C060BECGNW□
		1.5pF	±0.1pF	CL21C1R5BECGNW□			6.0pF	±0.25pF	CL21C060CECGNW□
		1.5pF	±0.25pF	CL21C1R5CECGNW□			6.0pF	±0.5pF	CL21C060DECWNW□
		1.6pF	±0.05pF	CL21C1R6AECGNW□			6.2pF	±0.05pF	CL21C6R2AECGNW□
		1.6pF	±0.1pF	CL21C1R6BECGNW□			6.2pF	±0.1pF	CL21C6R2BECGNW□
		1.6pF	±0.25pF	CL21C1R6CECGNW□			6.2pF	±0.25pF	CL21C6R2CECGNW□
		1.8pF	±0.05pF	CL21C1R8AECGNW□			6.2pF	±0.5pF	CL21C6R2DECWNW□
		1.8pF	±0.1pF	CL21C1R8BECGNW□			6.8pF	±0.05pF	CL21C6R8AECGNW□
		1.8pF	±0.25pF	CL21C1R8CECGNW□			6.8pF	±0.1pF	CL21C6R8BECGNW□
		2.0pF	±0.05pF	CL21C020AECGNW□			6.8pF	±0.25pF	CL21C6R8CECGNW□
		2.0pF	±0.1pF	CL21C020BECGNW□			6.8pF	±0.5pF	CL21C6R8DECWNW□
		2.0pF	±0.25pF	CL21C020CECGNW□			7.0pF	±0.05pF	CL21C070AECGNW□
		2.2pF	±0.05pF	CL21C2R2AECGNW□			7.0pF	±0.1pF	CL21C070BECGNW□
		2.2pF	±0.1pF	CL21C2R2BECGNW□			7.0pF	±0.25pF	CL21C070CECGNW□
		2.2pF	±0.25pF	CL21C2R2CECGNW□			7.0pF	±0.5pF	CL21C070DECWNW□
		2.4pF	±0.05pF	CL21C2R4AECGNW□			7.5pF	±0.05pF	CL21C7R5AECGNW□
		2.4pF	±0.1pF	CL21C2R4BECGNW□			7.5pF	±0.1pF	CL21C7R5BECGNW□
		2.4pF	±0.25pF	CL21C2R4CECGNW□			7.5pF	±0.25pF	CL21C7R5CECGNW□
		2.7pF	±0.05pF	CL21C2R7AECGNW□			7.5pF	±0.5pF	CL21C7R5DECWNW□
		2.7pF	±0.1pF	CL21C2R7BECGNW□			8.0pF	±0.05pF	CL21C080AECGNW□
		2.7pF	±0.25pF	CL21C2R7CECGNW□			8.0pF	±0.1pF	CL21C080BECGNW□
		3.0pF	±0.05pF	CL21C030AECGNW□			8.0pF	±0.25pF	CL21C080CECGNW□
		3.0pF	±0.1pF	CL21C030BECGNW□			8.0pF	±0.5pF	CL21C080DECWNW□
		3.0pF	±0.25pF	CL21C030CECGNW□			8.2pF	±0.05pF	CL21C8R2AECGNW□

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
 In order to move to the page directly, please click the here. ↑

Industrial Capacitors

NNW - COG / X5R / X6S / X7R / X7S

Product Line Up (COG)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	
0.95mm	250Vdc	8.2pF	±0.1pF	CL21C8R2BECGNW□	0.95mm	250Vdc	68pF	±5%	CL21C680JECGNW□	
		8.2pF	±0.25pF	CL21C8R2CECGNW□			82pF	±1%	CL21C820FECGNW□	
		8.2pF	±0.5pF	CL21C8R2DECGNW□			82pF	±2%	CL21C820GECGNW□	
		9.0pF	±0.05pF	CL21C090AECGNW□			82pF	±5%	CL21C820JECGNW□	
		9.0pF	±0.1pF	CL21C090BECGNW□			100pF	±1%	CL21C101FECGNW□	
		9.0pF	±0.25pF	CL21C090CECGNW□			100pF	±2%	CL21C101GECGNW□	
		9.0pF	±0.5pF	CL21C090DECGNW□			100pF	±5%	CL21C101JECGNW□	
		9.1pF	±0.05pF	CL21C9R1AECGNW□			100pF	±5%	CL21C101JECNNW□	
		9.1pF	±0.1pF	CL21C9R1BECGNW□	1.35mm	25Vdc	3.3nF	±1%	CL21C332FAFNNW□	
		9.1pF	±0.25pF	CL21C9R1CECGNW□			1.2nF	±5%	CL21C122JBFFNNW□	
		9.1pF	±0.5pF	CL21C9R1DECGNW□			1.2nF	±5%	CL21C122JBFFNNW□	
		10pF	±1%	CL21C100FECGNW□			1.5nF	±5%	CL21C152JBFFNNW□	
		10pF	±2%	CL21C100GECGNW□			2.2nF	±5%	CL21C222JBFFNNW□	
		10pF	±5%	CL21C100JECGNW□			2.7nF	±5%	CL21C272JBFFNNW□	
		10pF	±5%	CL21C100JECNNW□			2.7nF	±5%	CL21C272JBFFNNW□	
		11pF	±1%	CL21C110FECGNW□			3.3nF	±5%	CL21C332JBFFNNW□	
		11pF	±2%	CL21C110GECGNW□			3.3nF	±5%	CL21C332JBFFNNW□	
		11pF	±5%	CL21C110JECGNW□			3.9nF	±5%	CL21C392JBFFNNW□	
		12pF	±1%	CL21C120FECGNW□			4.7nF	±5%	CL21C472JBFFNNW□	
		12pF	±2%	CL21C120GECGNW□			4.7nF	±5%	CL21C472JBFFNNW□	
		12pF	±5%	CL21C120JECGNW□			100Vdc	±5%	CL21C102JCFNNW□	
		15pF	±1%	CL21C150FECGNW□			200Vdc	470pF	±5%	CL21C471JDFNNW□
		15pF	±2%	CL21C150GECGNW□			630Vdc	39pF	±5%	CL21C390JHFNNW□
		15pF	±5%	CL21C150JECGNW□	50Vdc	50Vdc	1.2nF	±5%	CL21C122JBFFNNW□	
		18pF	±1%	CL21C180FECGNW□			1.2nF	±5%	CL21C122JBFFNNW□	
		18pF	±2%	CL21C180GECGNW□			1.5nF	±5%	CL21C152JBFFNNW□	
		18pF	±5%	CL21C180JECGNW□			2.2nF	±5%	CL21C222JBFFNNW□	
		20pF	±1%	CL21C200FECGNW□			2.7nF	±5%	CL21C272JBFFNNW□	
		20pF	±2%	CL21C200GECGNW□			3.3nF	±5%	CL21C332JBFFNNW□	
		20pF	±5%	CL21C200JECGNW□			3.9nF	±5%	CL21C392JBFFNNW□	
		22pF	±1%	CL21C220FECGNW□			4.7nF	±5%	CL21C472JBFFNNW□	
		22pF	±2%	CL21C220GECGNW□			4.7nF	±5%	CL21C472JBFFNNW□	
		22pF	±5%	CL21C220JECGNW□			100Vdc	1.0nF	±5%	CL21C102JCFNNW□
		24pF	±1%	CL21C240FECGNW□			200Vdc	470pF	±5%	CL21C471JDFNNW□
		24pF	±2%	CL21C240GECGNW□			630Vdc	39pF	±5%	CL21C390JHFNNW□
		24pF	±5%	CL21C240JECGNW□			1.2nF	±5%	CL21C122JBFFNNW□	
		27pF	±1%	CL21C270FECGNW□			1.2nF	±5%	CL21C122JBFFNNW□	
		27pF	±2%	CL21C270GECGNW□			1.5nF	±5%	CL21C152JBFFNNW□	
		27pF	±5%	CL21C270JECGNW□			2.2nF	±5%	CL21C222JBFFNNW□	
		33pF	±1%	CL21C330FECGNW□			2.7nF	±5%	CL21C272JBFFNNW□	
		33pF	±2%	CL21C330GECGNW□			3.3nF	±5%	CL21C332JBFFNNW□	
		33pF	±5%	CL21C330JECGNW□			3.9nF	±5%	CL21C392JBFFNNW□	
		33pF	±5%	CL21C330JECNNW□			4.7nF	±5%	CL21C472JBFFNNW□	
		39pF	±1%	CL21C390FECGNW□			4.7nF	±5%	CL21C472JBFFNNW□	
		39pF	±2%	CL21C390GECGNW□			100Vdc	1.0nF	±5%	CL21C102JCFNNW□
		39pF	±5%	CL21C390JECGNW□			200Vdc	470pF	±5%	CL21C471JDFNNW□
		47pF	±1%	CL21C470FECGNW□			630Vdc	39pF	±5%	CL21C390JHFNNW□
		47pF	±2%	CL21C470GECGNW□			1.2nF	±5%	CL21C122JBFFNNW□	
		47pF	±5%	CL21C470JECGNW□			1.2nF	±5%	CL21C122JBFFNNW□	
		62pF	±1%	CL21C620FECGNW□			1.2nF	±5%	CL21C122JBFFNNW□	
		62pF	±2%	CL21C620GECGNW□			1.5nF	±5%	CL21C152JBFFNNW□	
		62pF	±5%	CL21C620JECGNW□			2.2nF	±5%	CL21C222JBFFNNW□	
		68pF	±1%	CL21C680FECGNW□			2.7nF	±5%	CL21C272JBFFNNW□	
		68pF	±2%	CL21C680GECGNW□			3.3nF	±5%	CL21C332JBFFNNW□	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (COG)

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
1.00mm	50Vdc	1.0nF	±5%	CL31C102JBCNNW□
		1.5nF	±2%	CL31C152GBCNNW□
	100Vdc	100pF	±5%	CL31C101JCCNNW□
		220pF	±5%	CL31C221JCCNNW□
		560pF	±5%	CL31C561JCCNNW□
		680pF	±5%	CL31C681JCCNNW□
		2.2nF	±5%	CL31C222JCCNNW□
	25Vdc	10nF	±1%	CL31C103FAFNNW□
		10nF	±2%	CL31C103GAFNNW□
		3.3nF	±5%	CL31C332JBFNNW□
	50Vdc	1.0nF	±5%	CL31C102JDFNNW□
		10pF	±5%	CL31C100JGFNNW□
1.40mm	500Vdc	39pF	±5%	CL31C390JGFNNW□
		220pF	±5%	CL31C221JGFNNW□
		330pF	±5%	CL31C331JGFNNW□
		470pF	±5%	CL31C471JGFNNW□
		220pF	±5%	CL31C221JHFNNW□
	25Vdc	47nF	±5%	CL31C473JAHNNW□
		100nF	±5%	CL31C104JAHNNW□
	50Vdc	5.6nF	±5%	CL31C562JBHNNW□
		6.8nF	±5%	CL31C682JBHNNW□
		12nF	±5%	CL31C123JBHNNW□
		22nF	±5%	CL31C223JBHNNW□
		27nF	±5%	CL31C273JBHNNW□
1.80mm	2kVdc	33nF	±5%	CL31C333JBHNNW□
		22pF	±10%	CL31C220KJHNNW□

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
1.45mm	1kVdc	100pF	±10%	CL32C101KIFNNW□
2.70mm	100Vdc	47nF	±5%	CL32C473JCJNNW□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
 In order to move to the page directly, please click the here. ↑

Industrial Capacitors

NNW - COG / X5R / X6S / X7R / X7S

Product Line Up (X5R)

■ Size : 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.33mm	6.3Vdc	10nF	±10%	CL03A103KQ3NNW □	
		100nF	±10%	CL03A104KQ3NNW □	Derating
		220nF	±10%	CL03A224KQ3NNW □	Derating Ref.
		220nF	±20%	CL03A224MQ3NNW □	Derating Ref.
	10Vdc	100nF	±10%	CL03A104KP3NNW □	Derating
		180pF	±10%	CL03A181KA3NNW □	Derating
		330pF	±10%	CL03A331KA3NNW □	Derating
		1.8nF	±10%	CL03A182KA3NNW □	Derating

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.55mm	6.3Vdc	220nF	±10%	CL05A224KQ5NNW □	
		330nF	±10%	CL05A334KQ5NNW □	
		470nF	±10%	CL05A474KQ5NNW □	
		1.0uF	±10%	CL05A105KQ5NNW □	Derating
		1.0uF	±20%	CL05A105MQ5NNW □	Derating
		2.2uF	±20%	CL05A225MQ5NNW □	Derating Ref.
	10Vdc	100nF	±10%	CL05A104KP5NNW □	
		220nF	±10%	CL05A224KP5NNW □	
		22nF	±10%	CL05A223K05NNW □	
		100nF	±10%	CL05A104K05NNW □	

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	6.3Vdc	470nF	±10%	CL10A474KQ8NNW □	
		1.0uF	±10%	CL10A105KQ8NNW □	
		2.2uF	±10%	CL10A225KQ8NNW □	
		4.7uF	±10%	CL10A475KQ8NNW □	
		10uF	±10%	CL10A106KQ8NNW □	Ref.
		10uF	±20%	CL10A106MQ8NNW □	Ref.
	10Vdc	220nF	±10%	CL10A224KP8NNW □	
		470nF	±10%	CL10A474KP8NNW □	
		1.0uF	±10%	CL10A105KP8NNW □	
		2.2uF	±10%	CL10A225KP8NNW □	
	16Vdc	10uF	±10%	CL10A106KP8NNW □	Derating Ref.
		1.0uF	±10%	CL10A105KO8NNW □	
		2.2uF	±10%	CL10A225KO8NNW □	
		4.7uF	±10%	CL10A475KO8NNW □	Derating

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	16Vdc	2.2uF	±10%	CL21A225KOCLNW □	
1.35mm	6.3Vdc	10uF	±10%	CL21A106KQFNNW □	
		10uF	±20%	CL21A106MQFNNW □	
		4.7uF	±10%	CL21A475KQFNNW □	
	10Vdc	4.7uF	±20%	CL21A475MQFNNW □	
	10uF	±10%		CL21A106KPFFNNW □	
	2.2uF	±10%		CL21A225KPFFNNW □	
	4.7uF	±10%		CL21A475KPFFNNW □	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

NNW - COG / X5R / X6S / X7R / X7S

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.35mm	10Vdc	4.7uF	±10%	CL21A475KPFNNW □	
		2.2uF	±10%	CL21A225KAFNNW □	
1.40mm	16Vdc	22uF	±20%	CL21A226MQQNNW □	
		10uF	±10%	CL21A106KOQNNW □	Derating
1.45mm	25Vdc	22uF	±10%	CL21A226KOQNNW □	Derating
		22uF	±20%	CL21A226MAQNNW □	Derating

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.25mm	10Vdc	10uF	±10%	CL31A106KPPLNW □	
1.80mm	6.3Vdc	10uF	±10%	CL31A106KQHNNW □	
		10uF	±20%	CL31A106MQHNNW □	
		22uF	±20%	CL31A226MQHNNW □	
		47uF	±20%	CL31A476MQHNNW □	Derating
		100uF	±20%	CL31A107MQHNNW □	Derating
	10Vdc	4.7uF	±10%	CL31A475KPHNNW □	
		10uF	±10%	CL31A106KPHNNW □	
		3.3uF	±10%	CL31A335KOHNNW □	
	16Vdc	4.7uF	±20%	CL31A475MOHNNW □	
		10uF	±10%	CL31A106KOHNNW □	
		10uF	±20%	CL31A106MOHNNW □	
		22uF	±20%	CL31A226MOHNNW □	Derating
	25Vdc	10uF	±10%	CL31A106KAHNNW □	
		22uF	±10%	CL31A226KAHNNW □	Derating

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	
0.95mm	16Vdc	10uF	±10%	CL32A106KOCLNW □		
1.70mm	16Vdc	10uF	±10%	CL32A106KOTLNW □		
		10uF	±20%	CL32A106KAULNW □		
		25Vdc	10uF	±10%	CL32A106KPINNW □	
		25Vdc	10uF	±20%	CL32A106MAILNW □	
		22uF	±20%	CL32A226MQJNNW □		
	10Vdc	22uF	±20%	CL32A226MPJNNW □		
		47uF	±20%	CL32A476MPJNNW □	Derating	
		10uF	±20%	CL32A106MOJNNW □		
		22uF	±10%	CL32A226KOJNNW □		
		22uF	±20%	CL32A226MOJNNW □		
	16Vdc	47uF	±10%	CL32A476KOJNNW □		
		47uF	±20%	CL32A476MOJNNW □		
		10uF	±20%	CL32A226KOJNNW □		
		47uF	±10%	CL32A476MOJNNW □		
		25Vdc	22uF	±10%	CL32A226KAJNNW □	
	25Vdc	100uF	±20%	CL32A107MQVNNW □	Derating	
		100uF	±20%	CL32A107MPVNNW □	Derating	

■ Size : 4.50 X 3.20mm (inch : 1812)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
3.50mm	6.3Vdc	100uF	±20%	CL43A107MQLNNW □	

Product Line Up (X6S)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.55mm	10Vdc	1.0uF	±10%	CL05X105KP5NNW□	<small>Derating</small>

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.80mm	4.0Vdc	47uF	±20%	CL31X476MRHNNW□	<small>Derating</small>

■ Size : 1.60 X 0.80 (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	6.3Vdc	10uF	±20%	CL10X106MQ8NNW□	<small>Derating</small>

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.80mm	6.3Vdc	100uF	±20%	CL32X107MQVNNW□	<small>Derating</small>

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.40mm	4.0Vdc	22uF	±20%	CL21X226MRQNNW□	<small>Derating</small>
	6.3Vdc	22uF	±20%	CL21X226MQQNNW□	<small>Derating</small>

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
 In order to move to the page directly, please click the here. ↑

Industrial Capacitors

NNW - COG / X5R / X65 / X7R / X7S

Product Line Up (X7R)

■ Size : 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.33mm	10Vdc	10nF	±10%	CL03B103KP3NNW□	
	25Vdc	330pF	±10%	CL03B331KA3NNW□	
		470pF	±10%	CL03B471KA3NNW□	
		1.00nF	±10%	CL03B102KA3NNW□	
		2.20nF	±10%	CL03B222KA3NNW□	

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.55mm	6.3Vdc	220nF	±10%	CL05B224KQ5NNW□	
		470nF	±10%	CL05B474KQ5NNW□	Ref.
	10Vdc	33nF	±10%	CL05B333KP5NNW□	
		100nF	±10%	CL05B104KP5NNW□	
	16Vdc	1.0nF	±10%	CL05B102K05NNW□	
		5.6nF	±10%	CL05B562K05NNW□	
		6.8nF	±10%	CL05B682K05NNW□	
		10nF	±5%	CL05B103J05NNW□	
		10nF	±10%	CL05B103K05NNW□	
		10nF	±20%	CL05B103M05NNW□	
25Vdc	50Vdc	15nF	±10%	CL05B153K05NNW□	
		22nF	±10%	CL05B223K05NNW□	
		33nF	±10%	CL05B333K05NNW□	
		33nF	±20%	CL05B333M05NNW□	
		47nF	±10%	CL05B473K05NNW□	
		47nF	±20%	CL05B473M05NNW□	
		100nF	±10%	CL05B104K05NNW□	
		560pF	±10%	CL05B561KA5NNW□	
		1.0nF	±10%	CL05B102KA5NNW□	
		4.7nF	±10%	CL05B472KA5NNW□	

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	10Vdc	220nF	±10%	CL10B224KP8NNW□	
		330nF	±10%	CL10B334KP8NNW□	
		2.2uF	±10%	CL10B225KP8NNW□	Ref.
16Vdc	25Vdc	18nF	±10%	CL10B183K08NNW□	
		22nF	±10%	CL10B223K08NNW□	
		27nF	±10%	CL10B273K08NNW□	
		33nF	±10%	CL10B333K08NNW□	
		47nF	±10%	CL10B473K08NNW□	
		100nF	±10%	CL10B104K08NNW□	
		100nF	±20%	CL10B104M08NNW□	
		120nF	±10%	CL10B124K08NNW□	
		150nF	±10%	CL10B154K08NNW□	
		220nF	±10%	CL10B224K08NNW□	
50Vdc	100Vdc	330nF	±10%	CL10B334K08NNW□	
		470nF	±10%	CL10B474K08NNW□	
		1.0uF	±20%	CL10B105M08NNW□	
		18nF	±10%	CL10B183KA8NNW□	
		22nF	±10%	CL10B223KA8NNW□	
		27nF	±10%	CL10B273KA8NNW□	
		47nF	±10%	CL10B473KA8NNW□	
		100nF	±5%	CL10B104JA8NNW□	
		100nF	±10%	CL10B104KA8NNW□	
		100nF	±20%	CL10B104MA8NNW□	
100Vdc	100Vdc	470nF	±10%	CL10B474KA8NNW□	
		1.0uF	±10%	CL10B105KA8NNW□	
		100pF	±10%	CL10B101KB8NNW□	
		150pF	±10%	CL10B151KB8NNW□	
		220pF	±10%	CL10B221KB8NNW□	
		270pF	±10%	CL10B271KB8NNW□	
		330pF	±10%	CL10B331KB8NNW□	
		470pF	±10%	CL10B471KB8NNW□	
		560pF	±10%	CL10B561KB8NNW□	
		680pF	±10%	CL10B681KB8NNW□	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (X7R)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.75mm	16Vdc	150nF	±10%	CL21B154KOANNW□	
	25Vdc	10nF	±10%	CL21B103KAANNW□	
	50Vdc	390pF	±10%	CL21B391KBANNW□	
		1.0nF	±10%	CL21B102KBANNW□	
		2.2nF	±10%	CL21B222KBANNW□	
		3.3nF	±5%	CL21B332JBANNW□	
		3.3nF	±10%	CL21B332KBANNW□	
		4.7nF	±10%	CL21B472KBANNW□	
		6.8nF	±10%	CL21B682KBANNW□	
		10nF	±10%	CL21B103KBANNW□	
		10nF	±20%	CL21B103MBANNW□	
		15nF	±10%	CL21B153KBANNW□	
		22nF	±10%	CL21B223KBANNW□	
		33nF	±10%	CL21B333KBANNW□	
	100Vdc	330pF	±10%	CL21B331KCANNW□	
		1.0nF	±10%	CL21B102KCANNW□	
		2.2nF	±10%	CL21B222KCANNW□	
0.95mm	16Vdc	100nF	±5%	CL21B104JOCNNW□	
		220nF	±10%	CL21B224KOCNNW□	
		330nF	±10%	CL21B334KOCNNW□	
	25Vdc	100nF	±10%	CL21B104KACNNW□	
	50Vdc	47nF	±10%	CL21B473KBCNNW□	
		100nF	±10%	CL21B104KBCNNW□	
		100nF	±20%	CL21B104MBCNNW□	
	200Vdc	1.0nF	±10%	CL21B102KDCNNW□	
		2.2nF	±10%	CL21B222KDCNNW□	
		4.7nF	±10%	CL21B472KDCNNW□	
		10nF	±10%	CL21B103KDCNNW□	
1.35mm	10Vdc	1.0uF	±10%	CL21B105KPFNNW□	
		1.0uF	±20%	CL21B105MPFNNW□	
		2.2uF	±10%	CL21B225KPFNNW□	
	16Vdc	470nF	±10%	CL21B474KOFNNW□	
		680nF	±10%	CL21B684KOFNNW□	
		1.0uF	±10%	CL21B105KOFNNW□	
		2.2uF	±10%	CL21B225KOFNNW□	
		4.7uF	±10%	CL21B475KOFNNW□	Ref
	25Vdc	150nF	±10%	CL21B154KAFNNW□	
		220nF	±10%	CL21B224KAFNNW□	
		470nF	±10%	CL21B474KAFNNW□	
		1.0uF	±10%	CL21B105KAFNNW□	
		2.2uF	±10%	CL21B225KAFNNW□	
	50Vdc	220nF	±10%	CL21B224KBFNNW□	
		330nF	±10%	CL21B334KBFNNW□	
		470nF	±10%	CL21B474KBFNNW□	
		680nF	±10%	CL21B684KBFNNW□	
		18nF	±10%	CL21B183KCFNNW□	
	100Vdc	22nF	±10%	CL21B223KCFNNW□	
		47nF	±10%	CL21B473KCFNNW□	
		100nF	±10%	CL21B104KCFNNW□	
		18nF	±10%	CL21B183KCFNNW□	
		22nF	±10%	CL21B223KCFNNW□	
1.40mm	6.3Vdc	10uF	±10%	CL21B106KQQNNW□	
	10Vdc	10uF	±10%	CL21B106KPQNNW□	

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	
1.00mm	16Vdc	470nF	±10%	CL31B474KOCNNW□		
		47nF	±10%	CL31B473KOCNNW□		
	50Vdc	100nF	±5%	CL31B104JBCNNW□		
		100nF	±10%	CL31B104KBCNNW□		
		10nF	±10%	CL31B103KBCNNW□		
		120nF	±10%	CL31B124KBCNNW□		
		150nF	±10%	CL31B154KBCNNW□		
		1.0nF	±10%	CL31B102KBCNNW□		
		3.3nF	±5%	CL31B332JBCNNW□		
		47nF	±10%	CL31B473KBCNNW□		
		10nF	±5%	CL31B103JCCNNW□		
		10nF	±20%	CL31B103MCCNNW□		
		15nF	±10%	CL31B153KCCNNW□		
		1.0nF	±10%	CL31B102KCCNNW□		
		22nF	±10%	CL31B223KCCNNW□		
		33nF	±10%	CL31B333KCCNNW□		
		47nF	±10%	CL31B473KCCNNW□		
	100Vdc	10nF	±20%	CL31B473MCCNNW□		
		47nF	±20%	CL31B473MCCNNW□		
1.25mm	25Vdc	1.0uF	±10%	CL31B105KAPLNW□	Derating	
	1.40mm	10Vdc	2.2uF	±10%	CL31B225KPFNNW□	
		16Vdc	1.0uF	±10%	CL31B105KOFNNW□	
	50Vdc	220nF	±10%	CL31B224KBFNNW□		
		220nF	±20%	CL31B224MBFNNW□		
		330nF	±10%	CL31B334KBFNNW□		
	100Vdc	100nF	±10%	CL31B104KCFNNW□		
	200Vdc	33nF	±10%	CL31B333KDFFNNW□		
		47nF	±10%	CL31B473KDFFNNW□		
		500Vdc	4.7nF	±10%	CL31B472KGFFNNW□	
			6.8nF	±10%	CL31B682KGFFNNW□	
1.80mm	6.3Vdc	22uF	±10%	CL31B226QHNNW□		
	10Vdc	10uF	±10%	CL31B106KPHNNW□		
		22uF	±10%	CL31B226KPHNNW□		
		4.7uF	±10%	CL31B475KPHNNW□		
		16Vdc	10uF	±10%	CL31B106KOHNNW□	
	25Vdc	2.2uF	±10%	CL31B225KOHNNW□		
		4.7uF	±10%	CL31B475KOHNNW□		
		10uF	±10%	CL31B106KAHNNW□		
		1.0uF	±5%	CL31B105JAHNNW□		
		1.0uF	±10%	CL31B105KAHNNW□		
	50Vdc	1.0uF	±20%	CL31B105MAHNNW□		
		2.2uF	±10%	CL31B225KAHNNW□		
		4.7uF	±10%	CL31B475KAHNNW□		
		470nF	±10%	CL31B105KBHNNW□		
		2.2uF	±10%	CL31B225KBHNNW□		
	100Vdc	470nF	±10%	CL31B474KBHNNW□		
		1.0uF	±10%	CL31B105KCHNNW□		
		68nF	±10%	CL31B683KDHHNNW□		
		250Vdc	47nF	±10%	CL31B473KEHNNW□	
		2kVdc	2.2nF	±10%	CL31B222KJHNNW□	Derating

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Industrial Capacitors

NNW - COG / X5R / X6S / X7R / X7S

Product Line Up (X7R)

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.45mm	25Vdc	470nF	±10%	CL32B474KAFNNW□	
		470nF	±20%	CL32B474MAFNNW□	
		1.0uF	±10%	CL32B105KAFNNW□	
	50Vdc	100nF	±20%	CL32B104MBFNNW□	
		220nF	±10%	CL32B224KBFNNW□	
		330nF	±10%	CL32B334KBFNNW□	
		470nF	±10%	CL32B474KBFNNW□	
	100Vdc	100nF	±10%	CL32B104KCFNNW□	
		150nF	±10%	CL32B154KCFNNW□	
	500Vdc	22nF	±10%	CL32B223KGFNNW□	
		2kVdc	±10%	CL32B102KJFNNW□	
1.80mm	100Vdc	220nF	±10%	CL32B224KCHNNW□	
		330nF	±10%	CL32B334KCHNNW□	
	200Vdc	47nF	±10%	CL32B473KDHNNW□	
		47nF	±10%	CL32B473KEHNNW□	
2.00mm	50Vdc	4.7uF	±10%	CL32B475KBUYNW□	
2.20mm	16Vdc	4.7uF	±10%	CL32B475KOINNW□	
	25Vdc	2.2uF	±10%	CL32B225KA1NNW□	
	630Vdc	47nF	±10%	CL32B473KHINNW□	
2.70mm	10Vdc	47uF	±10%	CL32B476KPJNNW□	Ref.
	16Vdc	22uF	±10%	CL32B226KOJNNW□	
		22uF	±20%	CL32B226MOJNNW□	
	25Vdc	10uF	±10%	CL32B106KAJNNW□	
		22uF	±10%	CL32B226KAJNNW□	
		22uF	±20%	CL32B226MAJNNW□	
	50Vdc	3.3uF	±10%	CL32B335KBJNNW□	
		10uF	±10%	CL32B106KBJNNW□	
	100Vdc	680nF	±10%	CL32B684KCJNNW□	
		1.0uF	±10%	CL32B105KCJNNW□	
	200Vdc	100nF	±10%	CL32B104KDJNNW□	

■ Size : 4.50 X 3.20mm (inch : 1812)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.45mm	200Vdc	100nF	±10%	CL43B104KDFNNW□	
	1kVdc	10nF	±10%	CL43B103KIFNNW□	Derating
1.80mm	100Vdc	470nF	±10%	CL43B474KCHNNW□	
2.70mm	250Vdc	220nF	±10%	CL43B224KEJNNW□	
	1kVdc	22nF	±10%	CL43B223KIJNNW□	Derating

■ Size : 5.70 X 5.00mm (inch : 2220)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.80mm	100Vdc	1.0uF	±10%	CL55B105KCHNNW□	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Soft-Termination Industrial Capacitors

ZNW / SNW - X6S / X7R

Feature





- Soft -Termination relaxes the applied thermal / mechanical stresses by ductile properties of metal - polymer composites.
- Can be applied to power (SMPS, DC - DC Converter) and industrial equipment
- ZNW, SNW series : Metal Epoxy
- Speical outgoing inspection for industrial application (HALT, etc)

Application

- Power(SMPS, DC - DC converter)
- Ideal for decoupling and filtering applications(Class II : X7R / X6S)

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
21	0805	2.00±0.10	1.25±0.10	0.65±0.10	A	0.50+0.20/-0.30
		2.00±0.10	1.25±0.10	0.85±0.10	C	
		2.00±0.10	1.25±0.10	1.15±0.10	M	
		2.00±0.10	1.25±0.10	1.25±0.10	F	
31	1206	3.20±0.15	1.60±0.15	0.85±0.15	C	0.50±0.30
		3.20±0.15	1.60±0.15	1.25±0.15	F	
		3.20±0.20	1.60±0.20	1.60±0.20	H	
32	1210	3.20±0.30	2.50±0.20	1.25±0.20	F	0.60±0.30
		3.20±0.30	2.50±0.20	1.60±0.20	H	
		3.20±0.30	2.50±0.20	2.00±0.20	I	
		3.20±0.30	2.50±0.20	2.50±0.20	J	

Soft-Termination Industrial Capacitors

ZNW / SNW - X6S / X7R

Industrial Capacitance Table (X6S / X7R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance									
		nF				uF					
		68	100	220	470	1.0	2.2	4.7	10	22	47
0805(2012)	100										
1206(3216)	100										
1210 (3225)	16										X6S
	100										

Product Line Up (X6S)

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.80mm	10Vdc	47uF	±10%	CL32X476KOVZNW □	Derating

Product Line Up (X7R)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.35mm	100Vdc	100nF	±10%	CL21B104KCFSNW □	
		220nF	±10%	CL21B224KCFSNW □	

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.80mm	100Vdc	1.0uF	±10%	CL31B105KCHSNW □	
		2.2uF	±10%	CL31B225KCHSNW □	

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.70mm	100Vdc	1.0uF	±10%	CL32B105KCJSNW □	
		2.2uF	±10%	CL32B225KCJSNW □	
2.80mm	100Vdc	4.7uF	±10%	CL32B475KCVZNW □	Derating

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Industrial Capacitors for Power Application

NFN - C0G / X5R / X6S / X7R

Feature





- Rated voltage 6.3V~100V,
- Temperature range -55°C to +125°C (C0G / X7R), -55°C to +105°C (X6S), -55°C to +85°C (X5R),
- Case size 0201 to 1210.
- Special outgoing inspection for Power application
(Bending Test : Sampling Test upto 2mm : X7R, 3mm : C0G)

Application

- Power supply (SMPS, DC – DC converter)
- Ideal for decoupling and filtering applications (Class II : X7R / X6S / X5R)
- Impedance matching, tuning, coupling in high frequency circuit (Class I : C0G)

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
03	0201	0.60±0.03	0.30±0.03	0.30±0.03	3	0.15±0.05
05	0402	1.00±0.05	0.50±0.05	0.50±0.05	5	0.25±0.10
10	0603	1.60±0.10	0.80±0.10	0.80±0.10	8	0.30±0.20
21	0805	2.00±0.10	1.25±0.10	0.65±0.10	A	0.50+0.20/-0.30
		2.00±0.10	1.25±0.10	0.85±0.10	C	
		2.00±0.10	1.25±0.10	1.15±0.10	M	
		2.00±0.10	1.25±0.10	1.25±0.10	F	
31	1206	3.20±0.15	1.60±0.15	0.85±0.15	C	0.50±0.30
		3.20±0.15	1.60±0.15	1.25±0.15	F	
		3.20±0.20	1.60±0.20	1.60±0.20	H	
32	1210	3.20±0.30	2.50±0.20	1.25±0.20	F	0.60±0.30
		3.20±0.30	2.50±0.20	1.60±0.20	H	
		3.20±0.30	2.50±0.20	2.00±0.20	I	
		3.20±0.30	2.50±0.20	2.50±0.20	J	

Industrial Capacitors for Power Application

NFN - C0G / X5R / X6S / X7R

Industrial Capacitance Table (C0G)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance																																										
		pF													nF																													
		1.0	1.0	10	12	18	22	27	33	56	100	180	220	270	330	470	560	680	910	1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
0402 (1005)	25																			1.0																								
	50																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
0603 (1608)	25																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
	50																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
	100																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
	250																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
0805 (2012)	25																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
	50																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
	100																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
	200																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
1206 (3216)	50																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
	100																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
	200																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
	500																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
	1k																			1.0	1.2	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2	10	15	18	22	27	33	39	47	56					
1210(3225)	100																																											

Industrial Capacitance Table (X5R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance											
		nF			uF								
		100	220	470	1.0	2.2	4.7	10	22	47	100	150	220
0201 (0603)	4.0												
	6.3												
	10												
0402 (1005)	4.0												
	6.3												
	10												
	16												
0603 (1608)	6.3												
	10												
	16												
	25												
	50												
0805 (2012)	6.3												
	10												
	16												
	25												
1206 (3216)	6.3												
	10												
	16												
	25												
	50												
1210 (3225)	6.3												
	10												
	16												
	25												

Industrial Capacitance Table (X6S)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance(uF)											
		0.1	0.22	0.47	1.0	2.2	4.7	10	22	47	100	220	
0402(1005)	6.3												
0805 (2012)	4.0												
	25												
1206(3216)	6.3												

Industrial Capacitors for Power Application

NFN - C0G / X5R / X6S / X7R

Industrial Capacitance Table (X7R / X7S)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance												
		pF					nF							
		100	220	330	470	680	1.0	2.2	3.3	4.7	6.8	10	22	47
0201(0603)	10													

Size inch (mm)	Rated Voltage (Vdc)	Capacitance																								
		nF							uF																	
1.0	2.2	3.3	4.7	10	15	22	33	47	68	100	120	150	220	330	470	680	1.0	2.2	3.3	4.7	6.8	10	22	47	100	
0402 (1005)	10																	X7S								
	16																									
	25																	X7S								
	50	0.27																								
0603 (1608)	6.3																									
	10																									
	16	1.50																								
	25																		X7S							
	50	0.10																								
0805 (2012)	6.3																									
	10																									
	16																									
	25																			X7S						
	50	0.10																								
	100																									
	200	0.22																								
1206 (3216)	6.3																									
	10																									
	16																									
	25																									
	35																									
	50																									
	100																									
	200																									
	250																									
	500																									
1210 (3225)	6.3																									
	10																									
	16																									
	25																									
	50																									
	100																									
	2k	0.22																								

Product Line Up (COG)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	25Vdc	1.0nF	±5%	CL05C102JA5NFN□	0.90mm	50Vdc	180pF	±5%	CL10C181JB8NFN□
	50Vdc	0.5pF	±0.1pF	CL05C0R5BB5NFN□		200pF	±5%	CL10C201JB8NFN□	
		0.5pF	±0.25pF	CL05C0R5CB5NFN□		220pF	±5%	CL10C221JB8NFN□	
		1.0pF	±0.25pF	CL05C010CB5NFN□		270pF	±5%	CL10C271JB8NFN□	
		2.0pF	±0.25pF	CL05C020CB5NFN□		330pF	±5%	CL10C331JB8NFN□	
		10pF	±0.25pF	CL05C100CB5NFN□		390pF	±5%	CL10C391JB8NFN□	
		10pF	±5%	CL05C100JB5NFN□		430pF	±5%	CL10C431JB8NFN□	
		15pF	±5%	CL05C150JB5NFN□		470pF	±5%	CL10C471JB8NFN□	
		18pF	±5%	CL05C180JB5NFN□		560pF	±5%	CL10C561JB8NFN□	
		20pF	±5%	CL05C200JB5NFN□		680pF	±5%	CL10C681JB8NFN□	
		22pF	±5%	CL05C220JB5NFN□		820pF	±5%	CL10C821JB8NFN□	
		27pF	±5%	CL05C270JB5NFN□		1.0nF	±5%	CL10C102JB8NFN□	
		33pF	±5%	CL05C330JB5NFN□		1.2nF	±5%	CL10C122JB8NFN□	
		47pF	±5%	CL05C470JB5NFN□		1.5nF	±5%	CL10C152JB8NFN□	
		56pF	±5%	CL05C560JB5NFN□		1.8nF	±5%	CL10C182JB8NFN□	
		68pF	±5%	CL05C680JB5NFN□		2.2nF	±5%	CL10C222JB8NFN□	
		100pF	±5%	CL05C101JB5NFN□		2.7nF	±5%	CL10C272JB8NFN□	
		120pF	±5%	CL05C121JB5NFN□		3.3nF	±5%	CL10C332JB8NFN□	
		150pF	±5%	CL05C151JB5NFN□		100Vdc	47pF	±5%	CL10C470JC8NFN□
		180pF	±5%	CL05C181JB5NFN□		220pF	±5%	CL10C221JC8NFN□	
		220pF	±5%	CL05C221JB5NFN□		470pF	±5%	CL10C471JC8NFN□	
		270pF	±5%	CL05C271JB5NFN□		250Vdc	470pF	±5%	CL10C471JE8NFN□
		330pF	±5%	CL05C331JB5NFN□					
		680pF	±5%	CL05C681JB5NFN□					

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.90mm	25Vdc	1.0nF	±5%	CL10C102JA8NFN□	0.75mm	50Vdc	0.5pF	±0.25pF	CL21C0R5CBANFN□
	50Vdc	0.5pF	±0.25pF	CL10C0R5CB8NFN□		1.0pF	±0.25pF	CL21C010CBANFN□	
		1.0pF	±0.25pF	CL10C010CB8NFN□		1.8pF	±0.25pF	CL21C1R8CBANFN□	
		3.9pF	±0.25pF	CL10C3R9CB8NFN□		2.0pF	±0.25pF	CL21C020CBANFN□	
		4.7pF	±0.25pF	CL10C4R7CB8NFN□		3.0pF	±0.25pF	CL21C030CBANFN□	
		5.0pF	±0.1pF	CL10C050BB8NFN□		3.9pF	±0.25pF	CL21C3R9CBANFN□	
		5.0pF	±0.25pF	CL10C050CB8NFN□		4.0pF	±0.25pF	CL21C040CBANFN□	
		10pF	±5%	CL10C100JB8NFN□		4.7pF	±0.25pF	CL21C4R7CBANFN□	
		12pF	±1%	CL10C120FB8NFN□		6.0pF	±0.5pF	CL21C060DBANFN□	
		12pF	±5%	CL10C120JB8NFN□		7.0pF	±0.5pF	CL21C070DBANFN□	
		15pF	±5%	CL10C150JB8NFN□		7.5pF	±0.5pF	CL21C7R5DBANFN□	
		18pF	±5%	CL10C180JB8NFN□		8.0pF	±0.5pF	CL21C080DBANFN□	
		20pF	±5%	CL10C200JB8NFN□		8.2pF	±0.5pF	CL21C8R2DBANFN□	
		22pF	±5%	CL10C220JB8NFN□		10pF	±5%	CL21C100JBANFN□	
		27pF	±5%	CL10C270JB8NFN□		12pF	±5%	CL21C120JBANFN□	
		33pF	±5%	CL10C330JB8NFN□		15pF	±5%	CL21C150JBANFN□	
		39pF	±5%	CL10C390JB8NFN□		18pF	±5%	CL21C180JBANFN□	
		47pF	±5%	CL10C470JB8NFN□		20pF	±5%	CL21C200JBANFN□	
		56pF	±5%	CL10C560JB8NFN□		22pF	±5%	CL21C220JBANFN□	
		62pF	±5%	CL10C620JB8NFN□		25pF	±5%	CL21C250JBANFN□	
		68pF	±5%	CL10C680JB8NFN□		27pF	±5%	CL21C270JBANFN□	
		82pF	±5%	CL10C820JB8NFN□		30pF	±5%	CL21C300JBANFN□	
		100pF	±5%	CL10C101JB8NFN□		33pF	±5%	CL21C330JBANFN□	
		120pF	±5%	CL10C121JB8NFN□		39pF	±5%	CL21C390JBANFN□	
		150pF	±5%	CL10C151JB8NFN□		47pF	±5%	CL21C470JBANFN□	
						51pF	±5%	CL21C510JBANFN□	
						56pF	±5%	CL21C560JBANFN□	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Industrial Capacitors for Power Application

NFN - C0G / X5R / X6S / X7R

Product Line Up (C0G)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.75mm	50Vdc	68pF	±5%	CL21C680JBCNFN □	1.00mm	50Vdc	1.0nF	±5%	CL31C102JBCNFN □
		82pF	±5%	CL21C820JBCNFN □			1.5nF	±5%	CL31C152JBCNFN □
		100pF	±5%	CL21C101JBCNFN □		100Vdc	100pF	±5%	CL31C101JCCNFN □
		120pF	±5%	CL21C121JBCNFN □			330pF	±5%	CL31C331JCCNFN □
		150pF	±5%	CL21C151JBCNFN □			470pF	±5%	CL31C471JCCNFN □
		180pF	±5%	CL21C181JBCNFN □		200Vdc	100pF	±5%	CL31C101JDCNFN □
		200pF	±5%	CL21C201JBCNFN □			220pF	±5%	CL31C221JDCNFN □
		220pF	±5%	CL21C221JBCNFN □		50Vdc	4.7nF	±5%	CL31C472JBFNFN □
		240pF	±5%	CL21C241JBCNFN □		500Vdc	33pF	±5%	CL31C330JGFNFN □
		270pF	±5%	CL21C271JBCNFN □			47pF	±5%	CL31C470JGFNFN □
		300pF	±5%	CL21C301JBCNFN □			100pF	±5%	CL31C101JGFNFN □
		330pF	±5%	CL21C331JBCNFN □			180pF	±5%	CL31C181JGFNFN □
		390pF	±5%	CL21C391JBCNFN □			220pF	±5%	CL31C221JGFNFN □
		470pF	±5%	CL21C471JBCNFN □			330pF	±5%	CL31C331JGFNFN □
		560pF	±5%	CL21C561JBCNFN □			390pF	±5%	CL31C391JGFNFN □
	100Vdc	22pF	±5%	CL21C220JCANFN □			470pF	±5%	CL31C471JGFNFN □
		33pF	±5%	CL21C330JCANFN □			560pF	±5%	CL31C561JGFNFN □
		100pF	±5%	CL21C101JCANFN □	1.40mm	630Vdc	10pF	±5%	CL31C100JHFNFN □
0.95mm	50Vdc	680pF	±5%	CL21C681JBCNFN □			15pF	±5%	CL31C150JHFNFN □
		820pF	±5%	CL21C821JBCNFN □			33pF	±5%	CL31C330JHFNFN □
		1.0nF	±5%	CL21C102JBCNFN □			47pF	±5%	CL31C470JHFNFN □
	100Vdc	470pF	±5%	CL21C471JCCNFN □			100pF	±5%	CL31C101JHFNFN □
		47pF	±5%	CL21C470JDCNFN □			150pF	±5%	CL31C151JHFNFN □
		100pF	±5%	CL21C101JDCNFN □			220pF	±5%	CL31C221JHFNFN □
	200Vdc	220pF	±5%	CL21C221JDCNFN □			220pF	±10%	CL31C221KHFNFN □
		4.7nF	±5%	CL21C472JAFNFN □	1.35mm		330pF	±5%	CL31C331JHFNFN □
		1.5nF	±5%	CL21C152JBFNFN □			470pF	±5%	CL31C471JHFNFN □
1.35mm	50Vdc	1.8nF	±5%	CL21C182JBFNFN □		1kVdc	10pF	±5%	CL31C100JIFNFN □
		2.2nF	±5%	CL21C222JBFNFN □			18pF	±5%	CL31C180JIFNFN □
		3.9nF	±5%	CL21C392JBFNFN □			22pF	±5%	CL31C220JIFNFN □
		4.7nF	±5%	CL21C472JBFNFN □			33pF	±5%	CL31C330JIFNFN □
		10nF	±5%	CL21C103JBFNFN □			47pF	±5%	CL31C470JIFNFN □
		1.0nF	±5%	CL21C102JDFNFN □			56pF	±5%	CL31C560JIFNFN □
		680pF	±5%	CL31C680JIFNFN □			68pF	±5%	CL31C680JIFNFN □
	200Vdc	1.0nF	±5%	CL21C101JIFNFN □			100pF	±5%	CL31C101JIFNFN □
		12pF	±5%	CL31C120JBCNFN □	1.80mm	500Vdc	680pF	±5%	CL31C681JGHNFN □
		15pF	±5%	CL31C150JBCNFN □			1.0nF	±5%	CL31C102JGHNFN □
1.00mm	50Vdc	18pF	±5%	CL31C180JBCNFN □			2.2nF	±5%	CL31C222JGHNFN □
		22pF	±5%	CL31C220JBCNFN □		630Vdc	680pF	±5%	CL31C681JHHNFN □
		33pF	±5%	CL31C330JBCNFN □			1.0nF	±5%	CL31C102JHHNFN □
		47pF	±5%	CL31C470JBCNFN □			1.2nF	±5%	CL31C122JHHNFN □
		56pF	±5%	CL31C560JBCNFN □			1.5nF	±5%	CL31C152JHHNFN □
		100pF	±5%	CL31C101JBCNFN □			2.2nF	±5%	CL31C222JHHNFN □
		100pF	±10%	CL31C101KBCNFN □			3.3nF	±5%	CL31C332JHHNFN □
		120pF	±5%	CL31C121JBCNFN □		1kVdc	220pF	±5%	CL31C221JHHNFN □
		220pF	±5%	CL31C221JBCNFN □					
		270pF	±5%	CL31C271JBCNFN □					
		330pF	±5%	CL31C331JBCNFN □					
		470pF	±5%	CL31C471JBCNFN □					
		560pF	±5%	CL31C561JBCNFN □					
		680pF	±5%	CL31C680JBCNFN □					
		1.0nF	±5%	CL31C101JCANFN □					
		1.5nF	±5%	CL31C152JCANFN □					
		2.2nF	±5%	CL31C222JCANFN □					
		3.3nF	±5%	CL31C332JCANFN □					
		4.7nF	±5%	CL31C472JCANFN □					
		6.8nF	±5%	CL31C682JCANFN □					
		1.0nF	±5%	CL31C101JCFNFN □					
		1.5nF	±5%	CL31C152JCFNFN □					
		2.2nF	±5%	CL31C222JCFNFN □					
		3.3nF	±5%	CL31C332JCFNFN □					
		4.7nF	±5%	CL31C472JCFNFN □					
		6.8nF	±5%	CL31C682JCFNFN □					
		1.0nF	±5%	CL31C101JDFNFN □					
		1.5nF	±5%	CL31C152JDFNFN □					
		2.2nF	±5%	CL31C222JDFNFN □					
		3.3nF	±5%	CL31C332JDFNFN □					
		4.7nF	±5%	CL31C472JDFNFN □					
		6.8nF	±5%	CL31C682JDFNFN □					
		1.0nF	±5%	CL31C101JIFNFN □					
		1.5nF	±5%	CL31C152JIFNFN □					
		2.2nF	±5%	CL31C222JIFNFN □					
		3.3nF	±5%	CL31C332JIFNFN □					
		4.7nF	±5%	CL31C472JIFNFN □					
		6.8nF	±5%	CL31C682JIFNFN □					
		1.0nF	±5%	CL31C101JHFNFN □					
		1.5nF	±5%	CL31C152JHFNFN □					
		2.2nF	±5%	CL31C222JHFNFN □					
		3.3nF	±5%	CL31C332JHFNFN □					
		4.7nF	±5%	CL31C472JHFNFN □					
		6.8nF	±5%	CL31C682JHFNFN □					
		1.0nF	±5%	CL31C101JHNNFN □					
		1.5nF	±5%	CL31C152JHNNFN □					
		2.2nF	±5%	CL31C222JHNNFN □					
		3.3nF	±5%	CL31C332JHNNFN □					
		4.7nF	±5%	CL31C472JHNNFN □					
		6.8nF	±5%	CL31C682JHNNFN □					
		1.0nF	±5%	CL31C101JINNFN □					
		1.5nF	±5%	CL31C152JINNFN □					
		2.2nF	±5%	CL31C222JINNFN □					
		3.3nF	±5%	CL31C332JINNFN □					
		4.7nF	±5%	CL31C472JINNFN □					
		6.8nF	±5%	CL31C682JINNFN □					
		1.0nF	±5%	CL31C101JPNNFN □					
		1.5nF	±5%	CL31C152JPNNFN □					
		2.2nF	±5%	CL31C222JPNNFN □					
		3.3nF	±5%	CL31C332JPNNFN □					
		4.7nF	±5%	CL31C472JPNNFN □					
		6.8nF	±5%	CL31C682JPNNFN □					
		1.0nF	±5%	CL31C101JQNFN □					
		1.5nF	±5%	CL31C152JQNFN □					
		2.2nF	±5%	CL31C222JQNFN □					
		3.3nF	±5%	CL31C332JQNFN □					
		4.7nF	±5%	CL31C472JQNFN □					
		6.8nF	±5%	CL31C682JQNFN □					
		1.0nF	±5%	CL31C101JQHNFN □					
		1.5nF	±5%	CL31C152JQHNFN □					
		2.2nF	±5%	CL31C222JQHNFN □					
		3.3nF	±5%	CL31C332JQHNFN □					
		4.7nF	±5%	CL31C472JQHNFN □					
		6.8nF	±5%	CL31C682JQHNFN □					
		1.0nF	±5%	CL31C101JQHNFN □					
		1.5nF	±5%	CL31C152JQHNFN □					
		2.2nF	±5%	CL31C222JQHNFN □					
		3.3nF	±5%	CL31C332JQHNFN □					
		4.7nF	±5%	CL31C472JQHNFN □					
		6.8nF	±5%	CL31C682JQHNFN □					
		1.0nF	±5%	CL31C101JQHNFN □					</

Product Line Up (X5R)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.55mm	4.0Vdc	2.2uF	±20%	CL05A225MR5NFN □	<small>Derating</small>
	6.3Vdc	470nF	±10%	CL05A474KQ5NFN □	
		1.0uF	±10%	CL05A105KQ5NFN □	<small>Derating</small>
	10Vdc	2.2uF	±10%	CL05A225KQ5NFN □	<small>Derating Ref.</small>
		100nF	±10%	CL05A104KP5NFN □	
		220nF	±10%	CL05A224KP5NFN □	
		470nF	±10%	CL05A474KP5NFN □	
	16Vdc	1.0uF	±10%	CL05A105KO5NFN □	<small>Derating</small>

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	16Vdc	22uF	±10%	CL31A226KOCLFN □	<small>Derating</small>
	1.80mm	22uF	±20%	CL31A226MOCLFN □	<small>Derating</small>
		10uF	±10%	CL31A106KQHNFN □	
		22uF	±10%	CL31A226KQHNFN □	
	6.3Vdc	22uF	±20%	CL31A226MQHNFN □	
		4.7uF	±10%	CL31A475KPHNFN □	
		10uF	±10%	CL31A106KPHNFN □	
		4.7uF	±10%	CL31A475KOHNFN □	
16Vdc	25Vdc	4.7uF	±20%	CL31A475MOHNFN □	
		10uF	±10%	CL31A106KOHNFN □	
		22uF	±10%	CL31A226KOHNFN □	
		3.3uF	±10%	CL31A335KAHNFN □	
	50Vdc	4.7uF	±10%	CL31A475KAHNFN □	
		10uF	±10%	CL31A106KAHNFN □	
		22uF	±10%	CL31A226KAHNFN □	<small>Derating</small>
		10uF	±10%	CL31A106KBHNFN □	

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.70mm	6.3Vdc	22uF	±10%	CL32A226KQJNFN □	
	10Vdc	22uF	±20%	CL32A226MQJNFN □	
		22uF	±10%	CL32A226KPJNFN □	
		10uF	±10%	CL32A106KOJNFN □	
	16Vdc	22uF	±10%	CL32A226KOJNFN □	
		10uF	±10%	CL32A106KAJNFN □	
		22uF	±10%	CL32A226KAJNFN □	
		10uF	±10%	CL32A106KAJNFN □	
25Vdc	2.80mm	10uF	±10%	CL32A106KAJNFN □	
		22uF	±10%	CL32A226KAJNFN □	
25Vdc	6.3Vdc	100uF	±20%	CL32A107MQVNFN □	<small>Derating</small>
	150uF	±20%	CL32A157MQVNFN □	<small>Derating</small>	

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.35mm	6.3Vdc	4.7uF	±10%	CL21A475KQFNFN □	
		10uF	±10%	CL21A106KQFNFN □	
	10Vdc	2.2uF	±10%	CL21A225KPFNFN □	
		4.7uF	±10%	CL21A475KPFNFN □	
		10uF	±10%	CL21A106KPFNFN □	
		2.2uF	±10%	CL21A225KOFNFN □	
	16Vdc	22uF	±10%	CL21A226KQQNFN □	
		10uF	±10%	CL21A106KOQNFN □	<small>Derating</small>
1.40mm	16Vdc	4.7uF	±10%	CL21A475KAQNFN □	
		22uF	±20%	CL21A226MAQNFN □	<small>Derating</small>
	25Vdc	10uF	±10%	CL21A106KAYNFN □	<small>Derating</small>
		10uF	±10%	CL21A106KAYNFN □	
1.45mm	25Vdc	10uF	±10%	CL21A106KAYNFN □	<small>Derating</small>

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Industrial Capacitors for Power Application

NFN - C0G / X5R / X6S / X7R

Product Line Up (X6S)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.55mm	6.3Vdc	1.0uF	±10%	CL05X105KQ5NFN □	<small>Derating</small>
0.57mm	2.5Vdc	2.2uF	±20%	CL05X225MS5NFN □	<small>Derating</small>

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.40mm	4.0Vdc	22uF	±20%	CL21X226MRQNFN □	<small>Derating</small>
1.45mm	25Vdc	10uF	±10%	CL21X106KAYNFN □	<small>Derating</small>

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.80mm	6.3Vdc	47uF	±20%	CL31X476MQHNFN □	<small>Derating</small>

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Product Line Up (X7R)

■ Size : 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.33mm	10Vdc	4.7nF	±10%	CL03B472KP3NFN□		0.90mm	16Vdc	47nF	±10%	CL10B473KO8NFN□	
		6.8nF	±10%	CL03B682KP3NFN□				68nF	±10%	CL10B683KO8NFN□	
		10nF	±10%	CL03B103KP3NFN□				100nF	±10%	CL10B104KO8NFN□	

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.55mm	10Vdc	100nF	±10%	CL05B104KP5NFN□		0.90mm	16Vdc	1.0nF	±10%	CL10B102KA8NFN□	
		330pF	±10%	CL05B331K05NFN□				10nF	±10%	CL10B103KA8NFN□	
		8.2nF	±10%	CL05B822K05NFN□				12nF	±10%	CL10B123KA8NFN□	
		10nF	±10%	CL05B103K05NFN□				15nF	±10%	CL10B153KA8NFN□	
		15nF	±10%	CL05B153K05NFN□				18nF	±10%	CL10B183KA8NFN□	
		22nF	±10%	CL05B223K05NFN□				22nF	±10%	CL10B223KA8NFN□	
		27nF	±10%	CL05B273K05NFN□				27nF	±10%	CL10B273KA8NFN□	
		33nF	±10%	CL05B333K05NFN□				33nF	±10%	CL10B333KA8NFN□	
		68nF	±10%	CL05B683K05NFN□				47nF	±10%	CL10B473KA8NFN□	
		100nF	±10%	CL05B104K05NFN□				68nF	±10%	CL10B683KA8NFN□	
	16Vdc	4.7nF	±10%	CL05B472KA5NFN□		0.90mm	25Vdc	100nF	±10%	CL10B104KA8NFN□	
		5.6nF	±10%	CL05B562KA5NFN□				150nF	±10%	CL10B154KA8NFN□	
		10nF	±10%	CL05B103KA5NFN□				220nF	±10%	CL10B224KA8NFN□	
		22nF	±10%	CL05B223KA5NFN□				470nF	±10%	CL10B474KA8NFN□	
	25Vdc	270pF	±10%	CL05B271KB5NFN□		0.90mm	50Vdc	1.0uF	±10%	CL10B105KA8NFN□	
		330pF	±10%	CL05B331KB5NFN□				100pF	±10%	CL10B101KB8NFN□	
		390pF	±10%	CL05B391KB5NFN□				150pF	±10%	CL10B151KB8NFN□	
		470pF	±10%	CL05B471KB5NFN□				180pF	±10%	CL10B181KB8NFN□	
		560pF	±10%	CL05B561KB5NFN□				220pF	±10%	CL10B221KB8NFN□	
		680pF	±10%	CL05B681KB5NFN□				270pF	±10%	CL10B271KB8NFN□	
		820pF	±10%	CL05B821KB5NFN□				330pF	±10%	CL10B331KB8NFN□	
		1.0nF	±5%	CL05B102JB5NFN□				390pF	±10%	CL10B391KB8NFN□	
		1.0nF	±10%	CL05B102KB5NFN□				470pF	±10%	CL10B471KB8NFN□	
		1.5nF	±10%	CL05B152KB5NFN□				560pF	±10%	CL10B561KB8NFN□	
		2.2nF	±10%	CL05B222KB5NFN□				820pF	±10%	CL10B821KB8NFN□	
		3.3nF	±10%	CL05B332KB5NFN□				1.0nF	±5%	CL10B102JB8NFN□	
		4.7nF	±10%	CL05B472KB5NFN□				1.0nF	±10%	CL10B102KB8NFN□	
		5.6nF	±10%	CL05B562KB5NFN□				1.2nF	±10%	CL10B122KB8NFN□	
		10nF	±10%	CL05B103KB5NFN□				1.5nF	±10%	CL10B152KB8NFN□	

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	6.3Vdc	1.0uF	±10%	CL10B105KQ8NFN□		0.90mm	16Vdc	1.8nF	±10%	CL10B182KB8NFN□	
		220nF	±10%	CL10B224KP8NFN□				2.2nF	±10%	CL10B222KB8NFN□	
		330nF	±10%	CL10B334KP8NFN□				2.7nF	±10%	CL10B272KB8NFN□	
		470nF	±10%	CL10B474KP8NFN□				3.3nF	±10%	CL10B332KB8NFN□	
		1.0uF	±10%	CL10B105KP8NFN□				3.9nF	±10%	CL10B392KB8NFN□	
	16Vdc	2.2uF	±10%	CL10B225KP8NFN□	Ref.			4.7nF	±10%	CL10B472KB8NFN□	
		1.5nF	±10%	CL10B152KO8NFN□				5.6nF	±10%	CL10B562KB8NFN□	
		3.3nF	±10%	CL10B332KO8NFN□				6.8nF	±10%	CL10B682KB8NFN□	
		10nF	±10%	CL10B103KO8NFN□				8.2nF	±10%	CL10B822KB8NFN□	
		15nF	±10%	CL10B153KO8NFN□				10nF	±5%	CL10B103JB8NFN□	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Industrial Capacitors for Power Application

NFN - C0G / X5R / X6S / X7R

Product Line Up (X7R)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	50Vdc	33nF	±10%	CL10B333KB8NPN □	
		39nF	±10%	CL10B393KB8NPN □	
		47nF	±10%	CL10B473KB8NPN □	
		56nF	±10%	CL10B563KB8NPN □	
		68nF	±10%	CL10B683KB8NPN □	
		82nF	±10%	CL10B823KB8NPN □	
		100nF	±10%	CL10B104KB8NPN □	
		100nF	±20%	CL10B104MB8NPN □	

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.75mm	25Vdc	1.0nF	±10%	CL21B102KAANFN □	
		10nF	±10%	CL21B103KAANFN □	
	50Vdc	100pF	±10%	CL21B101KBANFN □	
		180pF	±10%	CL21B181KBANFN □	
		220pF	±10%	CL21B221KBANFN □	
		270pF	±10%	CL21B271KBANFN □	
		330pF	±10%	CL21B331KBANFN □	
		390pF	±10%	CL21B391KBANFN □	
		470pF	±10%	CL21B471KBANFN □	
		560pF	±10%	CL21B561KBANFN □	
		820pF	±10%	CL21B821KBANFN □	
		1.0nF	±10%	CL21B102KBCNFN □	
		1.5nF	±10%	CL21B152KBCNFN □	
		2.2nF	±10%	CL21B222KBCNFN □	
		2.7nF	±10%	CL21B272KBCNFN □	
		3.3nF	±10%	CL21B332KBCNFN □	
		4.7nF	±10%	CL21B472KBCNFN □	
		6.8nF	±10%	CL21B682KBCNFN □	
		8.2nF	±10%	CL21B822KBCNFN □	
	100Vdc	10nF	±10%	CL21B103KBCNFN □	
		12nF	±10%	CL21B123KBCNFN □	
		15nF	±10%	CL21B153KBCNFN □	
		18nF	±10%	CL21B183KBCNFN □	
		20nF	±10%	CL21B203KBCNFN □	
		22nF	±10%	CL21B223KBCNFN □	
		27nF	±10%	CL21B273KBCNFN □	
		33nF	±10%	CL21B333KBCNFN □	
		1.0nF	±10%	CL21B102KCANFN □	
		2.2nF	±10%	CL21B222KCANFN □	
		4.7nF	±10%	CL21B472KCANFN □	
		6.8nF	±10%	CL21B682KCANFN □	
		10nF	±10%	CL21B103KCANFN □	
	100Vdc	220nF	±10%	CL21B224KOCNFN □	
		330nF	±10%	CL21B334KOCNFN □	
		100nF	±10%	CL21B104KACNFN □	
		150pF	±10%	CL21B151KBCNFN □	
		180pF	±10%	CL21B181KBCNFN □	
0.95mm	16Vdc	220nF	±10%	CL21B224KOCNFN □	
		330nF	±10%	CL21B334KOCNFN □	
	25Vdc	100nF	±10%	CL21B104KACNFN □	
		150pF	±10%	CL21B151KBCNFN □	
	50Vdc	180pF	±10%	CL21B181KBCNFN □	

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (X7R)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.35mm	100Vdc	220nF	±10%	CL21B224KCFNFN □	
1.40mm	6.3Vdc	4.7uF	±10%	CL21B475KQQNFN □	Ref.
		10uF	±10%	CL21B106KQQNFN □	
	10Vdc	10uF	±10%	CL21B106KPQNFN □	
	16Vdc	10uF	±10%	CL21B106KOQNFN □	

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.00mm	10Vdc	1.2uF	±10%	CL31B125KPCNFN □	
	16Vdc	330nF	±10%	CL31B334KOCNFN □	
	25Vdc	220nF	±10%	CL31B224KACNFN □	
	50Vdc	220pF	±10%	CL31B221KBCNFN □	
		330pF	±10%	CL31B331KBCNFN □	
		470pF	±10%	CL31B471KBCNFN □	
		560pF	±10%	CL31B561KBCNFN □	
		680pF	±10%	CL31B681KBCNFN □	
		1.5nF	±10%	CL31B152KBCNFN □	
		2.2nF	±10%	CL31B222KBCNFN □	
		2.7nF	±10%	CL31B272KBCNFN □	
		3.3nF	±10%	CL31B332KBCNFN □	
		4.7nF	±10%	CL31B472KBCNFN □	
		8.2nF	±10%	CL31B822KBCNFN □	
		10nF	±10%	CL31B103KBCNFN □	
		15nF	±10%	CL31B153KBCNFN □	
		33nF	±10%	CL31B333KBCNFN □	
		47nF	±10%	CL31B473KBCNFN □	
		68nF	±10%	CL31B683KBCNFN □	
	100Vdc	100nF	±10%	CL31B104KBCNFN □	
1.40mm	100Vdc	1.0nF	±10%	CL31B102KCCNFN □	
		2.2nF	±10%	CL31B222KCCNFN □	
		3.3nF	±10%	CL31B332KCCNFN □	
		10nF	±10%	CL31B103KCCNFN □	
		22nF	±10%	CL31B223KCCNFN □	
	200Vdc	470pF	±10%	CL31B471KDCNFN □	
		1.0nF	±10%	CL31B102KDCNFN □	
		330pF	±10%	CL31B334KDCNFN □	
		680pF	±10%	CL31B681KDCNFN □	
		1.0nF	±10%	CL31B102KDCNFN □	

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.40mm	630Vdc	2.2nF	±10%	CL31B222KHFNFN □	
		3.3nF	±10%	CL31B332KHFNFN □	
		4.7nF	±10%	CL31B472KHFNFN □	
		6.8nF	±10%	CL31B682KHFNFN □	
		10nF	±10%	CL31B103KHFNFN □	
	1kVdc	220pF	±10%	CL31B221KIFNFN □	Derating
		1.0nF	±10%	CL31B102KIFNFN □	Derating
		1.5nF	±10%	CL31B152KIFNFN □	Derating
		6.8uF	±10%	CL31B685KQHNFN □	
		10uF	±10%	CL31B106KQHNFN □	
1.80mm	10Vdc	4.7uF	±10%	CL31B475KPHNFN □	
		22uF	±10%	CL31B226KPHNFN □	
		2.2uF	±10%	CL31B225KOHNFN □	
		3.3uF	±10%	CL31B335KOHNFN □	
		4.7uF	±10%	CL31B475KOHNFN □	
	25Vdc	10uF	±10%	CL31B106KOHNFN □	
		680nF	±10%	CL31B684KAHNFN □	
		1.0uF	±10%	CL31B105KAHNFN □	
		2.2uF	±10%	CL31B225KAHNFN □	
		4.7uF	±10%	CL31B475KAHNFN □	
2.20mm	35Vdc	10uF	±10%	CL31B106KLHNFN □	Ref.
		470nF	±10%	CL31B474KBHNFN □	
		680nF	±10%	CL31B684KBHNFN □	
		1.0uF	±10%	CL31B105KBHNFN □	
		2.2uF	±10%	CL31B225KBHNFN □	
	50Vdc	4.7uF	±10%	CL31B475KBHNFN □	
		220nF	±10%	CL31B224KCHNFN □	
		1.0uF	±10%	CL31B105KCHNFN □	
		100nF	±10%	CL31B104KDHNFN □	
		250Vdc	100nF	±10%	CL31B333KGHNFN □
2.70mm	500Vdc	33nF	±10%	CL31B223KHHNFN □	
		22nF	±10%	CL31B333KHHNFN □	
		33nF	±10%	CL31B222KJHNFN □	
		2.2nF	±10%	CL32B225KBJNFN □	
		2.2nF	±10%	CL32B226MPJNFN □	
	100Vdc	10uF	±10%	CL32B106KOJNFN □	
		22uF	±10%	CL32B226KOJNFN □	
		10uF	±10%	CL32B106KAJNFN □	
		22uF	±10%	CL32B226KAJNFN □	
		2.2uF	±10%	CL32B225KBJNFN □	
3.30mm	25Vdc	10uF	±10%	CL32B106KCAJNFN □	
		22uF	±10%	CL32B226KCAJNFN □	
		10uF	±10%	CL32B106KCAJNFN □	
		22uF	±10%	CL32B226KCAJNFN □	
		2.2uF	±10%	CL32B225KCAJNFN □	
	50Vdc	2.2uF	±10%	CL32B225KBJNFN □	
		4.7uF	±10%	CL32B475KBJNFN □	
		10uF	±10%	CL32B106KBJNFN □	
		1.0uF	±10%	CL32B105KCJNFN □	
		1.0uF	±10%	CL32B105KCJNFN □	

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.20mm	10Vdc	10uF	±10%	CL32B106KPINFN □	
	6.3Vdc	22uF	±20%	CL32B226MQJNFN □	
		470nF	±10%	CL32B474KPJNFN □	
		22uF	±10%	CL32B226KPJNFN □	
		22uF	±20%	CL32B226MPJNFN □	
	16Vdc	10uF	±10%	CL32B106KOJNFN □	
		22uF	±10%	CL32B226KOJNFN □	
		10uF	±10%	CL32B106KAJNFN □	
		22uF	±10%	CL32B226KAJNFN □	
		2.2uF	±10%	CL32B225KBJNFN □	
2.70mm	50Vdc	4.7uF	±10%	CL32B475KBJNFN □	
		10uF	±10%	CL32B106KBJNFN □	
		1.0uF	±10%	CL32B105KBJNFN □	
		1.0uF	±10%	CL32B105KBJNFN □	
		1.0uF	±10%	CL32B105KBJNFN □	
	100Vdc	1.0uF	±10%	CL32B105KCJNFN □	
		1.0uF	±10%	CL32B105KCJNFN □	
		1.0uF	±10%	CL32B105KCJNFN □	
		1.0uF	±10%	CL32B105KCJNFN □	
		1.0uF	±10%	CL32B105KCJNFN □	

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Soft - Termination Capacitors for Power Application

ZFN / SFN / YFN – X7R

Feature




- Soft -Termination relaxes the applied thermal / mechanical stresses by ductile properties of metal-polymer composites.
- Special outgoing inspection for Power application (Bending Test : Sampling Test upto 2mm : X7R)
- Can be applied to power(SMPS, DC – DC Converter) and industrial equipment
- ZFN, SFN, YFN series : Metal Epoxy

Application

- Power(SMPS, DC – DC converter)
- Ideal for decoupling and filtering applications (Class II : X7R)

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
21	0805	1.60±0.10	0.80±0.10	0.80±0.10	8	0.30±0.20
		2.00±0.10	1.25±0.10	0.65±0.10	A	
		2.00±0.10	1.25±0.10	0.85±0.10	C	
		2.00±0.10	1.25±0.10	1.15±0.10	M	
		2.00±0.10	1.25±0.10	1.25±0.10	F	
31	1206	3.20±0.15	1.60±0.15	0.85±0.15	C	
		3.20±0.15	1.60±0.15	1.25±0.15	F	
		3.20±0.20	1.60±0.20	1.60±0.20	H	0.50±0.30

Industrial Capacitance Table (X7R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance																
		nF										uF						
		1.0	1.5	2.2	3.3	4.7	10	22	33	47	68	100	220	470	1.0	2.2	4.7	10
0402(1005)	50																	
	10																	
	16																	
	25																	
	50	0.47																
0805 (2012)	10																	
	16																	
	25																	
	50																	
1206 (3216)	16																	
	50																	

Product Line Up (ZFN - X7R)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	10Vdc	2.2uF	±10%	CL10B225KP8ZFN □	Ref. □
	16Vdc	1.0uF	±10%	CL10B105KO8ZFN □	

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.35mm	16Vdc	4.7uF	±10%	CL21B475KOFZFN □	Ref. □
	25Vdc	4.7uF	±10%	CL21B475KAFZFN □	Ref. □
	50Vdc	1.0uF	±10%	CL21B105KBFZFN □	
1.40mm	10Vdc	10uF	±10%	CL21B106KPQZFN □	

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.80mm	16Vdc	10uF	±10%	CL31B106KOHZFN □	
	50Vdc	4.7uF	±10%	CL31B475KBHZFN □	

Product Line Up (SFN - X7R)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.55mm	50Vdc	22nF	±10%	CL05B223KB5SFN □	

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	16Vdc	68nF	±10%	CL10B683K08SFN □	
		100nF	±10%	CL10B104K08SFN □	
		220nF	±10%	CL10B224K08SFN □	
		1.0uF	±10%	CL10B105K08SFN □	
25Vdc	25Vdc	10nF	±10%	CL10B103KA8SFN □	
		150nF	±10%	CL10B154KA8SFN □	
		220nF	±10%	CL10B224KA8SFN □	
		1.0uF	±10%	CL10B105KA8SFN □	
50Vdc	50Vdc	470pF	±10%	CL10B471KB8SFN □	
		1.0nF	±10%	CL10B102KB8SFN □	
		1.5nF	±10%	CL10B152KB8SFN □	
		2.2nF	±10%	CL10B222KB8SFN □	
		2.7nF	±10%	CL10B272KB8SFN □	
		3.3nF	±10%	CL10B332KB8SFN □	
		3.9nF	±10%	CL10B392KB8SFN □	
		4.7nF	±10%	CL10B472KB8SFN □	
		5.6nF	±10%	CL10B562KB8SFN □	
		6.8nF	±10%	CL10B682KB8SFN □	
		8.2nF	±10%	CL10B822KB8SFN □	
		10nF	±10%	CL10B103KB8SFN □	
		12nF	±10%	CL10B123KB8SFN □	
		15nF	±10%	CL10B153KB8SFN □	
		22nF	±10%	CL10B223KB8SFN □	
		27nF	±10%	CL10B273KB8SFN □	
		33nF	±10%	CL10B333KB8SFN □	
		39nF	±10%	CL10B393KB8SFN □	
		47nF	±10%	CL10B473KB8SFN □	
		56nF	±10%	CL10B563KB8SFN □	
		100nF	±10%	CL10B104KB8SFN □	
		220nF	±10%	CL10B224KB8SFN □	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Soft – Termination Capacitors for Power Application

ZFN / SFN / YFN – X7R

Product Line Up (SFN – X7R)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.70mm	50Vdc	330pF	±10%	CL21B331KB6SFN □		1.80mm	100Vdc	220nF	±10%	CL31B224KCHSFN □	
		470pF	±5%	CL21B471JB6SFN □				470nF	±10%	CL31B474KCHSFN □	
		560pF	±10%	CL21B561KB6SFN □				1.0uF	±10%	CL31B105KCHSFN □	
		680pF	±10%	CL21B681KB6SFN □				2.2uF	±10%	CL31B225KCHSFN □	
		2.2nF	±10%	CL21B222KB6SFN □			250Vdc	47nF	±10%	CL31B473KEHSFN □	
		3.3nF	±10%	CL21B332KB6SFN □				100nF	±10%	CL31B104KEHSFN □	
		4.7nF	±10%	CL21B472KB6SFN □				22nF	±10%	CL31B223KHHSFN □	
		6.8nF	±10%	CL21B682KB6SFN □				33nF	±10%	CL31B333KHHSFN □	
		8.2nF	±10%	CL21B822KB6SFN □							
		10nF	±10%	CL21B103KB6SFN □							
		15nF	±10%	CL21B153KB6SFN □							
		22nF	±10%	CL21B223KB6SFN □							
0.95mm	50Vdc	4.7nF	±10%	CL21B472KBCSFN □							
		10nF	±10%	CL21B103KBCSFN □							
		22nF	±10%	CL21B223KBCSFN □							
		39nF	±10%	CL21B393KBCSFN □							
		47nF	±10%	CL21B473KBCSFN □							
		100nF	±10%	CL21B104KBCSFN □							
	250Vdc	1.0nF	±10%	CL21B102KECSFN □							
		2.2nF	±10%	CL21B222KECSFN □							
1.35mm	16Vdc	1.0uF	±10%	CL21B105KOFSFN □							
		220nF	±10%	CL21B224KAFSFN □							
		470nF	±10%	CL21B474KAFSFN □							
		1.0uF	±10%	CL21B105KAFSFN □							
		2.2uF	±10%	CL21B225KAFSFN □							
	50Vdc	220nF	±10%	CL21B224KBFNFN □							
		470nF	±10%	CL21B474KBFNFN □							
		1.0uF	±10%	CL21B105KBFNFN □							
	100Vdc	100nF	±10%	CL21B104KCFSFN □							
		220nF	±10%	CL21B224KCFSFN □							
1.40mm	16Vdc	4.7uF	±10%	CL21B475KOQSFN □							

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.00mm	50Vdc	100nF	±10%	CL31B104KBCSFN □	
1.25mm	16Vdc	470nF	±10%	CL31B474KOPSFN □	
	50Vdc	1.0uF	±10%	CL31B105KBPFSN □	
1.40mm	630Vdc	220pF	±10%	CL31B221KHFSFN □	
		1.0nF	±10%	CL31B102KHFSFN □	
		1.5nF	±10%	CL31B152KHFSFN □	
		2.2nF	±10%	CL31B222KHFSFN □	
		2.7nF	±10%	CL31B272KHFSFN □	
		3.3nF	±10%	CL31B332KHFSFN □	
		4.7nF	±10%	CL31B472KHFSFN □	
		6.8nF	±10%	CL31B682KHFSFN □	
		10nF	±10%	CL31B103KHFSFN □	
	1kVdc	1.0nF	±10%	CL31B102KIFS FN □	Derating
1.80mm	25Vdc	10uF	±10%	CL31B106KAHSFN □	
	35Vdc	10uF	±10%	CL31B106KLHSFN □	Ref.

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑


Soft – Termination(3mm) Industrial Capacitors

ZW6 / SW6 – X7R / X7S


Feature




- Excellent bending strength($\geq 3\text{mm}$) & $40^\circ\text{C} 95\%\text{RH} 500\text{hr}$ with rated voltage
- Soft – Termination is applicable to all class II MLCC series
- W6 = Industrial(3mm bending) code for Network, Power, etc
- Speical outgoing inspection for industrial application (HALT, etc)
- Bending strength simulation



Cross-section of MLCC with Cu – Termination



Cross-section of MLCC with Soft – Termination



Soft – Termination relaxes the applied thermal – mechanical stresses by ductile properties of metal – polymer composites.


- Comparison of bending strength



Application

- Network, Power application and etc.
- Ideal for decoupling and filtering applications (Class II : X7R)

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
05	0402	1.00 ± 0.05	0.50 ± 0.05	0.50 ± 0.05	5	0.25 ± 0.10
10	0603	1.60 ± 0.10	0.80 ± 0.10	0.80 ± 0.10	8	0.30 ± 0.20
21	0805	2.00 ± 0.10	1.25 ± 0.10	0.85 ± 0.10	C	
		2.00 ± 0.10	1.25 ± 0.10	1.25 ± 0.10	F	0.50+0.20/-0.30
		2.00 ± 0.15	1.25 ± 0.15	1.25 ± 0.15	Q	
31	1206	3.20 ± 0.20	1.60 ± 0.20	1.15 ± 0.10	P	0.50 ± 0.30
		3.20 ± 0.15	1.60 ± 0.15	1.25 ± 0.15	F	
		3.20 ± 0.20	1.60 ± 0.20	1.60 ± 0.20	H	
32	1210	3.20 ± 0.30	2.50 ± 0.20	2.50 ± 0.20	J	0.60 ± 0.30
		3.20 ± 0.40	2.50 ± 0.30	2.50 ± 0.30	V	

Soft – Termination(3mm) Industrial Capacitors

ZW6 / SW6 – X7R /X7S

Industrial Capacitance Table (X7R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance															
		nF						uF									
		1.5	2.2	4.7	10	22	47	100	220	470	1.0	2.2	4.7	10	22	47	100
0402 (1005)	16																
	25																
	50																
0603 (1608)	16																
	25																
	50																
	100																
0805 (2012)	10																
	16																
	25																
	50																
	100																
1206 (3216)	10																
	16																
	25																
	50																
	100																
1210 (3225)	10																
	16																
	50																
	100																

Product Line Up (X7R)

Product Line Up (X7S)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	16Vdc	1.0uF	±10%	CL10B105K08ZW6□	
	25Vdc	1.0uF	±10%	CL10B105KA8ZW6□	
	50Vdc	100nF	±10%	CL10B104KB8ZW6□	

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.90mm	50Vdc	100uF	±10%	CL10Y104KB8ZW6□	

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.95mm	100Vdc	47nF	±10%	CL21B473KCCZW6□	
		100nF	±10%	CL21B104KCCZW6□	
1.35mm	25Vdc	1.0uF	±10%	CL21B105KAFZW6□	
		2.2uF	±10%	CL21B225KAFZW6□	
		4.7uF	±10%	CL21B475KAFZW6□	Ref
1.40mm	50Vdc	1.0uF	±10%	CL21B105KBFZW6□	
1.40mm	16Vdc	4.7uF	±10%	CL21B475KOQZW6□	Ref

■ Size: 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.25mm	100Vdc	100nF	±10%	CL31B104KCPZW6□	
1.40mm	100Vdc	100nF	±10%	CL31B104KCFZW6□	
1.80mm	16Vdc	10uF	±10%	CL31B106KOHZW6□	
		4.7uF	±10%	CL31B475KAHZW6□	
		10uF	±10%	CL31B106KAHZW6□	
2.80mm	50Vdc	4.7uF	±10%	CL31B475KBHZW6□	

■ Size: 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.70mm	50Vdc	10uF	±10%	CL32B106KBJZW6□	
	100Vdc	2.2uF	±10%	CL32B225KCJZW6□	
2.80mm	100Vdc	4.7uF	±10%	CL32B475KCVZW6□	Derating

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
 In order to move to the page directly, please click the here. ↑

Reinforced Soft – Termination(3mm) Industrial Capacitors

Z46 – X7R

Feature





- Excellent bending strength($\geq 3\text{mm}$) & $85^{\circ}\text{C} 85\%\text{RH} 1000\text{hr}$ with rated voltage
- Soft-Termination is applicable to all class II MLCC series
- Durability against thermal shock /cycles

Application

- Network, Power application and etc.
- Ideal for decoupling and filtering applications (Class II : X7R)

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
05	0402	1.00 ± 0.05	0.50 ± 0.05	0.50 ± 0.05	5	0.25 ± 0.10
10	0603	1.60 ± 0.10	0.80 ± 0.10	0.80 ± 0.10	8	0.30 ± 0.20
21	0805	2.00 ± 0.10	1.25 ± 0.10	0.60 ± 0.10	6	$0.50+0.20/-0.30$
		2.00 ± 0.10	1.25 ± 0.10	0.85 ± 0.10	C	
		2.00 ± 0.10	1.25 ± 0.10	1.25 ± 0.10	F	
		2.00 ± 0.15	1.25 ± 0.15	1.25 ± 0.15	Q	
31	1206	3.20 ± 0.20	1.60 ± 0.20	1.15 ± 0.10	P	0.50 ± 0.30
		3.20 ± 0.20	1.60 ± 0.20	1.60 ± 0.20	H	
32	1210	3.20 ± 0.30	2.50 ± 0.20	2.50 ± 0.20	J	0.60 ± 0.30

Industrial Capacitance Table (X7R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance											
		nF						uF					
		10	22	47	100	220	470	1.0	2.2	4.7	10	22	47
0402 (1005)	16												
	25												
	50												
0603 (1608)	16												
	25												
	50												
	100												
0805 (2012)	10												
	16												
	25												
	50												
	100												
1206 (3216)	10												
	16												
	25												
	50												
	100												
1210 (3225)	10												
	16												
	50												

Reinforced Soft – Termination(3mm) Industrial Capacitors

Z46 – X7R

Product Line Up (X7R)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	16Vdc	15nF	±10%	CL05B153K05Z46□
		22nF	±10%	CL05B223K05Z46□
		33nF	±10%	CL05B333K05Z46□
		47nF	±10%	CL05B473K05Z46□
		100nF	±10%	CL05B104K05Z46□
	25Vdc	1.0nF	±10%	CL05B102KA5Z46□
		4.7nF	±10%	CL05B472KA5Z46□
		10nF	±10%	CL05B103KA5Z46□
		22nF	±10%	CL05B223KA5Z46□
	50Vdc	330pF	±10%	CL05B331KB5Z46□
		470pF	±10%	CL05B471KB5Z46□
		1.0nF	±10%	CL05B102KB5Z46□
		1.5nF	±10%	CL05B152KB5Z46□
		2.2nF	±10%	CL05B222KB5Z46□
		4.7nF	±10%	CL05B472KB5Z46□
		10nF	±10%	CL05B103KB5Z46□
		15nF	±10%	CL05B153KB5Z46□
		22nF	±10%	CL05B223KB5Z46□

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	
0.90mm	10Vdc	1.0uF	±10%	CL10B105KP8Z46□	
		47nF	±10%	CL10B473K08Z46□	
		68nF	±10%	CL10B683K08Z46□	
		100nF	±10%	CL10B104K08Z46□	
		220nF	±10%	CL10B224K08Z46□	
	16Vdc	470nF	±10%	CL10B474K08Z46□	
		680nF	±10%	CL10B684K08Z46□	
		1.0uF	±10%	CL10B105K08Z46□	
		10nF	±10%	CL10B103KA8Z46□	
	25Vdc	68nF	±10%	CL10B683KA8Z46□	
		100nF	±10%	CL10B104KA8Z46□	
		150nF	±10%	CL10B154KA8Z46□	
		220nF	±10%	CL10B224KA8Z46□	
		470nF	±10%	CL10B474KA8Z46□	
		1.0uF	±10%	CL10B105KA8Z46□	
		220pF	±10%	CL10B221KB8Z46□	
50Vdc	50Vdc	470pF	±10%	CL10B471KB8Z46□	
		1.0nF	±10%	CL10B102KB8Z46□	
		1.2nF	±10%	CL10B122KB8Z46□	
		1.5nF	±10%	CL10B152KB8Z46□	
		2.2nF	±10%	CL10B222KB8Z46□	
		3.3nF	±10%	CL10B332KB8Z46□	
		4.7nF	±10%	CL10B472KB8Z46□	
		6.8nF	±10%	CL10B682KB8Z46□	
		10nF	±10%	CL10B103KB8Z46□	
		15nF	±10%	CL10B153KB8Z46□	
		22nF	±10%	CL10B223KB8Z46□	
		33nF	±10%	CL10B333KB8Z46□	
		47nF	±10%	CL10B473KB8Z46□	
		68nF	±10%	CL10B683KB8Z46□	
100Vdc		100nF	±10%	CL10B104KB8Z46□	
		150nF	±10%	CL10B154KB8Z46□	
		220nF	±10%	CL10B224KB8Z46□	
		270pF	±10%	CL10B271KC8Z46□	
		470pF	±10%	CL10B471KC8Z46□	
		1.0nF	±10%	CL10B102KC8Z46□	
		2.2nF	±10%	CL10B222KC8Z46□	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (X7R)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.70mm	50Vdc	1.0nF	±10%	CL21B102KB6Z46□	
		1.5nF	±10%	CL21B152KB6Z46□	
		2.2nF	±10%	CL21B222KB6Z46□	
		4.7nF	±10%	CL21B472KB6Z46□	
		10nF	±10%	CL21B103KB6Z46□	
		22nF	±10%	CL21B223KB6Z46□	
		1.0nF	±10%	CL21B102KC6Z46□	
	100Vdc	3.3nF	±10%	CL21B332KC6Z46□	
		4.7nF	±10%	CL21B472KC6Z46□	
		10nF	±10%	CL21B103KC6Z46□	
		15nF	±10%	CL21B153KC6Z46□	
		22nF	±10%	CL21B223KC6Z46□	
		1.0nF	±10%	CL21B102KCCZ46□	
		47nF	±10%	CL21B473KCCZ46□	
0.95mm	25Vdc	100nF	±10%	CL21B104KACZ46□	
		47nF	±10%	CL21B473KBCZ46□	
		68nF	±10%	CL21B683KBCZ46□	
	50Vdc	100nF	±10%	CL21B104KBCZ46□	
		47nF	±10%	CL21B473KCCZ46□	
		68nF	±10%	CL21B683KCCZ46□	
	100Vdc	100nF	±10%	CL21B104KCCZ46□	
		47nF	±10%	CL21B473KCCZ46□	
		68nF	±10%	CL21B683KCCZ46□	
1.35mm	16Vdc	470nF	±10%	CL21B474KOFZ46□	
		1.0uF	±10%	CL21B105KOFZ46□	
		2.2uF	±10%	CL21B225KOFZ46□	
	25Vdc	220nF	±10%	CL21B224KAFZ46□	
		1.0uF	±10%	CL21B105KAFZ46□	
		2.2uF	±10%	CL21B225KAFZ46□	
	35Vdc	1.0uF	±10%	CL21B105KLFZ46□	
		100nF	±10%	CL21B104KBFZ46□	
		180nF	±10%	CL21B184KBFZ46□	
1.40mm	50Vdc	220nF	±10%	CL21B224KBFZ46□	
		330nF	±10%	CL21B334KBFZ46□	
		470nF	±10%	CL21B474KBFZ46□	
	100Vdc	1.0uF	±10%	CL21B105KBFZ46□	
		100nF	±10%	CL21B104KCFZ46□	
		4.7uF	±10%	CL21B475KPFZ46□	Ref
	10Vdc	4.7uF	±10%	CL21B475KPQZ46□	Ref
		4.7uF	±10%	CL21B475KOQZ46□	Ref

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.25mm	25Vdc	1.0uF	±10%	CL31B105KAPZ46□	
		50Vdc	100nF	±10%	CL31B104KBPZ46□
		100Vdc	100nF	±10%	CL31B104KCPZ46□
		220nF	±10%	CL31B224KCPZ46□	
	16Vdc	2.2uF	±10%	CL31B225KOHZ46□	
		10uF	±10%	CL31B106KOHZ46□	
		25Vdc	1.5uF	±10%	CL31B155KAHZ46□
		2.2uF	±10%	CL31B225KAHZ46□	
1.80mm	50Vdc	3.3uF	±10%	CL31B335KAHZ46□	
		4.7uF	±10%	CL31B475KAHZ46□	
		10uF	±10%	CL31B106KAHZ46□	
		470nF	±10%	CL31B474KBHZ46□	
	50Vdc	680nF	±10%	CL31B684KBHZ46□	
		1.0uF	±10%	CL31B105KBHZ46□	
		1.5uF	±10%	CL31B155KBHZ46□	
		2.2uF	±10%	CL31B225KBHZ46□	
2.70mm	16Vdc	22uF	±10%	CL32B226KOJZ46□	
		22uF	±20%	CL32B226MOJZ46□	
		50Vdc	4.7uF	±10%	CL32B475KBJZ46□

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.70mm	16Vdc	22uF	±10%	CL32B226KOJZ46□	
		22uF	±20%	CL32B226MOJZ46□	
		50Vdc	4.7uF	±10%	CL32B475KBJZ46□

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
 In order to move to the page directly, please click the here. ↑

Reinforced Soft – Termination(5mm) Industrial Capacitors

Z4J – X7R

Feature




- Excellent bending strength($\geq 5\text{mm}$) & $85^{\circ}\text{C} 85\%\text{RH} 1000\text{hr}$ with rated voltage
- Soft – Termination is applicable to all class II MLCC series
- Durability against thermal shock / cycles

Application

- Network, Power application and etc.
- Ideal for decoupling and filtering applications (Class II : X7R)
(Directly connected to battery)

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)					
		L	W	T	Thickness Code	BW	
10	0603	1.60 ± 0.10	0.80 ± 0.10	0.80 ± 0.10	8	0.30 ± 0.20	
21	0805	2.00 ± 0.10	1.25 ± 0.10	1.25 ± 0.10	F	$0.50 \pm 0.20/-0.30$	

Industrial Capacitance Table (X7R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance									
		nF							uF		
		1.5	4.7	10	22	47	100	220	470	1.0	2.2
0603 (1608)	25										
	50										
0805 (2012)	25										
	50										

Product Line Up (X7R)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.90mm	25Vdc	220nF	$\pm 10\%$	CL10B224KA8Z4J□
		1.0uF	$\pm 10\%$	CL10B105KA8Z4J□
	50Vdc	1.5nF	$\pm 10\%$	CL10B152KB8Z4J□
		4.7nF	$\pm 10\%$	CL10B472KB8Z4J□
		22nF	$\pm 10\%$	CL10B223KB8Z4J□
		47nF	$\pm 10\%$	CL10B473KB8Z4J□
		100nF	$\pm 10\%$	CL10B104KB8Z4J□
		220nF	$\pm 10\%$	CL10B224KB8Z4J□
		470nF	$\pm 10\%$	CL10B474KB8Z4J□

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
1.35mm	25Vdc	2.2uF	$\pm 10\%$	CL21B225KAFZ4J□
	50Vdc	1.0uF	$\pm 10\%$	CL21B105KBFZ4J□

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑


High Q Industrial Capacitors

GNW / GQW - COG

Feature




- High Q and low ESR in high frequency range
- Tight tolerance available
- Expanding High - Q (Cu inner-electrode) line - up of 0402, 0603, 0805 case size (0201, 01005 products are already under mass production)
- High efficiency and low power consumption in RF circuit
- Speical outgoing inspection for industrial application (HALT, etc)
- Comparison of Q value in high frequency (Normal vs High - Q)



Application

- Power amplifier module for base - station and GHz range communications
- Smart Factory & Smart Home (IoT)

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
03	0201	0.60±0.03	0.30±0.03	0.30±0.03	3	0.15±0.05
05	0402	1.00±0.05	0.50±0.05	0.50±0.05	5	0.25±0.10
10	0603	1.60±0.15	0.80±0.15	0.65±0.15	A	0.30±0.20
21	0805	2.00±0.10	1.25±0.10	0.85±0.10	C	0.50+0.20/-0.30

High Q Industrial Capacitors

GNW / GQW – C0G

Industrial Capacitance Table (C0G)

Size inch. (mm)	T max. (mm)	Rated Voltage (Vdc)	Capacitance(pF)														
			0.1	0.5	1.0	1.5	2.2	3.3	4.7	6.8	10	15	22	33	47	6.8	100
01005 (0402)	0.22	16											27				
		25											27				
0201 (0603)	0.33	25												33			
		50												15			
0402(1005)	0.55	50												6.8			
0603 (1608)	0.90	50															100
		100															220
0805(2012)	1.00	250															

Product Line Up (COG)

■ Size: 0.60 X 0.30mm (inch : 0201)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.33mm	25Vdc	4.7pF	±0.25pF	CL03C4R7CA3GNW□
		10pF	±0.5pF	CL03C100DA3GNW□

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	50Vdc	0.1pF	±0.05pF	CL05COR1AB5GNW□
		0.1pF	±0.1pF	CL05COR1BB5GNW□
		0.2pF	±0.05pF	CL05COR2AB5GNW□
		0.2pF	±0.1pF	CL05COR2BB5GNW□
		0.3pF	±0.05pF	CL05COR3AB5GNW□
		0.3pF	±0.1pF	CL05COR3BB5GNW□
		0.4pF	±0.05pF	CL05COR4AB5GNW□
		0.4pF	±0.1pF	CL05COR4BB5GNW□
		0.5pF	±0.05pF	CL05COR5AB5GNW□
		0.5pF	±0.1pF	CL05COR5BB5GNW□
		0.6pF	±0.05pF	CL05COR6AB5GNW□
		0.6pF	±0.1pF	CL05COR6BB5GNW□
		0.7pF	±0.05pF	CL05COR7AB5GNW□
		0.7pF	±0.1pF	CL05COR7BB5GNW□
		0.8pF	±0.05pF	CL05COR8AB5GNW□
		0.8pF	±0.1pF	CL05COR8BB5GNW□
		0.9pF	±0.05pF	CL05COR9AB5GNW□
		0.9pF	±0.1pF	CL05COR9BB5GNW□
		1.0pF	±0.05pF	CL05C010AB5GNW□
		1.0pF	±0.1pF	CL05C010BB5GNW□
		1.0pF	±0.25pF	CL05C010CB5GNW□
		1.1pF	±0.05pF	CL05C1R1AB5GNW□
		1.1pF	±0.1pF	CL05C1R1BB5GNW□
		1.1pF	±0.25pF	CL05C1R1CB5GNW□
		1.2pF	±0.05pF	CL05C1R2AB5GNW□
		1.2pF	±0.1pF	CL05C1R2BB5GNW□
		1.2pF	±0.25pF	CL05C1R2CB5GNW□
		1.3pF	±0.05pF	CL05C1R3AB5GNW□
		1.3pF	±0.1pF	CL05C1R3BB5GNW□
		1.3pF	±0.25pF	CL05C1R3CB5GNW□
		1.5pF	±0.05pF	CL05C1R5AB5GNW□
		1.5pF	±0.1pF	CL05C1R5BB5GNW□
		1.5pF	±0.25pF	CL05C1R5CB5GNW□
		1.6pF	±0.05pF	CL05C1R6AB5GNW□
		1.6pF	±0.1pF	CL05C1R6BB5GNW□
		1.6pF	±0.25pF	CL05C1R6CB5GNW□
		1.8pF	±0.05pF	CL05C1R8AB5GNW□
		1.8pF	±0.1pF	CL05C1R8BB5GNW□
		1.8pF	±0.25pF	CL05C1R8CB5GNW□
		2.0pF	±0.05pF	CL05C020AB5GNW□
		2.0pF	±0.1pF	CL05C020BB5GNW□
		2.0pF	±0.25pF	CL05C020CB5GNW□
		2.2pF	±0.05pF	CL05C2R2AB5GNW□
		2.2pF	±0.1pF	CL05C2R2BB5GNW□
		2.2pF	±0.25pF	CL05C2R2CB5GNW□
		2.4pF	±0.05pF	CL05C2R4AB5GNW□
		2.4pF	±0.1pF	CL05C2R4BB5GNW□

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	50Vdc	2.4pF	±0.25pF	CL05C2R4CB5GNW□
		2.7pF	±0.05pF	CL05C2R7AB5GNW□
		2.7pF	±0.1pF	CL05C2R7BB5GNW□
		2.7pF	±0.25pF	CL05C2R7CB5GNW□
		3.0pF	±0.05pF	CL05C030AB5GNW□
		3.0pF	±0.1pF	CL05C030BB5GNW□
		3.0pF	±0.25pF	CL05C030CB5GNW□
		3.3pF	±0.05pF	CL05C3R3AB5GNW□
		3.3pF	±0.1pF	CL05C3R3BB5GNW□
		3.3pF	±0.25pF	CL05C3R3CB5GNW□
		3.6pF	±0.05pF	CL05C3R6AB5GNW□
		3.6pF	±0.1pF	CL05C3R6BB5GNW□
		3.6pF	±0.25pF	CL05C3R6CB5GNW□
		3.9pF	±0.05pF	CL05C3R9AB5GNW□
		3.9pF	±0.1pF	CL05C3R9BB5GNW□
		3.9pF	±0.25pF	CL05C3R9CB5GNW□
		4.0pF	±0.05pF	CL05C040AB5GNW□
		4.0pF	±0.1pF	CL05C040BB5GNW□
		4.0pF	±0.25pF	CL05C040CB5GNW□
		4.3pF	±0.05pF	CL05C4R3AB5GNW□
		4.3pF	±0.1pF	CL05C4R3BB5GNW□
		4.3pF	±0.25pF	CL05C4R3CB5GNW□
		4.7pF	±0.05pF	CL05C4R7AB5GNW□
		4.7pF	±0.1pF	CL05C4R7BB5GNW□
		4.7pF	±0.25pF	CL05C4R7CB5GNW□
		5.0pF	±0.05pF	CL05C050AB5GNW□
		5.0pF	±0.1pF	CL05C050BB5GNW□
		5.0pF	±0.25pF	CL05C050CB5GNW□
		5.1pF	±0.05pF	CL05C5R1AB5GNW□
		5.1pF	±0.1pF	CL05C5R1BB5GNW□
		5.1pF	±0.25pF	CL05C5R1CB5GNW□
		5.1pF	±0.5pF	CL05C5R1DB5GNW□
		5.6pF	±0.05pF	CL05C5R6AB5GNW□
		5.6pF	±0.1pF	CL05C5R6BB5GNW□
		5.6pF	±0.25pF	CL05C5R6CB5GNW□
		6.0pF	±0.05pF	CL05C060AB5GNW□
		6.0pF	±0.1pF	CL05C060BB5GNW□
		6.0pF	±0.25pF	CL05C060CB5GNW□
		6.2pF	±0.05pF	CL05C6R2AB5GNW□
		6.2pF	±0.1pF	CL05C6R2BB5GNW□
		6.2pF	±0.25pF	CL05C6R2CB5GNW□
		6.2pF	±0.5pF	CL05C6R2DB5GNW□
		6.8pF	±0.05pF	CL05C6R8AB5GNW□
		6.8pF	±0.1pF	CL05C6R8BB5GNW□
		6.8pF	±0.25pF	CL05C6R8CB5GNW□
		6.8pF	±0.5pF	CL05C6R8DB5GNW□
		7.0pF	±0.05pF	CL05C070AB5GNW□
		7.0pF	±0.1pF	CL05C070BB5GNW□
		7.0pF	±0.25pF	CL05C070CB5GNW□
		7.0pF	±0.5pF	CL05C070DB5GNW□
		7.5pF	±0.05pF	CL05C7R5AB5GNW□
		7.5pF	±0.1pF	CL05C7R5BB5GNW□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

High Q Industrial Capacitors

GNW / GQW - COG

Product Line Up (COG)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	50Vdc	7.5pF	±0.25pF	CL05C7R5CB5GNW□
		7.5pF	±0.5pF	CL05C7R5DB5GNW□
		8.0pF	±0.05pF	CL05C080AB5GNW□
		8.0pF	±0.1pF	CL05C080BB5GNW□
		8.0pF	±0.25pF	CL05C080CB5GNW□
		8.0pF	±0.5pF	CL05C080DB5GNW□
		8.2pF	±0.05pF	CL05C8R2AB5GNW□
		8.2pF	±0.1pF	CL05C8R2BB5GNW□
		8.2pF	±0.25pF	CL05C8R2CB5GNW□
		8.2pF	±0.5pF	CL05C8R2DB5GNW□
		9.0pF	±0.05pF	CL05C090AB5GNW□
		9.0pF	±0.1pF	CL05C090BB5GNW□
		9.0pF	±0.25pF	CL05C090CB5GNW□
		9.0pF	±0.5pF	CL05C090DB5GNW□
		9.1pF	±0.05pF	CL05C9R1AB5GNW□
		9.1pF	±0.1pF	CL05C9R1BB5GNW□
		9.1pF	±0.25pF	CL05C9R1CB5GNW□
		9.1pF	±0.5pF	CL05C9R1DB5GNW□
		10pF	±1%	CL05C100FB5GNW□
		10pF	±2%	CL05C100GB5GNW□
		10pF	±5%	CL05C100JB5GNW□
		11pF	±1%	CL05C110FB5GNW□
		11pF	±2%	CL05C110GB5GNW□
		11pF	±5%	CL05C110JB5GNW□
		12pF	±1%	CL05C120FB5GNW□
		12pF	±2%	CL05C120GB5GNW□
		12pF	±5%	CL05C120JB5GNW□
		15pF	±1%	CL05C150FB5GNW□
		15pF	±2%	CL05C150GB5GNW□
		15pF	±5%	CL05C150JB5GNW□
		18pF	±1%	CL05C180FB5GNW□
		18pF	±2%	CL05C180GB5GNW□
		18pF	±5%	CL05C180JB5GNW□
		20pF	±1%	CL05C200FB5GNW□
		20pF	±2%	CL05C200GB5GNW□
		20pF	±5%	CL05C200JB5GNW□
		22pF	±1%	CL05C220FB5GNW□
		22pF	±2%	CL05C220GB5GNW□
		22pF	±5%	CL05C220JB5GNW□
		24pF	±1%	CL05C240FB5GNW□
		24pF	±2%	CL05C240GB5GNW□
		24pF	±5%	CL05C240JB5GNW□
		27pF	±1%	CL05C270FB5GNW□
		27pF	±2%	CL05C270GB5GNW□
		27pF	±5%	CL05C270JB5GNW□
		33pF	±1%	CL05C330FB5GNW□
		33pF	±2%	CL05C330GB5GNW□
		33pF	±5%	CL05C330JB5GNW□
		39pF	±1%	CL05C390FB5GNW□
		39pF	±2%	CL05C390GB5GNW□
		39pF	±5%	CL05C390JB5GNW□
		47pF	±1%	CL05C470FB5GNW□
		47pF	±2%	CL05C470GB5GNW□
		47pF	±5%	CL05C470JB5GNW□

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.80mm	100Vdc	0.5pF	±0.1pF	CL10C0R5BCAGQW□
	250Vdc	0.1pF	±0.05pF	CL10C0R1AEAGQW□
		0.1pF	±0.1pF	CL10C0R1BEAGQW□
		0.2pF	±0.05pF	CL10C0R2AEAGQW□
		0.2pF	±0.1pF	CL10C0R2BEAGQW□
		0.3pF	±0.05pF	CL10C0R3AEAGQW□
		0.3pF	±0.1pF	CL10C0R3BEAGQW□
		0.3pF	±0.25pF	CL10C0R3CEAGQW□
		0.4pF	±0.05pF	CL10C0R4AEAGQW□
		0.4pF	±0.1pF	CL10C0R4BEAGQW□
		0.4pF	±0.25pF	CL10C0R4CEAGQW□
		0.5pF	±0.05pF	CL10C0R5AEAGQW□
		0.5pF	±0.1pF	CL10C0R5BEAGQW□
		0.5pF	±0.25pF	CL10C0R5CEAGQW□
		0.6pF	±0.05pF	CL10C0R6AEAGQW□
		0.6pF	±0.1pF	CL10C0R6BEAGQW□
		0.6pF	±0.25pF	CL10C0R6CEAGQW□
		0.7pF	±0.05pF	CL10C0R7AEAGQW□
		0.7pF	±0.1pF	CL10C0R7BEAGQW□
		0.7pF	±0.25pF	CL10C0R7CEAGQW□
		0.8pF	±0.05pF	CL10C0R8AEAGQW□
		0.8pF	±0.1pF	CL10C0R8BEAGQW□
		0.8pF	±0.25pF	CL10C0R8CEAGQW□
		0.9pF	±0.05pF	CL10C0R9AEAGQW□
		0.9pF	±0.1pF	CL10C0R9BEAGQW□
		0.9pF	±0.25pF	CL10C0R9CEAGQW□
		1.0pF	±0.05pF	CL10C010AEAGQW□
		1.0pF	±0.1pF	CL10C010BEAGQW□
		1.0pF	±0.25pF	CL10C010CEAGQW□
		1.1pF	±0.05pF	CL10C1R1AEAGQW□
		1.1pF	±0.1pF	CL10C1R1BEAGQW□
		1.1pF	±0.25pF	CL10C1R1CEAGQW□
		1.2pF	±0.05pF	CL10C1R2AEAGQW□
		1.2pF	±0.1pF	CL10C1R2BEAGQW□
		1.2pF	±0.25pF	CL10C1R2CEAGQW□
		1.3pF	±0.05pF	CL10C1R3AEAGQW□
		1.3pF	±0.1pF	CL10C1R3BEAGQW□
		1.3pF	±0.25pF	CL10C1R3CEAGQW□
		1.5pF	±0.05pF	CL10C1R5AEAGQW□
		1.5pF	±0.1pF	CL10C1R5BEAGQW□
		1.5pF	±0.25pF	CL10C1R5CEAGQW□
		1.6pF	±0.05pF	CL10C1R6AEAGQW□
		1.6pF	±0.1pF	CL10C1R6BEAGQW□
		1.6pF	±0.25pF	CL10C1R6CEAGQW□
		1.8pF	±0.05pF	CL10C1R8AEAGQW□
		1.8pF	±0.1pF	CL10C1R8BEAGQW□
		1.8pF	±0.25pF	CL10C1R8CEAGQW□
		2.0pF	±0.05pF	CL10C020AEAGQW□
		2.0pF	±0.1pF	CL10C020BEAGQW□
		2.0pF	±0.25pF	CL10C020CEAGQW□
		2.2pF	±0.05pF	CL10C2R2AEAGQW□
		2.2pF	±0.1pF	CL10C2R2BEAGQW□
		2.2pF	±0.25pF	CL10C2R2CEAGQW□
		2.4pF	±0.05pF	CL10C2R4AEAGQW□

* □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (COG)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.80mm	250Vdc	2.4pF	±0.1pF	CL10C2R4BEAGQW□	0.80mm	250Vdc	7.5pF	±0.1pF	CL10C7R5BEAGQW□
		2.4pF	±0.25pF	CL10C2R4CEAGQW□			7.5pF	±0.25pF	CL10C7R5CEAGQW□
		2.7pF	±0.05pF	CL10C2R7AEAGQW□			7.5pF	±0.5pF	CL10C7R5DEAGQW□
		2.7pF	±0.1pF	CL10C2R7BEAGQW□			8.0pF	±0.05pF	CL10C080AEAGQW□
		2.7pF	±0.25pF	CL10C2R7CEAGQW□			8.0pF	±0.1pF	CL10C080BEAGQW□
		3.0pF	±0.05pF	CL10C030AEAGQW□			8.0pF	±0.25pF	CL10C080CEAGQW□
		3.0pF	±0.1pF	CL10C030BEAGQW□			8.0pF	±0.5pF	CL10C080DEAGQW□
		3.0pF	±0.25pF	CL10C030CEAGQW□			8.2pF	±0.05pF	CL10C8R2AEAGQW□
		3.3pF	±0.05pF	CL10C3R3AEAGQW□			8.2pF	±0.1pF	CL10C8R2BEAGQW□
		3.3pF	±0.1pF	CL10C3R3BEAGQW□			8.2pF	±0.25pF	CL10C8R2CEAGQW□
		3.3pF	±0.25pF	CL10C3R3CEAGQW□			8.2pF	±0.5pF	CL10C8R2DEAGQW□
		3.6pF	±0.05pF	CL10C3R6AEAGQW□			9.0pF	±0.05pF	CL10C090AEAGQW□
		3.6pF	±0.1pF	CL10C3R6BEAGQW□			9.0pF	±0.1pF	CL10C090BEAGQW□
		3.6pF	±0.25pF	CL10C3R6CEAGQW□			9.0pF	±0.25pF	CL10C090CEAGQW□
		3.9pF	±0.05pF	CL10C3R9AEAGQW□			9.0pF	±0.5pF	CL10C090DEAGQW□
		3.9pF	±0.1pF	CL10C3R9BEAGQW□			9.1pF	±0.05pF	CL10C9R1AEAGQW□
		3.9pF	±0.25pF	CL10C3R9CEAGQW□			9.1pF	±0.1pF	CL10C9R1BEAGQW□
		4.0pF	±0.05pF	CL10C040AEAGQW□			9.1pF	±0.25pF	CL10C9R1CEAGQW□
		4.0pF	±0.1pF	CL10C040BEAGQW□			9.1pF	±0.5pF	CL10C9R1DEAGQW□
		4.0pF	±0.25pF	CL10C040CEAGQW□			10pF	±1%	CL10C100FEAGQW□
		4.3pF	±0.05pF	CL10C4R3AEAGQW□			10pF	±2%	CL10C100GEAGQW□
		4.3pF	±0.1pF	CL10C4R3BEAGQW□			10pF	±5%	CL10C100JEAGQW□
		4.3pF	±0.25pF	CL10C4R3CEAGQW□			11pF	±1%	CL10C110FEAGQW□
		4.7pF	±0.05pF	CL10C4R7AEAGQW□			11pF	±2%	CL10C110GEAGQW□
		4.7pF	±0.1pF	CL10C4R7BEAGQW□			11pF	±5%	CL10C110JEAGQW□
		4.7pF	±0.25pF	CL10C4R7CEAGQW□			12pF	±1%	CL10C120FEAGQW□
		5.0pF	±0.05pF	CL10C500AEAGQW□			12pF	±2%	CL10C120GEAGQW□
		5.0pF	±0.1pF	CL10C500BEAGQW□			12pF	±5%	CL10C120JEAGQW□
		5.0pF	±0.25pF	CL10C500CEAGQW□			15pF	±1%	CL10C150FEAGQW□
		5.1pF	±0.05pF	CL10C5R1AEAGQW□			15pF	±2%	CL10C150GEAGQW□
		5.1pF	±0.1pF	CL10C5R1BEAGQW□			15pF	±5%	CL10C150JEAGQW□
		5.1pF	±0.25pF	CL10C5R1CEAGQW□			18pF	±1%	CL10C180FEAGQW□
		5.1pF	±0.5pF	CL10C5R1DEAGQW□			18pF	±2%	CL10C180GEAGQW□
		5.6pF	±0.05pF	CL10C5R6AEAGQW□			18pF	±5%	CL10C180JEAGQW□
		5.6pF	±0.1pF	CL10C5R6BEAGQW□			20pF	±1%	CL10C200FEAGQW□
		5.6pF	±0.25pF	CL10C5R6CEAGQW□			20pF	±2%	CL10C200GEAGQW□
		5.6pF	±0.5pF	CL10C5R6DEAGQW□			20pF	±5%	CL10C200JEAGQW□
		6.0pF	±0.05pF	CL10C600AEAGQW□			22pF	±1%	CL10C220FEAGQW□
		6.0pF	±0.1pF	CL10C600BEAGQW□			22pF	±2%	CL10C220GEAGQW□
		6.0pF	±0.25pF	CL10C600CEAGQW□			22pF	±5%	CL10C220JEAGQW□
		6.0pF	±0.5pF	CL10C600DEAGQW□			24pF	±2%	CL10C240FEAGQW□
		6.2pF	±0.05pF	CL10C6R2AEAGQW□			24pF	±5%	CL10C240JEAGQW□
		6.2pF	±0.1pF	CL10C6R2BEAGQW□			27pF	±1%	CL10C270FEAGQW□
		6.2pF	±0.25pF	CL10C6R2CEAGQW□			27pF	±2%	CL10C270GEAGQW□
		6.2pF	±0.5pF	CL10C6R2DEAGQW□			27pF	±5%	CL10C270JEAGQW□
		6.8pF	±0.05pF	CL10C6R8AEAGQW□			33pF	±1%	CL10C330FEAGQW□
		6.8pF	±0.1pF	CL10C6R8BEAGQW□			33pF	±2%	CL10C330GEAGQW□
		6.8pF	±0.25pF	CL10C6R8CEAGQW□			33pF	±5%	CL10C330JEAGQW□
		6.8pF	±0.5pF	CL10C6R8DEAGQW□			39pF	±1%	CL10C390FEAGQW□
		7.0pF	±0.05pF	CL10C700AEAGQW□			39pF	±2%	CL10C390GEAGQW□
		7.0pF	±0.1pF	CL10C700BEAGQW□			39pF	±5%	CL10C390JEAGQW□
		7.0pF	±0.25pF	CL10C700CEAGQW□			47pF	±1%	CL10C470FEAGQW□
		7.0pF	±0.5pF	CL10C700DEAGQW□			47pF	±2%	CL10C470GEAGQW□
		7.5pF	±0.05pF	CL10C7R5AEAGQW□			47pF	±5%	CL10C470JEAGQW□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

High Q Industrial Capacitors

GNW / GQW - COG

Product Line Up (COG)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.95mm	250Vdc	0.5pF	±0.05pF	CL21C0R5AECGNW□	0.95mm	250Vdc	3.6pF	±0.05pF	CL21C3R6AECGNW□
		0.5pF	±0.1pF	CL21C0R5BECGNW□			3.6pF	±0.1pF	CL21C3R6BECGNW□
		0.5pF	±0.25pF	CL21C0R5CECGNW□			3.6pF	±0.25pF	CL21C3R6CECGNW□
		0.6pF	±0.05pF	CL21C0R6AECGNW□			3.9pF	±0.05pF	CL21C3R9AECGNW□
		0.6pF	±0.1pF	CL21C0R6BECGNW□			3.9pF	±0.1pF	CL21C3R9BECGNW□
		0.6pF	±0.25pF	CL21C0R6CECGNW□			3.9pF	±0.25pF	CL21C3R9CECGNW□
		0.7pF	±0.05pF	CL21C0R7AECGNW□			4.0pF	±0.05pF	CL21C040AECGNW□
		0.7pF	±0.1pF	CL21C0R7BECGNW□			4.0pF	±0.1pF	CL21C040BECGNW□
		0.7pF	±0.25pF	CL21C0R7CECGNW□			4.0pF	±0.25pF	CL21C040CECGNW□
		0.8pF	±0.05pF	CL21C0R8AECGNW□			4.3pF	±0.05pF	CL21C4R3AECGNW□
		0.8pF	±0.1pF	CL21C0R8BECGNW□			4.3pF	±0.1pF	CL21C4R3BECGNW□
		0.8pF	±0.25pF	CL21C0R8CECGNW□			4.3pF	±0.25pF	CL21C4R3CECGNW□
		0.9pF	±0.05pF	CL21C0R9AECGNW□			4.7pF	±0.05pF	CL21C4R7AECGNW□
		0.9pF	±0.1pF	CL21C0R9BECGNW□			4.7pF	±0.1pF	CL21C4R7BECGNW□
		0.9pF	±0.25pF	CL21C0R9CECGNW□			4.7pF	±0.25pF	CL21C4R7CECGNW□
		1.0pF	±0.05pF	CL21C010AECGNW□			5.0pF	±0.05pF	CL21C050AECGNW□
		1.0pF	±0.1pF	CL21C010BECGNW□			5.0pF	±0.1pF	CL21C050BECGNW□
		1.0pF	±0.25pF	CL21C010CECGNW□			5.0pF	±0.25pF	CL21C050CECGNW□
		1.1pF	±0.05pF	CL21C1R1AECGNW□			5.1pF	±0.05pF	CL21C5R1AECGNW□
		1.1pF	±0.1pF	CL21C1R1BECGNW□			5.1pF	±0.1pF	CL21C5R1BECGNW□
		1.1pF	±0.25pF	CL21C1R1CECGNW□			5.1pF	±0.25pF	CL21C5R1CECGNW□
		1.2pF	±0.05pF	CL21C1R2AECGNW□			5.1pF	±0.5pF	CL21C5R1DECWNW□
		1.2pF	±0.1pF	CL21C1R2BECGNW□			5.6pF	±0.05pF	CL21C5R6AECGNW□
		1.2pF	±0.25pF	CL21C1R2CECGNW□			5.6pF	±0.1pF	CL21C5R6BECGNW□
		1.3pF	±0.05pF	CL21C1R3AECGNW□			5.6pF	±0.25pF	CL21C5R6CECGNW□
		1.3pF	±0.1pF	CL21C1R3BECGNW□			5.6pF	±0.5pF	CL21C5R6DECWNW□
		1.3pF	±0.25pF	CL21C1R3CECGNW□			6.0pF	±0.05pF	CL21C060AECGNW□
		1.5pF	±0.05pF	CL21C1R5AECGNW□			6.0pF	±0.1pF	CL21C060BECGNW□
		1.5pF	±0.1pF	CL21C1R5BECGNW□			6.0pF	±0.25pF	CL21C060CECGNW□
		1.5pF	±0.25pF	CL21C1R5CECGNW□			6.0pF	±0.5pF	CL21C060DECWNW□
		1.6pF	±0.05pF	CL21C1R6AECGNW□			6.2pF	±0.05pF	CL21C6R2AECGNW□
		1.6pF	±0.1pF	CL21C1R6BECGNW□			6.2pF	±0.1pF	CL21C6R2BECGNW□
		1.6pF	±0.25pF	CL21C1R6CECGNW□			6.2pF	±0.25pF	CL21C6R2CECGNW□
		1.8pF	±0.05pF	CL21C1R8AECGNW□			6.2pF	±0.5pF	CL21C6R2DECWNW□
		1.8pF	±0.1pF	CL21C1R8BECGNW□			6.8pF	±0.05pF	CL21C6R8AECGNW□
		1.8pF	±0.25pF	CL21C1R8CECGNW□			6.8pF	±0.1pF	CL21C6R8BECGNW□
		2.0pF	±0.05pF	CL21C020AECGNW□			6.8pF	±0.25pF	CL21C6R8CECGNW□
		2.0pF	±0.1pF	CL21C020BECGNW□			6.8pF	±0.5pF	CL21C6R8DECWNW□
		2.0pF	±0.25pF	CL21C020CECGNW□			7.0pF	±0.05pF	CL21C070AECGNW□
		2.2pF	±0.05pF	CL21C2R2AECGNW□			7.0pF	±0.1pF	CL21C070BECGNW□
		2.2pF	±0.1pF	CL21C2R2BECGNW□			7.0pF	±0.25pF	CL21C070CECGNW□
		2.2pF	±0.25pF	CL21C2R2CECGNW□			7.0pF	±0.5pF	CL21C070DECWNW□
		2.4pF	±0.05pF	CL21C2R4AECGNW□			7.5pF	±0.05pF	CL21C7R5AECGNW□
		2.4pF	±0.1pF	CL21C2R4BECGNW□			7.5pF	±0.1pF	CL21C7R5BECGNW□
		2.4pF	±0.25pF	CL21C2R4CECGNW□			7.5pF	±0.25pF	CL21C7R5CECGNW□
		2.7pF	±0.05pF	CL21C2R7AECGNW□			7.5pF	±0.5pF	CL21C7R5DECWNW□
		2.7pF	±0.1pF	CL21C2R7BECGNW□			8.0pF	±0.05pF	CL21C080AECGNW□
		2.7pF	±0.25pF	CL21C2R7CECGNW□			8.0pF	±0.1pF	CL21C080BECGNW□
		3.0pF	±0.05pF	CL21C030AECGNW□			8.0pF	±0.25pF	CL21C080CECGNW□
		3.0pF	±0.1pF	CL21C030BECGNW□			8.0pF	±0.5pF	CL21C080DECWNW□
		3.0pF	±0.25pF	CL21C030CECGNW□			8.2pF	±0.05pF	CL21C8R2AECGNW□
		3.3pF	±0.05pF	CL21C3R3AECGNW□			8.2pF	±0.1pF	CL21C8R2BECGNW□
		3.3pF	±0.1pF	CL21C3R3BECGNW□			8.2pF	±0.25pF	CL21C8R2CECGNW□
		3.3pF	±0.25pF	CL21C3R3CECGNW□			8.2pF	±0.5pF	CL21C8R2DECWNW□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (COG)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.95mm	250Vdc	9.0pF	±0.05pF	CL21C090AECGNW□	0.95mm	250Vdc	100pF	±2%	CL21C101GECGNW□
		9.0pF	±0.1pF	CL21C090BECGNW□			100pF	±5%	CL21C101JECGNW□
		9.0pF	±0.25pF	CL21C090CECGNW□					
		9.0pF	±0.5pF	CL21C090DECWNW□					
		9.1pF	±0.05pF	CL21C9R1AECGNW□					
		9.1pF	±0.1pF	CL21C9R1BECGNW□					
		9.1pF	±0.25pF	CL21C9R1CECGNW□					
		9.1pF	±0.5pF	CL21C9R1DECWNW□					
		10pF	±1%	CL21C100FECGNW□					
		10pF	±2%	CL21C100GECGNW□					
		10pF	±5%	CL21C100JECGNW□					
		11pF	±1%	CL21C110FECGNW□					
		11pF	±2%	CL21C110GECGNW□					
		11pF	±5%	CL21C110JECGNW□					
		12pF	±1%	CL21C120FECGNW□					
		12pF	±2%	CL21C120GECGNW□					
		12pF	±5%	CL21C120JECGNW□					
		15pF	±1%	CL21C150FECGNW□					
		15pF	±2%	CL21C150GECGNW□					
		15pF	±5%	CL21C150JECGNW□					
		18pF	±1%	CL21C180FECGNW□					
		18pF	±2%	CL21C180GECGNW□					
		18pF	±5%	CL21C180JECGNW□					
		20pF	±1%	CL21C200FECGNW□					
		20pF	±2%	CL21C200GECGNW□					
		20pF	±5%	CL21C200JECGNW□					
		22pF	±1%	CL21C220FECGNW□					
		22pF	±2%	CL21C220GECGNW□					
		22pF	±5%	CL21C220JECGNW□					
		24pF	±1%	CL21C240FECGNW□					
		24pF	±2%	CL21C240GECGNW□					
		24pF	±5%	CL21C240JECGNW□					
		27pF	±1%	CL21C270FECGNW□					
		27pF	±2%	CL21C270GECGNW□					
		27pF	±5%	CL21C270JECGNW□					
		33pF	±1%	CL21C330FECGNW□					
		33pF	±2%	CL21C330GECGNW□					
		33pF	±5%	CL21C330JECGNW□					
		39pF	±1%	CL21C390FECGNW□					
		39pF	±2%	CL21C390GECGNW□					
		39pF	±5%	CL21C390JECGNW□					
		47pF	±1%	CL21C470FECGNW□					
		47pF	±2%	CL21C470GECGNW□					
		47pF	±5%	CL21C470JECGNW□					
		62pF	±1%	CL21C620FECGNW□					
		62pF	±2%	CL21C620GECGNW□					
		62pF	±5%	CL21C620JECGNW□					
		68pF	±1%	CL21C680FECGNW□					
		68pF	±2%	CL21C680GECGNW□					
		68pF	±5%	CL21C680JECGNW□					
		82pF	±1%	CL21C820FECGNW□					
		82pF	±2%	CL21C820GECGNW□					
		82pF	±5%	CL21C820JECGNW□					
		100pF	±1%	CL21C101FECGNW□					

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

High Effective Capacitance Industrial Capacitors


N3W - X5R / X7R

Feature



- Excellent DC – bias characteristics with fine powder
- Enhance high temperature reliability
- Special outgoing inspection for industrial application (HALT, etc)
- Advantage of fine powder technology

1210 X7R 4.7uF 50V




By using finer powder : Reduced capacitance degradation by bias and aging

Application

- 24 / 48V input line filter for power supply
- Network, Power application and etc.
- Ideal for decoupling and filtering applications (Class II : X7R)

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
05	0402	1.00±0.05	0.50±0.05	0.50±0.05	5	0.25±0.10
21	0805	2.00±0.10	1.25±0.10	1.25±0.10	F	0.50+0.20/-0.30
31	1206	3.20±0.20	1.60±0.20	1.60±0.20	H	0.50±0.30
32	1210	3.20±0.30	2.50±0.20	2.50±0.20	J	0.60±0.30
		3.20±0.40	2.50±0.30	2.50±0.30	V	

Industrial Capacitance Table (X5R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance									
		nF						uF			
		10	22	47	100	220	470	1.0	2.2	4.7	6.8
0805(2012)	6.3										

Industrial Capacitance Table (X7R)

Size inch (mm)	Rated Voltage (Vdc)	Capacitance									
		nF						uF			
		10	22	47	100	220	470	1.0	2.2	4.7	6.8
0402(1005)	16										
1206 (3216)	50										
	100										
1210 (3225)	50										
	100										

Product Line Up (X5R)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.35mm	6.3Vdc	10uF	±10%	CL21A106KQFN3W□	

Product Line Up (X7R)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
0.55mm	16Vdc	100nF	±10%	CL05B104K05N3W□	

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
1.80mm	50Vdc	4.7uF	±10%	CL31B475KBHN3W□	

■ Size : 3.20 X 2.50mm (inch : 1210)



Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Remark
2.70mm	50Vdc	10uF	±10%	CL32B106KBJN3W□	
		4.7uF	±10%	CL32B475KBJN3W□	

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148


In order to move to the page directly, please click the here. ↑

Reliability Test Condition

No.	Item	Performance	Test condition																																		
1	Appearance	No abnormal exterior appearance	Visual Inspection through Microscope (X10)																																		
2	Insulation resistance	10,000MΩ min. or 500MΩ ·μF min.(or*100MΩ ·μF) product whichever is smaller. (Rated voltage ≤16V:10,000MΩ min. or 100MΩ ·μFmin. product whichever is smaller)	Apply the rated voltage for 60~120sec. Rated voltage > 500V : Insulation resistance shall be measured with 500±50Vdc																																		
3	Withstanding voltage	No dielectric breakdown or mechanical breakdown	Apply the specified voltage*for 1~5 sec. Charge / Discharge current limit : 50mA max *CLASS I (Rated Voltage < 100V) : 300% of the rated Voltage CLASS II (Rated Voltage < 100V) : 250% of the rated Voltage In the case of rated Voltage ≥ 100V products, following condition should be applied. 100V ≤ Rated Voltage < 500V : 200% of the rated Voltage 500V ≤ Rated Voltage < 1000V : 150% of the rated Voltage Rated Voltage ≥ 1000V : 120% of the rated Voltage																																		
4	Capacitance	<table border="1"> <tr> <td>Class I</td> <td>Within the specified tolerance</td> </tr> <tr> <td>Class II</td> <td>Within the specified tolerance</td> </tr> </table>	Class I	Within the specified tolerance	Class II	Within the specified tolerance	<p>■ Class I</p> <table border="1"> <thead> <tr> <th>Capacitance</th> <th>Frequency</th> <th>Voltage</th> </tr> </thead> <tbody> <tr> <td>≤1,000pF</td> <td>1kHz ± 10%</td> <td rowspan="2">0.5 ~ 5Vrms</td> </tr> <tr> <td>>1,000pF</td> <td>1kHz ± 10%</td> </tr> </tbody> </table> <p>■ Class II</p> <table border="1"> <thead> <tr> <th>Capacitance</th> <th>Frequency</th> <th>Voltage</th> </tr> </thead> <tbody> <tr> <td>≤10μF</td> <td>1kHz ± 10%</td> <td>1.0 ± 0.2Vrms</td> </tr> <tr> <td>>10μF</td> <td>120Hz ± 20%</td> <td>0.5 ± 0.1Vrms</td> </tr> <tr> <td>Exception*</td> <td>1kHz ± 10%</td> <td>0.5 ± 0.1Vrms</td> </tr> </tbody> </table> <p>Capacitance shall be measured after the heat treatment of 150+0/-10°C for 1hr and leaving for 24±2hr at room temperature. (Class II)</p>	Capacitance	Frequency	Voltage	≤1,000pF	1kHz ± 10%	0.5 ~ 5Vrms	>1,000pF	1kHz ± 10%	Capacitance	Frequency	Voltage	≤10μF	1kHz ± 10%	1.0 ± 0.2Vrms	>10μF	120Hz ± 20%	0.5 ± 0.1Vrms	Exception*	1kHz ± 10%	0.5 ± 0.1Vrms										
Class I	Within the specified tolerance																																				
Class II	Within the specified tolerance																																				
Capacitance	Frequency	Voltage																																			
≤1,000pF	1kHz ± 10%	0.5 ~ 5Vrms																																			
>1,000pF	1kHz ± 10%																																				
Capacitance	Frequency	Voltage																																			
≤10μF	1kHz ± 10%	1.0 ± 0.2Vrms																																			
>10μF	120Hz ± 20%	0.5 ± 0.1Vrms																																			
Exception*	1kHz ± 10%	0.5 ± 0.1Vrms																																			
5	Tanδ	<table border="1"> <tr> <td colspan="2">1.Characteristic : A(X5R)</td> </tr> <tr> <td>Rated Voltage</td> <td>Spec</td> </tr> <tr> <td>50V / 35V</td> <td>0.025 max / 0.05 max*</td> </tr> <tr> <td>25V</td> <td>0.025 max / 0.05 max*/ 0.10 max*</td> </tr> <tr> <td>16V</td> <td>0.035 max / 0.05 max*/ 0.10 max*</td> </tr> <tr> <td>≤10V</td> <td>0.05 max / 0.10 max*</td> </tr> </table> <table border="1"> <tr> <td colspan="2">2.Characteristic : B(X7R), X(X6S), Y(X7S)</td> </tr> <tr> <td>Rated Voltage</td> <td>Spec</td> </tr> <tr> <td>50V≥ / 35V / 25V</td> <td>0.025 max / 0.05 max* / 0.10 max*</td> </tr> <tr> <td>16V</td> <td>0.035 max / 0.10 max*</td> </tr> <tr> <td>≤10V</td> <td>0.05 max/0.10 max*</td> </tr> </table> <table border="1"> <tr> <td colspan="2">3.Characteristic : F(Y5V)</td> </tr> <tr> <td>Rated Voltage</td> <td>Spec</td> </tr> <tr> <td>50V / 35V / 25V</td> <td>0.05 max / 0.07 max* / 0.09 max*</td> </tr> <tr> <td>16V</td> <td>0.07 max / 0.09 max* / 0.125 max*</td> </tr> <tr> <td>10V</td> <td>0.125 max/0.16 max*</td> </tr> <tr> <td>≤ 6.3V</td> <td>0.16 max</td> </tr> </table>	1.Characteristic : A(X5R)		Rated Voltage	Spec	50V / 35V	0.025 max / 0.05 max*	25V	0.025 max / 0.05 max*/ 0.10 max*	16V	0.035 max / 0.05 max*/ 0.10 max*	≤10V	0.05 max / 0.10 max*	2.Characteristic : B(X7R), X(X6S), Y(X7S)		Rated Voltage	Spec	50V≥ / 35V / 25V	0.025 max / 0.05 max* / 0.10 max*	16V	0.035 max / 0.10 max*	≤10V	0.05 max/0.10 max*	3.Characteristic : F(Y5V)		Rated Voltage	Spec	50V / 35V / 25V	0.05 max / 0.07 max* / 0.09 max*	16V	0.07 max / 0.09 max* / 0.125 max*	10V	0.125 max/0.16 max*	≤ 6.3V	0.16 max	<p>* The conditions of measurement may be altered upon request. You can check the specification at the web site or contact sales people for each product with mark*</p>
1.Characteristic : A(X5R)																																					
Rated Voltage	Spec																																				
50V / 35V	0.025 max / 0.05 max*																																				
25V	0.025 max / 0.05 max*/ 0.10 max*																																				
16V	0.035 max / 0.05 max*/ 0.10 max*																																				
≤10V	0.05 max / 0.10 max*																																				
2.Characteristic : B(X7R), X(X6S), Y(X7S)																																					
Rated Voltage	Spec																																				
50V≥ / 35V / 25V	0.025 max / 0.05 max* / 0.10 max*																																				
16V	0.035 max / 0.10 max*																																				
≤10V	0.05 max/0.10 max*																																				
3.Characteristic : F(Y5V)																																					
Rated Voltage	Spec																																				
50V / 35V / 25V	0.05 max / 0.07 max* / 0.09 max*																																				
16V	0.07 max / 0.09 max* / 0.125 max*																																				
10V	0.125 max/0.16 max*																																				
≤ 6.3V	0.16 max																																				
6	Temperature characteristics of capacitance	<table border="1"> <tr> <td>Class I</td> <td>Characteristic</td> <td>Temp. coefficient (PPM/°C)</td> </tr> <tr> <td></td> <td>C(COG)</td> <td>0±30</td> </tr> </table> <table border="1"> <tr> <td>Class II</td> <td>Characteristic</td> <td>Capacitance change(%) with No bias</td> </tr> <tr> <td></td> <td>A(X5R) / B(X7R)</td> <td>±15%</td> </tr> <tr> <td></td> <td>X(X6S) / Y(X7S)</td> <td>±22%</td> </tr> <tr> <td></td> <td>Z(X7T)</td> <td>+22% ~ -33%</td> </tr> <tr> <td></td> <td>F(Y5V)</td> <td>+22% ~ -82%</td> </tr> </table>	Class I	Characteristic	Temp. coefficient (PPM/°C)		C(COG)	0±30	Class II	Characteristic	Capacitance change(%) with No bias		A(X5R) / B(X7R)	±15%		X(X6S) / Y(X7S)	±22%		Z(X7T)	+22% ~ -33%		F(Y5V)	+22% ~ -82%	<p>Capacitance shall be measured by the steps shown in the following table.</p> <table border="1"> <thead> <tr> <th>Step</th> <th>Temperature(°C)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>25±2</td> </tr> <tr> <td>2</td> <td>Min. operating temp.±2</td> </tr> <tr> <td>3</td> <td>25±2</td> </tr> <tr> <td>4</td> <td>Max. operating temp.±2</td> </tr> <tr> <td>5</td> <td>25±2</td> </tr> </tbody> </table> <p>■ Class I</p> <p>Temperature Coefficient shall be calculated from the formula as below</p> $\text{Temp. Coefficient} = \frac{C_2 - C_1}{C_1 \times \Delta T} \times 10^6 [\text{ppm}/\text{°C}]$ <p>C1 : Capacitance at step 3 C2 : Capacitance at 125°C ΔT : 125°C - 25°C = 100°C</p> <p>■ Class II</p> <p>Capacitance change shall be calculated from the formula as below</p> $\Delta C = \frac{C_2 - C_1}{C_1} \times 100(\%)$ <p>C1 : Capacitance at step 3 C2 : Capacitance at step 2 or step 4</p>	Step	Temperature(°C)	1	25±2	2	Min. operating temp.±2	3	25±2	4	Max. operating temp.±2	5	25±2	
Class I	Characteristic	Temp. coefficient (PPM/°C)																																			
	C(COG)	0±30																																			
Class II	Characteristic	Capacitance change(%) with No bias																																			
	A(X5R) / B(X7R)	±15%																																			
	X(X6S) / Y(X7S)	±22%																																			
	Z(X7T)	+22% ~ -33%																																			
	F(Y5V)	+22% ~ -82%																																			
Step	Temperature(°C)																																				
1	25±2																																				
2	Min. operating temp.±2																																				
3	25±2																																				
4	Max. operating temp.±2																																				
5	25±2																																				

No.	Item	Performance		Test condition										
7	Adhesive strength of termination	No indication of peeling shall occur on the terminal electrode.		Apply 500g.f pressure for 10±1 sec. ※ 200g.f for size 0201 / 100g.f for size 01005 										
8	Bending strength	Appearance	No mechanical damage shall occur.											
		Capacitance	Characteristic	Capacitance change										
			Class I	Within±5% or ±0.5pF whichever is larger										
			Class II	A(X5R), B(X7R), X(X6S), Y(X7S) Z(X7T) F(Y5V)										
				Within±12.5%										
				Within±30%										
9	Solderability	More than 75% of the terminal surface is to be soldered newly, so metal part does not come out or dissolve ※ Industrial Capacitor : Z46 / Z4J Code, More than 95%		<table border="1"> <thead> <tr> <th>Solder</th><th>Sn_Ag3_0.5Cu</th></tr> </thead> <tbody> <tr> <td>Solder temp.</td><td>245±5°C</td></tr> <tr> <td>Flux</td><td>RMA Type</td></tr> <tr> <td>Dip time</td><td>3±0.3sec.</td></tr> <tr> <td>Pre - heating</td><td>at 80~120°C for 10 ~ 30sec.</td></tr> </tbody> </table> 	Solder	Sn_Ag3_0.5Cu	Solder temp.	245±5°C	Flux	RMA Type	Dip time	3±0.3sec.	Pre - heating	at 80~120°C for 10 ~ 30sec.
Solder	Sn_Ag3_0.5Cu													
Solder temp.	245±5°C													
Flux	RMA Type													
Dip time	3±0.3sec.													
Pre - heating	at 80~120°C for 10 ~ 30sec.													
10	Resistance to soldering heat	Appearance	No mechanical damage shall occur.											
		Capacitance	Characteristic	Capacitance change										
			Class I	±2.5% or ±0.25pF whichever is larger										
			Class II	A(X5R), B(X7R), X(X6S), Y(X7S) Z(X7T) F(Y5V)										
				Within±7.5%										
				Within±20%										
		Q (Class I)	Within the specified initial value											
		Tanδ (Class II)	Within the specified initial value											
		Insulation resistance	Within the specified initial value											
		Withstanding voltage	No breakdown of dielectric											
11	Vibration test	Appearance	No mechanical damage shall occur.											
		Capacitance	Characteristic	Capacitance change										
			Class I	±2.5% or ±0.25pF whichever is larger										
			Class II	A(X5R), B(X7R) X(X6S), Y(X7S) Z(X7T) F(Y5V)										
				Within±5%										
				Within±5%										
				Within±10%										
		Q (Class I)	Within the specified initial value											
		Tanδ (Class II)	Within the specified initial value											
		Insulation resistance	Within the specified initial value											

- Bending Limit : 1mm • Test Speed : 1.0mm / sec.
- Keep the test board at the limit point in 5sec. then Measure Capacitance.
- ※ Industrial Capacitor
 - SW6 / ZW6 / Z46 Code, Bending Limit : 3mm
 - Z4J Code, Bending Limit : 5mm



Solder	Sn_Ag3_0.5Cu
Solder temp.	245±5°C
Flux	RMA Type
Dip time	3±0.3sec.
Pre - heating	at 80~120°C for 10 ~ 30sec.

Solder temperature: 270±5°C DIP TIME : 10±1 sec.
Each termination shall be fully immersed and preheated as below :

Step	Temp.(°C)	Time(sec.)
1	80~100	60
2	150~180	60

Perform the initial measurement according to Note1.
Please refer to p.131

Final measurement
Leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.

The capacitor shall be subjected to a harmonic motion having a total amplitude of 1.5mm changing frequency from 10Hz to 55Hz and back to 10Hz in about 1 min.

Repeat this for 2hours each in 3mutually perpendicular directions

※ Industrial Capacitor : Z46 / Z4J Code
With frequency from 10 ~ 2000Hz during 20min.
3 directions X 12 times (total 36 times, 12hr)

Perform the initial measurement according to Note1.
Please refer to p.131

Final measurement
Leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.

Reliability Test Condition

No.	Item	Performance		Test condition
12	Moisture resistance	Appearance		No mechanical damage shall occur.
		Capacitance	Characteristic	Capacitance change
			Class I	$\pm 7.5\%$ or $\pm 0.75\text{pF}$ whichever is larger
		Class II	A(X5R), B(X7R), X(X6S), Y(X7S)	Within $\pm 12.5\%$
			Z(X7T)	
		Q (Class I)	F(Y5V)	$\pm 30\%$
			Capacitance $\geq 30\text{pF}$: $Q \geq 200$ $< 30\text{pF}$: $Q \geq 100 + 10/3 \times C$ (C : Capacitance)	
		Tan δ (Class II)	1. Capacitance : A(X5R) 0.05 max / 0.075 max* (35V / 50V) 0.05 max / 0.075 max* / 0.125 max* (16V / 25V) 0.075 max / 0.125 max* ($\leq 10\text{V}$) 2. Capacitance : B(X7R), X(X6S) 0.05 max / 0.125 max* (16V / 25V / 35V / 50V \geq) 0.075 max / 0.125 max* ($\leq 10\text{V}$) 3. Capacitance : F(Y5V) 0.09 max (50V) 0.09 max / 0.125 max* (25V / 35V) 0.09 max / 0.125 max* / 0.16 max* (16V) 0.16 max / 0.195 max* (10V) 0.195 max (4V / 6.3V) 4. Industrial Capacitor : Z46/Z4J Code 0.035 max* ($\geq 25\text{V}$) 0.050 max* (16V) 0.075 max* (10V)	
		Insulation resistance	500M Ω min. or $25\text{M}\Omega \cdot \mu\text{F}$ min. product whichever is smaller / $12.5\text{M}\Omega \cdot \mu\text{F}$ or over*	
13	High temperature resistance	Appearance		No mechanical damage shall occur.
		Capacitance	Characteristic	Capacitance change
			Class I	$\pm 3\%$ or $\pm 0.30\text{pF}$ whichever is larger
		Class II	A(X5R), B(X7R), X(X6S), Y(X7S)	Within $\pm 12.5\%$
			Z(X7T)	
		Q (Class I)	F(Y5V)	30%
			Capacitance $\geq 30\text{pF}$: $Q \geq 350$ $10\text{pF} \leq \text{Capacitance} < 30\text{pF}$: $Q \geq 275 + 2.5C$ Capacitance $< 10\text{pF}$: $Q \geq 200 + 10 \times C$ (C : Capacitance)	
		Tan δ (Class II)	1. Capacitance : A(X5R) 0.05 max / 0.075 max* (35V / 50V) 0.05 max / 0.075 max* / 0.125 max* (16V / 25V) 0.075 max / 0.125 max* ($\leq 10\text{V}$) 2. Capacitance : B(X7R), X(X6S) 0.05 max / 0.125 max* (16V / 25V / 35V / 50V \geq) 0.075 max / 0.125 max* ($\leq 10\text{V}$) 3. Capacitance : F(Y5V) 0.09 max (50V) 0.09 max / 0.125 max* (25V / 35V) 0.09 max / 0.125 max* / 0.16 max* (16V) 0.16 max / 0.195 max* (10V) 0.195 max (4V / 6.3V) 4. Industrial Capacitor : Z46/Z4J Code 0.035 max* ($\geq 25\text{V}$) 0.050 max* (16V) 0.075 max* (10V)	
		Insulation resistance	1,000M Ω min. or $50\text{M}\Omega \cdot \mu\text{F}$ min. product whichever is smaller / $25\text{M}\Omega \cdot \mu\text{F}$ or over*	

No.	Item	Performance		Test condition				
14	Temperature cycle	Appearance	No mechanical damage shall occur.		Capacitor shall be subjected to 5 cycles. ※ Industrial Capacitor : Z46 / Z4J Code, 1000 cycles.			
		Capacitance	Characteristic	Capacitance change				
			Class I	±2.5% or ±0.25pF whichever is larger				
			A(X5R)	Within ±7.5% / ±10% / ±15%*				
		Class II	B(X7R)	Within ±7.5%				
			X(X6S), Y(X7S) Z(X7T)	Within ±15%				
			F(Y5V)	Within ±20%				
		Q (Class I)	Within the specified initial value		Perform the initial measurement according to Note1. Please refer to p.131			
		Tanδ (Class II)	Within the specified initial value		Final measurement Leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.			
		Insulation resistance	Within the specified initial value					
15	Mechanical Shock (Only for Z46/Z4J Code)	Appearance	No abnormal exterior appearance.		Three shocks in each direction should be applied along 3 mutually perpendicular axes of the test specimen (18 shocks)			
		Capacitance	Characteristic	Capacitance change				
			Class II	Within ±10%				
		Tanδ (Class II)	1. Capacitance : B(X7R) 0.025 max* (25V) 0.035 max* (16V) 0.050 max* (6.3V/10V)					
		IR	1,000MΩ min. or 50MΩ · μF min. product whichever is smaller / 12.5MΩ · μF or over*					

Recommended Soldering Method					
Size inch(mm)	Temperature Characteristic	Capacitance	Condition		
			Flow	Reflow	
01005(0402)	-	-	-	○	○
0201(0603)					
0402(1005)					
0603(1608)	Class I	-	○	○	○
	Class II	C < 1uF	○	○	○
		C ≥ 1uF	-	-	○
0805(2012)	Class I	-	○	○	○
	Class II	C < 4.7uF	○	○	○
		C ≥ 4.7uF	-	-	○
1206(3216)	Array	-	-	-	○
	Class I	-	○	○	○
	Class II	C < 10uF	○	○	○
		C ≥ 10uF	-	-	○
1210(3225)	-	-	-	○	○
1808(4520)					
1812(4532)					
2220(5750)					

Note 1. Initial Measurement For Class II

Perform the heat treatment at 150°C +0/-10°C for 1 hour and leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.

Note 2. Lateral Measurement

1. CLASS I

Leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.

2. CLASS II

Perform the heat treatment at 150°C +0/-10°C for 1 hour and leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.

Note 3. All Size in Reliability Test Condition Section is "inch"

Premium Capacitors for Automotive Applications

CL	10	B	104	K	B	8	W	P	N	C
1	2	3	4	5	6	7	8	9	10	11

1 SERIES CODE

CL = Multilayer Ceramic Capacitors

2 SIZE CODE

Code	inch(mm)	Code	inch(mm)	Code	inch(mm)
05	0402(1005)	21	0805(2012)	32	1210(3225)
10	0603(1608)	31	1206(3216)		

3 DIELECTRIC CODE

Class I

Symbol	EIA Code	Operation Temperature Range(°C)	Temperature Coefficient(ppm/°C)
C	COG	-55 ~ +125	0±30

Class II

Symbol	EIA Code	Operation Temperature Range(°C)	Capacitance Change(%)
B	X7R	-55 ~ +125	±15
Y	X7S	-55 ~ +125	±22

4 CAPACITANCE CODE

Capacitance expressed in pF. 2 significant digits plus number of zeros.

example) 106=10×10⁶=10,000,000pF

For Values <10pF, Letter R denotes decimal point

example) 1R5 =1.5pF

5 TOLERANCE CODE

Capacitance Tolerance

Code	Capacitance Tolerance	TC	Capacitance series	Remark
C	±0.25pF	COG	E-12 series*	under 5pF
D	±0.5pF	COG	E-12 series*	5pF < Cp < 10pF
J	±5%	COG	E-12 series	≥ 10pF
K	±10%	X7R/X7S	E-6 series	
M	±20%	X7R/X7S	E-6 series	

* E-24 series is also available

※ This code has only typical specifications. Please refer to individual specifications.

Series	Capacitance Step											
	1.0				2.2				4.7		6.8	
E-3	1.0	1.2	1.5	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2
E-6	1.0	1.1	1.2	1.3	2.2	2.4	2.7	3.0	4.7	5.1	5.6	6.2
E-12	1.0	1.2	1.5	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2
E-24	1.0	1.6	1.8	2.0	3.3	3.6	3.9	4.3	6.8	7.5	8.2	9.1
	1.5											

6 RATED VOLTAGE CODE

Q = 6.3V P = 10V O = 16V A = 25V B = 50V C = 100V

7 THICKNESS CODE

(Unit:mm)			
Size mm(inch)	Code	Thickness*	Tolerance
1005(0402)	5	0.50	±0.05
1608(0603)	8	0.80	±0.10
	6	0.60	±0.10
2012(0805)	C	0.85	±0.10
	F	1.25	±0.10
	Q	1.25	±0.15
	C	0.85	±0.15
	P	1.15	±0.10
3216(1206)	H	1.60	±0.20
	I	2.00	±0.20
	J	2.50	±0.20

* In case of Higher Bending Strength , ESD protection capacitors, Please refer to individual specifications.

※ This code has only typical specifications. Please refer to individual specifications.

8 DESIGN CODE

Code	Inner electrode	Termination	Plating material	Design
1	Ni	Cu	Ni_Sn 100%	Standard
V	Ni	Cu/Metal Epoxy	Ni_Sn 100%	Standard
W	Ni	Cu/Metal Epoxy	Ni_Sn 100%	Open Mode
X	Ni	Cu/Metal Epoxy	Ni_Sn 100%	Float Mode

※ This code has only typical specifications. Please refer to individual specifications.

9 PRODUCT CODE OR SIZE CONTROL CODE

P = Automotive product meet AEC -Q200.

10 CONTROL CODE

N = Standard J = Higher Bending Strength E = ESD Protection

11 PACKAGING CODE

Code	Type	Code	Type
C	Cardbord Tape, 7" reel	E	Embossed Tape, 7" reel
D/L	Cardbord Tape, 13" reel (Quantity option)	F	Embossed Tape, 13" reel

※ If you want to learn to the code or quantity in detail, please see page 148.

In order to move to the page directly, please click the here. ↑

General Automotive Capacitors

Feature




- Automotive products are manufactured in state of the art facilities recommend for registration to ISO / TS 16949 : 2002.
- Automotive products meet AEC - Q200 requirements.
- Automotive products are RoHS compliant.
- Automotive products meet JEDEC - 020 - D requirements.
- X7R dielectric components have BME and metal - epoxy terminations with a Ni / Sn plated overcoat.
- COG dielectric components contain BME and copper terminations with a Ni / Sn plated overcoat.
- Size 0603 / 0805 / 1206 is suitable for flow and reflow soldering.
Size 0402 and smaller (≤ 0402) and 1210 and bigger (≥ 1210) is suitable for reflow soldering.

Application

- Automotive Electronic Equipment
(Powertrain, Safety, Body & Chassis, Convenience, Infotainment)

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
05	0402	1.00±0.05	0.50±0.05	0.50±0.05	5	0.25±0.10
10	0603	1.60±0.10	0.80±0.10	0.80±0.10	8	0.30±0.20
21	0805	2.00±0.10	1.25±0.10	0.60±0.10	6	0.50+0.20/-0.30
				0.85±0.10	C	
		2.00±0.15	1.25±0.15	1.25±0.10	F	
				1.25±0.15	Q	
31	1206	3.20±0.15	1.60±0.15	0.85±0.15	C	0.50±0.30
				1.15±0.10	P	
32	1210	3.20±0.20	1.60±0.20	1.60±0.20	H	0.60±0.30
				2.00±0.20	I	
				2.50±0.20	J	

Automotive Capacitance Table (COG)

Size inch (mm)	Thickness (mm)	Rated Voltage (Vdc)	Capacitance									
			pF						nF			
			10	22	47	100	220	470	1.0	2.2	4.7	10
0402 (1005)	0.50	50										
		100										
0603 (1608)	0.80	50										
		100					270					
0805 (2012)	0.60 0.85 1.25	50										
		100										

Automotive Capacitance Table (X7R)

Size inch (mm)	Thickness (mm)	Rated Voltage (Vdc)	Capacitance									
			nF						uF			
			10	22	47	100	220	470	1.0	2.2	4.7	10
0402 (1005)	0.50	10										
		16										
		25										
		50										
0603 (1608)	0.80	10										
		16										
		25										
		50										
		100										
0805 (2012)	1.25	10										
	0.85	16										
	1.25											
	0.60											
	0.85	25										
	1.25											
	0.60											
	0.85	50										
	1.25											
	0.60											
	0.85	100										
	1.25											
1206 (3216)	1.60	10										
	1.15	16										
	1.60											
	0.85											
	1.15	25										
	1.60											
	0.85											
	1.15	50										
	1.60											
	0.85	100										
1210 (3225)	2.50	10										
	2.50	16										
	2.50	25										
	2.50	50										

General Automotive Capacitors

Product Line Up (Automotive Capacitors - COG)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	50Vdc	4.7pF	±0.25pF	CL05C4R7CB51PN□
		6.8pF	±0.5pF	CL05C6R8DB51PN□
		10pF	±5%	CL05C100JB51PN□
		12pF	±5%	CL05C120JB51PN□
		15pF	±5%	CL05C150JB51PN□
		18pF	±5%	CL05C180JB51PN□
		22pF	±5%	CL05C220JB51PN□
		33pF	±5%	CL05C330JB51PN□
		39pF	±5%	CL05C390JB51PN□
		47pF	±5%	CL05C470JB51PN□
		56pF	±5%	CL05C560JB51PN□
		68pF	±5%	CL05C680JB51PN□
		82pF	±5%	CL05C820JB51PN□
		100pF	±5%	CL05C101JB51PN□
		120pF	±5%	CL05C121JB51PN□
		150pF	±5%	CL05C151JB51PN□
		180pF	±5%	CL05C181JB51PN□
		220pF	±5%	CL05C221JB51PN□
100Vdc	100Vdc	4.7pF	±0.25pF	CL05C4R7CC51PN□
		6.8pF	±0.5pF	CL05C6R8DC51PN□
		10pF	±5%	CL05C100JC51PN□
		12pF	±5%	CL05C120JC51PN□
		15pF	±5%	CL05C150JC51PN□
		18pF	±5%	CL05C180JC51PN□
		22pF	±5%	CL05C220JC51PN□
		27pF	±5%	CL05C270JC51PN□
		33pF	±5%	CL05C330JC51PN□
		39pF	±5%	CL05C390JC51PN□
		47pF	±5%	CL05C470JC51PN□
		56pF	±5%	CL05C560JC51PN□
		68pF	±5%	CL05C680JC51PN□
		82pF	±5%	CL05C820JC51PN□
		100pF	±5%	CL05C101JC51PN□
		120pF	±5%	CL05C121JC51PN□
		150pF	±5%	CL05C151JC51PN□
		180pF	±5%	CL05C181JC51PN□
		220pF	±5%	CL05C221JC51PN□

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.90mm	50Vdc	4.7pF	±0.25pF	CL10C4R7CB81PN□
		6.8pF	±0.5pF	CL10C6R8DB81PN□
		10pF	±5%	CL10C100JB81PN□
		12pF	±5%	CL10C120JB81PN□
		15pF	±5%	CL10C150JB81PN□
		18pF	±5%	CL10C180JB81PN□
		22pF	±5%	CL10C220JB81PN□
		27pF	±5%	CL10C270JB81PN□
		33pF	±5%	CL10C330JB81PN□
		39pF	±5%	CL10C390JB81PN□
		47pF	±5%	CL10C470JB81PN□
		56pF	±5%	CL10C560JB81PN□
		68pF	±5%	CL10C680JB81PN□
		82pF	±5%	CL10C820JB81PN□
		100pF	±5%	CL10C101JB81PN□
		120pF	±5%	CL10C121JB81PN□
		150pF	±5%	CL10C151JB81PN□
		180pF	±5%	CL10C181JB81PN□
		220pF	±5%	CL10C221JB81PN□
100Vdc	100Vdc	4.7pF	±0.25pF	CL10C4R7CC81PN□
		6.8pF	±0.5pF	CL10C6R8DC81PN□
		10pF	±5%	CL10C100JC81PN□
		12pF	±5%	CL10C120JC81PN□
		15pF	±5%	CL10C150JC81PN□
		18pF	±5%	CL10C180JC81PN□
		22pF	±5%	CL10C220JC81PN□
		27pF	±5%	CL10C270JC81PN□
		33pF	±5%	CL10C330JC81PN□
		39pF	±5%	CL10C390JC81PN□
		47pF	±5%	CL10C470JC81PN□
		56pF	±5%	CL10C560JC81PN□
		68pF	±5%	CL10C680JC81PN□
		82pF	±5%	CL10C820JC81PN□
		100pF	±5%	CL10C101JC81PN□
		120pF	±5%	CL10C121JC81PN□
		150pF	±5%	CL10C151JC81PN□
		180pF	±5%	CL10C181JC81PN□
		220pF	±5%	CL10C221JC81PN□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Product Line Up (Automotive Capacitors - COG)

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.70mm	50Vdc	10pF	±5%	CL21C100JB61PN□	0.95mm	100Vdc	470pF	±5%	CL21C471JCC1PN□
		12pF	±5%	CL21C120JB61PN□			560pF	±5%	CL21C561JCC1PN□
		15pF	±5%	CL21C150JB61PN□			680pF	±5%	CL21C681JCC1PN□
		18pF	±5%	CL21C180JB61PN□			820pF	±5%	CL21C821JCC1PN□
		22pF	±5%	CL21C220JB61PN□			1.0nF	±5%	CL21C102JCC1PN□
		27pF	±5%	CL21C270JB61PN□	1.35mm	50Vdc	1.0nF	±5%	CL21C102JBF1PN□
		33pF	±5%	CL21C330JB61PN□			1.2nF	±5%	CL21C122JBF1PN□
		39pF	±5%	CL21C390JB61PN□			1.5nF	±5%	CL21C152JBF1PN□
		47pF	±5%	CL21C470JB61PN□			1.8nF	±5%	CL21C182JBF1PN□
		56pF	±5%	CL21C560JB61PN□			2.2nF	±5%	CL21C222JBF1PN□
		68pF	±5%	CL21C680JB61PN□			2.7nF	±5%	CL21C272JBF1PN□
		82pF	±5%	CL21C820JB61PN□			3.3nF	±5%	CL21C332JBF1PN□
		100pF	±5%	CL21C101JB61PN□			3.9nF	±5%	CL21C392JBF1PN□
		120pF	±5%	CL21C121JB61PN□			4.7nF	±5%	CL21C472JBF1PN□
		150pF	±5%	CL21C151JB61PN□			5.6nF	±5%	CL21C562JBF1PN□
		180pF	±5%	CL21C181JB61PN□			6.8nF	±5%	CL21C682JBF1PN□
		220pF	±5%	CL21C221JB61PN□			8.2nF	±5%	CL21C822JBF1PN□
		270pF	±5%	CL21C271JB61PN□			10nF	±5%	CL21C103JBF1PN□
		330pF	±5%	CL21C331JB61PN□			1.0nF	±5%	CL21C102JCF1PN□
		390pF	±5%	CL21C391JB61PN□					
100Vdc	100Vdc	10pF	±5%	CL21C100JC61PN□					
		12pF	±5%	CL21C120JC61PN□					
		15pF	±5%	CL21C150JC61PN□					
		18pF	±5%	CL21C180JC61PN□					
		22pF	±5%	CL21C220JC61PN□					
		27pF	±5%	CL21C270JC61PN□					
		33pF	±5%	CL21C330JC61PN□					
		39pF	±5%	CL21C390JC61PN□					
		47pF	±5%	CL21C470JC61PN□					
		56pF	±5%	CL21C560JC61PN□					
		68pF	±5%	CL21C680JC61PN□					
		82pF	±5%	CL21C820JC61PN□					
		100pF	±5%	CL21C101JC61PN□					
		120pF	±5%	CL21C121JC61PN□					
		150pF	±5%	CL21C151JC61PN□					
		180pF	±5%	CL21C181JC61PN□					
		220pF	±5%	CL21C221JC61PN□					
		270pF	±5%	CL21C271JC61PN□					
		330pF	±5%	CL21C331JC61PN□					
		390pF	±5%	CL21C391JC61PN□					
0.95mm	50Vdc	470pF	±5%	CL21C471JBC1PN□					
		560pF	±5%	CL21C561JBC1PN□					
		680pF	±5%	CL21C681JBC1PN□					
		820pF	±5%	CL21C821JBC1PN□					
		1.0nF	±5%	CL21C102JBC1PN□					
		1.2nF	±5%	CL21C122JBC1PN□					
		1.5nF	±5%	CL21C152JBC1PN□					
		1.8nF	±5%	CL21C182JBC1PN□					
		2.2nF	±5%	CL21C222JBC1PN□					
		2.7nF	±5%	CL21C272JBC1PN□					
		3.3nF	±5%	CL21C332JBC1PN□					
		3.9nF	±5%	CL21C392JBC1PN□					
		4.7nF	±5%	CL21C472JBC1PN□					
		5.6nF	±5%	CL21C562JBC1PN□					

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

General Automotive Capacitors

Product Line Up (Automotive Capacitors – X7R)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	10Vdc	100nF	±10%	CL05B104KP5VPN □
	16Vdc	1.0nF	±10%	CL05B102K05VPN □
		1.5nF	±10%	CL05B152K05VPN □
		2.2nF	±10%	CL05B222K05VPN □
		3.3nF	±10%	CL05B332K05VPN □
		4.7nF	±10%	CL05B472K05VPN □
		6.8nF	±10%	CL05B682K05VPN □
		10nF	±10%	CL05B103K05VPN □
		15nF	±10%	CL05B153K05VPN □
		22nF	±10%	CL05B223K05VPN □
		33nF	±10%	CL05B333K05VPN □
		47nF	±10%	CL05B473K05VPN □
		68nF	±10%	CL05B683K05VPN □
		100nF	±10%	CL05B104K05VPN □
	25Vdc	1.0nF	±10%	CL05B102KA5VPN □
		1.5nF	±10%	CL05B152KA5VPN □
		2.2nF	±10%	CL05B222KA5VPN □
		3.3nF	±10%	CL05B332KA5VPN □
		4.7nF	±10%	CL05B472KA5VPN □
		6.8nF	±10%	CL05B682KA5VPN □
		10nF	±10%	CL05B103KA5VPN □
		15nF	±10%	CL05B153KA5VPN □
		22nF	±10%	CL05B223KA5VPN □
		33nF	±10%	CL05B333KA5VPN □
		47nF	±10%	CL05B473KA5VPN □
	50Vdc	330pF	±10%	CL05B331KB5VPN □
		470pF	±10%	CL05B471KB5VPN □
		560pF	±10%	CL05B561KB5VPN □
		680pF	±10%	CL05B681KB5VPN □
		1.0nF	±10%	CL05B102KB5VPN □
		1.5nF	±10%	CL05B152KB5VPN □
		2.2nF	±10%	CL05B222KB5VPN □
		3.3nF	±10%	CL05B332KB5VPN □
		4.7nF	±10%	CL05B472KB5VPN □
		6.8nF	±10%	CL05B682KB5VPN □
		10nF	±10%	CL05B103KB5VPN □
		15nF	±10%	CL05B153KB5VPN □
		22nF	±10%	CL05B223KB5VPN □
		33nF	±10%	CL05B333KB5VPN □
		47nF	±10%	CL05B473KB5VPN □

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.90mm	10Vdc	1.0uF	±10%	CL10B105KP8VPN □
	16Vdc	47nF	±10%	CL10B473K08VPN □
		68nF	±10%	CL10B683K08VPN □
		100nF	±10%	CL10B104K08VPN □
		150nF	±10%	CL10B154K08VPN □
		220nF	±10%	CL10B224K08VPN □
		330nF	±10%	CL10B334K08VPN □
		470nF	±10%	CL10B474K08VPN □
		680nF	±10%	CL10B684K08VPN □
		1.0uF	±10%	CL10B105K08VPN □
	25Vdc	1.0nF	±10%	CL10B102KA8VPN □
		1.5nF	±10%	CL10B152KA8VPN □
		2.2nF	±10%	CL10B222KA8VPN □
		3.3nF	±10%	CL10B332KA8VPN □
		4.7nF	±10%	CL10B472KA8VPN □
		6.8nF	±10%	CL10B682KA8VPN □
		10nF	±10%	CL10B103KA8VPN □
		15nF	±10%	CL10B153KA8VPN □
		22nF	±10%	CL10B223KA8VPN □
		33nF	±10%	CL10B333KA8VPN □
		47nF	±10%	CL10B473KA8VPN □
		68nF	±10%	CL10B683KA8VPN □
		100nF	±10%	CL10B104KA8VPN □
		150nF	±10%	CL10B154KA8VPN □
		220nF	±10%	CL10B224KA8VPN □
	50Vdc	330nF	±10%	CL10B334KA8VPN □
		470nF	±10%	CL10B474KA8VPN □
		470pF	±10%	CL10B471KB8VPN □
		1.0nF	±10%	CL10B102KB8VPN □
		1.5nF	±10%	CL10B152KB8VPN □
		2.2nF	±10%	CL10B222KB8VPN □
		3.3nF	±10%	CL10B332KB8VPN □
		4.7nF	±10%	CL10B472KB8VPN □
		6.8nF	±10%	CL10B682KB8VPN □
		10nF	±10%	CL10B103KB8VPN □
		15nF	±10%	CL10B153KB8VPN □
		22nF	±10%	CL10B223KB8VPN □
		33nF	±10%	CL10B333KB8VPN □
		47nF	±10%	CL10B473KB8VPN □
		68nF	±10%	CL10B683KB8VPN □
		100nF	±10%	CL10B104KB8VPN □
	100Vdc	100nF	±10%	CL10B104KB8VPN □
		150nF	±10%	CL10B154KB8VPN □
		220nF	±10%	CL10B224KB8VPN □
		330pF	±10%	CL10B331KC8VPN □
		470pF	±10%	CL10B471KC8VPN □

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148
In order to move to the page directly, please click the here. ↑

Product Line Up (Automotive Capacitors - X7R)

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	
0.90mm	100Vdc	2.2nF	±10%	CL10B222KC8WPN□	0.90mm	50Vdc	100nF	±10%	CL21B104KBFVPN□	
		3.3nF	±10%	CL10B332KC8WPN□			150nF	±10%	CL21B154KBFVPN□	
		4.7nF	±10%	CL10B472KC8WPN□			220nF	±10%	CL21B224KBFVPN□	
		6.8nF	±10%	CL10B682KC8WPN□			330nF	±10%	CL21B334KBFVPN□	
		10nF	±10%	CL10B103KC8WPN□			470nF	±10%	CL21B474KBFVPN□	
		15nF	±10%	CL10B153KC8WPN□			680nF	±10%	CL21B684KBFVPN□	
		22nF	±10%	CL10B223KC8WPN□			1.0uF	±10%	CL21B105KBFVPN□	
		33nF	±10%	CL10B333KC8WPN□			100nF	±10%	CL21B104KCPVPN□	
		47nF	±10%	CL10B473KC8WPN□		1.40mm	100Vdc	4.7uF	±10%	CL21B475KPQVPN□
							16Vdc	4.7uF	±10%	CL21B475KOQVPN□

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.70mm	50Vdc	1.0nF	±10%	CL21B102KB6WPN□
		2.2nF	±10%	CL21B222KB6WPN□
		4.7nF	±10%	CL21B472KB6WPN□
		10nF	±10%	CL21B103KB6WPN□
		15nF	±10%	CL21B153KB6WPN□
		22nF	±10%	CL21B223KB6WPN□
	100Vdc	1.0nF	±10%	CL21B102KC6WPN□
		2.2nF	±10%	CL21B222KC6WPN□
		4.7nF	±10%	CL21B472KC6WPN□
		10nF	±10%	CL21B103KC6WPN□
0.95mm	16Vdc	100nF	±10%	CL21B104KOCVPN□
	25Vdc	47nF	±10%	CL21B473KACVPN□
		68nF	±10%	CL21B683KACVPN□
		100nF	±10%	CL21B104KACVPN□
	50Vdc	33nF	±10%	CL21B333KBCVPN□
		47nF	±10%	CL21B473KBCVPN□
		68nF	±10%	CL21B683KBCVPN□
		100nF	±10%	CL21B104KBCVPN□
	100Vdc	33nF	±10%	CL21B333KCCVPN□
		47nF	±10%	CL21B473KCCVPN□
		68nF	±10%	CL21B683KCCVPN□
		100nF	±10%	CL21B104KCCVPN□
1.35mm	10Vdc	1.0uF	±10%	CL21B105KPFVPN□
		2.2uF	±10%	CL21B225KPFVPN□
	16Vdc	150nF	±10%	CL21B154KOFVPN□
		220nF	±10%	CL21B224KOFVPN□
		330nF	±10%	CL21B334KOFVPN□
		470nF	±10%	CL21B474KOFVPN□
		680nF	±10%	CL21B684KOFVPN□
		1.0uF	±10%	CL21B105KOFVPN□
		2.2uF	±10%	CL21B225KOFVPN□
	25Vdc	150nF	±10%	CL21B154KAFVPN□
		220nF	±10%	CL21B224KAFVPN□
		330nF	±10%	CL21B334KAFVPN□
		470nF	±10%	CL21B474KAFVPN□
		680nF	±10%	CL21B684KAFVPN□
		1.0uF	±10%	CL21B105KAFVPN□
		2.2uF	±10%	CL21B225KAFVPN□

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number	
1.00mm	25Vdc	220nF	±10%	CL31B224KACVPN□	
		330nF	±10%	CL31B334KACVPN□	
		470nF	±10%	CL31B474KACVPN□	
		100nF	±10%	CL31B104KBCVPN□	
	100Vdc	100nF	±10%	CL31B104KCCVPN□	
		16Vdc	1.0uF	±10%	CL31B105KOPVPN□
		25Vdc	680nF	±10%	CL31B684KAPVPN□
		1.0uF	±10%	CL31B105KAPVPN□	
		50Vdc	100nF	±10%	CL31B104KBPVPN□
		100Vdc	100nF	±10%	CL31B104KCCWPN□
1.25mm	16Vdc	1.0uF	±10%	CL31B105KOPVPN□	
		25Vdc	680nF	±10%	CL31B684KAPVPN□
		1.0uF	±10%	CL31B105KAPVPN□	
		50Vdc	100nF	±10%	CL31B104KBPVPN□
	100Vdc	220nF	±10%	CL31B224KBPVPN□	
		100Vdc	100nF	±10%	CL31B104KCPVPN□
		150nF	±10%	CL31B154KCPVPN□	
		220nF	±10%	CL31B224KCPVPN□	
		100Vdc	100nF	±10%	CL31B104KCPVPN□
		150nF	±10%	CL31B154KCPVPN□	
1.80mm	10Vdc	4.7uF	±10%	CL31B475KPHVPN□	
		10uF	±10%	CL31B106KPHVPN□	
		16Vdc	2.2uF	±10%	CL31B225KOHVPN□
		4.7uF	±10%	CL31B475KOHVPN□	
	25Vdc	10uF	±10%	CL31B106KOHVPN□	
		2.2uF	±10%	CL31B225KAHVPN□	
		4.7uF	±10%	CL31B475KAHVPN□	
		10uF	±10%	CL31B106KAHVPN□	
		330nF	±10%	CL31B334KBHVPN□	
		470nF	±10%	CL31B474KBHVPN□	
2.70mm	50Vdc	680nF	±10%	CL31B684KBHVPN□	
		1.0uF	±10%	CL31B105KBHVPN□	
		2.2uF	±10%	CL31B225KBHVPN□	
		4.7uF	±10%	CL31B475KBHVPN□	
	100Vdc	330nF	±10%	CL32B226KJVPN□	
		470nF	±10%	CL32B226KOJVPN□	
		680nF	±10%	CL32B475KAJVPN□	
		1.0uF	±10%	CL32B105KAJVPN□	
		2.2uF	±10%	CL32B225KAJVPN□	
		4.7uF	±10%	CL32B475KBJVPN□	

■ Size : 3.20 X 2.50mm (inch : 1210)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
2.70mm	10Vdc	22uF	±10%	CL32B226KJVPN□
		22uF	±10%	CL32B226KOJVPN□
		4.7uF	±10%	CL32B475KAJVPN□
		4.7uF	±10%	CL32B475KBJVPN□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148


In order to move to the page directly, please click the here. ↑

Special Automotive Capacitors

Higher Bending Strength

Feature




- AEC - Q200 qualified, 5mm bending strength guarantee.
- Strong thermal - mechanical properties.



Application

- Critical circuits and Battery line circuits.
(Prevent a module / sub - system failure in the event of a cracked / shorted capacitor)

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)				
		L	W	T	Thickness Code	BW
05	0402	1.00±0.10	0.50±0.05	0.50±0.05	5	0.25±0.10
10	0603	1.60±0.20	0.80±0.10	0.80±0.10	8	0.30±0.20
21	0805	2.00±0.30	1.25±0.20	0.85±0.10	C	0.50+0.20/-0.30
				1.25±0.20	F	
31	1206	3.20±0.30	1.60±0.30	1.60±0.30	H	0.50±0.30
32	1210	3.20±0.40	2.50±0.30	2.50±0.30	J	0.60±0.30

Higher Bending Strength Capacitance Table (X7R)

Size inch (mm)	Thickness (mm)	Rated Voltage (Vdc)	Capacitance									
			nF						uF			
			10	22	47	100	220	470	1.0	2.2	4.7	10
0402 (1005)	0.50	16										
		50										
0603(1608)	0.80	25										
0805(2012)	1.25	25										
1206(3216)	1.60	16										

Product Line Up (Higher Bending Strength Capacitors - X7R)

■ Size : 1.00 X 0.50mm (inch : 0402)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.55mm	16Vdc	10nF	±10%	CL05B103K05VPJ□
		22nF	±10%	CL05B223K05VPJ□
		47nF	±10%	CL05B473K05VPJ□
		100nF	±10%	CL05B104K05VPJ□
	25Vdc	10nF	±10%	CL05B103KA5VPJ□
		22nF	±10%	CL05B223KA5VPJ□
	50Vdc	10nF	±10%	CL05B103KB5VPJ□
		22nF	±10%	CL05B223KB5VPJ□

■ Size : 1.60 X 0.80mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
0.90mm	10Vdc	1.0uF	±10%	CL10B105KP8VPJ□
	16Vdc	1.0uF	±10%	CL10B105KO8VPJ□
	25Vdc	1.0uF	±10%	CL10B105KA8VPJ□

■ Size : 2.00 X 1.25mm (inch : 0805)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
1.45mm	10Vdc	1.0uF	±10%	CL21B105KPFVPJ□
	16Vdc	1.0uF	±10%	CL21B105KOFVPJ□
	25Vdc	1.0uF	±10%	CL21B105KAFVPJ□

■ Size : 3.20 X 1.60mm (inch : 1206)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
1.90mm	10Vdc	4.7uF	±10%	CL31B475KPHVPJ□
	16Vdc	4.7uF	±10%	CL31B475KOHVPJ□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148


In order to move to the page directly, please click the here. ↑

Special Automotive Capacitors

ESD Protection

Feature


- Compliance with the IEC 61000 - 4 - 2 standard for ESD immunity.
- Enhanced DC - Bias & Breakdown voltage.



Application

- Input and output sections in a wide range of automotive electronics.

Structure and Dimensions



Size Code	EIA Code	Dimension(mm)					
		L	W	T	BW		
10	0603	1.70±0.10	0.90±0.10	0.90±0.10	0.30±0.20		

ESD Protection Capacitance Table (X7R)

Size inch (mm)	Thickness (mm)	Rated Voltage (Vdc)	Capacitance(nF)									
			1.0	1.5	2.2	3.3	4.7	6.8	10	15	22	33
0603(1608)	0.80	100										

Product Lineup (ESD Protection Capacitors – X7R)

■ Size : 1.70 X 0.90mm (inch : 0603)

Thickness Max.	Rated Voltage	Capacitance	Capacitance Tolerance	Part Number
1.00mm	100Vdc	1.0nF	±10%	CL10B102KC84PE□
		1.5nF	±10%	CL10B152KC84PE□
		2.2nF	±10%	CL10B222KC84PE□
		3.3nF	±10%	CL10B332KC84PE□
		4.7nF	±10%	CL10B472KC84PE□
		6.8nF	±10%	CL10B682KC84PE□
		10nF	±10%	CL10B103KC84PE□

※ □ mark means packaging code. If you want to learn the code or quantity in detail, please see p.148

In order to move to the page directly, please click the here. ↑

Reliability Test Conditions

No.	Item	Performance			Test condition
1	Pre-and Post-Stress Electrical Test	-			
2	High Temperature Exposure	Appearance		No abnormal exterior appearance	
		Capacitance Change	Class I	Within $\pm 2.5\%$ or $\pm 0.25\text{pF}$, (Whichever is larger)	Unpowered, 1000hrs@T = 125°C Initial Measurement Perform the heat treatment at 150°C +0/-10°C for 1 hour and leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement. Final Measurement Leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.
			Class II	Within $\pm 10\%$	
		Q	Class I	Capacitance $\geq 30\text{pF}$: $Q \geq 1,000$ $< 30\text{pF}$: $Q \geq 400 + 20 \times C$ (C : Capacitance)	
			Tanδ	Rated Voltage $\geq 25\text{V}$: 0.030 max $\geq 16\text{V}$: 0.050 max $\geq 10\text{V}$: 0.075 max *1)	
		IR		More than 10,000MΩ or 500MΩ X μF (Whichever is smaller) *1)	
3	Temperature Cycling	Appearance		No abnormal exterior appearance	
		Capacitance Change	Class I	Within $\pm 2.5\%$ or $\pm 0.25\text{pF}$, (Whichever is larger)	1000Cycles Initial Measurement Perform the heat treatment at 150°C +0/-10°C for 1 hour and leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement. Final Measurement Leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.
			Class II	Within $\pm 10\%$	
		Q	Class I	Capacitance $\geq 30\text{pF}$: $Q \geq 1,000$ $< 30\text{pF}$: $Q \geq 400 + 20 \times C$ (C : Capacitance)	
			Tanδ	Rated Voltage $\geq 25\text{V}$: 0.030 max $\geq 16\text{V}$: 0.050 max $\geq 10\text{V}$: 0.075 max *1)	
		IR		More than 10,000MΩ or 500MΩ X μF (Whichever is smaller) *1)	
4	Destructive Physical Analysis	No defects or abnormalities			Per EIA 469
5	Biased Humidity	Appearance		No abnormal exterior appearance	
		Capacitance Change	Class I	Within $\pm 2.5\%$ or $\pm 0.25\text{pF}$, (Whichever is larger)	1000hrs 85°C / 85%RH, Rated voltage and 1.3~1.5V, (add 100kohm resistor) Initial Measurement Perform the heat treatment at 150°C +0/-10°C for 1 hour and leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement. Final Measurement Perform the heat treatment at 150°C +0/-10°C for 1 hour and leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.
			Class II	Within $\pm 12.5\%$	
		Q	Class I	Capacitance $\geq 30\text{pF}$: $Q \geq 200$ $< 30\text{pF}$: $Q \geq 100 + (10/3) \times C$ (C : Capacitance)	
			Tanδ	Rated Voltage $\geq 25\text{V}$: 0.035 max $\geq 16\text{V}$: 0.050 max $\geq 10\text{V}$: 0.075 max *1)	
		IR		More than 500MΩ or 25MΩ X μF (Whichever is smaller) *1)	
6	High Temperature Operating Life	Appearance		No abnormal exterior appearance	
		Capacitance Change	Class I	Within $\pm 3.0\%$ or $\pm 0.3\text{pF}$, (Whichever is larger)	1000hrs @ TA=125°C, 200% Rated Voltage, *2) Initial Measurement Perform the heat treatment at 150°C +0/-10°C for 1 hour and leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement. Final Measurement Perform the heat treatment at 150°C +0/-10°C for 1 hour and leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.
			Class II	Within $\pm 12.5\%$	
		Q	Class I	Capacitance $\geq 30\text{pF}$: $Q \geq 350$ $\geq 10\text{pF}$: $Q \geq 275 + (5/2) \times C$ $< 10\text{pF}$: $Q \geq 200 + 10 \times C$ (C : Capacitance)	
			Tanδ	Rated Voltage $\geq 25\text{V}$: 0.035 max $\geq 16\text{V}$: 0.050 max $\geq 10\text{V}$: 0.075 max *1)	
		IR		More than 1,000MΩ or 50MΩ X μF (Whichever is smaller) *1)	

*1) : Indicates typical specification. Please refer to individual specifications.

*2) : Some of the parts are applicable in rated voltage X 150% or X 120%. Please refer to individual specifications.

Reliability Test Conditions

No.	Item		Performance	Test condition			
7	External Visual		No abnormal exterior appearance	Microscope (x10)			
8	Physical Dimensions		Within the specified dimensions	Using the calipers			
9	Mechanical Shock	Appearance		No abnormal exterior appearance			
		Capacitance Change	Class I	Within $\pm 2.5\%$ or $\pm 0.25\text{pF}$, (Whichever is larger)	Three shocks in each direction should be applied along 3 mutually perpendicular axes of the test specimen (18 shocks)		
			Class II	Within $\pm 10\%$			
		Q	Class I	Capacitance $\geq 30\text{pF} : Q \geq 1,000$ $< 30\text{pF} : Q \geq 400 + 20 \times C$ (C : Capacitance)	Initial Measurement Perform the heat treatment at $150^\circ\text{C} +0/-10^\circ\text{C}$ for 1 hour and leave the capacitor in ambient condition for 24 ± 2 hours before measurement. Then perform the measurement.		
		Tan δ	Class II	Rated Voltage $\geq 25\text{V} : 0.025 \text{ max}$ $\geq 16\text{V} : 0.035 \text{ max}$ $\geq 10\text{V} : 0.050 \text{ max}$	Final Measurement Leave the capacitor in ambient condition for 24 ± 2 hours before measurement. Then perform the measurement.		
		IR		More than $10,000\text{M}\Omega$ or $500\text{M}\Omega \times \mu\text{F}$ (Whichever is smaller)	*1)		
10	Vibration	Appearance		No abnormal exterior appearance			
		Capacitance Change	Class I	Within $\pm 2.5\%$ or $\pm 0.25\text{pF}$, (Whichever is larger)	5g's for 20min., 12cycles each of 3 orientations, Use 8" x 5" PCB 0.031" Thick 7 secure points on one long side and 2 secure points at corners of opposite sides. Parts mounted within 2" from any secure point. Test from 10~2000Hz.		
			Class II	Within $\pm 10\%$			
		Q	Class I	Capacitance $\geq 30\text{pF} : Q \geq 1,000$ $< 30\text{pF} : Q \geq 400 + 20 \times C$ (C : Capacitance)	Initial Measurement Perform the heat treatment at $150^\circ\text{C} +0/-10^\circ\text{C}$ for 1 hour and leave the capacitor in ambient condition for 24 ± 2 hours before measurement. Then perform the measurement.		
		Tan δ	Class II	Rated Voltage $\geq 25\text{V} : 0.025 \text{ max}$ $\geq 16\text{V} : 0.035 \text{ max}$ $\geq 10\text{V} : 0.050 \text{ max}$	Final Measurement Leave the capacitor in ambient condition for 24 ± 2 hours before measurement. Then perform the measurement.		
		IR		More than $10,000\text{M}\Omega$ or $500\text{M}\Omega \times \mu\text{F}$ (Whichever is smaller)	*1)		
11	Resistance to Solder Heat	Appearance		No abnormal exterior appearance			
		Capacitance Change	Class I	Within $\pm 2.5\%$ or $\pm 0.25\text{pF}$, (Whichever is larger)	Solder pot : $260 \pm 5^\circ\text{C}$, $10 \pm 1\text{sec}$. Initial Measurement Perform the heat treatment at $150^\circ\text{C} +0/-10^\circ\text{C}$ for 1 hour and leave the capacitor in ambient condition for 24 ± 2 hours before measurement. Then perform the measurement.		
			Class II	Within $\pm 10\%$			
		Q	Class I	Capacitance $\geq 30\text{pF} : Q \geq 1,000$ $< 30\text{pF} : Q \geq 400 + 20 \times C$ (C : Capacitance)	Final Measurement Leave the capacitor in ambient condition for 24 ± 2 hours before measurement. Then perform the measurement.		
		Tan δ	Class II	Rated Voltage $\geq 25\text{V} : 0.025 \text{ max}$ $\geq 16\text{V} : 0.035 \text{ max}$ $\geq 10\text{V} : 0.050 \text{ max}$			
		IR		More than $10,000\text{M}\Omega$ or $500\text{M}\Omega \times \mu\text{F}$ (Whichever is smaller)	*1)		
12	ESD	Appearance		No abnormal exterior appearance			
		Capacitance Change	Class I	Within $\pm 2.5\%$ or $\pm 0.25\text{pF}$, (Whichever is larger)	Initial Measurement Perform the heat treatment at $150^\circ\text{C} +0/-10^\circ\text{C}$ for 1 hour and leave the capacitor in ambient condition for 24 ± 2 hours before measurement. Then perform the measurement.		
			Class II	Within $\pm 10\%$			
		Q	Class I	Capacitance $\geq 30\text{pF} : Q \geq 1,000$ $< 30\text{pF} : Q \geq 400 + 20 \times C$ (C : Capacitance)	Final Measurement Perform the heat treatment at $150^\circ\text{C} +0/-10^\circ\text{C}$ for 1 hour and leave the capacitor in ambient condition for 24 ± 2 hours before measurement. Then perform the measurement.		
		Tan δ	Class II	Rated Voltage $\geq 25\text{V} : 0.025 \text{ max}$ $\geq 16\text{V} : 0.035 \text{ max}$ $\geq 10\text{V} : 0.050 \text{ max}$			
		IR		More than $10,000\text{M}\Omega$ or $500\text{M}\Omega \times \mu\text{F}$ (Whichever is smaller)	*1)		
13	Solderability		95% of the terminations is to be soldered evenly and continuously	a) Preheat at 155°C for 4 hrs, Immerse in solder for 5s at $235 \pm 5^\circ\text{C}$ b) Steam aging for 8 hrs, Immerse in solder for 5s at $235 \pm 5^\circ\text{C}$ c) Steam aging for 8 hrs, Immerse in solder for 120s at $260 \pm 5^\circ\text{C}$ solder : a solution ethanol and rosin			

* *1) : Indicates typical specification. Please refer to individual specifications.

No.	Item		Performance	Test condition												
14	Electrical Characterization	Capacitance		The Capacitance / D.F. should be measured at 25°C, * Capacitance shall be measured after the heat treatment of 150+0/-10°C for 1hr and leaving for 24±2hr at room temperature. (Class II)												
		Q	Class I	Capacitance ≥ 30pF : Q≥ 1,000 < 30pF : Q≥ 400 + 20 X C (C : Capacitance)												
		Tanδ	Class II	Rated Voltage ≥ 25V : 0.025 max ≥ 16V : 0.035 max ≥ 10V : 0.050 max		*1) I.R. should be measured with a DC voltage not exceeding Rated Voltage @25°C, @125°C for 60 ~ 120 sec.										
		IR@25°C	Class I	More than 100,000MΩ or 1,000MΩ X μF (Whichever is smaller)												
			Class II	More than 10,000MΩ or 500MΩ X μF (Whichever is smaller)												
		IR@125°C	Class I	More than 10,000MΩ or 100MΩ X μF (Whichever is smaller)												
			Class II	More than 1,000MΩ or 10MΩ X μF (Whichever is smaller)												
		Dielectric Strength		No dielectric breakdown or mechanical breakdown												
15	Board Flex	Appearance		Bending to the limit for 60 seconds. Limit : Class I - 3mm Class II - 2mm *1)												
		Capacitance Change	Class I	Initial Measurement Perform the heat treatment at 150°C +0/-10°C for 1 hour and leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.												
			Class II	Final Measurement Leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.												
16	Terminal Strength (SMD)	Appearance		18N, for 60±1 sec. * 0603(1608) ~10N, 0402(1005) ~2N												
		Capacitance Change	Class I	Initial Measurement Perform the heat treatment at 150°C +0/-10°C for 1 hour and leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.												
			Class II	Final Measurement Leave the capacitor in ambient condition for 24±2 hours before measurement. Then perform the measurement.												
17	Beam Load		Destruction value should be exceed Chip Length ≤ 2.5mm a) Chip Thickness > 0.5mm : 20N b) Chip Thickness ≤ 0.5mm : 8N Chip Length ≥ 3.2mm a) Chip Thickness ≥ 1.25mm : 54.5N b) Chip Thickness < 1.25mm : 15N		Beam speed Chip Length ≤ 2.5mm, 0.50±0.05mm / sec. Chip Length ≥ 3.5mm, 2.50±0.25mm / sec.											
18	Capacitance Temperature Characteristics	Capacitance Change	Class I	Capacitance shall be measured by the steps shown in the following table.												
			Class II	<table border="1"> <thead> <tr> <th>Step</th><th>Temperature(°C)</th></tr> </thead> <tbody> <tr> <td>1</td><td>25±2</td></tr> <tr> <td>2</td><td>Min. operating temp.±2</td></tr> <tr> <td>3</td><td>25±2</td></tr> <tr> <td>4</td><td>Max. operating temp.±2</td></tr> <tr> <td>5</td><td>25±2</td></tr> </tbody> </table> <p>■ Class I Temperature Coefficient shall be calculated from the formula as below Temp. Coefficient = $\frac{C_2 - C_1}{C_1 \times \Delta T} \times 10^6$ [ppm / °C] C1 : Capacitance at step 3 C2 : Capacitance at 125°C ΔT : 125°C - 25°C = 100°C</p> <p>■ Class II Capacitance change shall be calculated from the formula as below $\Delta C = \frac{C_2 - C_1}{C_1} \times 100\% \quad C_1 : Capacitance at step 3 C2 : Capacitance at step 2 or step 4$</p>				Step	Temperature(°C)	1	25±2	2	Min. operating temp.±2	3	25±2	4
Step	Temperature(°C)															
1	25±2															
2	Min. operating temp.±2															
3	25±2															
4	Max. operating temp.±2															
5	25±2															


※ *1) : Indicates typical specification. Please refer to individual specifications.

If you want more detailed information, Please Visit Samsung Electro-mechanics website (www.semiconductor.samsung.com)

Packaging Specifications

- Taping Packaging design : Packaging design follows IEC 60286 – 3 standard
(IEC 60286 – 3 Packaging of components for automatic handling – parts 3)

Cardboard(Paper) tape : 4mm pitch




Unit : mm

Symbol		A	B	W	F	E	P1	P2	P0	D	t
Size inch(mm)	0504 (1410)	1.30 ± 0.20	1.70 ± 0.20	8.00 ± 0.30	3.50 ± 0.05	1.75 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	4.00 ± 0.10	$\varnothing 1.50$ $+0.10/-0$	1.10 Below
	0603 0306 (1608) (0816)	1.10 ± 0.20	1.90 ± 0.20								
	0805 0508 (2012) (1220)	1.60 ± 0.20	2.40 ± 0.20								
	1206 0612 (3216) (1632)	2.00 ± 0.20	3.60 ± 0.20								

* According to normal size, we fill out A, B in the table above. The data may be changed as special size tolerance.

Cardboard(Paper) tape : 2mm pitch




Unit : mm

Symbol		A	B	W	F	E	P1	P2	P0	D	t
Size inch(mm)	01005 (0402)	0.25 ± 0.02	0.45 ± 0.02	8.00 ± 0.30	3.50 ± 0.05	1.75 ± 0.10	2.00 ± 0.10	2.00 ± 0.05	4.00 ± 0.10	$\varnothing 1.50$ $+0.10/-0.03$	0.25 ± 0.02 0.37 ± 0.03 0.37 ± 0.05 0.60 ± 0.05 0.37 ± 0.03
	0201 (0603)	0.38 ± 0.03	0.68 ± 0.03								
	0402 (1005)	0.62 ± 0.05	1.12 ± 0.05								
	0204 (0510)	0.62+0.05 $/-0.10$	1.12+0.05 $/-0.10$								

* According to normal size, we fill out A, B in the table above. The data may be changed as special size tolerance.

Embossed(Plastic) tape




Unit : mm

Symbol Type	A	B	W	F	E	P1	P2	P0	D	t1	t0	
Size inch(mm)	01005 (0402)	0.25 ± 0.02	0.45 ± 0.02	4.00 ± 0.05	1.80 ± 0.02	0.90 ± 0.05	1.00 ± 0.02	1.00 ± 0.02	2.00 ± 0.04	$\emptyset 0.80$ ± 0.04	0.25 ± 0.02	0.50 Max
	0603 (1608)	1.05 ± 0.15	1.90 ± 0.15	8.00 ± 0.30	3.50 ± 0.05	4.00 ± 0.10	2.00 ± 0.05	4.00 ± 0.10	$\emptyset 1.50$ ± 0.10 $/-0.03$	2.90 Max	0.60 Below	
	0805 (2012)	1.45 ± 0.20	2.30 ± 0.20									
	1206 (3216)	1.90 ± 0.20	3.50 ± 0.20									
	1210 (3225)	2.80 ± 0.20	3.60 ± 0.20	12.00 ± 0.30	5.60 ± 0.05	1.75 ± 0.10	8.00 ± 0.10	2.00 ± 0.05	4.00 ± 0.10	3.80 Max	0.60 Below	
	1808 (4520)	2.30 ± 0.20	4.90 ± 0.20									
	1812 (4532)	3.60 ± 0.20	4.90 ± 0.20									
	2220 (5750)	5.50 ± 0.20	6.20 ± 0.20									
	0204 (5010)	0.62 $+0.05$ -0.10	1.12 $+0.05$ -0.10	0.80 ± 0.30	3.50 ± 0.05	4.00 ± 0.10	300mm / min	Unreeling Direction	2.50 Max	2.50 Max	2.50 Max	
	0306 (0816)	1.10 ± 0.20	1.90 ± 0.20									
	0508 (1220)	1.45 ± 0.20	2.30 ± 0.20									
	0612 (1632)	2.00 ± 0.20	3.60 ± 0.20									

※ According to normal size, we fill out A, B in the table above. The data may be changed as special size tolerance.


Peeling off of Tape

- $10g.f \leq \text{Peel off force} \leq 70g.f$



Packaging Specifications

Taping figure



Packaging Code & Quantity

Unit : kpcs

Size inch(mm)	Thickness code	Cardboard(Paper) Type										
		7" Reel					10" Reel		13" Reel			
		C	8	H	Z*	Y*	O	D	L	2*	7*	3
01005(0402)	2	20	-	-	-	-	-	100	-	-	-	-
0201(0603)	3	10	-	15	10	10	30	50	-	150	50	-
	3	10	-	15	-	-	30	50	-	-	-	-
0402(1005)	5	10	8	-	10	10	30	50	40	100	50	-
	7,8(THMC)	-	8	-	-	-	-	-	-	-	-	30
0504(1410)	8	4	-	-	-	-	10	10	15	-	-	-
	5	4	-	-	-	-	30	50	-	-	-	-
0603(1608)	8	4	-	-	4	4	10	10	15	-	-	-
	9,N	4	-	-	-	-	-	-	-	-	-	-
0805(2012)	A,C	4	-	-	-	-	10	10	15	-	-	-
1206(3216)	C	4	-	-	-	-	10	10	15	-	-	-


* 2 = 1mm Pitch / Z = Chip aligned for horizontal / Y, 7 = Chip aligned for vertical

Unit : kpcs

Size inch(mm)	Thickness code	Embossed(Plastic) Type						Bulk case Type	Bulk Type
		7" Reel				10" Reel	13" Reel		
		E	G	W*	R*	S	F	P	B
01005(0402)	2	50	-	-	-	-	-	-	-
0201(0603)	1	10	-	-	-	-	-	-	-
0402(1005)	1,2,L	15	-	-	-	-	-	-	-
	3,5	-	-	-	-	-	-	50	-
0603(1608)	8	3	-	-	3	-	10	15	-
	E,M	3	-	-	-	-	-	-	-
0604(1610)	D	3	-	3	-	6	10	-	-
	A,C	-	-	-	-	-	-	10	-
0805(2012)	E	2	3	2	-	6	10	5	-
	F	2	3	2	-	6	10	5	-
	Q	2	3	2	-	6	10	5	-
1206(3216)	E,P,F	2	3	-	-	6	10	-	-
	H	2	-	2	-	4	8	-	-
	9,D,C,O	2	-	-	-	-	10	-	-
	E,F,M	2	-	-	-	-	10	-	-
1210(3225)	H,T	2	-	-	-	4	8	-	-
	I,U	2	-	-	-	-	4	-	-
	J,V	1	-	1	-	-	4	-	-
	S	2	-	-	-	-	8	-	-
1808(4520)	F	2	-	-	-	-	-	-	-
	F	1	-	-	-	-	4	-	-
1812(4532)	H,I	1	-	-	-	-	4	-	-
	J,L	-	-	-	-	-	2	-	-
2220(5750)	H,I,J	-	-	-	-	-	2	-	-

* R = Chip aligned for horizontal / W = Chip aligned for vertical


Reel Dimensions



Unit : mm					
Symbol	Tape Width	A	B	C	D
7" Reel	4mm	$\varnothing 178 \pm 2.0$	MIN $\varnothing 50$	$\varnothing 13 \pm 0.5$	21 ± 0.8
	8mm	$\varnothing 178 \pm 2.0$	MIN $\varnothing 50$	$\varnothing 13 \pm 0.5$	21 ± 0.8
	12mm	$\varnothing 178 \pm 2.0$	MIN $\varnothing 50$	$\varnothing 13 \pm 0.5$	21 ± 0.8
10" Reel	8mm	$\varnothing 258 \pm 2.0$	MIN $\varnothing 70$	$\varnothing 13 \pm 0.5$	21 ± 0.8
	8mm	$\varnothing 330 \pm 2.0$	MIN $\varnothing 70$	$\varnothing 13 \pm 0.5$	21 ± 0.8
	12mm	$\varnothing 330 \pm 2.0$	MIN $\varnothing 70$	$\varnothing 13 \pm 0.5$	21 ± 0.8
Symbol	Tape Width	E	W	t	
7" Reel	4mm	2.0 ± 0.5	5.0 ± 0.5	1.2 ± 0.2	
	8mm	2.0 ± 0.5	10 ± 1.5	0.9 ± 0.2	
	12mm	2.0 ± 0.5	13 ± 0.5	1.2 ± 0.2	
10" Reel	8mm	2.0 ± 0.5	10 ± 1.5	1.8 ± 0.2	
	8mm	2.0 ± 0.5	10 ± 1.5	1.8 ± 0.2	
	12mm	2.0 ± 0.5	13 ± 0.5	2.2 ± 0.2	

Bulk Case Packaging

- Bulk case packaging can reduce the stock space and transportation costs.
- The bulk feeding system can increase the productivity.
- It can eliminate the components loss.



Unit : mm						
Symbol	A	B	T	C	D	E
Dimension	6.80 ± 0.10	8.80 ± 0.10	12 ± 0.10	$1.50 \pm 0.10 / -0$	$2.00 +0 / -0.10$	$3.00 +0.20 / -0$
Symbol	F	W	G	H	L	I
Dimension	$31.5 +0.20 / -0$	$36 +0 / -0.20$	19 ± 0.35	7.00 ± 0.35	110 ± 0.70	5.00 ± 0.35

■ QUANTITY

Unit : pcs

Size Inch(mm)	0402(1005)	0603(1608)	0805(2012)	
			$T \leq 0.85\text{mm}$	$T \geq 1.0\text{mm}$
Quantity	50,000	10,000 or 15,000	10,000	5,000

Application Manual for Surface Mounting

1. Storage of products

1-1. Storage Environment

Tape packing materials are designed to withstand long-term storage, but they will degrade more rapidly in the presence of high temperature or high humidity. Therefore, the products must be stored in an ambient 0 ~ 40°C with a relative humidity of 0 ~ 70%. Allowable storage period is within 6 months from the outgoing date of delivery.

1-2. Corrosive Gases

Since sulfur and chlorine may degrade the solderability of the end termination, it is important to store the capacitors in an environment free of these gases.


1-3. Temperature Fluctuations

Since dew condensation may occur by the differences in temperature when the products are taken out of storage, it is important to maintain a temperature - controlled environment.

2. Design of Solder Land Pattern

When designing printed circuit boards, the shape and size of the solder lands must allow for the proper amount of solder on the capacitor. The amount of solder at the end terminations has a direct effect on the probability that the chip will crack. The greater amount of solder, the larger amount of stress on the chip, and the more likely that it will break. Use the following illustrations as guidelines for proper Solder land design.

Recommendation of solder Land Shape and Size



3. Adhesives

MLCCs generally require the use of an adhesive to position the chips to the circuit board prior to soldering.

3-1. Requirements for Adhesives

They must have enough adhesion so that the chips will not fall off or move during the handling of the circuit board.

They must maintain their adhesive strength when exposed to soldering temperatures.

They should not spread or run when applied to the circuit board.


They should have a long pot life.

They should harden quickly.

They should not corrode the circuit board or chip material.

They should be a good insulator.

They should be non-toxic, and not produce harmful gases, nor be harmful when touched.



Type	21	31
a	Min. 0.2	Min. 0.2
b	70 ~100μm	70 ~100μm
c	> 0	> 0

3-2. Application Method

It is important to use the proper amount of adhesive. Too little will cause poor adhesion to the circuit board, and too much may strain the conductor pattern, thereby causing defective soldering. The following illustrations show the proper quantity of adhesive.

3-3. Adhesive hardening Characteristics

To prevent oxidation of the terminations, the adhesive must harden at 160°C or less, within 2 minutes or less


4. Mounting

4-1. Mounting Head Pressure

Excessive pressure will cause chip capacitors to crack.
The pressure between nozzle and chip capacitor will be 300g maximum during mounting.

4-2. Bending Stress

Bending of printed circuit board by mounting head when double-sided circuit boards are used, chip capacitors first are mounted and soldered onto one side of the board.
When the capacitors are mounted onto the other side, it is important to support the board as shown in the illustration.
If the circuit board is not supported, it may bend, causing the already – installed capacitors to crack.



5. Flux

Although highly – activated flux gives better solderability, substances which increase activity may also degrade the insulation of the chip capacitors. To avoid such degradation, it is recommended that a mildly activated rosin flux (less than 0.2% chlorine) be used

6. Soldering

Since a multilayer ceramic chip capacitor comes into direct contact with melted solder during soldering, it is exposed to potentially mechanical stress caused by the sudden temperature change. The capacitor may also be subject to silver migration, and to contamination by the flux. Because of these factors, soldering technique is critical.

6-1. Soldering Methods

Method	Classification
Reflow soldering	- Overall heating
	- Local heating
Flow soldering	- Single wave - Double wave


6-2. Soldering Profile

To avoid the crack problem by sudden temperature change, follow the temperature profile in the adjacent graph.

Application Manual for Surface Mounting


6-3. Pb-Free (Sn 100%) Plating

• REFLOW SOLDERING



Soldering Temp.(°C)	Pre - heating Time (①, sec.)	Soldering Time(②, sec.)
260+0 / -5	60 ~ 120	60 ~ 150

• FLOW SOLDERING



ΔT (°C)	Soldering Temp. (°C)	Pre - heating Time (① + ②, sec.)	Soldering Time (③, sec.)
≤ 150 (1206 and below size)	260 ± 3	≥ 120	≤ 5

• SOLDER IRON(Hand Soldering)


Variation of Temp.(°C)	Soldering Temp.(°C)	Pre - heating Time(sec.)	Soldering Time(sec.)	Cooling Time(sec.)	Condition of Iron Facilities		
					Wattage	Tip Diameter	Soldering Time
$\Delta T \leq 130$	300 ± 10 °C max.	≥ 60 sec.	≤ 4 sec.	-	20W max.	3mm max.	4sec max.

※ Caution – Iron tip should not contact with ceramic body directly

6-4. Manual Soldering

Manual soldering can pose a great risk of creating thermal cracks in chip capacitors. The hot soldering iron tip comes into direct contact with the end terminations, and operator's carelessness may cause the tip of the soldering iron to come into direct contact with the ceramic body of the capacitor. Therefore the soldering iron must be handled carefully, and close attention must be paid to the selection of the soldering iron tip and to temperature control of the tip.

6-5. Amount of Solder



6-6. Cooling

Natural cooling using air is recommended. If the chips are dipped into solvent for cleaning, the temperature difference(ΔT) must be less than 100°C

6-7. Cleaning

If rosin flux is used, cleaning usually is unnecessary. When strongly activated flux is used, chlorine in the flux may dissolve into some types of cleaning fluids, thereby affecting the chip capacitors. This means that the cleaning fluid must be carefully selected, and should always be new.

7. Notes for Separating Multiple, Shared PC Boards

A multi-PC board is separated into many individual circuit boards after soldering has been completed. If the board is bent or distorted at the time of separation, cracks may occur in the chip capacitors. Carefully choose a separation method that minimizes the bending of the circuit board.

Certifications


ISO / TS 16949



ISO 14001



OHSAS18001



Sony Green Partner



QC 080000 IECQ HSPM



Quality System Certification status for each factory site


Certification	Suwon (Korea)	Busan (Korea)	Calamba (Philippines)	Tianjin (China)	Binhai (China)
ISO / TS 16949	BSI TS 91430-000	BSI TS 91430-001	BSI TS 91430-005	BSI TS 91430-007	BSI TS 91430-007
Date Validity	2013-10-25 ~ 2016-10-24	2016-07-31 ~ 2018-09-14	2015-07-20 ~ 2018-07-19	2014-11-18 ~ 2017-11-17	2014-11-18 ~ 2017-11-17
ISO 14001	20BK00223-UK	20BK00223-UK	EMS_77354	CNBJ320761-UK	CNBJ320761-UK
Date Validity	2016-06-25 ~ 2018-09-14	2016-06-25 ~ 2018-09-14	2015-07-13 ~ 2018-07-12	2015-04-15 ~ 2018-04-14	2015-04-15 ~ 2018-04-14
OHSAS 18001	BK50217	BK50217	OHS_568723	CN100043A	CN100043A
Date Validity	2013-06-25 ~ 2019-06-24	2013-06-25 ~ 2019-06-24	2010-12-21 ~ 2016-10-13	2015-04-15 ~ 2018-04-14	2015-04-15 ~ 2018-04-14
QC 080000	KR-HSPM-1011	KR-HSPM-1012	PI-HSPM-1001	PRC-HSPM-1767	PRC-HSPM-1767-2
Date Validity	2016-07-02 ~ 2019-07-01	2016-07-14 ~ 2019-07-19	2016-07-11 ~ 2019-07-04	2016-07-11 ~ 2019-07-26	2016-07-11 ~ 2019-07-26
Sony Green Partner Date Validity	2016-02-22 ~ 2018-05-31				

Homepage

<http://www.Samsungsem.com>

SEMCO LCR web-site

SEMCO web - site supports all technical data & information for our partner.



LCR Web Library

The software of "LCR Web Library" provides the characteristics of SEMCO's products on the website.
[\(http://weblib.samsungsem.com/\)](http://weblib.samsungsem.com/)

- S-parameter and Spice Model of MLCC, Inductor and Bead.
- The acoustic noise data of MLCC
- Capacitance of MLCC according to Temperature and DC bias

Part Number	Capacitance	Size (Width/mm)	Rated Voltage	TCC	Thickness Max	Tolerance
CL311104RSPAN	100pF	03050816	4Vdc	XTR	0.11 mm	+0.1%
CL311105RSPAN	1uF	03050816	4Vdc	XTR	0.15 mm	+0.25%
CL311474RSPAN	470pF	03050816	4Vdc	XSR	0.21 mm	+0.1%
CL324102RPNAN	1uF	030505402	10Vdc	XSR	0.22 mm	+0.1%
CL324102GZNNN	1uF	030505402	10Vdc	XSR	0.22 mm	+0.1%
CL324103RPNAN	10uF	030505402	10Vdc	XSR	0.22 mm	+0.1%
CL324103GZNNN	10uF	030505402	10Vdc	XSR	0.22 mm	+0.1%
CL324104RPNAN	100pF	030505402	4Vdc	XSR	0.22 mm	+0.1%
CL324104RSPAN	100pF	030505402	4Vdc	XSR	0.22 mm	+0.1%
CL324105RSPAN	1uF	030505403	8.3Vdc	XSR	0.55 mm	+0.25%
CL324105GZNNN	1.8uF	030505402	10Vdc	XSR	0.22 mm	+0.1%
CL324222RPNAN	2.2uF	030505402	10Vdc	XSR	0.22 mm	+0.1%
CL324254RQZNNN	220pF	030505402	8.3Vdc	XSR	0.22 mm	+0.1%
CL324502RQZNNN	6.8nF	030505402	8.3Vdc	XTR	0.22 mm	+0.1%
CL325221RQZNNN	220pF	030505402	10Vdc	XTR	0.22 mm	+0.1%
CL325331RQZNNN	330pF	030505402	10Vdc	XTR	0.22 mm	+0.1%
CL325402RQZNNN	470pF	030505402	4Vdc	XTR	0.22 mm	+0.1%

Disclaimer & Limitation of Use and Application

1. This catalogue is valid only to the products purchased either from us or through our official distributors. Should you have any question regarding our product specifications, please contact our sales personnel or application engineers.
2. Product specifications included in this catalogue are effective as of [September. 30, 2016]. Please be advised that they are standard product specifications for reference only. We may change, modify or discontinue the product specifications without notice at any time. Before placing an order, you need to check with our personnel about the validity of the product specifications that you are referring to.
3. We may modify or cease to produce the products listed in this catalogue without notice.
4. Without obtaining our permission, you should not be allowed to reproduce, copy, use or transfer any content or information contained this catalogue in any manner whatsoever for any purpose.
5. WE WILL NOT ASSUME ANY RESPONSIBILITIES WHATSOEVER FOR ANY CLAIM, DISPUTE, DAMAGE OR LIABILITY WITH REGARDS TO THE INTELLECTUAL PROPERTY RIGHTS OR OTHER RELATED RIGHTS OF OURS OR ANY THIRD PARTY ASSOCIATED WITH YOUR USE OF OUR PRODUCTS AND/OR INFORMATION CONTAINED IN THIS CATALOGUE. WE EXPRESSLY DISCLAIM THAT NO LICENSE IS GRANTED REGARDING THE AFOREMENTIONED RIGHTS.
6. THE PRODUCTS LISTED IN THIS CATALOGUE ARE NOT DESIGNED AND MANUFACTURED FOR ANY USE AND APPLICATIONS SET FORTH BELOW. PLEASE NOTE THAT ANY MISUSE OF THE PRODUCTS DEVIATING FROM PRODUCTS SPECIFICATIONS OR INFORMATION PROVIDED IN THIS CATALOGUE MAY CAUSE SERIOUS PROPERTY DAMAGES OR PERSONAL INJURY. WE WILL NOT BE LIABLE FOR ANY DAMAGES RESULTING FROM ANY MISUSE OF THE PRODUCTS, SPECIFICALLY INCLUDING USING THE PRODUCTS FOR HIGH RELIABILITY APPLICATIONS AS LISTED BELOW.

IF YOU HAVE ANY QUESTIONS REGARDING THIS 'LIMITATION OF USE AND APPLICATION', YOU SHOULD FIRST CONTACT OUR SALES PERSONNEL OR APPLICATION ENGINEERS.

- ① Aerospace/Aviation equipment
- ② Medical equipment
- ③ Military equipment
- ④ Disaster prevention/crime prevention equipment
- ⑤ Any other applications with the same as or similar complexity or reliability to the applications set forth above.



MEMO

www.Samsungsem.com





Passive components sales offices

Head office

Maeyoung-ro 150 (Maetan-dong) Yeongtong-gu, Suwon-city, Gyeonggi Province, Korea 16674
Tel : +82-31-210-5114

America Sales Office

San Jose Office
Samsung Electromechanics America Inc
3655 North First Street
San Jose, CA, 95134
TEL : +1-503-869-8083
E-mail : philip.elliott@samsung.com

Europe Sales Office

Frankfurt office
Samsung Electro-Mechanics GmbH, Kölnerstr. 12
65760 Eschborn Germany
TEL : +49-6196-66-7259
E-mail : benjamin.blume@samsung.com

Domestic Distributors

Korchip Corporation
359, Manan-ro, Manan-gu, Anyang-si, Gyeonggi-do, Korea
Tel : +82-31-361-8100
E-mail : parts@korchip.com

SAMT
315, Yeongdong-daero, Gangnam-gu, Seoul, Korea
Tel : +82-2-3458-9000
E-mail : info@isamt.com

CHUNGMAC
13, Heungdeok 1-ro, Giheung-gu, Yongin-si,
Gyeonggi-do, Korea
Tel : +82-31-234-2367
E-mail : webmaster@chungmac.co.kr

YOUNGDUK
632, Seobusaet-gil, Geumcheon-gu, Seoul, Korea
Tel : +82-2-2107-7860
E-mail : dryblood@hanmail.net

Asia Sales Offices

Shenzhen Office
Shenzhen Office-14F, Tower A, SCC Building, Junction of Houhai Blvd.
and Haide 1st Rd., Nanshan Dist., Shenzhen City, China
TEL : +86-755-8608-5562
E-mail : alex77.zhang@samsung.com

Shanghai Office
9F Room CD, Shanghai HNA Building, No.898 Pu Ming Rd.,
Pudong New Area Dist., Shanghai City, China, 200122
TEL : +86-21-2231-4353
E-mail : jerry.qu@samsung.com

Beijing Office
14F Room C1C2, China Merchants Tower, No.118 Jianguo Rd.,
Chaoyang Dist., Beijing City, China, 100022
TEL : +86-10-6566-8100-6606
E-mail : kiko.wang@samsung.com

Taipei Office
9F-1, No.399 Rueykuang Rd., Neihu Dist., Taipei City, Taiwan
TEL : +886-2-2656-8350
E-mail : kevin0130.wang@samsung.com

Japan(Tokyo) Office
Samsung Electro-Mechanics Japan Co.,Ltd
-Shinagawa Grand Central Tower 9F,
2-16-4, Kounan, Minato-ku, Tokyo, Japan
TEL : +81-3-6369-6452
E-mail : hikota.suga@samsung.com

Singapore Office
Samsung Electro-Mechanics Private Limited - 3 Church Street
Samsung Hub #23-01 Singapore
TEL : +65-6933-2636
E-mail : jessica.benegildo@samsung.com

India Office
Vipul Tech Square, Tower C, Golf Course Road, Sector - 43,
Gurgaon - 122001, Haryana, India
TEL : +91-124-4841800
E-mail : munish.kumar@samsung.com

Passive components manufacturing sites

Suwon Plant(Korea)
Meayoungro 150 (Maetan-dong) Yeongtong-gu,
Suwon Gyeonggi-do 16674
Tel : +82-31-210-5114

Busan Plant (Korea)
Noksan Saneopjungro 333 (Songjeong-dong),
Gangseo-gu, Busan 46754
Tel : +82-51-970-7114, 8114

Tianjin Plant (China)
27, Heiniucheng-Road, Tianjin, China 300210
Tel : +86-22-2830-3333

Binhai Plant(China)
80, Xiaqing road, TEDA west district, Tianjin, China
TEL : +86-22-2830-3333(3500)

Philippines Plant (Philippines)
BLK 5&6 Calamba Premiere International Park Brgy.
Batino Calamba, Laguna Philippines
TEL : +63-49-508-8300

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [samsung](#) manufacturer:

Other Similar products are found below :

[DA61-04475B](#) [DA97-17194A](#) [RC2012F2001CS](#) [CL10B472JB8NNND](#) [KM44C4100BK-60](#) [CL05C160JB5NCNC](#) [CL21C151FBANNWC](#)
[M471B5673EH1-CH900](#) [K4H510838B-TCB3](#) [RC1608F86R6CS](#) [CL31C120JBCNNNC](#) [CL21CR47BBANNNC](#) [CL32C103JBFNNNE](#)
[CL31B223JBCNNNC](#) [CL21C221JDCNFNC](#) [CL21B223KBANNWC](#) [CL10B563KB8NFNC](#) [CL10B473KB8SFNC](#) [CL10B122KB8NFNC](#) [SI-](#)
[B8T171550WW](#) [SL-B8V2N70LAWW](#) [BN96-35590A](#) [BN96-31876D](#) [DC97-15103A](#) [DA67-02638B](#) [BN96-32239D](#) [BN39-02189A](#) [BN39-](#)
[02190A](#) [DA61-08574A](#) [DA97-17215A](#) [DC47-00027F](#) [AH59-02748B](#) [3903-001209](#) [RC1005F103CS](#) [RF062PJ150CS](#) [CL10A335MQ8NNNC](#)
[CL10B823KA8NNNC](#) [CL10C680JB8NFNC](#) [CL31B681KHFNFNE](#) [CL31C101JCCNFNC](#) [RC1608F753CS](#) [RC1005FR100CS](#)
[CL10F334ZO8NNNC](#) [CL31C331KBCNBNC](#) [CL31B683KBCNNNC](#) [CL21C2R4CBANNNC](#) [CL05B104MP5NNNC](#) [DC97-16350E](#) [AH81-](#)
[09068A](#) [DC66-00814A](#)